



Usage Guideline

CBPRPlus- camt.106.001.03_ChargesPayment- Request_MultipleCharges

CBPRPlus SR2026 (Combined)

This document describes a usage guideline restricting the base message **MX camt.106.001.03**. You can also consult [this information online](#).

Published by Cross Border Payments and Reporting Plus (CBPR+) and generated by [MyStandards](#).

20 February 2026

Table of Contents

Message Functionality 3

1 Restriction summary 5

2 Structure 7

3 ISO 20022 Rules 9

4 Message Building Blocks 11

5 Message Components 20

6 Message Datatypes 259

Legal Notices 290

Message Functionality

This Usage Guideline is based on the camt.106.001.03 message definition. In addition, Cross Border Payments and Reporting Plus (CBPR+) has defined usage of BusinessApplicationHeaderV02 as mandatory. The following section will be dealing with the camt.106.001.03 only.

Overview

Usage:

This camt.106 message is used to request the multiple transaction charges, interest and/or other expenses which are previously unknown to the Receiver.

Principles:

1) AGENTS IDENTIFICATION - Textual Rules

-> If BICFI is present, then (Name & Postal Address) is NOT allowed (ClearingSystemMemberIdentification and LEI may complement) - However, in case of conflicting information, the BICFI will always take precedence.

-> If BICFI is absent, (Name & Postal Address) OR [(Name & Postal Address) and ClearingSystemMemberIdentification] must be present.

Exception: If BICFI is absent, whenever Debtor Agent, Creditor Agent and all agents in between are located within the same country, the clearing code only may be used.

2) Character Set:

All proprietary and Text fields EXCLUDING Name and Address for all actors and Related Remittance Information and Remittance are limited to the FIN-X-Character set.

All Name and Address for all actors, Related Remittance Information and Remittance Information (structured and unstructured), Email Address where included as part of a proxy element are extended to support the following additional characters:

!#\$%&*='^_`{|}~";<>@[\\]

< is replaced with <

> is replaced with >

Collection Description

This is the Cross Border Payment and Reporting Collection for SR2026.

These are FINAL usage guidelines.

The usage guidelines are available on the CBPR+ SR2026 Readiness Portal for testing.

The Collection contains:

30 Usage Guidelines that will be live on the network as of November 2026.

Outline

The CBPRPlus SR2026 (Combined) / CBPRPlus-camt.106.001.03_ChargesPaymentRequest_MultipleCharges message is composed of 3 building blocks

a. GroupHeader

Unique identification of the charges message.

b. Charges

Provides information on the charges to be paid by the charge bearer(s) related to the processing of the underlying transaction.

c. SupplementaryData

Additional information that cannot be captured in the structured elements and/or any other specific block.

1 Restriction summary

This Usage Guideline restricts the camt.106.001.03 message. This also includes the BusinessApplicationHeaderV02.

Restriction Type	See page
Removed elements	14, 15, 19, 27, 27, 27, 27, 32, 32, 32, 32, 32, 35, 35, 35, 35, 35, 37, 39, 47, 47, 59, 59, 59, 60, 61, 65, 65, 67, 69, 74, 78, 79, 80, 85, 86, 93, 93, 95, 102, 103, 103, 103, 103, 104, 104, 104, 104, 104, 104, 104, 104, 104, 104, 104, 120, 120, 120, 120, 121, 121, 121, 121, 122, 122, 122, 122, 128, 128, 128, 128, 128, 135, 135, 135, 135, 135, 138, 142, 158, 158, 167, 169, 169, 169, 169, 180, 184, 192, 192, 192, 193, 193, 193, 193, 193, 193, 193, 197, 197, 197, 197, 197, 205, 205, 205, 205, 205, 217, 217, 219, 223, 242, 244, 252, 252, 257, 258, 258, 272, 272, 272
Make mandatory	13, 51, 51, 51, 51, 51, 51, 51, 55, 62, 63, 64, 71, 73, 102, 106, 106, 106, 106, 106, 107, 107, 107, 107, 107, 107, 107, 107, 119, 119, 119, 119, 152, 156, 159, 162, 199, 199, 200, 200, 200, 202, 202, 202, 202, 203, 220, 222, 230, 230, 230, 230, 230, 242, 243, 244, 244, 246, 247, 248, 248, 253
Reduce Multiplicity	16, 183, 203, 203, 203, 203, 203, 215, 215, 215, 215, 215, 222, 228
Ignore	n.a.
Text rules	16, 44, 45, 46, 66, 66, 66, 66, 66, 71, 71, 71, 71, 75, 75, 75, 75, 77, 77, 77, 77, 78, 78, 79, 79, 79, 82, 83, 83, 83, 83, 90, 90, 90, 90, 90, 91, 92, 92, 92, 92, 99, 99, 99, 99, 99, 100, 100, 101, 101, 101, 127, 127, 127, 128, 128, 159, 160, 160, 160, 178, 237, 237, 237, 237, 239, 239, 239, 239
Conditional rules	n.a.
Formal rules	11, 17, 17, 17, 29, 30, 30, 30, 31, 33, 33, 34, 34, 34, 36, 38, 61, 64, 68, 68, 68, 68, 69, 73, 75, 76, 131, 131, 132, 132, 132, 133, 133, 133, 134, 134, 137, 137, 141, 141, 254
Fixed values	13, 13
Truncates	n.a.
Comments	n.a.

Restriction Type	See page
Annotations	n.a.
Changed datatypes	12, 14, 15, 24, 24, 24, 24, 24, 24, 24, 24, 24, 24, 24, 25, 44, 45, 45, 46, 47, 52, 52, 52, 52, 52, 53, 53, 53, 53, 53, 53, 56, 57, 57, 57, 57, 58, 58, 58, 58, 58, 58, 58, 58, 62, 64, 70, 81, 88, 94, 95, 97, 107, 108, 108, 108, 108, 108, 108, 108, 108, 108, 108, 108, 108, 108, 109, 109, 115, 115, 115, 117, 117, 117, 126, 126, 126, 126, 126, 130, 130, 130, 130, 130, 140, 143, 143, 144, 144, 144, 144, 144, 144, 144, 144, 144, 145, 145, 145, 145, 145, 145, 145, 145, 145, 145, 146, 147, 152, 153, 155, 156, 157, 157, 163, 177, 193, 193, 194, 194, 194, 194, 194, 194, 194, 194, 195, 195, 195, 195, 195, 195, 195, 195, 195, 195, 196, 196, 196, 196, 196, 196, 196, 197, 197, 197, 198, 198, 198, 198, 198, 198, 198, 198, 198, 198, 199, 199, 199, 199, 199, 200, 200, 200, 200, 200, 200, 200, 201, 201, 201, 201, 201, 201, 201, 201, 202, 202, 202, 202, 202, 203, 203, 203, 203, 204, 206, 206, 206, 206, 206, 206, 206, 206, 206, 206, 207, 207, 207, 207, 207, 207, 207, 207, 208, 208, 208, 208, 208, 208, 208, 208, 208, 209, 209, 209, 209, 209, 209, 209, 209, 209, 210, 210, 210, 210, 210, 210, 211, 211, 211, 211, 211, 211, 211, 211, 211, 211, 212, 212, 212, 212, 212, 212, 212, 212, 213, 213, 213, 213, 213, 213, 213, 213, 213, 214, 214, 214, 214, 214, 214, 214, 214, 214, 215, 215, 215, 216, 216, 216, 218, 218, 218, 218, 219, 219, 220, 220, 220, 220, 221, 221, 221, 222, 224, 224, 224, 225, 225, 225, 226, 226, 227, 227, 227, 228, 231, 231, 231, 231, 231, 231, 231, 231, 231, 231, 231, 231, 233, 233, 233, 233, 233, 233, 233, 233, 233, 233, 233, 234, 237, 242, 242, 244, 245, 245, 246, 246, 246, 246, 247, 247, 247, 247, 248, 248, 248, 249, 249, 249, 249, 249, 250, 250, 250, 250, 250, 250, 251, 251, 251, 251, 253, 253, 253, 254, 254, 255, 256, 256, 256, 257, 257, 258
Extensions	n.a.
Synonyms	n.a.

2 Structure

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	<i>BusinessApplicationHeaderV02</i>	<AppHdr>		[1..1]		
	CharacterSet	<CharSet>		[0..1]		11
	From	<Fr>		[1..1]		11
	OrganisationIdentification	<OrgId>	{Or	[1..1]		169
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		169
	To	<To>		[1..1]		12
	OrganisationIdentification	<OrgId>	{Or	[1..1]		169
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		169
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]		12
	MessageDefinitionIdentifier	<MsgDefIdr>		[1..1]		12
	BusinessService	<BizSvc>		[0..1]	 	13
	MarketPractice	<MktPrctc>		[0..1]		13
	Registry	<Regy>		[1..1]		161
	Identification	<Id>		[1..1]		161
	CreationDate	<CreDt>		[1..1]		14
	BusinessProcessingDate	<BizPrcgDt>		[0..1]		14
	CopyDuplicate	<CpyDplct>		[0..1]		14
	PossibleDuplicate	<PssblDplct>		[0..1]		14
	Priority	<Prty>		[0..1]		15
	Signature	<Sgntr>		[0..1]		15
	Related	<Rltd>		[0..*]	 R[0..1]	15
	CharacterSet	<CharSet>		[0..1]		43
	From	<Fr>		[1..1]		43
	To	<To>		[1..1]		44
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]		44
	MessageDefinitionIdentifier	<MsgDefIdr>		[1..1]		45
	BusinessService	<BizSvc>		[0..1]		45
	CreationDate	<CreDt>		[1..1]		46

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CopyDuplicate	<CpyDplct>		[0..1]		46
	PossibleDuplicate	<PssblDplct>		[0..1]		46
	Priority	<Prty>		[0..1]		47
	Signature	<Sgntr>		[0..1]		47
	<i>ChargesPaymentRequestV03</i>	<ChrgsPmtReq>		[1..1]		16
	GroupHeader	<GrpHdr>		[1..1]		17
	MessageIdentification	<MsgId>		[1..1]		157
	CreationDateTime	<CreDtTm>		[1..1]		157
	ChargesRequestor	<ChrgsRqstr>		[0..1]		157
	SettlementInstruction	<SttlmInstr>		[0..1]		158
	TotalCharges	<TtlChrgs>		[0..1]		158
	ChargesAccountAgent	<ChrgsAcctAgt>		[0..1]		159
	ChargesAccountAgentAccount	<ChrgsAcctAgtAcct>		[0..1]		160
	Charges	<Chrgs>		[1..1]		18
	Single	<Sngl>	{Or	[1..1]		59
	PerTransaction	<PerTx>	Or	[1..1]		60
	PerType	<PerTp>	Or}	[1..*]	 	61
	SupplementaryData	<SplmtryData>		[0..*]		18
	PlaceAndName	<PlcAndNm>		[0..1]		240
	Envelope	<Envlp>		[1..1]		240

3 ISO 20022 Rules

R3 RelatedPresentWhenCopyDupl ✓

Related MUST contain the relevant BusinessMessageHeader elements of the BusinessMessage to which this BusinessMessage relates.

If CopyDuplicate is present, then Related MUST be present.

Error handling:

- *Error severity:* Warning
- *Error Code:* H00001
- *Error Text:* Element Related is missing

R6 ChargesAccountAgentHeaderOrSingle1Rule ✓

When GroupHeader/ChargesAccountAgent is present or GroupHeader/ChargesAccountAgentAccount is present then Charges/Single/ChargesAccountAgent must be absent and Charges/Single/ChargesAccountAgentAccount must be absent.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00629
- *Error Text:* Missing charges account

R7 ChargesAccountAgentHeaderOrSingle2Rule ✓

When Charges/Single/ChargesAccountAgent is present or Charges/Single/ChargesAccountAgentAccount is present then GroupHeader/ChargesAccountAgent must be absent and GroupHeader/ChargesAccountAgentAccount must be absent.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00630
- *Error Text:* Missing charges account

R8 ChargesAccountAgentHeaderOrTransaction1Rule ✓

When GroupHeader/ChargesAccountAgent is present or GroupHeader/ChargesAccountAgentAccount is present then Charges/PerTransaction/ChargesAccountAgent must be absent and Charges/PerTransaction/ChargesAccountAgentAccount must be absent and Charges/PerTransaction/Record/ChargesAccountAgent must be absent and Charges/PerTransaction/Record/ChargesAccountAgentAccount must be absent.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00631
- *Error Text:* Missing charges account

R9 ChargesAccountAgentHeaderOrTransaction2Rule ✓

When Charges/PerTransaction/ChargesAccount is present or Charges/PerTransaction/ChargesAccountOwner is present or Charges/PerTransaction/Record/ChargesAccount is present or Charges/PerTransaction/Record/ChargesAccountOwner then GroupHeader/ChargesAccountAgent must be absent and GroupHeader/ChargesAccountAgentAccount must be absent.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00632
- *Error Text:* Missing charges account

R10 ChargesAccountAgentHeaderOrType1Rule ✓

When GroupHeader/ChargesAccountAgent is present or GroupHeader/ChargesAccountAgentAccount is present then Charges/PerType/ChargesAccountAgent must be absent and Charges/PerType/ChargesAccountAgentAccount must be absent and Charges/PerType/Record/ChargesAccountAgent must be absent and Charges/PerType/Record/ChargesAccountAgentAccount must be absent.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00633
- *Error Text:* Missing charges account

R11 ChargesAccountAgentHeaderOrType2Rule ✓

When Charges/PerType/ChargesAccountAgent is present or Charges/PerType/ChargesAccountAgentAccount is present or Charges/PerType/Record/ChargesAccountAgent is present or Charges/PerType/Record/ChargesAccountAgentAccount then GroupHeader/ChargesAccountAgent must be absent and GroupHeader/ChargesAccountAgentAccount must be absent.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00634
- *Error Text:* Missing charges account

R12 ChargesRequestorGroupHeaderRule ✓

When GroupHeader/ChargesRequestor is present then Charges/Single/ChargesRequestor must be absent and Charges/PerTransaction/Record[*]/ChargesRequestor must be absent and Charges/PerType[*]/Record[*]/ChargesRequestor must be absent.

All may be absent.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00647
- *Error Text:* Invalid message content for ChargesRequestor

4 Message Building Blocks

Note The following chapter identifies the building blocks of the CBPRPlus SR2026 (Combined) / CBPRPlus-camt.106.001.03_ChargesPaymentRequest_MultipleCharges message definition.

Usage Guideline on Root Node

- on camt.106.001.03/fullmessage

- **CBPR_BusinessMessageIdentifier_FormalRule:**

The Business Message Identifier must match the Message Identification in the Group Header.

For each [Full Message], every occurrence of [Full Message/BusinessApplication-HeaderV02/BusinessMessageIdentifier] value must be equal to every occurrence of [Full Message/Document/ChargesPaymentRequestV03/GroupHeader/MessageIdentification] value

4.1 Header Building Blocks

Note The following chapter identifies the building blocks of the BusinessApplicationHeaderV02 definition.

4.1.1 CharSet

XML Tag: CharSet

Presence: [0..1]

Definition: Contains the character set of the text-based elements used in the Business Message.

Datatype: ["UnicodeChartsCode" on page 289](#)

4.1.2 From

XML Tag: Fr

Presence: [1..1]

Definition: The sending MessagingEndpoint that has created this Business Message for the receiving MessagingEndpoint that will process this Business Message.

Note the sending MessagingEndpoint might be different from the sending address potentially contained in the transport header (as defined in the transport layer).

The **Fr** block contains the following elements (see datatype ["Party44Choice__1" on page 168](#) for details)

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		169
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		169

4.1.3 To

XML Tag: To

Presence: [1..1]

Definition: The MessagingEndpoint designated by the sending MessagingEndpoint to be the recipient who will ultimately process this Business Message.

Note the receiving MessagingEndpoint might be different from the receiving address potentially contained in the transport header (as defined in the transport layer).

The **To** block contains the following elements (see datatype "[Party44Choice__1](#)" on page 168 for details)

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		169
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		169

4.1.4 BusinessMessageIdentifier

XML Tag: BizMsgIdr

Presence: [1..1]

Definition: Unambiguously identifies the Business Message to the MessagingEndpoint that has created the Business Message.

Datatype: "[CBPR_RestrictedFINXMax35Text](#)" on page 268

Usage Guideline details

- on [camt.106.001.03/header/BusinessMessageIdentifier](#)
 Type changed to: [CBPR_RestrictedFINXMax35Text](#) on page 268

4.1.5 MessageDefinitionIdentifier

XML Tag: MsgDefIdr

Presence: [1..1]

Definition: Contains the MessageIdentifier that defines the BusinessMessage.

It must contain a MessageIdentifier published on the ISO 20022 website.

example camt.001.001.03.

Datatype: "Max35Text" on page 284

Usage Guideline details

- on camt.106.001.03/header/MessageDefinitionIdentifier
Single value: camt.106.001.03

4.1.6 BusinessService

XML Tag: BizSvc

Presence: [0..1]

Definition: Specifies the business service agreed between the two MessagingEndpoints under which rules this Business Message is exchanged.

To be used when there is a choice of processing services or processing service levels.

Example: E&I.

Datatype: "Max35Text" on page 284

Usage Guideline details

- on camt.106.001.03/header/BusinessService
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.106.001.03/header/BusinessService
Single value: swift.cbprplus.mlp.01

4.1.7 MarketPractice

XML Tag: MktPrctc

Presence: [0..1]

Definition: Specifies the market practice to which the message conforms. The market practices are a set of rules agreed between parties that restricts the usage of the messages in order to achieve better STP (Straight Through Processing) rates.

A market practice specification may also extend the underlying message specification by using extensions or supplementary data of this underlying message.

The **MktPrctc** block contains the following elements (see datatype "ImplementationSpecification1" on page 160 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Registry	<Regy>		[1..1]		161
	Identification	<Id>		[1..1]		161

4.1.8 CreationDate

XML Tag: CreDt

Presence: [1..1]

Definition: Date and time when this Business Message (header) was created.

Datatype: "CBPR_DateTime" on page 265

Usage Guideline details

- **on camt.106.001.03/.header/CreationDate**
Type changed to: CBPR_DateTime on page 265

4.1.9 BusinessProcessingDate

XML Tag: BizPrcgDt

Presence: [0..1]

Definition: Processing date and time indicated by the sender for the receiver of the business message. This date may be different from the date and time provided in the CreationDate.

Usage: Market practice or bilateral agreement should specify how this element should be used.

Datatype: "ISODatetime" on page 281

Usage Guideline details

- **This element(camt.106.001.03/.header/BusinessProcessingDate) is removed.**

4.1.10 CopyDuplicate

XML Tag: CpyDplct

Presence: [0..1]

Definition: Indicates whether the message is a Copy, a Duplicate or a copy of a duplicate of a previously sent ISO 20022 Message.

Datatype: "CopyDuplicate1Code" on page 270

4.1.11 PossibleDuplicate

XML Tag: PssblDplct

Presence: [0..1]

Definition: Flag indicating if the Business Message exchanged between the MessagingEndpoints is possibly a duplicate.

If the receiving MessagingEndpoint did not receive the original, then this Business Message should be processed as if it were the original.

If the receiving MessagingEndpoint did receive the original, then it should perform necessary actions to avoid processing this Business Message again.

This will guarantee business idempotent behaviour.

NOTE: this is named "PossResend" in FIX - this is an application level resend not a network level re-transmission.

Datatype: "YesNoIndicator" on page 289

4.1.12 Priority

XML Tag: Prty

Presence: [0..1]

Definition: Relative indication of the processing precedence of the message over a (set of) Business Messages with assigned priorities.

Datatype: "Priority2Code" on page 288

Usage Guideline details

- **on camt.106.001.03/.header/Priority**
Type changed to: Priority2Code on page 288

4.1.13 Signature

XML Tag: Sgntr

Presence: [0..1]

Definition: Contains the digital signature of the Business Entity authorised to sign this Business Message.

Usage Guideline details

- **This element(camt.106.001.03/.header/Signature) is removed.**

4.1.14 Related

XML Tag: Rltd

Presence: [0..*]

Definition: Specifies the Business Application Header(s) of the Business Message(s) to which this Business Message relates.

Can be used when replying to a query; can also be used when canceling or amending.

The **Rltd** block contains the following elements (see datatype "BusinessApplicationHeader5__1" on page 43 for details)

Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CharacterSet	<CharSet>		[0..1]		43
	From	<Fr>		[1..1]		43
	To	<To>		[1..1]		44
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]		44
	MessageDefinitionIdentifier	<MsgDefIdr>		[1..1]		45
	BusinessService	<BizSvc>		[0..1]		45
	CreationDate	<CreDt>		[1..1]		46
	CopyDuplicate	<CpyDplct>		[0..1]		46
	PossibleDuplicate	<PssblDplct>		[0..1]		46
	Priority	<Prty>		[0..1]		47
	Signature	<Sgntr>		[0..1]		47

Usage Guideline details

- on **camt.106.001.03/header/Related**

This element has change repeatability, the maximum occurrence has been changed to : 1

- on **camt.106.001.03/header/Related**

- **CBPR_Related_Business_Application_Header_TextualRule:**

If used, the Related BAH must transport the exact same information as in the BAH of the related message.

4.2 Payload Building Blocks

Note The following chapter identifies the building blocks of the CBPRPlus SR2026 (Combined) / CBPRPlus-camt.106.001.03_ChargesPaymentRequest_MultipleCharges payload definition.

Usage Guideline on Root Node

- on **camt.106.001.03/**

– **CBPR_Group Header_TotalChargesAmount_Currency_FormalRule:**

The currency used in every occurrence of GroupHeader/TotalCharges/TotalChargesAmount must be equal to the currency used in every occurrence of Charges/PerTransaction/Record/TotalChargesPerRecord/TotalChargesAmount.

For each [Full Message/Document/ChargesPaymentRequestV03], every occurrence of [ChargesPaymentRequestV03/GroupHeader/TotalCharges/TotalChargesAmount/Currency] must have the same value than every occurrence of [ChargesPaymentRequestV03/Charges/PerTransaction/Record/TotalChargesPerRecord/TotalChargesAmount/Currency]

• **on camt.106.001.03/**

– **CBPR_GroupHeader_TotalChargesAmount_Sum_FormalRule:**

TotalChargesAmount present in GroupHeader/TotalCharges must equal the sum of all occurrences of Charges/PerTransaction/Record/TotalChargesPerRecord/TotalChargesAmount.

For each [Full Message/Document/ChargesPaymentRequestV03], every occurrence of [ChargesPaymentRequestV03/GroupHeader/TotalCharges/TotalChargesAmount] value must be equal to the sum of all occurrences of the following element(s) [ChargesPaymentRequestV03/Charges/PerTransaction/Record/TotalChargesPerRecord/TotalChargesAmount]

• **on camt.106.001.03/**

– **CBPR_Group Header_NumberOfChargesRecords_FormalRule:**

The value of GroupHeader/TotalCharges/NumberOfChargesRecords must be equal to the number of occurrences of Charges/PerTransaction/Record.

For each [Full Message/Document/ChargesPaymentRequestV03], every occurrence of [ChargesPaymentRequestV03/GroupHeader/TotalCharges/NumberOfChargesRecords] value must be equal to the number of occurrences of [ChargesPaymentRequestV03/Charges/PerTransaction/Record]

4.2.1 GroupHeader

XML Tag: GrpHdr

Presence: [1..1]

Definition: Unique identification of the charges message.

The **GrpHdr** block contains the following elements (see datatype "GroupHeader130_1" on page 156 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	MessageIdentification	<MsgId>		[1..1]	⚠	157
	CreationDateTime	<CreDtTm>		[1..1]	⚠	157
	ChargesRequestor	<ChrgsRqstr>		[0..1]	🚫	157
	SettlementInstruction	<SttlmInstr>		[0..1]	🚫	158
	TotalCharges	<TtlChrgs>		[0..1]	M	158
	ChargesAccountAgent	<ChrgsAcctAgt>		[0..1]	⚠	159
	ChargesAccountAgentAccount	<ChrgsAcctAgtAcct>		[0..1]		160

4.2.2 Charges

XML Tag: Chrgs

Presence: [1..1]

Definition: Provides information on the charges to be paid by the charge bearer(s) related to the processing of the underlying transaction.

The **Chrgs** block contains the following elements (see datatype "Charges6Choice__1" on page 59 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Single	<Sngl>	{Or	[1..1]	🚫	59
	PerTransaction	<PerTx>	Or	[1..1]		60
	PerType	<PerTp>	Or}	[1..*]	🚫 ⚠	61

4.2.3 SupplementaryData

XML Tag: SplmtryData

Presence: [0..*]

Definition: Additional information that cannot be captured in the structured elements and/or any other specific block.

The **SplmtryData** block contains the following elements (see datatype "SupplementaryData1" on page 240 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PlaceAndName	<PlcAndNm>		[0..1]		240
	Envelope	<Envlp>		[1..1]		240

Usage Guideline details

- This element(**camt.106.001.03/SupplementaryData**) is removed.

5 Message Components

Note The following chapter identifies the message components.

5.1 AccountIdentification4Choice

Definition: Specifies the unique identification of an account as assigned by the account servicer.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	IBAN	<IBAN>	{Or	[1..1]		20
	Other	<Othr>	Or}	[1..1]		20

Used in element(s)

"Identification" on page 48

5.1.1 IBAN

XML Tag: IBAN

Presence: [1..1]

Definition: International Bank Account Number (IBAN) - identifier used internationally by financial institutions to uniquely identify the account of a customer. Further specifications of the format and content of the IBAN can be found in the standard ISO 13616 "Banking and related financial services - International Bank Account Number (IBAN)" version 1997-10-01, or later revisions.

Datatype: "IBAN2007Identifier" on page 280

5.1.2 Other

XML Tag: Othr

Presence: [1..1]

Definition: Unique identification of an account, as assigned by the account servicer, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericAccountIdentification1](#)" on page 142 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		142
	SchemeName	<SchmeNm>		[0..1]		142
	Issuer	<Issr>		[0..1]		143

5.2 AccountIdentification4Choice__1

Definition: Specifies the unique identification of an account as assigned by the account servicer.

🚫 Removed - 🚫 Partial Removed - ⬡ Ignored - ⬡ Partial Ignored - ⚠ Details below -
 M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	IBAN	<IBAN>	{Or	[1..1]		21
	Other	<Othr>	Or}	[1..1]		21

Used in element(s)

"Identification" on page 50

5.2.1 IBAN

XML Tag: IBAN

Presence: [1..1]

Definition: International Bank Account Number (IBAN) - identifier used internationally by financial institutions to uniquely identify the account of a customer. Further specifications of the format and content of the IBAN can be found in the standard ISO 13616 "Banking and related financial services - International Bank Account Number (IBAN)" version 1997-10-01, or later revisions.

Datatype: "IBAN2007Identifier" on page 280

5.2.2 Other

XML Tag: Othr

Presence: [1..1]

Definition: Unique identification of an account, as assigned by the account servicer, using an identification scheme.

The **Othr** block contains the following elements (see datatype "GenericAccountIdentification1__1" on page 143 for details)

🚫 Removed - 🚫 Partial Removed - ⬡ Ignored - ⬡ Partial Ignored - ⚠ Details below -
 M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]	⚠	143
	SchemeName	<SchmeNm>		[0..1]		144
	Issuer	<Issr>		[0..1]	⚠	145

5.3 AccountIdentification4Choice__2

Definition: Specifies the unique identification of an account as assigned by the account servicer.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	IBAN	<IBAN>	{Or	[1..1]		22
	Other	<Othr>	Or}	[1..1]		22

Used in element(s)

"Identification" on page 54

5.3.1 IBAN

XML Tag: IBAN

Presence: [1..1]

Definition: International Bank Account Number (IBAN) - identifier used internationally by financial institutions to uniquely identify the account of a customer. Further specifications of the format and content of the IBAN can be found in the standard ISO 13616 "Banking and related financial services - International Bank Account Number (IBAN)" version 1997-10-01, or later revisions.

Datatype: "IBAN2007Identifier" on page 280

5.3.2 Other

XML Tag: Othr

Presence: [1..1]

Definition: Unique identification of an account, as assigned by the account servicer, using an identification scheme.

The **Othr** block contains the following elements (see datatype "GenericAccountIdentification1__2" on page 146 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		146
	SchemeName	<SchmeNm>		[0..1]		146
	Issuer	<Issr>		[0..1]		146

5.4 AccountSchemeName1Choice

Definition: Sets of elements to identify a name of the identification scheme.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		23
	Proprietary	<Prtry>	Or}	[1..1]		23

Used in element(s)

"SchemeName" on page 142

5.4.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalAccountIdentification1Code" on page 273

5.4.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 284

5.5 AccountSchemeName1Choice__1

Definition: Sets of elements to identify a name of the identification scheme.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		23
	Proprietary	<Prtry>	Or}	[1..1]		23

Used in element(s)

"SchemeName" on page 144, "SchemeName" on page 146

5.5.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalAccountIdentification1Code" on page 273

5.5.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 268

Usage Guideline details

- on camt.106.001.03/Charges/PerTransaction/Record/ChargesAccountAgentAccount/Identification/Other/SchemeName/Proprietary
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on camt.106.001.03/Charges/PerType/Record/DebtorAgentAccount/Identification/Other/SchemeName/Proprietary
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on camt.106.001.03/Charges/Single/DebtorAgentAccount/Identification/Other/SchemeName/Proprietary
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on camt.106.001.03/Charges/PerTransaction/ChargesAccountAgentAccount/Identification/Other/SchemeName/Proprietary
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on camt.106.001.03/Charges/PerType/Record/ChargesAccountAgentAccount/Identification/Other/SchemeName/Proprietary
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on camt.106.001.03/Charges/PerTransaction/Record/DebtorAgentAccount/Identification/Other/SchemeName/Proprietary
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on camt.106.001.03/Charges/Single/ChargesAccountAgentAccount/Identification/Other/SchemeName/Proprietary
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on camt.106.001.03/Charges/PerType/ChargesAccountAgentAccount/Identification/Other/SchemeName/Proprietary
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on camt.106.001.03/GroupHeader/ChargesAccountAgentAccount/Identification/Other/SchemeName/Proprietary
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on camt.106.001.03/Charges/PerTransaction/Record/DebtorAccount/Identification/Other/SchemeName/Proprietary
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAgentAccount/Identification/Other/SchemeName/Proprietary
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)

- on [camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAccount/Identification/Other/SchemeName/Proprietary](#)

Type changed to: [CBPR_RestrictedFINXMax35Text](#) on page 268

5.6 AddressType3Choice

Definition: Choice of formats for the type of address.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		25
	Proprietary	<Prtry>	Or}	[1..1]		25

Used in element(s)

["AddressType" on page 185](#),
 ["AddressType" on page 188](#),
 ["AddressType" on page 192](#),
 ["AddressType" on page 204](#),
 ["AddressType" on page 217](#),
 ["AddressType" on page 223](#)

5.6.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Type of address expressed as a code.

Datatype: ["AddressType2Code" on page 261](#)

5.6.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Type of address expressed as a proprietary code.

The **Prtry** block contains the following elements (see datatype ["GenericIdentification30" on page 148](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		149
	Issuer	<Issr>		[1..1]		149
	SchemeName	<SchmeNm>		[0..1]		149

5.7 BranchAndFinancialInstitutionIdentification6__1

Definition: Unique and unambiguous identification of a financial institution or a branch of a financial institution.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		26
	BranchIdentification	<BrnchId>		[0..1]	🚫	26

Used in element(s)

"FinancialInstitutionIdentification" on page 169

5.7.1 FinancialInstitutionIdentification

XML Tag: FinInstnId

Presence: [1..1]

Definition: Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

The **FinInstnId** block contains the following elements (see datatype "[FinancialInstitutionIdentification18_1](#)" on page 118 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]	M	119
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		119
	LEI	<LEI>		[0..1]		120
	Name	<Nm>		[0..1]	🚫	120
	PostalAddress	<PstlAdr>		[0..1]	🚫	120
	Other	<Othr>		[0..1]	🚫	121

5.7.2 BranchIdentification

XML Tag: BrnchId

Presence: [0..1]

Definition: Identifies a specific branch of a financial institution.

Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

The **BrnchId** block contains the following elements (see datatype "[BranchData3](#)" on page 39 for details)

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		40
	LEI	<LEI>		[0..1]		40
	Name	<Nm>		[0..1]		40
	PostalAddress	<PstlAdr>		[0..1]		40

Usage Guideline details

- This element([camt.106.001.03/header/Related/To/FinancialInstitutionIdentification/BranchIdentification](#)) is removed.
- This element([camt.106.001.03/header/To/FinancialInstitutionIdentification/BranchIdentification](#)) is removed.
- This element([camt.106.001.03/header/Related/From/FinancialInstitutionIdentification/BranchIdentification](#)) is removed.
- This element([camt.106.001.03/header/From/FinancialInstitutionIdentification/BranchIdentification](#)) is removed.

5.8 BranchAndFinancialInstitutionIdentification8

Definition: Unique and unambiguous identification of a financial institution or a branch of a financial institution.

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		27
	BranchIdentification	<BrnchId>		[0..1]		28

Used in element(s)

["ChargesRequestor" on page 157](#), ["ChargesRequestor" on page 95](#), ["ChargesRequestor" on page 86](#), ["Creditor" on page 235](#), ["CreditorAgent" on page 234](#)

5.8.1 FinancialInstitutionIdentification

XML Tag: FinInstnId

Presence: [1..1]

Definition: Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

The **FinInstnId** block contains the following elements (see datatype "[FinancialInstitutionIdentification23](#)" on page 122 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		122
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		123
	LEI	<LEI>		[0..1]		123
	Name	<Nm>		[0..1]		123
	PostalAddress	<PstlAdr>		[0..1]		123
	Other	<Othr>		[0..1]		124

5.8.2 BranchIdentification

XML Tag: BrnchId

Presence: [0..1]

Definition: Identifies a specific branch of a financial institution.

Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

The **BrnchId** block contains the following elements (see datatype "[BranchData5](#)" on page 41 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		41
	LEI	<LEI>		[0..1]		41
	Name	<Nm>		[0..1]		42
	PostalAddress	<PstlAdr>		[0..1]		42

5.9 BranchAndFinancialInstitutionIdentification8__1

Definition: Unique and unambiguous identification of a financial institution or a branch of a financial institution.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		29
	BranchIdentification	<BrnchId>		[0..1]		31

Used in element(s)

"ChargesAccountAgent" on page 159, "ChargesRequestor" on page 70, "Creditor" on page 238, "CreditorAgent" on page 237, "DebtorAgent" on page 76

5.9.1 FinancialInstitutionIdentification

XML Tag: FinInstnId

Presence: [1..1]

Definition: Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

The **FinInstnId** block contains the following elements (see datatype "FinancialInstitutionIdentification23_1" on page 124 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		125
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		125
	LEI	<LEI>		[0..1]		125
	Name	<Nm>		[0..1]		126
	PostalAddress	<PstlAdr>		[0..1]		126
	Other	<Othr>		[0..1]		128

Usage Guideline details

- on camt.106.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification

– CBPR_Agent_Name_Postal_Address_FormaRule:

Name and Address must always be present together.

For each [Full Message/Document/ChargesPaymentRequestV03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification],
for each [FinancialInstitutionIdentification], if
at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] is (are) present
then

at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] must be present
 and for each [FinancialInstitutionIdentification], if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] must be present

- **on camt.106.001.03/GroupHeader/ChargesAccountAgent/FinancialInstitutionIdentification**

- **CBPR_Agent_Name_Postal_Address_FormaRule:**

Name and Address must always be present together.

For each [Full Message/Document/ChargesPaymentRequestV03/GroupHeader/ChargesAccountAgent/FinancialInstitutionIdentification],
 for each [FinancialInstitutionIdentification], if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] must be present
 and for each [FinancialInstitutionIdentification], if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] must be present

- **on camt.106.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification**

- **CBPR_Agent_Name_Postal_Address_FormaRule:**

Name and Address must always be present together.

For each [Full Message/Document/ChargesPaymentRequestV03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification],
 for each [FinancialInstitutionIdentification], if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] must be present
 and for each [FinancialInstitutionIdentification], if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] must be present

- **on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAgent/FinancialInstitutionIdentification**

- **CBPR_Agent_Name_Postal_Address_FormaRule:**

Name and Address must always be present together.

```

For each [Full Message/Document/ChargesPaymentRequestV03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAgent/FinancialInstitutionIdentification],
  for each [FinancialInstitutionIdentification], if
    at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] is (are) present
    then
      at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] must be present
      and for each [FinancialInstitutionIdentification], if
        at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] is (are) present
        then
          at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] must be present

```

- **on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/Creditor/FinancialInstitutionIdentification**

– **CBPR_Agent_Name_Postal_Address_FormaRule:**

Name and Address must always be present together.

```

For each [Full Message/Document/ChargesPaymentRequestV03/Charges/PerTransaction/Record/SettlementInstruction/Creditor/FinancialInstitutionIdentification],
  for each [FinancialInstitutionIdentification], if
    at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] is (are) present
    then
      at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] must be present
      and for each [FinancialInstitutionIdentification], if
        at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] is (are) present
        then
          at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] must be present

```

5.9.2 BranchIdentification

XML Tag: BrnchId

Presence: [0..1]

Definition: Identifies a specific branch of a financial institution.

Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

The **BrnchId** block contains the following elements (see datatype "[BranchData5](#)" on page 41 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		41
	LEI	<LEI>		[0..1]		41
	Name	<Nm>		[0..1]		42
	PostalAddress	<PstlAdr>		[0..1]		42

Usage Guideline details

- This element(camt.106.001.03/Charges/PerTransaction/Record/ChargesRequestor/BranchIdentification) is removed.
- This element(camt.106.001.03/GroupHeader/ChargesAccountAgent/BranchIdentification) is removed.
- This element(camt.106.001.03/Charges/PerTransaction/Record/DebtorAgent/BranchIdentification) is removed.
- This element(camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/Creditor-Agent/BranchIdentification) is removed.
- This element(camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/Creditor/BranchIdentification) is removed.

5.10 BranchAndFinancialInstitutionIdentification8__2

Definition: Unique and unambiguous identification of a financial institution or a branch of a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		32
	BranchIdentification	<BrnchId>		[0..1]		35

Used in element(s)

["ChargesAccountAgent" on page 100](#),
 ["ChargesAccountAgent" on page 78](#),
 ["ChargesAccountAgent" on page 82](#),
 ["DebtorAgent" on page 98](#),
 ["DebtorAgent" on page 89](#)

5.10.1 FinancialInstitutionIdentification

XML Tag: FinInstnId

Presence: [1..1]

Definition: Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

The **FinInstnId** block contains the following elements (see datatype "FinancialInstitutionIdentification23__2" on page 128 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		129
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		129
	LEI	<LEI>		[0..1]		129
	Name	<Nm>		[0..1]		130
	PostalAddress	<PstlAdr>		[0..1]		130
	Other	<Othr>		[0..1]		134

Usage Guideline details

- on camt.106.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification

- CBPR_AgentNamePostalAddress_FormalRule:

Name and Address must always be present together.

```

For each [Full Message/Document/ChargesPaymentRequestV03/Charges/PerType/Record/
DebtorAgent/FinancialInstitutionIdentification],
  for each [FinancialInstitutionIdentification], if
    at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] is (are) present
    then
      at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] must be present
      and for each [FinancialInstitutionIdentification], if
        at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] is (are) present
        then
          at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] must be present
  
```

- on camt.106.001.03/Charges/Single/ChargesAccountAgent/FinancialInstitutionIdentification

- CBPR_AgentNamePostalAddress_FormalRule:

Name and Address must always be present together.

```

For each [Full Message/Document/ChargesPaymentRequestV03/Charges/Single/ChargesAccountAgent/FinancialInstitutionIdentification],
  for each [FinancialInstitutionIdentification], if
    at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] is (are) present
    then
      at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] must be present
  
```

and for each [FinancialInstitutionIdentification], if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] must be present

- **on camt.106.001.03/Charges/PerTransaction/Record/ChargesAccountAgent/FinancialInstitutionIdentification**

– **CBPR_AgentNamePostalAddress_FormalRule:**

Name and Address must always be present together.

For each [Full Message/Document/ChargesPaymentRequestV03/Charges/PerTransaction/Record/ChargesAccountAgent/FinancialInstitutionIdentification],
 for each [FinancialInstitutionIdentification], if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] must be present
 and for each [FinancialInstitutionIdentification], if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] must be present

- **on camt.106.001.03/Charges/PerType/ChargesAccountAgent/FinancialInstitutionIdentification**

– **CBPR_AgentNamePostalAddress_FormalRule:**

Name and Address must always be present together.

For each [Full Message/Document/ChargesPaymentRequestV03/Charges/PerType/ChargesAccountAgent/FinancialInstitutionIdentification],
 for each [FinancialInstitutionIdentification], if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] must be present
 and for each [FinancialInstitutionIdentification], if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] must be present

- **on camt.106.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification**

– **CBPR_AgentNamePostalAddress_FormalRule:**

Name and Address must always be present together.

For each [Full Message/Document/ChargesPaymentRequestV03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification],

```

    for each [FinancialInstitutionIdentification], if
      at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] is (are) present
    then
      at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] must be present
    and for each [FinancialInstitutionIdentification], if
      at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] is (are) present
    then
      at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] must be present

```

5.10.2 BranchIdentification

XML Tag: BrnchId

Presence: [0..1]

Definition: Identifies a specific branch of a financial institution.

Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

The **BrnchId** block contains the following elements (see datatype "[BranchData5](#)" on page 41 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		41
	LEI	<LEI>		[0..1]		41
	Name	<Nm>		[0..1]		42
	PostalAddress	<PstlAdr>		[0..1]		42

Usage Guideline details

- This element(camt.106.001.03/Charges/PerType/ChargesAccountAgent/BranchIdentification) is removed.
- This element(camt.106.001.03/Charges/Single/ChargesAccountAgent/BranchIdentification) is removed.
- This element(camt.106.001.03/Charges/PerType/Record/DebtorAgent/BranchIdentification) is removed.
- This element(camt.106.001.03/Charges/PerTransaction/Record/ChargesAccountAgent/BranchIdentification) is removed.
- This element(camt.106.001.03/Charges/Single/DebtorAgent/BranchIdentification) is removed.

5.11 BranchAndFinancialInstitutionIdentification8__3

Definition: Unique and unambiguous identification of a financial institution or a branch of a financial institution.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
 M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]	⚠	36
	BranchIdentification	<BrnchId>		[0..1]	🚫	37

Used in element(s)

"ChargesAccountAgent" on page 65

5.11.1 FinancialInstitutionIdentification

XML Tag: FinInstnId

Presence: [1..1]

Definition: Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

The **FinInstnId** block contains the following elements (see datatype "FinancialInstitutionIdentification23__3" on page 135 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
 M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		135
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		136
	LEI	<LEI>		[0..1]		136
	Name	<Nm>		[0..1]		136
	PostalAddress	<PstlAdr>		[0..1]	⚠	136
	Other	<Othr>		[0..1]	🚫	138

Usage Guideline details

- on camt.106.001.03/Charges/PerTransaction/ChargesAccountAgent/FinancialInstitutionIdentification

– CBPR_AgentNamePostalAddress_FormalRule:

Name and Address must always be present together.

For each [Full Message/Document/ChargesPaymentRequestV03/Charges/PerTransaction/ChargesAccountAgent/FinancialInstitutionIdentification],
 for each [FinancialInstitutionIdentification], if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] must be present
 and for each [FinancialInstitutionIdentification], if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] must be present

5.11.2 BranchIdentification

XML Tag: BrnchId

Presence: [0..1]

Definition: Identifies a specific branch of a financial institution.

Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

The **BrnchId** block contains the following elements (see datatype "[BranchData5](#)" on page 41 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		41
	LEI	<LEI>		[0..1]		41
	Name	<Nm>		[0..1]		42
	PostalAddress	<PstAdr>		[0..1]		42

Usage Guideline details

- This element(camt.106.001.03/Charges/PerTransaction/ChargesAccountAgent/BranchIdentification) is removed.

5.12 BranchAndFinancialInstitutionIdentification8__4

Definition: Unique and unambiguous identification of a financial institution or a branch of a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		38
	BranchIdentification	<BrnchId>		[0..1]		39

Used in element(s)

"ChargesAccountAgent" on page 91

5.12.1 FinancialInstitutionIdentification

XML Tag: FinInstnId

Presence: [1..1]

Definition: Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

The **FinInstnId** block contains the following elements (see datatype "FinancialInstitutionIdentification23_4" on page 138 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		139
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		139
	LEI	<LEI>		[0..1]		139
	Name	<Nm>		[0..1]		139
	PostalAddress	<PstlAdr>		[0..1]		140
	Other	<Othr>		[0..1]		141

Usage Guideline details

- on camt.106.001.03/Charges/PerType/Record/ChargesAccountAgent/FinancialInstitutionIdentification
 - CBPR_AgentNamePostalAddress_FormalRule:

Name and Address must always be present together.

For each [Full Message/Document/ChargesPaymentRequestV03/Charges/PerType/Record/ChargesAccountAgent/FinancialInstitutionIdentification],
 for each [FinancialInstitutionIdentification], if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] must be present
 and for each [FinancialInstitutionIdentification], if

at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] must be present

5.12.2 BranchIdentification

XML Tag: BrnchId

Presence: [0..1]

Definition: Identifies a specific branch of a financial institution.

Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

The **BrnchId** block contains the following elements (see datatype "[BranchData5](#)" on page 41 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		41
	LEI	<LEI>		[0..1]		41
	Name	<Nm>		[0..1]		42
	PostalAddress	<PstAdr>		[0..1]		42

Usage Guideline details

- This element(camt.106.001.03/Charges/PerType/Record/ChargesAccountAgent/BranchIdentification) is removed.

5.13 BranchData3

Definition: Information that locates and identifies a specific branch of a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		40
	LEI	<LEI>		[0..1]		40
	Name	<Nm>		[0..1]		40
	PostalAddress	<PstAdr>		[0..1]		40

Used in element(s)

["BranchIdentification" on page 26](#)

5.13.1 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a branch of a financial institution.

Datatype: ["Max35Text" on page 284](#)

5.13.2 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identification for the branch of the financial institution.

Datatype: ["LEIIdentifier" on page 281](#)

5.13.3 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: ["Max140Text" on page 282](#)

5.13.4 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype ["PostalAddress24" on page 184](#) for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -

 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		185
	Department	<Dept>		[0..1]		185
	SubDepartment	<SubDept>		[0..1]		185
	StreetName	<StrtNm>		[0..1]		185
	BuildingNumber	<BldgNb>		[0..1]		185
	BuildingName	<BldgNm>		[0..1]		185
	Floor	<Flr>		[0..1]		186

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PostBox	<PstBx>		[0..1]		186
	Room	<Room>		[0..1]		186
	PostCode	<PstCd>		[0..1]		186
	TownName	<TwnNm>		[0..1]		186
	TownLocationName	<TwnLctnNm>		[0..1]		186
	DistrictName	<DstrctNm>		[0..1]		187
	CountrySubDivision	<CtrySubDvsn>		[0..1]		187
	Country	<Ctry>		[0..1]		187
	AddressLine	<AdrLine>		[0..7]		187

5.14 BranchData5

Definition: Information that locates and identifies a specific branch of a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		41
	LEI	<LEI>		[0..1]		41
	Name	<Nm>		[0..1]		42
	PostalAddress	<PstAdr>		[0..1]		42

Used in element(s)

["BranchIdentification" on page 28](#),
 ["BranchIdentification" on page 31](#),
 ["BranchIdentification" on page 35](#),
 ["BranchIdentification" on page 37](#),
 ["BranchIdentification" on page 39](#)

5.14.1 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a branch of a financial institution.

Datatype: ["Max35Text" on page 284](#)

5.14.2 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identification for the branch of the financial institution.

Datatype: "LEIIdentifier" on page 281

5.14.3 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "Max140Text" on page 282

5.14.4 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress27" on page 187 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		188
	CareOf	<CareOf>		[0..1]		188
	Department	<Dept>		[0..1]		189
	SubDepartment	<SubDept>		[0..1]		189
	StreetName	<StrtNm>		[0..1]		189
	BuildingNumber	<BldgNb>		[0..1]		189
	BuildingName	<BldgNm>		[0..1]		189
	Floor	<Flr>		[0..1]		189
	UnitNumber	<UnitNb>		[0..1]		190
	PostBox	<PstBx>		[0..1]		190
	Room	<Room>		[0..1]		190
	PostCode	<PstCd>		[0..1]		190
	TownName	<TwnNm>		[0..1]		190
	TownLocationName	<TwnLctnNm>		[0..1]		190
	DistrictName	<DstrctNm>		[0..1]		191
	CountrySubDivision	<CtrySubDvsn>		[0..1]		191
	Country	<Ctry>		[0..1]		191
	AddressLine	<AdrLine>		[0..7]		191

5.15 BusinessApplicationHeader5__1

Definition: Specifies the Business Application Header of the Business Message.

Can be used when replying to a query; can also be used when canceling or amending.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CharacterSet	<CharSet>		[0..1]		43
	From	<Fr>		[1..1]		43
	To	<To>		[1..1]		44
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]		44
	MessageDefinitionIdentifier	<MsgDefIdr>		[1..1]		45
	BusinessService	<BizSvc>		[0..1]		45
	CreationDate	<CreDt>		[1..1]		46
	CopyDuplicate	<CpyDplct>		[0..1]		46
	PossibleDuplicate	<PssblDplct>		[0..1]		46
	Priority	<Prty>		[0..1]		47
	Signature	<Sgntr>		[0..1]		47

Used in element(s)

"Related" on page 15

5.15.1 CharacterSet

XML Tag: CharSet

Presence: [0..1]

Definition: Contains the character set of the text-based elements used in the Business Message.

Datatype: "UnicodeChartsCode" on page 289

5.15.2 From

XML Tag: Fr

Presence: [1..1]

Definition: The sending MessagingEndpoint that has created this Business Message for the receiving MessagingEndpoint that will process this Business Message.

Note the sending MessagingEndpoint might be different from the sending address potentially contained in the transport header (as defined in the transport layer).

The **Fr** block contains the following elements (see datatype "[Party44Choice__1](#)" on page 168 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]	🚫	169
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		169

5.15.3 To

XML Tag: To

Presence: [1..1]

Definition: The MessagingEndpoint designated by the sending MessagingEndpoint to be the recipient who will ultimately process this Business Message.

Note the receiving MessagingEndpoint might be different from the receiving address potentially contained in the transport header (as defined in the transport layer).

The **To** block contains the following elements (see datatype "[Party44Choice__1](#)" on page 168 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]	🚫	169
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		169

5.15.4 BusinessMessageIdentifier

XML Tag: BizMsgIdr

Presence: [1..1]

Definition: Unambiguously identifies the Business Message to the MessagingEndpoint that has created the Business Message.

Datatype: "[CBPR_RestrictedFINXMax35Text](#)" on page 268

Usage Guideline details

- on [camt.106.001.03/header/Related/BusinessMessageIdentifier](#)
Type changed to: [CBPR_RestrictedFINXMax35Text](#) on page 268
- on [camt.106.001.03/header/Related/BusinessMessageIdentifier](#)
 – **CBPR_BusinessMessageIdentifier_TextualRule:**

The Business Message Identifier is the unique identifier of the Business Message instance that is being transported with this header, as defined by the sending application or system.

Must contain the Message Identification element from the Group Header of the underlying message, where available (as is typically the case with pacs, pain, and camt messages, for example). If Message Identification is not available in the underlying message, then this element must contain the unique identifier of the Business Message instance.

5.15.5 MessageDefinitionIdentifier

XML Tag: MsgDefIdr

Presence: [1..1]

Definition: Contains the MessageIdentifier that defines the BusinessMessage.

It must contain a MessageIdentifier published on the ISO 20022 website.

example camt.001.001.03.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 268](#)

Usage Guideline details

- on **camt.106.001.03/header/Related/MessageDefinitionIdentifier**

Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)

- on **camt.106.001.03/header/Related/MessageDefinitionIdentifier**

– **CBPR_MessageDefinitionIdentifier_TextualRule:**

The Message Definition Identifier of the Business Message instance that is being transported with this header. In general, it must be formatted exactly as it appears in the namespace of the Business Message instance.

5.15.6 BusinessService

XML Tag: BizSvc

Presence: [0..1]

Definition: Specifies the business service agreed between the two MessagingEndpoints under which rules this Business Message is exchanged.

To be used when there is a choice of processing services or processing service levels.

Example: E&I.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 268](#)

Usage Guideline details

- on **camt.106.001.03/header/Related/BusinessService**

Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)

- on **camt.106.001.03/.header/Related/BusinessService**

- **CBPR_RelatedBAHBusinessService_TextualRule:**

If related BAH is present, then it is recommended to transport the element Business Service.

5.15.7 **CreationDate**

XML Tag: CreDt

Presence: [1..1]

Definition: Date and time when this Business Message (header) was created.

Note Times must be normalized, using the "Z" annotation.

Datatype: "CBPR_DateTime" on page 265

Usage Guideline details

- on **camt.106.001.03/.header/Related/CreationDate**

Type changed to: CBPR_DateTime on page 265

5.15.8 **CopyDuplicate**

XML Tag: CpyDplct

Presence: [0..1]

Definition: Indicates whether the message is a Copy, a Duplicate or a copy of a duplicate of a previously sent ISO 20022 Message.

Datatype: "CopyDuplicate1Code" on page 270

5.15.9 **PossibleDuplicate**

XML Tag: PssblDplct

Presence: [0..1]

Definition: Flag indicating if the Business Message exchanged between the MessagingEndpoints is possibly a duplicate.

If the receiving MessagingEndpoint did not receive the original, then this Business Message should be processed as if it were the original.

If the receiving MessagingEndpoint did receive the original, then it should perform necessary actions to avoid processing this Business Message again.

This will guarantee business idempotent behaviour.

NOTE: this is named "PossResend" in FIX - this is an application level resend not a network level re-transmission.

Datatype: ["YesNoIndicator" on page 289](#)

Usage Guideline details

- This element([camt.106.001.03/header/Related/PossibleDuplicate](#)) is removed.

5.15.10 Priority

XML Tag: Prty

Presence: [0..1]

Definition: Relative indication of the processing precedence of the message over a (set of) Business Messages with assigned priorities.

Datatype: ["Priority2Code" on page 288](#)

Usage Guideline details

- on [camt.106.001.03/header/Related/Priority](#)
Type changed to: [Priority2Code on page 288](#)

5.15.11 Signature

XML Tag: Sgntr

Presence: [0..1]

Definition: Contains the digital signature of the Business Entity authorised to sign this Business Message.

Usage Guideline details

- This element([camt.106.001.03/header/Related/Signature](#)) is removed.

5.16 CashAccount40

Definition: Provides the details to identify an account.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		48
	Type	<Tp>		[0..1]		48
	Currency	<Ccy>		[0..1]		49

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		49
	Proxy	<Prxy>		[0..1]		49

Rules

R14 IdentificationOrProxyPresenceRule ✓

Identification must be present or Proxy must be present. Both may be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00498
- *Error Text:* Missing account identification or account proxy.

Guidelines

1. IdentificationAndProxyGuideline

If the account identification is not defined through a conventional identification such as an email address or a mobile number, then the proxy element should be used for the identification of the account.

Used in element(s)

"CreditorAccount" on page 235, "CreditorAgentAccount" on page 235, "DebtorAccount" on page 98, "DebtorAccount" on page 89

5.16.1 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification for the account between the account owner and the account servicer.

The **Id** block contains the following elements (see datatype "AccountIdentification4Choice" on page 20 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	IBAN	<IBAN>	{Or	[1..1]		20
	Other	<Othr>	Or}	[1..1]		20

5.16.2 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the nature, or use of the account.

The **Tp** block contains the following elements (see datatype "[CashAccountType2Choice](#)" on page 56 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		56
	Proprietary	<Prtry>	Or}	[1..1]		56

5.16.3 Currency

XML Tag: Ccy

Presence: [0..1]

Definition: Identification of the currency in which the account is held.

Usage: Currency should only be used in case one and the same account number covers several currencies

and the initiating party needs to identify which currency needs to be used for settlement on the account.

Datatype: "[ActiveOrHistoricCurrencyCode](#)" on page 260

5.16.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name of the account, as assigned by the account servicing institution, in agreement with the account owner in order to provide an additional means of identification of the account.

Usage: The account name is different from the account owner name. The account name is used in certain user communities to provide a means of identifying the account, in addition to the account owner's identity and the account number.

Datatype: "[Max70Text](#)" on page 285

5.16.5 Proxy

XML Tag: Prxy

Presence: [0..1]

Definition: Specifies an alternate assumed name for the identification of the account.

The **Prxy** block contains the following elements (see datatype "[ProxyAccountIdentification1](#)" on page 229 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		229
	Identification	<Id>		[1..1]		229

5.17 CashAccount40__1

Definition: Provides the details to identify an account.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		50
	Type	<Tp>		[0..1]		51
	Currency	<Ccy>		[0..1]		52
	Name	<Nm>		[0..1]		52
	Proxy	<Prxy>		[0..1]		53

Rules

R22 IdentificationOrProxyPresenceRule ✓

Identification must be present or Proxy must be present. Both may be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00498
- *Error Text:* Missing account identification or account proxy.

Guidelines

1. IdentificationAndProxyGuideline

If the account identification is not defined through a conventional identification such as an email address or a mobile number, then the proxy element should be used for the identification of the account.

Used in element(s)

["ChargesAccountAgentAccount" on page 160](#),
 ["ChargesAccountAgentAccount" on page 101](#),
 ["ChargesAccountAgentAccount" on page 66](#),
 ["ChargesAccountAgentAccount" on page 79](#),
 ["ChargesAccountAgentAccount" on page 83](#),
 ["ChargesAccountAgentAccount" on page 92](#),
 ["CreditorAccount" on page 239](#),
 ["CreditorAgentAccount" on page 238](#),
 ["DebtorAccount" on page 76](#),
 ["DebtorAgentAccount" on page 77](#),
 ["DebtorAgentAccount" on page 90](#)

5.17.1 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification for the account between the account owner and the account servicer.

The **Id** block contains the following elements (see datatype "[AccountIdentification4Choice__1](#)" on [page 21](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	IBAN	<IBAN>	{Or	[1..1]		21
	Other	<Othr>	Or}	[1..1]		21

Usage Guideline details

- on camt.106.001.03/Charges/PerTransaction/Record/ChargesAccountAgentAccount/Identification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.106.001.03/Charges/PerTransaction/Record/DebtorAgentAccount/Identification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.106.001.03/Charges/Single/ChargesAccountAgentAccount/Identification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.106.001.03/GroupHeader/ChargesAccountAgentAccount/Identification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.106.001.03/Charges/PerTransaction/ChargesAccountAgentAccount/Identification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAgentAccount/Identification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAccount/Identification**
This element is now mandatory, the minimum occurrence has been changed to : 1

5.17.2 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the nature, or use of the account.

The **Tp** block contains the following elements (see datatype "[CashAccountType2Choice__1](#)" on [page 57](#) for details)

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		57
	Proprietary	<Prtry>	Or}	[1..1]		57

5.17.3 Currency

XML Tag: Ccy

Presence: [0..1]

Definition: Identification of the currency in which the account is held.

Usage: Currency should only be used in case one and the same account number covers several currencies

and the initiating party needs to identify which currency needs to be used for settlement on the account.

Datatype: "ActiveOrHistoricCurrencyCode" on page 260

5.17.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name of the account, as assigned by the account servicing institution, in agreement with the account owner in order to provide an additional means of identification of the account.

Usage: The account name is different from the account owner name. The account name is used in certain user communities to provide a means of identifying the account, in addition to the account owner's identity and the account number.

Datatype: "CBPR_RestrictedFINXMax70Text" on page 269

Usage Guideline details

- on camt.106.001.03/Charges/PerType/ChargesAccountAgentAccount/Name**
 Type changed to: CBPR_RestrictedFINXMax70Text on page 269
- on camt.106.001.03/GroupHeader/ChargesAccountAgentAccount/Name**
 Type changed to: CBPR_RestrictedFINXMax70Text on page 269
- on camt.106.001.03/Charges/PerTransaction/Record/ChargesAccountAgentAccount/Name**
 Type changed to: CBPR_RestrictedFINXMax70Text on page 269
- on camt.106.001.03/Charges/PerTransaction/Record/DebtorAgentAccount/Name**
 Type changed to: CBPR_RestrictedFINXMax70Text on page 269
- on camt.106.001.03/Charges/PerTransaction/ChargesAccountAgentAccount/Name**

Type changed to: [CBPR_RestrictedFINXMax70Text on page 269](#)

- on [camt.106.001.03/Charges/PerType/Record/ChargesAccountAgentAccount/Name](#)

Type changed to: [CBPR_RestrictedFINXMax70Text on page 269](#)

- on [camt.106.001.03/Charges/PerType/Record/DebtorAgentAccount/Name](#)

Type changed to: [CBPR_RestrictedFINXMax70Text on page 269](#)

- on [camt.106.001.03/Charges/Single/ChargesAccountAgentAccount/Name](#)

Type changed to: [CBPR_RestrictedFINXMax70Text on page 269](#)

- on [camt.106.001.03/Charges/PerTransaction/Record/DebtorAccount/Name](#)

Type changed to: [CBPR_RestrictedFINXMax70Text on page 269](#)

- on [camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAgentAccount/Name](#)

Type changed to: [CBPR_RestrictedFINXMax70Text on page 269](#)

- on [camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAccount/Name](#)

Type changed to: [CBPR_RestrictedFINXMax70Text on page 269](#)

5.17.5 Proxy

XML Tag: Prxy

Presence: [0..1]

Definition: Specifies an alternate assumed name for the identification of the account.

The **Prxy** block contains the following elements (see datatype "[ProxyAccountIdentification1__1](#)" on [page 229](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		230
	Identification	<Id>		[1..1]		230

5.18 CashAccount40__2

Definition: Provides the details to identify an account.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		54

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		55
	Currency	<Ccy>		[0..1]		55
	Name	<Nm>		[0..1]		55
	Proxy	<Prxy>		[0..1]		56

Rules

R23 IdentificationOrProxyPresenceRule ✓

Identification must be present or Proxy must be present. Both may be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00498
- *Error Text:* Missing account identification or account proxy.

Guidelines

1. IdentificationAndProxyGuideline

If the account identification is not defined through a conventional identification such as an email address or a mobile number, then the proxy element should be used for the identification of the account.

Used in element(s)

"DebtorAgentAccount" on page 99

5.18.1 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification for the account between the account owner and the account servicer.

The **Id** block contains the following elements (see datatype "AccountIdentification4Choice__2" on page 21 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	IBAN	<IBAN>	{Or	[1..1]		22
	Other	<Othr>	Or}	[1..1]		22

Usage Guideline details

- **on camt.106.001.03/Charges/Single/DebtorAgentAccount/Identification**

This element is now mandatory, the minimum occurrence has been changed to : 1

5.18.2 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the nature, or use of the account.

The **Tp** block contains the following elements (see datatype "[CashAccountType2Choice__1](#)" on [page 57](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		57
	Proprietary	<Prtry>	Or}	[1..1]		57

5.18.3 Currency

XML Tag: Ccy

Presence: [0..1]

Definition: Identification of the currency in which the account is held.

Usage: Currency should only be used in case one and the same account number covers several currencies

and the initiating party needs to identify which currency needs to be used for settlement on the account.

Datatype: "[ActiveOrHistoricCurrencyCode](#)" on [page 260](#)

5.18.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name of the account, as assigned by the account servicing institution, in agreement with the account owner in order to provide an additional means of identification of the account.

Usage: The account name is different from the account owner name. The account name is used in certain user communities to provide a means of identifying the account, in addition to the account owner's identity and the account number.

Datatype: "[CBPR_RestrictedFINXMax70Text](#)" on [page 269](#)

Usage Guideline details

- on camt.106.001.03/Charges/Single/DebtorAgentAccount/Name
Type changed to: CBPR_RestrictedFINXMax70Text on page 269

5.18.5 Proxy

XML Tag: Prxy

Presence: [0..1]

Definition: Specifies an alternate assumed name for the identification of the account.

The **Prxy** block contains the following elements (see datatype "ProxyAccountIdentification1__1" on page 229 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		230
	Identification	<Id>		[1..1]		230

5.19 CashAccountType2Choice

Definition: Nature or use of the account.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		56
	Proprietary	<Prtry>	Or}	[1..1]		56

Used in element(s)

"Type" on page 48

5.19.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Account type, in a coded form.

Datatype: "ExternalCashAccountType1Code" on page 274

5.19.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Nature or use of the account in a proprietary form.

Datatype: ["Max35Text" on page 284](#)

5.20 CashAccountType2Choice__1

Definition: Nature or use of the account.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		57
	Proprietary	<Prtry>	Or}	[1..1]		57

Used in element(s)

["Type" on page 51](#), ["Type" on page 55](#)

5.20.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Account type, in a coded form.

Datatype: ["ExternalCashAccountType1Code" on page 274](#)

5.20.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Nature or use of the account in a proprietary form.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 268](#)

Usage Guideline details

- on [camt.106.001.03/Charges/PerType/Record/ChargesAccountAgentAccount/Type/Proprietary](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on [camt.106.001.03/Charges/PerTransaction/ChargesAccountAgentAccount/Type/Proprietary](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on [camt.106.001.03/Charges/PerType/Record/DebtorAgentAccount/Type/Proprietary](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on [camt.106.001.03/Charges/PerTransaction/Record/DebtorAgentAccount/Type/Proprietary](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)

- on camt.106.001.03/Charges/PerTransaction/Record/ChargesAccountAgentAccount/Type/Proprietary
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on camt.106.001.03/GroupHeader/ChargesAccountAgentAccount/Type/Proprietary
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on camt.106.001.03/Charges/Single/ChargesAccountAgentAccount/Type/Proprietary
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on camt.106.001.03/Charges/PerType/ChargesAccountAgentAccount/Type/Proprietary
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on camt.106.001.03/Charges/Single/DebtorAgentAccount/Type/Proprietary
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on camt.106.001.03/Charges/PerTransaction/Record/DebtorAccount/Type/Proprietary
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAgentAccount/Type/Proprietary
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAccount/Type/Proprietary
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)

5.21 ChargeType3Choice

Definition: Specifies the charge type.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		58
	Proprietary	<Prtry>	Or}	[1..1]		59

Used in element(s)

["Type" on page 101](#), ["Type" on page 63](#), ["Type" on page 84](#)

5.21.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Charge type, in a coded form.

Datatype: ["ExternalChargeType1Code" on page 275](#)

5.21.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Type of charge in a proprietary form, as defined by the issuer.

The **Prtry** block contains the following elements (see datatype "[GenericIdentification3](#)" on page 148 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		148
	Issuer	<Issr>		[0..1]		148

Usage Guideline details

- This element([camt.106.001.03/Charges/PerTransaction/Record/ChargesBreakdown/Type/Proprietary](#)) is removed.
- This element([camt.106.001.03/Charges/PerType/Type/Proprietary](#)) is removed.
- This element([camt.106.001.03/Charges/Single/Type/Proprietary](#)) is removed.

5.22 Charges6Choice__1

Definition: Provides information on the charges to be paid by the charge bearer(s) related to the processing of the underlying transaction.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Single	<Sngl>	{Or	[1..1]		59
	PerTransaction	<PerTx>	Or	[1..1]		60
	PerType	<PerTp>	Or}	[1..*]	 	61

Used in element(s)

["Charges" on page 18](#)

5.22.1 Single

XML Tag: Sngl

Presence: [1..1]

Definition: Charges related to a single payment transaction.

The **Sngl** block contains the following elements (see datatype "ChargesRecord12__1" on page 93 for details)

Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ChargesIdentification	<ChrgsId>		[0..1]		94
	RecordIdentification	<RcrdId>		[0..1]		94
	ChargesRequestor	<ChrgsRqstr>		[0..1]		95
	SettlementInstruction	<SttlInstr>		[0..1]		95
	UnderlyingTransaction	<UndrlygTx>		[1..1]		96
	Amount	<Amt>		[1..1]		96
	CreditDebitIndicator	<CdtDbtInd>		[0..1]		97
	ValueDate	<ValDt>		[0..1]		97
	Debtor	<Dbtr>		[0..1]		97
	DebtorAccount	<DbtrAcct>		[0..1]		98
	DebtorAgent	<DbtrAgt>		[0..1]		98
	DebtorAgentAccount	<DbtrAgtAcct>		[0..1]		99
	ChargesAccountAgent	<ChrgsAcctAgt>		[0..1]		100
	ChargesAccountAgentAccount	<ChrgsAcctAgtAcct>		[0..1]		101
	Type	<Tp>		[0..1]	M	101
	InstructionForInstructedAgent	<InstrForInstAgt>		[0..1]		102
	AdditionalInformation	<AddtlInf>		[0..1]		102

Usage Guideline details

- This element(camt.106.001.03/Charges/Single) is removed.

5.22.2 PerTransaction

XML Tag: PerTx

Presence: [1..1]

Definition: Charges broken down per payment transaction.

The **PerTx** block contains the following elements (see datatype "ChargesPerTransaction6__1" on page 63 for details)

Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ChargesIdentification	<ChrgsId>		[0..1]	M 	64
	TotalChargesPerTransaction	<TtlChrgsPerTx>		[0..1]		65
	ChargesAccountAgent	<ChrgsAcctAgt>		[0..1]	 	65
	ChargesAccountAgentAccount	<ChrgsAcctAgtAcct>		[0..1]		66
	Record	<Rcrd>		[1..*]		67
	AdditionalInformation	<AddtlInf>		[0..1]		69

5.22.3 PerType

XML Tag: PerTp

Presence: [1..*]

Definition: Charges broken down per type of charges.

The **PerTp** block contains the following elements (see datatype "[ChargesPerType6__1](#)" on page 80 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ChargesIdentification	<ChrgsId>		[0..1]		81
	TotalChargesPerChargeType	<TtlChrgsPerChrgTp>		[0..1]		81
	ChargesAccountAgent	<ChrgsAcctAgt>		[0..1]		82
	ChargesAccountAgentAccount	<ChrgsAcctAgtAcct>		[0..1]		83
	Type	<Tp>		[1..1]		84
	Record	<Rcrd>		[1..*]		84
	AdditionalInformation	<AddtlInf>		[0..1]		85

Usage Guideline details

- This element([camt.106.001.03/Charges/PerType](#)) is removed.
- on [camt.106.001.03/Charges/PerType](#)

- **CBPR_NumberOfChargesRecords_FormalRule:**

The NumberOfChargesRecords must be equal to the number of occurrences of Record.

For each [Full Message/Document/ChargesPaymentRequestV03/Charges/PerType], every occurrence of [PerType/TotalChargesPerChargeType/NumberOfChargesRecords] value must be equal to the number of occurrences of [PerType/Record]

5.23 ChargesBreakdown1__1

Definition: Provides a breakdown of the charges per type.

❌ Removed - ❌ Partial Removed - ⬡ Ignored - ⬡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Amount	<Amt>		[1..1]	⚠	62
	CreditDebitIndicator	<CdtDbtInd>		[0..1]	M	62
	Type	<Tp>		[0..1]	M	63

Used in element(s)

"ChargesBreakdown" on page 73

5.23.1 Amount

XML Tag: Amt

Presence: [1..1]

Definition: Amount of transaction charges to be paid by the charge bearer.

Datatype: "CBPR_Amount__1" on page 264

Usage Guideline details

- on camt.106.001.03/Charges/PerTransaction/Record/ChargesBreakdown/Amount
Type changed to: CBPR_Amount on page 263

5.23.2 CreditDebitIndicator

XML Tag: CdtDbtInd

Presence: [0..1]

Definition: Indicates whether the charges amount is a credit or a debit amount.

Usage: A zero amount is considered to be a credit.

Datatype: "CreditDebitCode" on page 272

Usage Guideline details

- on camt.106.001.03/Charges/PerTransaction/Record/ChargesBreakdown/CreditDebitIndicator
This element is now mandatory, the minimum occurrence has been changed to : 1

5.23.3 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the type of charge.

The **Tp** block contains the following elements (see datatype "ChargeType3Choice" on page 58 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		58
	Proprietary	<Prtry>	Or}	[1..1]		59

Usage Guideline details

- on camt.106.001.03/Charges/PerTransaction/Record/ChargesBreakdown/Type
This element is now mandatory, the minimum occurrence has been changed to : 1

5.24 ChargesPerTransaction6__1

Definition: Provides information on the charges related to the payment transaction.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ChargesIdentification	<ChrgsId>		[0..1]	 	64
	TotalChargesPerTransaction	<TtlChrgsPerTx>		[0..1]		65
	ChargesAccountAgent	<ChrgsAcctAgt>		[0..1]	 	65
	ChargesAccountAgentAccount	<ChrgsAcctAgtAcct>		[0..1]		66
	Record	<Rcrd>		[1..*]		67
	AdditionalInformation	<AddtlInf>		[0..1]		69

Rules

R24 ChargesAccountAgent2Rule ✓

When Record/ChargesAccountAgent is present or Record/ChargesAccountAgentAccount is present then ChargesAccountAgent must be absent and ChargesAccountAgentAccount must be absent.

Error handling:

– Error severity: Fatal

- *Error Code:* X00641
- *Error Text:* Missing charges account

R25 ChargesAccountAgentRule ✓

When ChargesAccountAgent is present or ChargesAccountAgentAccount is present then Record/ChargesAccountAgent must be absent and Record/ChargesAccountAgentAccount must be absent.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00639
- *Error Text:* Missing charges account

Used in element(s)

"PerTransaction" on page 60

5.24.1 ChargesIdentification

XML Tag: ChrgsId

Presence: [0..1]

Definition: Unique and unambiguous identification of the charges information for reconciliation purpose.

Usage: this identification shall be used as the end-to-end identification in the resulting message for the payment of the charges, to allow for automated reconciliation.

Datatype: "CBPR_RestrictedFINXMax16Text" on page 266

Usage Guideline details

- **on camt.106.001.03/Charges/PerTransaction/ChargesIdentification**

This element is now mandatory, the minimum occurrence has been changed to : 1

- **on camt.106.001.03/Charges/PerTransaction/ChargesIdentification**

Type changed to: CBPR_RestrictedFINXMax16Text on page 266

- **on camt.106.001.03/Charges/PerTransaction/ChargesIdentification**

- **CBPR_ChargeIdentification_FormalRule:**

This element must not start or end with a slash '/' and must not contain two consecutive slashes '//'.

For each [Full Message/Document/ChargesPaymentRequestV03/Charges/PerTransaction/ChargesIdentification],
the value of every occurrence of [ChargesIdentification] must not comply with the following XML pattern : `'(/.*)|(.*/)|(.*/.*)'`

5.24.2 TotalChargesPerTransaction

XML Tag: TtlChrgsPerTx

Presence: [0..1]

Definition: Total charges claimed for the transaction.

The **TtlChrgsPerTx** block contains the following elements (see datatype "[TotalCharges7](#)" on page 240 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NumberOfChargesRecords	<NbOfChrgsRcrds>		[1..1]		241
	ControlSum	<CtrlSum>		[0..1]		241
	TotalChargesAmount	<TtlChrgsAmt>		[0..1]		241
	CreditDebitIndicator	<CdtDbtInd>		[0..1]		241

Usage Guideline details

- This element([camt.106.001.03/Charges/PerTransaction/TotalChargesPerTransaction](#)) is removed.

5.24.3 ChargesAccountAgent

XML Tag: ChrgsAcctAgt

Presence: [0..1]

Definition: Agent that services the charges account.

Usage: this element should be used where the charge being claimed does not relate to the processing of a payment transaction e.g. it relates to an investigation or other process. This identifies the agent that services the account from which charges are to be settled from.

The **ChrgsAcctAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification8__3](#)" on page 36 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		36
	BranchIdentification	<BrnchId>		[0..1]		37

Usage Guideline details

- This element([camt.106.001.03/Charges/PerTransaction/ChargesAccountAgent](#)) is removed.

- **on camt.106.001.03/Charges/PerTransaction/ChargesAccountAgent**
 - **CBPR_Agent_Option2_TextualRule:**

(Clearing Code OR LEI) AND (Name AND (Unstructured postal address OR [Structured postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.
- **on camt.106.001.03/Charges/PerTransaction/ChargesAccountAgent**
 - **CBPR_Agent_Option1_TextualRule:**

BICFI, complemented optionally with a LEI (preferred option)
- **on camt.106.001.03/Charges/PerTransaction/ChargesAccountAgent**
 - **CBPR_Co-existence_PostalAddress_TextualRule:**

Address Line (Unstructured Address) remains available only for cases when the payment is initiated in FIN, or by an MI, during coexistence only. The Structured PostalAddress remains the preferred option.

Therefore:

 - If a payment is initiated on FIN, or by an MI, and the postal address is unstructured, the outgoing ISO 20022 message will transport unstructured postal address, up to the Creditor Agent.
 - If a payment is initiated in ISO 20022, postal address must be structured.
- **on camt.106.001.03/Charges/PerTransaction/ChargesAccountAgent**
 - **CBPR_Agent_Option3_TextualRule:**

Name AND (Unstructured OR [Structured postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.
- **on camt.106.001.03/Charges/PerTransaction/ChargesAccountAgent**
 - **CBPR_Agent_National_only_TextualRule:**

Whenever Debtor Agent, Creditor Agent and all agents in between are located within the same country, the clearing code only may be used.

5.24.4 ChargesAccountAgentAccount

XML Tag: ChrgsAcctAgtAcct

Presence: [0..1]

Definition: Account of the agent that services the charges account.

Usage: this element should be used where the charge being claimed does not relate to the processing of a payment transaction e.g. it relates to an investigation or other process. This identifies the account from which charges are to be settled from.

The **ChrgsAcctAgtAcct** block contains the following elements (see datatype "CashAccount40__1" on page 50 for details)

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		50
	Type	<Tp>		[0..1]		51
	Currency	<Ccy>		[0..1]		52
	Name	<Nm>		[0..1]		52
	Proxy	<Prxy>		[0..1]		53

Usage Guideline details

- This element([camt.106.001.03/Charges/PerTransaction/ChargesAccountAgentAccount](#)) is removed.

5.24.5 Record

XML Tag: Rcrd

Presence: [1..*]

Definition: Itemised charges record per transaction.

The **Rcrd** block contains the following elements (see datatype "[ChargesPerTransactionRecord6__1](#)" on [page 69](#) for details)

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	RecordIdentification	<RcrdId>		[0..1]		70
	ChargesRequestor	<ChrgsRqstr>		[0..1]		70
	SettlementInstruction	<SttlInstr>		[0..1]		71
	UnderlyingTransaction	<UndrlygTx>		[1..1]		72
	TotalChargesPerRecord	<TtlChrgsPerRcrd>		[0..1]		73
	ChargesBreakdown	<ChrgsBrkdown>		[1..*]		73
	ValueDate	<ValDt>		[0..1]		74
	Debtor	<Dbtr>		[0..1]		74
	DebtorAccount	<DbtrAcct>		[0..1]		76
	DebtorAgent	<DbtrAgt>		[0..1]		76
	DebtorAgentAccount	<DbtrAgtAcct>		[0..1]		77
	ChargesAccountAgent	<ChrgsAcctAgt>		[0..1]		78

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ChargesAccountAgentAccount	<ChrgsAcctAgtAcct>		[0..1]		79
	InstructionForInstructedAgent	<InstrForInstdAgt>		[0..1]		80
	AdditionalInformation	<AddtlInf>		[0..1]		80

Usage Guideline details

- on camt.106.001.03/Charges/PerTransaction/Record

- CBPR_Record_ChargesBreakdownAmount_Currency_FormalRule:

The currency used in every occurrence of Record/TotalChargesPerRecord/TotalChargesAmount must be equal to the currency used in every occurrence of Record/ChargesBreakdown/Amount.

For each [Full Message/Document/ChargesPaymentRequestV03/Charges/PerTransaction/Record], every occurrence of [Record/TotalChargesPerRecord/TotalChargesAmount/Currency] value must be equal to every occurrence of [Record/ChargesBreakdown/Amount/Currency] value

- on camt.106.001.03/Charges/PerTransaction/Record

- CBPR_Record_TotalChargesAmount_Sum_FormalRule:

TotalChargesAmount present in Record/TotalChargesPerRecord must equal the sum of all occurrences of Record/ChargesBreakdown/Amount.

For each [Full Message/Document/ChargesPaymentRequestV03/Charges/PerTransaction/Record], every occurrence of [Record/TotalChargesPerRecord/TotalChargesAmount] value must be equal to the sum of all occurrences of the following element(s) [Record/ChargesBreakdown/Amount]

- on camt.106.001.03/Charges/PerTransaction/Record

- CBPR_Record_MessageNameIdentification_InstructionIdentification_FormalRule:

If "Message Name Identification" is populated with pacs.008 or pacs.009 or MT103/202/205, then InstructionIdentification is mandatory.

For each [Full Message/Document/ChargesPaymentRequestV03/Charges/PerTransaction/Record], if the value of every occurrence of [Record/UnderlyingTransaction/MessageNameIdentification] complies with the following XML pattern : 'pacs\.\00[89]\.\001\.[0-9]{2}|MT103|MT202|MT205', then at least one occurrence of the following element(s) [Record/UnderlyingTransaction/InstructionIdentification] must be present

- on camt.106.001.03/Charges/PerTransaction/Record

- CBPR_Record_NumberOfChargesBreakdownItems_FormalRule:

Charges/PerTransaction/Record/TotalChargesPerRecord/NumberOfChargesBreakdownItems must equal the number of occurrences of Charges/PerTransaction/Record/ChargesBreakdown.

For each [Full Message/Document/ChargesPaymentRequestV03/Charges/PerTransaction/Record], every occurrence of [Record/TotalChargesPerRecord/NumberOfChargesBreakdownItems] value must be equal to the number of occurrences of [Record/ChargesBreakdown]

- **on camt.106.001.03/Charges/PerTransaction/Record**

- **CBPR_MessageNameIdentification_UETR_FormalRule:**

If "Message Name Identification" is populated with pacs.008 or pacs.009 or MT103/202/205, then UETR is mandatory.

For each [Full Message/Document/ChargesPaymentRequestV03/Charges/PerTransaction/Record], if the value of every occurrence of [Record/UnderlyingTransaction/MessageNameIdentification] complies with the following XML pattern : 'pacs\.\00[89]\.\001\.[0-9]{2}|MT103|MT202|MT205', then at least one occurrence of the following element(s) [Record/UnderlyingTransaction/UETR] must be present

5.24.6 AdditionalInformation

XML Tag: AddtlInf

Presence: [0..1]

Definition: Further details on the reason for the charges.

Datatype: "Max140Text" on page 282

Usage Guideline details

- This element(camt.106.001.03/Charges/PerTransaction/AdditionalInformation) is removed.

5.25 ChargesPerTransactionRecord6__1

Definition: Provides a detailed breakdown of the charges per payment transaction.

ⓧ Removed - ⓧ Partial Removed - ♦ Ignored - ♦ Partial Ignored - ⚠ Details below -
 M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	RecordIdentification	<RcrdId>		[0..1]	⚠	70
	ChargesRequestor	<ChrgsRqstr>		[0..1]	M ⚠	70

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	SettlementInstruction	<SttlmInstr>		[0..1]		71
	UnderlyingTransaction	<UndrlygTx>		[1..1]	⚠	72
	TotalChargesPerRecord	<TtlChrgsPerRcrd>		[0..1]	M	73
	ChargesBreakdown	<ChrgsBrkdwn>		[1..*]		73
	ValueDate	<ValDt>		[0..1]	⊘	74
	Debtor	<Dbtr>		[0..1]	⚠	74
	DebtorAccount	<DbtrAcct>		[0..1]		76
	DebtorAgent	<DbtrAgt>		[0..1]	⚠	76
	DebtorAgentAccount	<DbtrAgtAcct>		[0..1]		77
	ChargesAccountAgent	<ChrgsAcctAgt>		[0..1]	⊘ ⚠	78
	ChargesAccountAgentAccount	<ChrgsAcctAgtAcct>		[0..1]	⊘	79
	InstructionForInstructedAgent	<InstrForInstAgt>		[0..1]		80
	AdditionalInformation	<AddtlInf>		[0..1]	⊘	80

Used in element(s)

"Record" on page 67

5.25.1 RecordIdentification

XML Tag: RcrdId

Presence: [0..1]

Definition: Unique and unambiguous identification of the charges record for reconciliation purpose.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 268

Usage Guideline details

- on camt.106.001.03/Charges/PerTransaction/Record/RecordIdentification

Type changed to: CBPR_RestrictedFINXMax35Text on page 268

5.25.2 ChargesRequestor

XML Tag: ChrgsRqstr

Presence: [0..1]

Definition: Agent that requests the charges, if other than the sender.

The **ChrgsRqstr** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification8_1" on page 28 for details)

⊘ Removed - ⊘ Partial Removed - ♦ Ignored - ♦ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		29
	BranchIdentification	<BrnchId>		[0..1]		31

Usage Guideline details

- **on camt.106.001.03/Charges/PerTransaction/Record/ChargesRequestor**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on camt.106.001.03/Charges/PerTransaction/Record/ChargesRequestor**
 - **CBPR_Agent_Option_2_TextualRule:**
 (Clearing Code OR LEI) AND (Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country])). It is recommended to also add the post code when available
- **on camt.106.001.03/Charges/PerTransaction/Record/ChargesRequestor**
 - **CBPR_Agent_Option_1_TextualRule:**
 BICFI, complemented optionally with a LEI (preferred option)
- **on camt.106.001.03/Charges/PerTransaction/Record/ChargesRequestor**
 - **CBPR_Agent_Option_3_TextualRule:**
 Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country])). It is recommended to also add the post code when available
- **on camt.106.001.03/Charges/PerTransaction/Record/ChargesRequestor**
 - **CBPR_Agent_National_only_TextualRule:**
 Whenever all agents in the chain are located within the same country, the clearing code only may be used.

5.25.3 SettlementInstruction

XML Tag: SttlmInstr

Presence: [0..1]

Definition: Specifies the details on how the settlement of the subsequent transaction(s) is completed.

Usage: this agent and party data should be mapped as-is onto the resulting message for the payment of the charges.

The **SttlmInstr** block contains the following elements (see datatype "SettlementInstruction19_1" on page 236 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	RequestedSettlementDate	<ReqdSttlmDt>		[0..1]	⚠	236
	CreditorAgent	<CdtrAgt>		[1..1]	⚠	237
	CreditorAgentAccount	<CdtrAgtAcct>		[0..1]		238
	Creditor	<Cdtr>		[0..1]	⚠	238
	CreditorAccount	<CdtrAcct>		[0..1]		239

5.25.4 UnderlyingTransaction

XML Tag: UndrlygTx

Presence: [1..1]

Definition: Identifies the underlying transaction(s) to which the charges apply.

The **UndrlygTx** block contains the following elements (see datatype "TransactionReferences7__2" on page 252 for details)

⊘ Removed - ⊘ Partial Removed - ◇ Ignored - ◇ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	MessageIdentification	<MsgId>		[0..1]	⚠	253
	MessageNameIdentification	<MsgNmId>		[0..1]	M ⚠	253
	AccountServicerReference	<AcctSvcrRef>		[0..1]	⚠	253
	PaymentInformationIdentification	<PmtInfId>		[0..1]	⚠	254
	InstructionIdentification	<InstrId>		[0..1]	⚠	254
	EndToEndIdentification	<EndToEndId>		[0..1]	⚠	255
	UETR	<UETR>		[0..1]		255
	TransactionIdentification	<TxId>		[0..1]	⚠	255
	MandateIdentification	<MndtId>		[0..1]	⚠	256
	ChequeNumber	<ChqNb>		[0..1]	⚠	256
	ClearingSystemReference	<ClrSysRef>		[0..1]	⊘	256
	AccountOwnerTransactionIdentification	<AcctOwnrTxId>		[0..1]	⚠	257
	AccountServicerTransactionIdentification	<AcctSvcrTxId>		[0..1]	⚠	257
	MarketInfrastructureTransactionIdentification	<MktInfstrctrTxId>		[0..1]	⊘	257
	ProcessingIdentification	<PrcgId>		[0..1]	⚠	258
	Proprietary	<Prtry>		[0..*]	⊘	258

Usage Guideline details

- on camt.106.001.03/Charges/PerTransaction/Record/UnderlyingTransaction

- CBPR_Record_UnderlyingTransaction_Presence_FormalRule:

In Underlying Transaction, in addition to the "Message Name Identification", one other identification must be provided.

For each [Full Message/Document/ChargesPaymentRequestV03/Charges/PerTransaction/Record/UnderlyingTransaction], if the following element(s) [UnderlyingTransaction/MessageIdentification] and [UnderlyingTransaction/AccountServicerReference] and [UnderlyingTransaction/PaymentInformationIdentification] and [UnderlyingTransaction/InstructionIdentification] and [UnderlyingTransaction/EndToEndIdentification] and [UnderlyingTransaction/UETR] and [UnderlyingTransaction/TransactionIdentification] and [UnderlyingTransaction/MandateIdentification] and [UnderlyingTransaction/ChequeNumber] and [UnderlyingTransaction/AccountOwnerTransactionIdentification] and [UnderlyingTransaction/AccountServicerTransactionIdentification] is (are) absent, then at least one occurrence of the following element(s) [UnderlyingTransaction/ProcessingIdentification] must be present

5.25.5 TotalChargesPerRecord

XML Tag: TtlChrgsPerRcrd

Presence: [0..1]

Definition: Total charges claimed for the transaction record.

The **TtlChrgsPerRcrd** block contains the following elements (see datatype "TotalCharges8_1" on page 243 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NumberOfChargesBreakdownItems	<NbOfChrgsBrkdwnItms>		[1..1]		243
	ControlSum	<CtrlSum>		[0..1]	🚫	243
	TotalChargesAmount	<TtlChrgsAmt>		[0..1]	M ⚠	244
	CreditDebitIndicator	<CdtDbtInd>		[0..1]	M	244

Usage Guideline details

- on camt.106.001.03/Charges/PerTransaction/Record/TotalChargesPerRecord

This element is now mandatory, the minimum occurrence has been changed to : 1

5.25.6 ChargesBreakdown

XML Tag: ChrgsBrkdwn

Presence: [1..*]

Definition: Provides the detailed breakdown of the charges per type.

The **ChrgsBrkdwn** block contains the following elements (see datatype "ChargesBreakdown1__1" on page 62 for details)

⊘ Removed - ⊘ Partial Removed - ◇ Ignored - ◇ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Amount	<Amt>		[1..1]	⚠	62
	CreditDebitIndicator	<CdtDbtInd>		[0..1]	M	62
	Type	<Tp>		[0..1]	M	63

5.25.7 ValueDate

XML Tag: ValDt

Presence: [0..1]

Definition: Date and time at which the charges are or will be available.

The **ValDt** block contains the following elements (see datatype "DateAndDateTime2Choice__1" on page 114 for details)

⊘ Removed - ⊘ Partial Removed - ◇ Ignored - ◇ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Date	<Dt>	{Or	[1..1]		115
	DateTime	<DtTm>	Or}	[1..1]	⚠	115

Usage Guideline details

- This element(camt.106.001.03/Charges/PerTransaction/Record/ValueDate) is removed.

5.25.8 Debtor

XML Tag: Dbtr

Presence: [0..1]

Definition: Specifies the debtor of the initial payment transaction.

The **Dbtr** block contains the following elements (see datatype "PartyIdentification272__1" on page 177 for details)

⊘ Removed - ⊘ Partial Removed - ◇ Ignored - ◇ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		177
	PostalAddress	<PstlAdr>		[0..1]		177
	Identification	<Id>		[0..1]		178
	CountryOfResidence	<CtryOfRes>		[0..1]		179
	ContactDetails	<CtctDtls>		[0..1]		179

Usage Guideline details

- **on camt.106.001.03/Charges/PerTransaction/Record/Debtor**

- **CBPR_Debtor_Option_3_Jurisdictions_only_TextualRule:**

For Jurisdictional transactions, Debtor/ Name is mandatory with either Debtor Account OR Debtor Identification (that is within a country or for regions under same legislations - eg EEA)

Countries impacted by the Jurisdictional rule:

Belgium, Bulgaria, Czechia, Denmark, Germany, Estonia, Ireland, Greece, Spain, France, Croatia, Italy, Cyprus, Latvia, Lithuania, Luxembourg, Hungary, Malta, Netherlands, Austria, Poland, Portugal, Romania, Slovenia, Slovakia, Finland, Sweden - Iceland, Liechtenstein, Norway.

Note: The jurisdictional rules apply only when all agents in the payment chain underly the same jurisdiction.

- **on camt.106.001.03/Charges/PerTransaction/Record/Debtor**

- **CBPR_Debtor_BIC_Presence_TextualRule:**

If Any BIC is present, then (Name and Postal Address) is NOT allowed (other elements remain optional) - However, in case of conflicting information, AnyBIC will always take precedence.

- **on camt.106.001.03/Charges/PerTransaction/Record/Debtor**

- **CBPR_Debtor_Option_1_TextualRule:**

Organisation Identification/AnyBIC AND (Account Number OR Organisation Identification/Other)

- **on camt.106.001.03/Charges/PerTransaction/Record/Debtor**

- **CBPR_Debtor_Option_2_TextualRule:**

Name AND ([Structured Address with minimum Town Name & Country (+ recommended to add Post code when available)]OR [Hybrid postal address with minimum Town Name and Country (+ recommended to add Post code when available)] AND (Account Number OR Identification: Private or Organisation)

- **on camt.106.001.03/Charges/PerTransaction/Record/Debtor**

- **CBPR_Party_Name_Postal_Address_FormalRule:**

If Postal Address is present then Name is mandatory.

For each [Full Message/Document/ChargesPaymentRequestV03/Charges/PerTransaction/Record/Debtor], at least one occurrence of [Debtor/Name] must be present when at least one occurrence of [Debtor/PostalAddress] is present

- on camt.106.001.03/Charges/PerTransaction/Record/Debtor

- CBPR_Party_Name_Any_BIC_FormaRule:

If AnyBIC is absent then Name is mandatory and it is recommended to also provide the Postal Address.

For each [Full Message/Document/ChargesPaymentRequestV03/Charges/PerTransaction/Record/Debtor], at least one occurrence of [Debtor/Name] must be present when [Debtor/Identification/OrganisationIdentification/AnyBIC] is absent

5.25.9 DebtorAccount

XML Tag: DbtrAcct

Presence: [0..1]

Definition: Specifies the account of the debtor of the initial payment transaction.

The **DbtrAcct** block contains the following elements (see datatype "CashAccount40__1" on page 50 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		50
	Type	<Tp>		[0..1]		51
	Currency	<Ccy>		[0..1]		52
	Name	<Nm>		[0..1]		52
	Proxy	<Prxy>		[0..1]		53

5.25.10 DebtorAgent

XML Tag: DbtrAgt

Presence: [0..1]

Definition: Specifies the debtor agent of the initial payment transaction, if different from the charges account agent.

The **DbtrAgt** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification8__1" on page 28 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		29
	BranchIdentification	<BrnchId>		[0..1]		31

Usage Guideline details

- **on camt.106.001.03/Charges/PerTransaction/Record/DebtorAgent**
 - **CBPR_Agent_National_only_TextualRule:**

Whenever all agents in the chain are located within the same country, the clearing code only may be used.
- **on camt.106.001.03/Charges/PerTransaction/Record/DebtorAgent**
 - **CBPR_Agent_Option_3_TextualRule:**

Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country]). It is recommended to also add the post code when available
- **on camt.106.001.03/Charges/PerTransaction/Record/DebtorAgent**
 - **CBPR_Agent_Option_1_TextualRule:**

BICFI, complemented optionally with a LEI (preferred option)
- **on camt.106.001.03/Charges/PerTransaction/Record/DebtorAgent**
 - **CBPR_Agent_Option_2_TextualRule:**

(Clearing Code OR LEI) AND (Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country])). It is recommended to also add the post code when available

5.25.11 DebtorAgentAccount

XML Tag: DbtrAgtAcct

Presence: [0..1]

Definition: Specifies the account of the debtor agent of the initial payment transaction, when instructing agent is different from the charges account owner.

The **DbtrAgtAcct** block contains the following elements (see datatype "CashAccount40__1" on page 50 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		50
	Type	<Tp>		[0..1]		51

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Currency	<Ccy>		[0..1]		52
	Name	<Nm>		[0..1]	⚠	52
	Proxy	<Prxy>		[0..1]		53

5.25.12 ChargesAccountAgent

XML Tag: ChrgsAcctAgt

Presence: [0..1]

Definition: Agent that services the charges account.

Usage: this element should be used where the charge being claimed does not relate to the processing of a payment transaction e.g. it relates to an investigation or other process. This identifies the agent that services the account from which charges are to be settled from.

The **ChrgsAcctAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification8__2](#)" on page 32 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
 M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]	⚠	32
	BranchIdentification	<BrnchId>		[0..1]	🚫	35

Usage Guideline details

- This element([camt.106.001.03/Charges/PerTransaction/Record/ChargesAccountAgent](#)) is removed.
- on [camt.106.001.03/Charges/PerTransaction/Record/ChargesAccountAgent](#)
 - **CBPR_Agent_Option1_TextualRule:**
 BICFI, complemented optionally with a LEI (preferred option)
- on [camt.106.001.03/Charges/PerTransaction/Record/ChargesAccountAgent](#)
 - **CBPR_Co-existence_PostalAddress_TextualRule:**
 Address Line (Unstructured Address) remains available only for cases when the payment is initiated in FIN, or by an MI, during coexistence only. The Structured PostalAddress remains the preferred option.

 Therefore:
 - If a payment is initiated on FIN, or by an MI, and the postal address is unstructured, the outgoing ISO 20022 message will transport unstructured postal address, up to the Creditor Agent.
 - If a payment is initiated in ISO 20022, postal address must be structured.

- on **camt.106.001.03/Charges/PerTransaction/Record/ChargesAccountAgent**

- **CBPR_Agent_National_only_TextualRule:**

Whenever Debtor Agent, Creditor Agent and all agents in between are located within the same country, the clearing code only may be used.

- on **camt.106.001.03/Charges/PerTransaction/Record/ChargesAccountAgent**

- **CBPR_Agent_Option2_TextualRule:**

(Clearing Code OR LEI) AND (Name AND (Unstructured postal address OR [Structured postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.

- on **camt.106.001.03/Charges/PerTransaction/Record/ChargesAccountAgent**

- **CBPR_Agent_Option3_TextualRule:**

Name AND (Unstructured OR [Structured postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.

5.25.13 ChargesAccountAgentAccount

XML Tag: ChrgsAcctAgtAcct

Presence: [0..1]

Definition: Account of the agent that services the charges account.

Usage: this element should be used where the charge being claimed does not relate to the processing of a payment transaction e.g. it relates to an investigation or other process. This identifies the account from which charges are to be settled from.

The **ChrgsAcctAgtAcct** block contains the following elements (see datatype "CashAccount40__1" on page 50 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -

 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		50
	Type	<Tp>		[0..1]		51
	Currency	<Ccy>		[0..1]		52
	Name	<Nm>		[0..1]		52
	Proxy	<Prxy>		[0..1]		53

Usage Guideline details

- This element(**camt.106.001.03/Charges/PerTransaction/Record/ChargesAccountAgentAccount**) is removed.

5.25.14 InstructionForInstructedAgent

XML Tag: InstrForInstdAgt

Presence: [0..1]

Definition: Further information related to the processing of the payment adjustment instruction that may need to be acted upon by the next agent.

The **InstrForInstdAgt** block contains the following elements (see datatype "InstructionForInstructedAgent1__1" on page 162 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>		[0..1]		162
	InstructionInformation	<InstrInf>		[0..1]		163

5.25.15 AdditionalInformation

XML Tag: AddtlInf

Presence: [0..1]

Definition: Further details on the reason for the charges.

Datatype: "Max140Text" on page 282

Usage Guideline details

- This element(camt.106.001.03/Charges/PerTransaction/Record/AdditionalInformation) is removed.

5.26 ChargesPerType6__1

Definition: Provides a detailed breakdown of the charges per type of charges.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ChargesIdentification	<ChrgsId>		[0..1]		81
	TotalChargesPerChargeType	<TtlChrgsPerChrgTp>		[0..1]		81
	ChargesAccountAgent	<ChrgsAcctAgt>		[0..1]		82
	ChargesAccountAgentAccount	<ChrgsAcctAgtAcct>		[0..1]		83
	Type	<Tp>		[1..1]		84
	Record	<Rcrd>		[1..*]		84
	AdditionalInformation	<AddtlInf>		[0..1]		85

Rules

R26 ChargesAccountAgent2Rule ✓

When Record/ChargesAccountAgent is present or Record/ChargesAccountAgentAccount is present then ChargesAccountAgent must be absent and ChargesAccountAgentAccount must be absent.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00640
- *Error Text:* Missing charges account

R27 ChargesAccountAgentRule ✓

When ChargesAccountAgent is present or ChargesAccountAgentAccount is present then Record/ChargesAccountAgent must be absent and Record/ChargesAccountAgentAccount must be absent.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00639
- *Error Text:* Missing charges account

Used in element(s)

["PerType" on page 61](#)

5.26.1 ChargesIdentification

XML Tag: ChrgsId

Presence: [0..1]

Definition: Unique and unambiguous identification of the charges information for reconciliation purpose.

Usage: this identification shall be used as the end-to-end identification in the resulting message for the payment of the charges, to allow for automated reconciliation.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 268](#)

Usage Guideline details

- **on camt.106.001.03/Charges/PerType/ChargesIdentification**
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)

5.26.2 TotalChargesPerChargeType

XML Tag: TtlChrgsPerChrgTp

Presence: [0..1]

Definition: Total charges claimed through for the specified charge type.

The **TtlChrgsPerChrgTp** block contains the following elements (see datatype "TotalCharges7__1" on page 241 for details)

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NumberOfChargesRecords	<NbOfChrgsRcrds>		[1..1]		242
	ControlSum	<CtrlSum>		[0..1]		242
	TotalChargesAmount	<TtlChrgsAmt>		[0..1]	⚠	242
	CreditDebitIndicator	<CdtDbtInd>		[0..1]		243

5.26.3 ChargesAccountAgent

XML Tag: ChrgsAcctAgt

Presence: [0..1]

Definition: Agent that services the charges account.

Usage: this element should be used where the charge being claimed does not relate to the processing of a payment transaction e.g. it relates to an investigation or other process. This identifies the agent that services the account from which charges are to be settled from.

The **ChrgsAcctAgt** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification8__2" on page 32 for details)

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]	⚠	32
	BranchIdentification	<BrnchId>		[0..1]	🚫	35

Usage Guideline details

- on camt.106.001.03/Charges/PerType/ChargesAccountAgent

- CBPR_Co-existence_PostalAddress_TextualRule:

Address Line (Unstructured Address) remains available only for cases when the payment is initiated in FIN, or by an MI, during coexistence only. The Structured PostalAddress remains the preferred option.

Therefore:

- If a payment is initiated on FIN, or by an MI, and the postal address is unstructured, the outgoing ISO 20022 message will transport unstructured postal address, up to the Creditor Agent.
- If a payment is initiated in ISO 20022, postal address must be structured.

- on **camt.106.001.03/Charges/PerType/ChargesAccountAgent**
 - **CBPR_Agent_Option1_TextualRule:**
BICFI, complemented optionally with a LEI (preferred option)
- on **camt.106.001.03/Charges/PerType/ChargesAccountAgent**
 - **CBPR_Agent_Option3_TextualRule:**
Name AND (Unstructured OR [Structured postal address with minimum Town Name and Country]). It is recommended to also add the post code when available.
- on **camt.106.001.03/Charges/PerType/ChargesAccountAgent**
 - **CBPR_Agent_National_only_TextualRule:**
Whenever Debtor Agent, Creditor Agent and all agents in between are located within the same country, the clearing code only may be used.
- on **camt.106.001.03/Charges/PerType/ChargesAccountAgent**
 - **CBPR_Agent_Option2_TextualRule:**
(Clearing Code OR LEI) AND (Name AND (Unstructured postal address OR [Structured postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.

5.26.4 ChargesAccountAgentAccount

XML Tag: ChrgsAcctAgtAcct

Presence: [0..1]

Definition: Account of the agent that services the charges account.

Usage: this element should be used where the charge being claimed does not relate to the processing of a payment transaction e.g. it relates to an investigation or other process. This identifies the account from which charges are to be settled from.

The **ChrgsAcctAgtAcct** block contains the following elements (see datatype "CashAccount40__1" on page 50 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		50
	Type	<Tp>		[0..1]		51
	Currency	<Ccy>		[0..1]		52
	Name	<Nm>		[0..1]		52
	Proxy	<Prxy>		[0..1]		53

5.26.5 Type

XML Tag: Tp

Presence: [1..1]

Definition: Specifies the type of charge.

The **Tp** block contains the following elements (see datatype "ChargeType3Choice" on page 58 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		58
	Proprietary	<Prtry>	Or}	[1..1]		59

5.26.6 Record

XML Tag: Rcrd

Presence: [1..*]

Definition: Itemised charges record per charges type.

The **Rcrd** block contains the following elements (see datatype "ChargesPerTypeRecord6__1" on page 85 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	RecordIdentification	<RcrdId>		[0..1]		86
	ChargesRequestor	<ChrgsRqstr>		[0..1]		86
	SettlementInstruction	<SttlmInstr>		[0..1]		86
	UnderlyingTransaction	<UndrlygTx>		[1..1]		87
	Amount	<Amt>		[1..1]		88
	CreditDebitIndicator	<CdtDbtInd>		[0..1]		88
	ValueDate	<ValDt>		[0..1]		88
	Debtor	<Dbtr>		[0..1]		88
	DebtorAccount	<DbtrAcct>		[0..1]		89
	DebtorAgent	<DbtrAgt>		[0..1]		89
	DebtorAgentAccount	<DbtrAgtAcct>		[0..1]		90
	ChargesAccountAgent	<ChrgsAcctAgt>		[0..1]		91
	ChargesAccountAgentAccount	<ChrgsAcctAgtAcct>		[0..1]		92

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	InstructionForInstructedAgent	<InstrForInstdAgt>		[0..1]		93
	AdditionalInformation	<AddtlInf>		[0..1]		93

5.26.7 AdditionalInformation

XML Tag: AddtlInf

Presence: [0..1]

Definition: Further details on the reason for the charges.

Datatype: "Max140Text" on page 282

Usage Guideline details

- This element([camt.106.001.03/Charges/PerType/AdditionalInformation](#)) is removed.

5.27 ChargesPerTypeRecord6__1

Definition: Provides further individual record details on the charges related to the payment transaction.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	RecordIdentification	<RcrdId>		[0..1]		86
	ChargesRequestor	<ChrgsRqstr>		[0..1]		86
	SettlementInstruction	<SttlmInstr>		[0..1]		86
	UnderlyingTransaction	<UndrlygTx>		[1..1]		87
	Amount	<Amt>		[1..1]		88
	CreditDebitIndicator	<CdtDbtInd>		[0..1]		88
	ValueDate	<ValDt>		[0..1]		88
	Debtor	<Dbtr>		[0..1]		88
	DebtorAccount	<DbtrAcct>		[0..1]		89
	DebtorAgent	<DbtrAgt>		[0..1]		89
	DebtorAgentAccount	<DbtrAgtAcct>		[0..1]		90
	ChargesAccountAgent	<ChrgsAcctAgt>		[0..1]		91
	ChargesAccountAgentAccount	<ChrgsAcctAgtAcct>		[0..1]		92
	InstructionForInstructedAgent	<InstrForInstdAgt>		[0..1]		93
	AdditionalInformation	<AddtlInf>		[0..1]		93

Used in element(s)

["Record" on page 84](#)

5.27.1 RecordIdentification

XML Tag: RcrdId

Presence: [0..1]

Definition: Unique and unambiguous identification of the charges record for reconciliation purpose.

Datatype: ["Max35Text" on page 284](#)

Usage Guideline details

- This element([camt.106.001.03/Charges/PerType/Record/RecordIdentification](#)) is removed.

5.27.2 ChargesRequestor

XML Tag: ChrgsRqstr

Presence: [0..1]

Definition: Agent that requests the charges, if other than the sender.

The **ChrgsRqstr** block contains the following elements (see datatype ["BranchAndFinancialInstitutionIdentification8" on page 27](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		27
	BranchIdentification	<BrnchId>		[0..1]		28

5.27.3 SettlementInstruction

XML Tag: SttlmInstr

Presence: [0..1]

Definition: Specifies the details on how the settlement of the subsequent transaction(s) is completed.

Usage: this agent and party data should be mapped as-is onto the resulting message for the payment of the charges.

The **SttlmInstr** block contains the following elements (see datatype ["SettlementInstruction19" on page 234](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	RequestedSettlementDate	<ReqdSttlmDt>		[0..1]		234
	CreditorAgent	<CdtrAgt>		[1..1]		234
	CreditorAgentAccount	<CdtrAgtAcct>		[0..1]		235
	Creditor	<Cdtr>		[0..1]		235
	CreditorAccount	<CdtrAcct>		[0..1]		235

5.27.4 UnderlyingTransaction

XML Tag: UndrlygTx

Presence: [1..1]

Definition: Identifies the underlying transaction(s) to which the charges apply.

The **UndrlygTx** block contains the following elements (see datatype "TransactionReferences7__1" on page 244 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	MessageIdentification	<MsgId>		[0..1]		245
	MessageNameIdentification	<MsgNmId>		[0..1]		246
	AccountServicerReference	<AcctSvcrRef>		[0..1]		246
	PaymentInformationIdentification	<PmtInfId>		[0..1]		246
	InstructionIdentification	<InstrId>		[0..1]		247
	EndToEndIdentification	<EndToEndId>		[0..1]		247
	UETR	<UETR>		[0..1]		248
	TransactionIdentification	<TxId>		[0..1]		248
	MandateIdentification	<MndtId>		[0..1]		249
	ChequeNumber	<ChqNb>		[0..1]		249
	ClearingSystemReference	<ClrSysRef>		[0..1]		249
	AccountOwnerTransactionIdentification	<AcctOwnrTxId>		[0..1]		250
	AccountServicerTransactionIdentification	<AcctSvcrTxId>		[0..1]		250
	MarketInfrastructureTransactionIdentification	<MktInfstrctrTxId>		[0..1]		251
	ProcessingIdentification	<PrcgId>		[0..1]		251
	Proprietary	<Prtry>		[0..*]		251

5.27.5 Amount

XML Tag: Amt

Presence: [1..1]

Definition: Amount of transaction charges to be paid by the charge bearer.

Datatype: ["CBPR_Amount__1" on page 264](#)

Usage Guideline details

- on [camt.106.001.03/Charges/PerType/Record/Amount](#)
Type changed to: [CBPR_Amount on page 263](#)

5.27.6 CreditDebitIndicator

XML Tag: CdtDbtInd

Presence: [0..1]

Definition: Indicates whether the charges amount is a credit or a debit amount.

Usage: A zero amount is considered to be a credit.

Datatype: ["CreditDebitCode" on page 272](#)

5.27.7 ValueDate

XML Tag: ValDt

Presence: [0..1]

Definition: Date and time at which the charges are or will be available.

The **ValDt** block contains the following elements (see datatype ["DateAndDateTime2Choice__1" on page 114](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Date	<Dt>	{Or	[1..1]		115
	DateTime	<DtTm>	Or}	[1..1]		115

5.27.8 Debtor

XML Tag: Dbtr

Presence: [0..1]

Definition: Specifies the debtor of the initial payment transaction.

The **Dbtr** block contains the following elements (see datatype ["PartyIdentification272" on page 174](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		174
	PostalAddress	<PstlAdr>		[0..1]		175
	Identification	<Id>		[0..1]		175
	CountryOfResidence	<CtryOfRes>		[0..1]		176
	ContactDetails	<CtctDtls>		[0..1]		176

5.27.9 DebtorAccount

XML Tag: DbtrAcct

Presence: [0..1]

Definition: Specifies the account of the debtor of the initial payment transaction.

The **DbtrAcct** block contains the following elements (see datatype "[CashAccount40](#)" on page 47 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		48
	Type	<Tp>		[0..1]		48
	Currency	<Ccy>		[0..1]		49
	Name	<Nm>		[0..1]		49
	Proxy	<Prxy>		[0..1]		49

5.27.10 DebtorAgent

XML Tag: DbtrAgt

Presence: [0..1]

Definition: Specifies the debtor agent of the initial payment transaction, if different from the charges account agent.

The **DbtrAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification8_2](#)" on page 32 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		32

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BranchIdentification	<BrnchId>		[0..1]		35

Usage Guideline details

- **on camt.106.001.03/Charges/PerType/Record/DebtorAgent**
 - **CBPR_Agent_Option1_TextualRule:**

BICFI, complemented optionally with a LEI (preferred option)
- **on camt.106.001.03/Charges/PerType/Record/DebtorAgent**
 - **CBPR_Co-existence_PostalAddress_TextualRule:**

Address Line (Unstructured Address) remains available only for cases when the payment is initiated in FIN, or by an MI, during coexistence only. The Structured PostalAddress remains the preferred option.

Therefore:

 - If a payment is initiated on FIN, or by an MI, and the postal address is unstructured, the outgoing ISO 20022 message will transport unstructured postal address, up to the Creditor Agent.
 - If a payment is initiated in ISO 20022, postal address must be structured.
- **on camt.106.001.03/Charges/PerType/Record/DebtorAgent**
 - **CBPR_Agent_Option2_TextualRule:**

(Clearing Code OR LEI) AND (Name AND (Unstructured postal address OR [Structured postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.
- **on camt.106.001.03/Charges/PerType/Record/DebtorAgent**
 - **CBPR_Agent_Option3_TextualRule:**

Name AND (Unstructured OR [Structured postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.
- **on camt.106.001.03/Charges/PerType/Record/DebtorAgent**
 - **CBPR_Agent_National_only_TextualRule:**

Whenever Debtor Agent, Creditor Agent and all agents in between are located within the same country, the clearing code only may be used.

5.27.11 DebtorAgentAccount

XML Tag: DbtrAgtAcct

Presence: [0..1]

Definition: Specifies the account of the debtor agent of the initial payment transaction, when instructing agent is different from the charges account owner.

The **DbtrAgtAcct** block contains the following elements (see datatype "CashAccount40__1" on page 50 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		50
	Type	<Tp>		[0..1]		51
	Currency	<Ccy>		[0..1]		52
	Name	<Nm>		[0..1]	⚠	52
	Proxy	<Prxy>		[0..1]		53

5.27.12 ChargesAccountAgent

XML Tag: ChrgsAcctAgt

Presence: [0..1]

Definition: Agent that services the charges account.

Usage: this element should be used where the charge being claimed does not relate to the processing of a payment transaction e.g. it relates to an investigation or other process. This identifies the agent that services the account from which charges are to be settled from.

The **ChrgsAcctAgt** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification8__4" on page 37 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]	⚠	38
	BranchIdentification	<BrnchId>		[0..1]	🚫	39

Usage Guideline details

- on camt.106.001.03/Charges/PerType/Record/ChargesAccountAgent

- CBPR_Co-existence_PostalAddress_TextualRule:

Address Line (Unstructured Address) remains available only for cases when the payment is initiated in FIN, or by an MI, during coexistence only. The Structured PostalAddress remains the preferred option.

Therefore:

- If a payment is initiated on FIN, or by an MI, and the postal address is unstructured, the outgoing ISO 20022 message will transport unstructured postal address, up to the Creditor Agent.

- If a payment is initiated in ISO 20022, postal address must be structured.
- on **camt.106.001.03/Charges/PerType/Record/ChargesAccountAgent**
 - **CBPR_Agent_Option2_TextualRule:**

(Clearing Code OR LEI) AND (Name AND (Unstructured postal address OR [Structured postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.
- on **camt.106.001.03/Charges/PerType/Record/ChargesAccountAgent**
 - **CBPR_Agent_Option1_TextualRule:**

BICFI, complemented optionally with a LEI (preferred option)
- on **camt.106.001.03/Charges/PerType/Record/ChargesAccountAgent**
 - **CBPR_Agent_National_only_TextualRule:**

Whenever Debtor Agent, Creditor Agent and all agents in between are located within the same country, the clearing code only may be used.
- on **camt.106.001.03/Charges/PerType/Record/ChargesAccountAgent**
 - **CBPR_Agent_Option3_TextualRule:**

Name AND (Unstructured OR [Structured postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.

5.27.13 ChargesAccountAgentAccount

XML Tag: ChrgsAcctAgtAcct

Presence: [0..1]

Definition: Account of the agent that services the charges account.

Usage: this element should be used where the charge being claimed does not relate to the processing of a payment transaction e.g. it relates to an investigation or other process. This identifies the account from which charges are to be settled from.

The **ChrgsAcctAgtAcct** block contains the following elements (see datatype "CashAccount40__1" on page 50 for details)

❌ Removed -
 ❌ Partial Removed -
 ◆ Ignored -
 ◆ Partial Ignored -
 ⚠ Details below -
 M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		50
	Type	<Tp>		[0..1]		51
	Currency	<Ccy>		[0..1]		52
	Name	<Nm>		[0..1]	⚠	52
	Proxy	<Prxy>		[0..1]		53

5.27.14 InstructionForInstructedAgent

XML Tag: InstrForInstdAgt

Presence: [0..1]

Definition: Further information related to the processing of the payment adjustment instruction that may need to be acted upon by the next agent.

The **InstrForInstdAgt** block contains the following elements (see datatype "InstructionForInstructedAgent1" on page 161 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>		[0..1]		162
	InstructionInformation	<InstrInf>		[0..1]		162

Usage Guideline details

- This element(camt.106.001.03/Charges/PerType/Record/InstructionForInstructedAgent) is removed.

5.27.15 AdditionalInformation

XML Tag: AddtlInf

Presence: [0..1]

Definition: Further details on the reason for the charges.

Datatype: "Max140Text" on page 282

Usage Guideline details

- This element(camt.106.001.03/Charges/PerType/Record/AdditionalInformation) is removed.

5.28 ChargesRecord12__1

Definition: Provides further individual record details on the charges related to the payment transaction.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ChargesIdentification	<ChrgsId>		[0..1]		94
	RecordIdentification	<RcrdId>		[0..1]	 	94
	ChargesRequestor	<ChrgsRqstr>		[0..1]		95

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	SettlementInstruction	<SttlmInstr>		[0..1]		95
	UnderlyingTransaction	<UndrlygTx>		[1..1]		96
	Amount	<Amt>		[1..1]		96
	CreditDebitIndicator	<CdtDbtInd>		[0..1]		97
	ValueDate	<ValDt>		[0..1]		97
	Debtor	<Dbtr>		[0..1]		97
	DebtorAccount	<DbtrAcct>		[0..1]		98
	DebtorAgent	<DbtrAgt>		[0..1]		98
	DebtorAgentAccount	<DbtrAgtAcct>		[0..1]		99
	ChargesAccountAgent	<ChrgsAcctAgt>		[0..1]		100
	ChargesAccountAgentAccount	<ChrgsAcctAgtAcct>		[0..1]		101
	Type	<Tp>		[0..1]		101
	InstructionForInstructedAgent	<InstrForInstAgt>		[0..1]		102
	AdditionalInformation	<AddtlInf>		[0..1]		102

Used in element(s)

"Single" on page 59

5.28.1 ChargesIdentification

XML Tag: ChrgsId

Presence: [0..1]

Definition: Unique and unambiguous identification of the charges information for reconciliation purpose.

Usage: this identification shall be used as the end-to-end identification in the resulting message for the payment of the charges, to allow for automated reconciliation.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 268

Usage Guideline details

- on camt.106.001.03/Charges/Single/ChargesIdentification
Type changed to: CBPR_RestrictedFINXMax35Text on page 268

5.28.2 RecordIdentification

XML Tag: RcrdId

Presence: [0..1]

Definition: Unique and unambiguous identification of the charges record for reconciliation purpose.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 268

Usage Guideline details

- This element(**camt.106.001.03/Charges/Single/RecordIdentification**) is removed.
- on **camt.106.001.03/Charges/Single/RecordIdentification**
Type changed to: CBPR_RestrictedFINXMax35Text on page 268

5.28.3 ChargesRequestor

XML Tag: ChrgsRqstr

Presence: [0..1]

Definition: Agent that requests the charges, if other than the sender.

The **ChrgsRqstr** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification8" on page 27 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		27
	BranchIdentification	<BrnchId>		[0..1]		28

5.28.4 SettlementInstruction

XML Tag: SttlmInstr

Presence: [0..1]

Definition: Specifies the details on how the settlement of the subsequent transaction(s) is completed.

Usage: this agent and party data should be mapped as-is onto the resulting message for the payment of the charges.

The **SttlmInstr** block contains the following elements (see datatype "SettlementInstruction19" on page 234 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	RequestedSettlementDate	<ReqdSttlmDt>		[0..1]		234
	CreditorAgent	<CdtrAgt>		[1..1]		234
	CreditorAgentAccount	<CdtrAgtAcct>		[0..1]		235
	Creditor	<Cdtr>		[0..1]		235

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CreditorAccount	<CdtrAcct>		[0..1]		235

5.28.5 UnderlyingTransaction

XML Tag: UndrlygTx

Presence: [1..1]

Definition: Identifies the underlying transaction(s) to which the charges apply.

The **UndrlygTx** block contains the following elements (see datatype "[TransactionReferences7__1](#)" on page 244 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	MessageIdentification	<MsgId>		[0..1]		245
	MessageNameIdentification	<MsgNmId>		[0..1]	 	246
	AccountServicerReference	<AcctSvcrRef>		[0..1]		246
	PaymentInformationIdentification	<PmtInfId>		[0..1]		246
	InstructionIdentification	<InstrId>		[0..1]	 	247
	EndToEndIdentification	<EndToEndId>		[0..1]		247
	UETR	<UETR>		[0..1]		248
	TransactionIdentification	<TxId>		[0..1]		248
	MandateIdentification	<MndtId>		[0..1]		249
	ChequeNumber	<ChqNb>		[0..1]		249
	ClearingSystemReference	<ClrSysRef>		[0..1]		249
	AccountOwnerTransactionIdentification	<AcctOwnrTxId>		[0..1]		250
	AccountServicerTransactionIdentification	<AcctSvcrTxId>		[0..1]		250
	MarketInfrastructureTransactionIdentification	<MktInfstrctrTxId>		[0..1]		251
	ProcessingIdentification	<PrcgId>		[0..1]		251
	Proprietary	<Prtry>		[0..*]		251

5.28.6 Amount

XML Tag: Amt

Presence: [1..1]

Definition: Amount of transaction charges to be paid by the charge bearer.

Datatype: ["CBPR_Amount__1" on page 264](#)

Usage Guideline details

- on [camt.106.001.03/Charges/Single/Amount](#)
Type changed to: [CBPR_Amount on page 263](#)

5.28.7 CreditDebitIndicator

XML Tag: CdtDbtInd

Presence: [0..1]

Definition: Indicates whether the charges amount is a credit or a debit amount.

Usage: A zero amount is considered to be a credit.

Datatype: ["CreditDebitCode" on page 272](#)

5.28.8 ValueDate

XML Tag: ValDt

Presence: [0..1]

Definition: Date and time at which the charges are or will be available.

The **ValDt** block contains the following elements (see datatype ["DateAndDateTime2Choice__1" on page 114](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Date	<Dt>	{Or	[1..1]		115
	DateTime	<DtTm>	Or}	[1..1]		115

5.28.9 Debtor

XML Tag: Dbtr

Presence: [0..1]

Definition: Specifies the debtor of the initial payment transaction.

The **Dbtr** block contains the following elements (see datatype ["PartyIdentification272" on page 174](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		174
	PostalAddress	<PstlAdr>		[0..1]		175

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		175
	CountryOfResidence	<CtryOfRes>		[0..1]		176
	ContactDetails	<CtctDtls>		[0..1]		176

5.28.10 DebtorAccount

XML Tag: DbtrAcct

Presence: [0..1]

Definition: Specifies the account of the debtor of the initial payment transaction.

The **DbtrAcct** block contains the following elements (see datatype "[CashAccount40](#)" on page 47 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		48
	Type	<Tp>		[0..1]		48
	Currency	<Ccy>		[0..1]		49
	Name	<Nm>		[0..1]		49
	Proxy	<Prxy>		[0..1]		49

5.28.11 DebtorAgent

XML Tag: DbtrAgt

Presence: [0..1]

Definition: Specifies the debtor agent of the initial payment transaction, if different from the charges account agent.

The **DbtrAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification8__2](#)" on page 32 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		32
	BranchIdentification	<BrnchId>		[0..1]		35

Usage Guideline details

- on camt.106.001.03/Charges/Single/DebtorAgent

– **CBPR_Agent_National_only_TextualRule:**

Whenever Debtor Agent, Creditor Agent and all agents in between are located within the same country, the clearing code only may be used.

• **on camt.106.001.03/Charges/Single/DebtorAgent**

– **CBPR_Agent_Option1_TextualRule:**

BICFI, complemented optionally with a LEI (preferred option)

• **on camt.106.001.03/Charges/Single/DebtorAgent**

– **CBPR_Co-existence_PostalAddress_TextualRule:**

Address Line (Unstructured Address) remains available only for cases when the payment is initiated in FIN, or by an MI, during coexistence only. The Structured PostalAddress remains the preferred option.

Therefore:

- If a payment is initiated on FIN, or by an MI, and the postal address is unstructured, the outgoing ISO 20022 message will transport unstructured postal address, up to the Creditor Agent.

- If a payment is initiated in ISO 20022, postal address must be structured.

• **on camt.106.001.03/Charges/Single/DebtorAgent**

– **CBPR_Agent_Option3_TextualRule:**

Name AND (Unstructured OR [Structured postal address with minimum Town Name and Country]). It is recommended to also add the post code when available.

• **on camt.106.001.03/Charges/Single/DebtorAgent**

– **CBPR_Agent_Option2_TextualRule:**

(Clearing Code OR LEI) AND (Name AND (Unstructured postal address OR [Structured postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.

5.28.12 DebtorAgentAccount

XML Tag: DbtrAgtAcct

Presence: [0..1]

Definition: Specifies the account of the debtor agent of the initial payment transaction, when instructing agent is different from the charges account owner.

The **DbtrAgtAcct** block contains the following elements (see datatype "[CashAccount40__2](#)" on [page 53](#) for details)

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]	M	54

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		55
	Currency	<Ccy>		[0..1]		55
	Name	<Nm>		[0..1]	⚠	55
	Proxy	<Prxy>		[0..1]		56

5.28.13 ChargesAccountAgent

XML Tag: ChrgsAcctAgt

Presence: [0..1]

Definition: Agent that services the charges account.

Usage: this element should be used where the charge being claimed does not relate to the processing of a payment transaction e.g. it relates to an investigation or other process. This identifies the agent that services the account from which charges are to be settled from.

The **ChrgsAcctAgt** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification8_2" on page 32 for details)

ⓧ Removed - ⓧ Partial Removed - ♦ Ignored - ♦ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]	⚠	32
	BranchIdentification	<BrnchId>		[0..1]	ⓧ	35

Usage Guideline details

- on camt.106.001.03/Charges/Single/ChargesAccountAgent

- CBPR_Co-existence_PostalAddress_TextualRule:

Address Line (Unstructured Address) remains available only for cases when the payment is initiated in FIN, or by an MI, during coexistence only. The Structured PostalAddress remains the preferred option.

Therefore:

- If a payment is initiated on FIN, or by an MI, and the postal address is unstructured, the outgoing ISO 20022 message will transport unstructured postal address, up to the Creditor Agent.
- If a payment is initiated in ISO 20022, postal address must be structured.

- on camt.106.001.03/Charges/Single/ChargesAccountAgent

- CBPR_Agent_Option1_TextualRule:

BICFI, complemented optionally with a LEI (preferred option)

- on **camt.106.001.03/Charges/Single/ChargesAccountAgent**
 - **CBPR_Agent_Option2_TextualRule:**
(Clearing Code OR LEI) AND (Name AND (Unstructured postal address OR [Structured postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.
- on **camt.106.001.03/Charges/Single/ChargesAccountAgent**
 - **CBPR_Agent_Option3_TextualRule:**
Name AND (Unstructured OR [Structured postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.
- on **camt.106.001.03/Charges/Single/ChargesAccountAgent**
 - **CBPR_Agent_National_only_TextualRule:**
Whenever Debtor Agent, Creditor Agent and all agents in between are located within the same country, the clearing code only may be used.

5.28.14 ChargesAccountAgentAccount

XML Tag: ChrgsAcctAgtAcct

Presence: [0..1]

Definition: Account of the agent that services the charges account.

Usage: this element should be used where the charge being claimed does not relate to the processing of a payment transaction e.g. it relates to an investigation or other process. This identifies the account from which charges are to be settled from.

The **ChrgsAcctAgtAcct** block contains the following elements (see datatype "CashAccount40__1" on page 50 for details)

❌ Removed - ❌ Partial Removed - ◆ Ignored - ◆ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]	M	50
	Type	<Tp>		[0..1]		51
	Currency	<Ccy>		[0..1]		52
	Name	<Nm>		[0..1]	⚠	52
	Proxy	<Prxy>		[0..1]		53

5.28.15 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the type of charge.

The **Tp** block contains the following elements (see datatype "[ChargeType3Choice](#)" on page 58 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		58
	Proprietary	<Prtry>	Or}	[1..1]	🚫	59

Usage Guideline details

- **on camt.106.001.03/Charges/Single/Type**

This element is now mandatory, the minimum occurrence has been changed to : 1

5.28.16 InstructionForInstructedAgent

XML Tag: InstrForInstdAgt

Presence: [0..1]

Definition: Further information related to the processing of the payment adjustment instruction that may need to be acted upon by the next agent.

The **InstrForInstdAgt** block contains the following elements (see datatype "[InstructionForInstructedAgent1](#)" on page 161 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>		[0..1]		162
	InstructionInformation	<InstrInf>		[0..1]		162

Usage Guideline details

- **This element(camt.106.001.03/Charges/Single/InstructionForInstructedAgent) is removed.**

5.28.17 AdditionalInformation

XML Tag: AddtlInf

Presence: [0..1]

Definition: Further details on the reason for the charges.

Datatype: "[Max140Text](#)" on page 282

Usage Guideline details

- This element([camt.106.001.03/Charges/Single/AdditionalInformation](#)) is removed.

5.29 ClearingSystemIdentification2Choice

Definition: Choice of a clearing system identifier.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		103
	Proprietary	<Prtry>	Or}	[1..1]		103

Used in element(s)

"ClearingSystemIdentification" on page 105, "ClearingSystemIdentification" on page 106

5.29.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Identification of a clearing system, in a coded form as published in an external list.

Datatype: ["ExternalClearingSystemIdentification1Code"](#) on page 275

5.29.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Identification code for a clearing system, that has not yet been identified in the list of clearing systems.

Datatype: ["Max35Text"](#) on page 284

Usage Guideline details

- This element([camt.106.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary](#)) is removed.
- This element([camt.106.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary](#)) is removed.
- This element([camt.106.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary](#)) is removed.

- This element(camt.106.001.03/Charges/Single/ChargesAccountAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(camt.106.001.03/Charges/PerTransaction/ChargesAccountAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(camt.106.001.03/Charges/PerType/Record/ChargesAccountAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(camt.106.001.03/Charges/PerType/ChargesAccountAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(camt.106.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(camt.106.001.03/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(camt.106.001.03/GroupHeader/ChargesAccountAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(camt.106.001.03/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(camt.106.001.03/Charges/PerTransaction/Record/ChargesAccountAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(camt.106.001.03/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(camt.106.001.03/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/Creditor/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.

5.30 ClearingSystemMemberIdentification2

Definition: Unique identification, as assigned by a clearing system, to unambiguously identify a member of the clearing system.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]		105
	MemberIdentification	<MmbId>		[1..1]		105

Used in element(s)

"ClearingSystemMemberIdentification" on page 123

5.30.1 ClearingSystemIdentification

XML Tag: ClrSysId

Presence: [0..1]

Definition: Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed.

The **ClrSysId** block contains the following elements (see datatype "[ClearingSystemIdentification2Choice](#)" on page 103 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		103
	Proprietary	<Prtry>	Or}	[1..1]		103

5.30.2 MemberIdentification

XML Tag: MmbId

Presence: [1..1]

Definition: Identification of a member of a clearing system.

Datatype: "[Max35Text](#)" on page 284

5.31 ClearingSystemMemberIdentification2__1

Definition: Unique identification, as assigned by a clearing system, to unambiguously identify a member of the clearing system.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]		106
	MemberIdentification	<MmbId>		[1..1]		107

Used in element(s)

"ClearingSystemMemberIdentification" on page 119, "ClearingSystemMemberIdentification" on page 125, "ClearingSystemMemberIdentification" on page 129, "ClearingSystemMemberIdentification" on page 136, "ClearingSystemMemberIdentification" on page 139

5.31.1 ClearingSystemIdentification

XML Tag: ClrSysId

Presence: [0..1]

Definition: Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed.

The **ClrSysId** block contains the following elements (see datatype "ClearingSystemIdentification2Choice" on page 103 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		103
	Proprietary	<Prtry>	Or}	[1..1]		103

Usage Guideline details

- on camt.106.001.03/Charges/PerType/ChargesAccountAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.106.001.03/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.106.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.106.001.03/Charges/PerType/Record/ChargesAccountAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.106.001.03/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.106.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.106.001.03/Charges/PerTransaction/ChargesAccountAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**

This element is now mandatory, the minimum occurrence has been changed to : 1

- **on camt.106.001.03/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**

This element is now mandatory, the minimum occurrence has been changed to : 1

- **on camt.106.001.03/.header/RelatedTo/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**

This element is now mandatory, the minimum occurrence has been changed to : 1

- **on camt.106.001.03/Charges/Single/ChargesAccountAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**

This element is now mandatory, the minimum occurrence has been changed to : 1

- **on camt.106.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**

This element is now mandatory, the minimum occurrence has been changed to : 1

- **on camt.106.001.03/Charges/PerTransaction/Record/ChargesAccountAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**

This element is now mandatory, the minimum occurrence has been changed to : 1

- **on camt.106.001.03/GroupHeader/ChargesAccountAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**

This element is now mandatory, the minimum occurrence has been changed to : 1

- **on camt.106.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**

This element is now mandatory, the minimum occurrence has been changed to : 1

- **on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**

This element is now mandatory, the minimum occurrence has been changed to : 1

- **on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/Creditor/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**

This element is now mandatory, the minimum occurrence has been changed to : 1

5.31.2 MemberIdentification

XML Tag: Mmbld

Presence: [1..1]

Definition: Identification of a member of a clearing system.

Datatype: "CBPR_RestrictedFINXMax28Text" on page 267

Usage Guideline details

- **on camt.106.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification**

Type changed to: [CBPR_RestrictedFINXMax28Text on page 267](#)

- on camt.106.001.03/Charges/PerTransaction/ChargesAccountAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification

Type changed to: [CBPR_RestrictedFINXMax28Text on page 267](#)

- on camt.106.001.03/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification

Type changed to: [CBPR_RestrictedFINXMax28Text on page 267](#)

- on camt.106.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification

Type changed to: [CBPR_RestrictedFINXMax28Text on page 267](#)

- on camt.106.001.03/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification

Type changed to: [CBPR_RestrictedFINXMax28Text on page 267](#)

- on camt.106.001.03/Charges/PerTransaction/Record/ChargesAccountAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification

Type changed to: [CBPR_RestrictedFINXMax28Text on page 267](#)

- on camt.106.001.03/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification

Type changed to: [CBPR_RestrictedFINXMax28Text on page 267](#)

- on camt.106.001.03/Charges/Single/ChargesAccountAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification

Type changed to: [CBPR_RestrictedFINXMax28Text on page 267](#)

- on camt.106.001.03/Charges/PerType/ChargesAccountAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification

Type changed to: [CBPR_RestrictedFINXMax28Text on page 267](#)

- on camt.106.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification

Type changed to: [CBPR_RestrictedFINXMax28Text on page 267](#)

- on camt.106.001.03/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification

Type changed to: [CBPR_RestrictedFINXMax28Text on page 267](#)

- on camt.106.001.03/GroupHeader/ChargesAccountAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification

Type changed to: [CBPR_RestrictedFINXMax28Text on page 267](#)

- on camt.106.001.03/Charges/PerType/Record/ChargesAccountAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification

Type changed to: [CBPR_RestrictedFINXMax28Text on page 267](#)

- on camt.106.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification

Type changed to: [CBPR_RestrictedFINXMax28Text on page 267](#)

- on [camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification](#)

Type changed to: [CBPR_RestrictedFINXMax28Text on page 267](#)

- on [camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/Creditor/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification](#)

Type changed to: [CBPR_RestrictedFINXMax28Text on page 267](#)

5.32 Contact13

Definition: Specifies the details of the contact person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NamePrefix	<NmPrfx>		[0..1]		109
	Name	<Nm>		[0..1]		110
	PhoneNumber	<PhneNb>		[0..1]		110
	MobileNumber	<MobNb>		[0..1]		110
	FaxNumber	<FaxNb>		[0..1]		110
	URLAddress	<URLAdr>		[0..1]		110
	EmailAddress	<EmailAdr>		[0..1]		110
	EmailPurpose	<EmailPurp>		[0..1]		111
	JobTitle	<JobTitl>		[0..1]		111
	Responsibility	<Rspnsblty>		[0..1]		111
	Department	<Dept>		[0..1]		111
	Other	<Othr>		[0..*]		111
	PreferredMethod	<PrefrdMtd>		[0..1]		111

Used in element(s)

["ContactDetails" on page 176](#), ["ContactDetails" on page 179](#)

5.32.1 NamePrefix

XML Tag: NmPrfx

Presence: [0..1]

Definition: Specifies the terms used to formally address a person.

Datatype: ["NamePrefix2Code" on page 285](#)

5.32.2 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: "Max140Text" on page 282

5.32.3 PhoneNumber

XML Tag: PhneNb

Presence: [0..1]

Definition: Collection of information that identifies a phone number, as defined by telecom services.

Datatype: "PhoneNumber" on page 286

5.32.4 MobileNumber

XML Tag: MobNb

Presence: [0..1]

Definition: Collection of information that identifies a mobile phone number, as defined by telecom services.

Datatype: "PhoneNumber" on page 286

5.32.5 FaxNumber

XML Tag: FaxNb

Presence: [0..1]

Definition: Collection of information that identifies a FAX number, as defined by telecom services.

Datatype: "PhoneNumber" on page 286

5.32.6 URLAddress

XML Tag: URLAdr

Presence: [0..1]

Definition: Address for the Universal Resource Locator (URL), for example an address used over the www (HTTP) service.

Datatype: "Max2048Text" on page 283

5.32.7 EmailAddress

XML Tag: EmailAdr

Presence: [0..1]

Definition: Address for electronic mail (e-mail).

Datatype: "Max256Text" on page 283

5.32.8 EmailPurpose

XML Tag: EmailPurp

Presence: [0..1]

Definition: Purpose for which an email address may be used.

Datatype: ["Max35Text" on page 284](#)

5.32.9 JobTitle

XML Tag: JobTitl

Presence: [0..1]

Definition: Title of the function.

Datatype: ["Max35Text" on page 284](#)

5.32.10 Responsibility

XML Tag: Rspnsblty

Presence: [0..1]

Definition: Role of a person in an organisation.

Datatype: ["Max35Text" on page 284](#)

5.32.11 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: ["Max70Text" on page 285](#)

5.32.12 Other

XML Tag: Othr

Presence: [0..*]

Definition: Contact details in another form.

The **Othr** block contains the following elements (see datatype ["OtherContact1" on page 167](#) for details)

⊘ Removed - !⊘ Partial Removed - ◇ Ignored - !◇ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ChannelType	<ChanlTp>		[1..1]		167
	Identification	<Id>		[0..1]		167

5.32.13 PreferredMethod

XML Tag: PrefrdMtd

Presence: [0..1]

Definition: Preferred method used to reach the contact.

Datatype: "PreferredContactMethod2Code" on page 287

5.33 Contact4

Definition: Specifies the details of the contact person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NamePrefix	<NmPrfx>		[0..1]		112
	Name	<Nm>		[0..1]		112
	PhoneNumber	<PhneNb>		[0..1]		113
	MobileNumber	<MobNb>		[0..1]		113
	FaxNumber	<FaxNb>		[0..1]		113
	EmailAddress	<EmailAdr>		[0..1]		113
	EmailPurpose	<EmailPurp>		[0..1]		113
	JobTitle	<JobTitt>		[0..1]		113
	Responsibility	<Rspnsblty>		[0..1]		114
	Department	<Dept>		[0..1]		114
	Other	<Othr>		[0..*]		114
	PreferredMethod	<PrefrdMtd>		[0..1]		114

Used in element(s)

"ContactDetails" on page 173

5.33.1 NamePrefix

XML Tag: NmPrfx

Presence: [0..1]

Definition: Specifies the terms used to formally address a person.

Datatype: "NamePrefix2Code" on page 285

5.33.2 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: ["Max140Text" on page 282](#)

5.33.3 **PhoneNumber**

XML Tag: PhneNb

Presence: [0..1]

Definition: Collection of information that identifies a phone number, as defined by telecom services.

Datatype: ["PhoneNumber" on page 286](#)

5.33.4 **MobileNumber**

XML Tag: MobNb

Presence: [0..1]

Definition: Collection of information that identifies a mobile phone number, as defined by telecom services.

Datatype: ["PhoneNumber" on page 286](#)

5.33.5 **FaxNumber**

XML Tag: FaxNb

Presence: [0..1]

Definition: Collection of information that identifies a FAX number, as defined by telecom services.

Datatype: ["PhoneNumber" on page 286](#)

5.33.6 **EmailAddress**

XML Tag: EmailAdr

Presence: [0..1]

Definition: Address for electronic mail (e-mail).

Datatype: ["Max2048Text" on page 283](#)

5.33.7 **EmailPurpose**

XML Tag: EmailPurp

Presence: [0..1]

Definition: Purpose for which an email address may be used.

Datatype: ["Max35Text" on page 284](#)

5.33.8 **JobTitle**

XML Tag: JobTitl

Presence: [0..1]

Definition: Title of the function.

Datatype: ["Max35Text" on page 284](#)

5.33.9 Responsibility

XML Tag: Rspnsblty

Presence: [0..1]

Definition: Role of a person in an organisation.

Datatype: "Max35Text" on page 284

5.33.10 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: "Max70Text" on page 285

5.33.11 Other

XML Tag: Othr

Presence: [0..*]

Definition: Contact details in another form.

The **Othr** block contains the following elements (see datatype "OtherContact1" on page 167 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ChannelType	<ChanlTp>		[1..1]		167
	Identification	<Id>		[0..1]		167

5.33.12 PreferredMethod

XML Tag: PrefrdMtd

Presence: [0..1]

Definition: Preferred method used to reach the contact.

Datatype: "PreferredContactMethod1Code" on page 286

5.34 DateAndDateTime2Choice__1

Definition: Choice between a date or a date and time format.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Date	<Dt>	{Or	[1..1]		115

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateTime	<DtTm>	Or}	[1..1]		115

Used in element(s)

["ValueDate" on page 97](#), ["ValueDate" on page 74](#), ["ValueDate" on page 88](#)

5.34.1 Date

XML Tag: Dt

Presence: [1..1]

Definition: Specified date.

Datatype: ["ISODate" on page 280](#)

5.34.2 DateTime

XML Tag: DtTm

Presence: [1..1]

Definition: Specified date and time.

Datatype: ["CBPR_DateTime" on page 265](#)

Usage Guideline details

- on [camt.106.001.03/Charges/PerType/Record/ValueDate/DateTime](#)
Type changed to: [CBPR_DateTime on page 265](#)
- on [camt.106.001.03/Charges/PerTransaction/Record/ValueDate/DateTime](#)
Type changed to: [CBPR_DateTime on page 265](#)
- on [camt.106.001.03/Charges/Single/ValueDate/DateTime](#)
Type changed to: [CBPR_DateTime on page 265](#)

5.35 DateAndPlaceOfBirth1

Definition: Date and place of birth of a person.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BirthDate	<BirthDt>		[1..1]		116
	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		116
	CityOfBirth	<CityOfBirth>		[1..1]		116
	CountryOfBirth	<CtrtyOfBirth>		[1..1]		116

Used in element(s)

["DateAndPlaceOfBirth" on page 180](#), ["DateAndPlaceOfBirth" on page 181](#)

5.35.1 BirthDate

XML Tag: BirthDt

Presence: [1..1]

Definition: Date on which a person is born.

Datatype: ["ISODate" on page 280](#)

5.35.2 ProvinceOfBirth

XML Tag: PrvcOfBirth

Presence: [0..1]

Definition: Province where a person was born.

Datatype: ["Max35Text" on page 284](#)

5.35.3 CityOfBirth

XML Tag: CityOfBirth

Presence: [1..1]

Definition: City where a person was born.

Datatype: ["Max35Text" on page 284](#)

5.35.4 CountryOfBirth

XML Tag: CtryOfBirth

Presence: [1..1]

Definition: Country where a person was born.

Datatype: ["CountryCode" on page 271](#)

5.36 DateAndPlaceOfBirth1__1

Definition: Date and place of birth of a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BirthDate	<BirthDt>		[1..1]		117
	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		117
	CityOfBirth	<CityOfBirth>		[1..1]		117
	CountryOfBirth	<CtryOfBirth>		[1..1]		117

Used in element(s)

["DateAndPlaceOfBirth" on page 182](#)

5.36.1 BirthDate

XML Tag: BirthDt

Presence: [1..1]

Definition: Date on which a person is born.

Datatype: ["CBPR_Date" on page 264](#)

Usage Guideline details

- on [camt.106.001.03/Charges/PerTransaction/Record/Debtor/Identification/PrivateIdentification/DateAndPlaceOfBirth/BirthDate](#)

Type changed to: [CBPR_Date on page 264](#)

5.36.2 ProvinceOfBirth

XML Tag: PrvcOfBirth

Presence: [0..1]

Definition: Province where a person was born.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 269](#)

Usage Guideline details

- on [camt.106.001.03/Charges/PerTransaction/Record/Debtor/Identification/PrivateIdentification/DateAndPlaceOfBirth/ProvinceOfBirth](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)

5.36.3 CityOfBirth

XML Tag: CityOfBirth

Presence: [1..1]

Definition: City where a person was born.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 269](#)

Usage Guideline details

- on [camt.106.001.03/Charges/PerTransaction/Record/Debtor/Identification/PrivateIdentification/DateAndPlaceOfBirth/CityOfBirth](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)

5.36.4 CountryOfBirth

XML Tag: CtryOfBirth

Presence: [1..1]

Definition: Country where a person was born.

Datatype: "CountryCode" on page 271

5.37 FinancialIdentificationSchemeName1Choice

Definition: Sets of elements to identify a name of the organisation identification scheme.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		118
	Proprietary	<Prtry>	Or}	[1..1]		118

Used in element(s)

"SchemeName" on page 147

5.37.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalFinancialInstitutionIdentification1Code" on page 276

5.37.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 284

5.38 FinancialInstitutionIdentification18__1

Definition: Specifies the details to identify a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		119
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		119

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	LEI	<LEI>		[0..1]		120
	Name	<Nm>		[0..1]	🚫	120
	PostalAddress	<PstlAdr>		[0..1]	🚫	120
	Other	<Othr>		[0..1]	🚫	121

Used in element(s)

"FinancialInstitutionIdentification" on page 26

5.38.1 BICFI

XML Tag: BICFI

Presence: [0..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: "BICFIDec2014Identifier" on page 262

Usage Guideline details

- on **camt.106.001.03/header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **camt.106.001.03/header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **camt.106.001.03/header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **camt.106.001.03/header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI**
This element is now mandatory, the minimum occurrence has been changed to : 1

5.38.2 ClearingSystemMemberIdentification

XML Tag: ClrSysMmbld

Presence: [0..1]

Definition: Information used to identify a member within a clearing system.

The **ClrSysMmbld** block contains the following elements (see datatype "ClearingSystemMemberIdentification2__1" on page 105 for details)

🚫 Removed - 🚫 Partial Removed - ✦ Ignored - ✦ Partial Ignored - ⚠️ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]	M	106
	MemberIdentification	<MmbId>		[1..1]	⚠	107

5.38.3 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identifier of the financial institution.

Datatype: "LEIIdentifier" on page 281

5.38.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "Max140Text" on page 282

Usage Guideline details

- This element(camt.106.001.03/header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name) is removed.
- This element(camt.106.001.03/header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name) is removed.
- This element(camt.106.001.03/header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name) is removed.
- This element(camt.106.001.03/header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name) is removed.

5.38.5 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24" on page 184 for details)

ⓧ Removed - **ⓧ** Partial Removed - **◇** Ignored - **◇** Partial Ignored - **⚠** Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		185

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Department	<Dept>		[0..1]		185
	SubDepartment	<SubDept>		[0..1]		185
	StreetName	<StrtNm>		[0..1]		185
	BuildingNumber	<BldgNb>		[0..1]		185
	BuildingName	<BldgNm>		[0..1]		185
	Floor	<Flr>		[0..1]		186
	PostBox	<PstBx>		[0..1]		186
	Room	<Room>		[0..1]		186
	PostCode	<PstCd>		[0..1]		186
	TownName	<TwnNm>		[0..1]		186
	TownLocationName	<TwnLctnNm>		[0..1]		186
	DistrictName	<DstrctNm>		[0..1]		187
	CountrySubDivision	<CtrySubDvsn>		[0..1]		187
	Country	<Ctry>		[0..1]		187
	AddressLine	<AdrLine>		[0..7]		187

Usage Guideline details

- This element([camt.106.001.03/header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress](#)) is removed.
- This element([camt.106.001.03/header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress](#)) is removed.
- This element([camt.106.001.03/header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress](#)) is removed.
- This element([camt.106.001.03/header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress](#)) is removed.

5.38.6 Other

XML Tag: Othr

Presence: [0..1]

Definition: Unique identification of an agent, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericFinancialIdentification1](#)" on [page 147](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		147
	SchemeName	<SchmeNm>		[0..1]		147
	Issuer	<Issr>		[0..1]		148

Usage Guideline details

- This element(camt.106.001.03/header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other) is removed.
- This element(camt.106.001.03/header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other) is removed.
- This element(camt.106.001.03/header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other) is removed.
- This element(camt.106.001.03/header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other) is removed.

5.39 FinancialInstitutionIdentification23

Definition: Specifies the details to identify a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		122
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		123
	LEI	<LEI>		[0..1]		123
	Name	<Nm>		[0..1]		123
	PostalAddress	<PstlAdr>		[0..1]		123
	Other	<Othr>		[0..1]		124

Used in element(s)

"FinancialInstitutionIdentification" on page 27

5.39.1 BICFI

XML Tag: BICFI

Presence: [0..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: ["BICFIDec2014Identifier" on page 262](#)

5.39.2 ClearingSystemMemberIdentification

XML Tag: `ClrSysMmbld`

Presence: [0..1]

Definition: Information used to identify a member within a clearing system.

The **ClrSysMmbld** block contains the following elements (see datatype ["ClearingSystemMemberIdentification2" on page 104](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]		105
	MemberIdentification	<Mmbld>		[1..1]		105

5.39.3 LEI

XML Tag: `LEI`

Presence: [0..1]

Definition: Legal entity identifier of the financial institution.

Datatype: ["LEIIdentifier" on page 281](#)

5.39.4 Name

XML Tag: `Nm`

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: ["Max140Text" on page 282](#)

5.39.5 PostalAddress

XML Tag: `PstlAdr`

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype ["PostalAddress27" on page 187](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		188
	CareOf	<CareOf>		[0..1]		188

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Department	<Dept>		[0..1]		189
	SubDepartment	<SubDept>		[0..1]		189
	StreetName	<StrtNm>		[0..1]		189
	BuildingNumber	<BldgNb>		[0..1]		189
	BuildingName	<BldgNm>		[0..1]		189
	Floor	<Flr>		[0..1]		189
	UnitNumber	<UnitNb>		[0..1]		190
	PostBox	<PstBx>		[0..1]		190
	Room	<Room>		[0..1]		190
	PostCode	<PstCd>		[0..1]		190
	TownName	<TwnNm>		[0..1]		190
	TownLocationName	<TwnLctnNm>		[0..1]		190
	DistrictName	<DstrctNm>		[0..1]		191
	CountrySubDivision	<CtrySubDvsn>		[0..1]		191
	Country	<Ctry>		[0..1]		191
	AddressLine	<AdrLine>		[0..7]		191

5.39.6 Other

XML Tag: Othr

Presence: [0..1]

Definition: Unique identification of an agent, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "GenericFinancialIdentification1" on page 147 for details)

⊘ Removed - ⊘ Partial Removed - ◇ Ignored - ◇ Partial Ignored - ▲ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		147
	SchemeName	<SchmeNm>		[0..1]		147
	Issuer	<Issr>		[0..1]		148

5.40 FinancialInstitutionIdentification23__1

Definition: Specifies the details to identify a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		125
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		125
	LEI	<LEI>		[0..1]		125
	Name	<Nm>		[0..1]		126
	PostalAddress	<PstlAdr>		[0..1]		126
	Other	<Othr>		[0..1]		128

Used in element(s)

"FinancialInstitutionIdentification" on page 29

5.40.1 BICFI

XML Tag: BICFI

Presence: [0..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: "BICFIDec2014Identifier" on page 262

5.40.2 ClearingSystemMemberIdentification

XML Tag: ClrSysMmbld

Presence: [0..1]

Definition: Information used to identify a member within a clearing system.

The **ClrSysMmbld** block contains the following elements (see datatype "[ClearingSystemMemberIdentification2__1](#)" on page 105 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]		106
	MemberIdentification	<Mmbld>		[1..1]		107

5.40.3 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identifier of the financial institution.

Datatype: "LEIIdentifier" on page 281

5.40.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "CBPR_RestrictedFINXMax140Text_Extended" on page 266

Usage Guideline details

- on camt.106.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/Name
Type changed to: [CBPR_RestrictedFINXMax140Text_Extended on page 266](#)
- on camt.106.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/Name
Type changed to: [CBPR_RestrictedFINXMax140Text_Extended on page 266](#)
- on camt.106.001.03/GroupHeader/ChargesAccountAgent/FinancialInstitutionIdentification/Name
Type changed to: [CBPR_RestrictedFINXMax140Text_Extended on page 266](#)
- on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAgent/FinancialInstitutionIdentification/Name
Type changed to: [CBPR_RestrictedFINXMax140Text_Extended on page 266](#)
- on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/Creditor/FinancialInstitutionIdentification/Name
Type changed to: [CBPR_RestrictedFINXMax140Text_Extended on page 266](#)

5.40.5 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress27__1" on page 191 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]	🚫	192
	CareOf	<CareOf>		[0..1]	🚫	193
	Department	<Dept>		[0..1]	⚠	193

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	SubDepartment	<SubDept>		[0..1]		194
	StreetName	<StrtNm>		[0..1]		194
	BuildingNumber	<BldgNb>		[0..1]		195
	BuildingName	<BldgNm>		[0..1]		196
	Floor	<Flr>		[0..1]		196
	UnitNumber	<UnitNb>		[0..1]		197
	PostBox	<PstBx>		[0..1]		197
	Room	<Room>		[0..1]		198
	PostCode	<PstCd>		[0..1]		199
	TownName	<TwnNm>		[0..1]	 	199
	TownLocationName	<TwnLctnNm>		[0..1]		200
	DistrictName	<DstrctNm>		[0..1]		201
	CountrySubDivision	<CtrySubDvsn>		[0..1]		201
	Country	<Ctry>		[0..1]		202
	AddressLine	<AdrlLine>		[0..7]	 R[0..2] R[0..2] R[0..2] R[0..2]	203

Usage Guideline details

- on camt.106.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/PostalAddress
 - CBPR_Duplication_Postal_Address_TextualRule:

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.
- on camt.106.001.03/GroupHeader/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress
 - CBPR_Duplication_Postal_Address_TextualRule:

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.
- on camt.106.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress
 - CBPR_Duplication_Postal_Address_TextualRule:

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.
- on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAgent/FinancialInstitutionIdentification/PostalAddress

– **CBPR_Duplication_Postal_Address_TextualRule:**

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.

- **on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/Creditor/FinancialInstitutionIdentification/PostalAddress**

– **CBPR_Duplication_Postal_Address_TextualRule:**

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.

5.40.6 Other

XML Tag: Othr

Presence: [0..1]

Definition: Unique identification of an agent, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericFinancialIdentification1](#)" on page 147 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		147
	SchemeName	<SchmeNm>		[0..1]		147
	Issuer	<Issr>		[0..1]		148

Usage Guideline details

- This element(camt.106.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/Other) is removed.
- This element(camt.106.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/Other) is removed.
- This element(camt.106.001.03/GroupHeader/ChargesAccountAgent/FinancialInstitutionIdentification/Other) is removed.
- This element(camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/Creditor-Agent/FinancialInstitutionIdentification/Other) is removed.
- This element(camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/Creditor/FinancialInstitutionIdentification/Other) is removed.

5.41 FinancialInstitutionIdentification23__2

Definition: Specifies the details to identify a financial institution.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		129
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		129
	LEI	<LEI>		[0..1]		129
	Name	<Nm>		[0..1]	⚠	130
	PostalAddress	<PstlAdr>		[0..1]	⚠	130
	Other	<Othr>		[0..1]	🚫	134

Used in element(s)

"FinancialInstitutionIdentification" on page 32

5.41.1 BICFI

XML Tag: BICFI

Presence: [0..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: "BICFIDec2014Identifier" on page 262

5.41.2 ClearingSystemMemberIdentification

XML Tag: ClrSysMmbld

Presence: [0..1]

Definition: Information used to identify a member within a clearing system.

The **ClrSysMmbld** block contains the following elements (see datatype "ClearingSystemMemberIdentification2__1" on page 105 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]	M	106
	MemberIdentification	<Mmbld>		[1..1]	⚠	107

5.41.3 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identifier of the financial institution.

Datatype: "LEIIdentifier" on page 281

5.41.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "CBPR_RestrictedFINXMax140Text_Extended" on page 266

Usage Guideline details

- on camt.106.001.03/Charges/PerTransaction/Record/ChargesAccountAgent/FinancialInstitutionIdentification/Name
Type changed to: [CBPR_RestrictedFINXMax140Text_Extended on page 266](#)
- on camt.106.001.03/Charges/Single/ChargesAccountAgent/FinancialInstitutionIdentification/Name
Type changed to: [CBPR_RestrictedFINXMax140Text_Extended on page 266](#)
- on camt.106.001.03/Charges/PerType/ChargesAccountAgent/FinancialInstitutionIdentification/Name
Type changed to: [CBPR_RestrictedFINXMax140Text_Extended on page 266](#)
- on camt.106.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/Name
Type changed to: [CBPR_RestrictedFINXMax140Text_Extended on page 266](#)
- on camt.106.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/Name
Type changed to: [CBPR_RestrictedFINXMax140Text_Extended on page 266](#)

5.41.5 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress27__2" on page 204 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]	🚫	204
	CareOf	<CareOf>		[0..1]		205
	Department	<Dept>		[0..1]	⚠	205

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	SubDepartment	<SubDept>		[0..1]		206
	StreetName	<StrtNm>		[0..1]		207
	BuildingNumber	<BldgNb>		[0..1]		207
	BuildingName	<BldgNm>		[0..1]		208
	Floor	<Flr>		[0..1]		209
	UnitNumber	<UnitNb>		[0..1]		209
	PostBox	<PstBx>		[0..1]		210
	Room	<Room>		[0..1]		210
	PostCode	<PstCd>		[0..1]		211
	TownName	<TwnNm>		[0..1]		212
	TownLocationName	<TwnLctnNm>		[0..1]		212
	DistrictName	<DstrctNm>		[0..1]		213
	CountrySubDivision	<CtrySubDvsn>		[0..1]		214
	Country	<Ctry>		[0..1]		214
	AddressLine	<AdrlLine>		[0..7]	 R[0..3] R[0..3] R[0..3] R[0..3]	215

Usage Guideline details

- on camt.106.001.03/Charges/PerTransaction/Record/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress

- CBPR_StructuredvsUnstructured_FormalRule:

If PostalAddress is used and if AddressLine is present, then all other optional elements in PostalAddress must be absent.

For each [Full Message/Document/ChargesPaymentRequestV03/Charges/PerTransaction/Record/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress], if

at least one occurrence of the following element(s) [PostalAddress/AddressLine] is (are) present
, then

the following element(s) [PostalAddress/Department] and [PostalAddress/Sub-Department] and [PostalAddress/StreetName] and [PostalAddress/BuildingNumber] and [PostalAddress/BuildingName] and [PostalAddress/Floor] and [PostalAddress/PostBox] and [PostalAddress/Room] and [PostalAddress/PostCode] and [PostalAddress/TownName] and [PostalAddress/TownLocationName] and [PostalAddress/DistrictName] and [PostalAddress/CountrySubDivision] and [PostalAddress/Country] must be absent

- on camt.106.001.03/Charges/PerTransaction/Record/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress

- CBPR_TownNameAndCountry_FormalRule:

If Postal Address is used, and if Address Line is absent, then Town Name and Country must be present.

For each [Full Message/Document/ChargesPaymentRequestV03/Charges/PerTransaction/Record/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress], if
 the following element(s) [PostalAddress/AddressLine] is (are) absent
 , then
 at least one occurrence of the following element(s) [PostalAddress/TownName]
 and [PostalAddress/Country] must be present

- **on camt.106.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/PostalAddress**

- **CBPR_StructuredvsUnstructured_FormalRule:**

If PostalAddress is used and if AddressLine is present, then all other optional elements in PostalAddress must be absent.

For each [Full Message/Document/ChargesPaymentRequestV03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/PostalAddress], if
 at least one occurrence of the following element(s) [PostalAddress/AddressLine] is (are) present
 , then
 at least one occurrence of the following element(s) [PostalAddress/Department] and [PostalAddress/SubDepartment] and [PostalAddress/StreetName] and [PostalAddress/BuildingNumber] and [PostalAddress/BuildingName] and [PostalAddress/Floor] and [PostalAddress/PostBox] and [PostalAddress/Room] and [PostalAddress/PostCode] and [PostalAddress/TownName] and [PostalAddress/TownLocationName] and [PostalAddress/DistrictName] and [PostalAddress/CountrySubDivision] and [PostalAddress/Country] must be present

- **on camt.106.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/PostalAddress**

- **CBPR_TownNameAndCountry_FormalRule:**

If Postal Address is used, and if Address Line is absent, then Town Name and Country must be present.

For each [Full Message/Document/ChargesPaymentRequestV03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/PostalAddress], if
 the following element(s) [PostalAddress/AddressLine] is (are) absent
 , then
 at least one occurrence of the following element(s) [PostalAddress/TownName]
 and [PostalAddress/Country] must be present

- **on camt.106.001.03/Charges/Single/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress**

- **CBPR_TownNameAndCountry_FormalRule:**

If Postal Address is used, and if Address Line is absent, then Town Name and Country must be present.

For each [Full Message/Document/ChargesPaymentRequestV03/Charges/Single/ChargeAccountAgent/FinancialInstitutionIdentification/PostalAddress], if
the following element(s) [PostalAddress/AddressLine] is (are) absent
, then
at least one occurrence of the following element(s) [PostalAddress/TownName]
and [PostalAddress/Country] must be present

- **on camt.106.001.03/Charges/Single/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress**

– **CBPR_StructuredvsUnstructured_FormalRule:**

If PostalAddress is used and if AddressLine is present, then all other optional elements in PostalAddress must be absent.

For each [Full Message/Document/ChargesPaymentRequestV03/Charges/Single/ChargeAccountAgent/FinancialInstitutionIdentification/PostalAddress], if
at least one occurrence of the following element(s) [PostalAddress/AddressLine] is (are) present
, then
the following element(s) [PostalAddress/Department] and [PostalAddress/Sub-Department] and [PostalAddress/StreetName] and [PostalAddress/BuildingNumber] and [PostalAddress/BuildingName] and [PostalAddress/Floor] and [PostalAddress/PostBox] and [PostalAddress/Room] and [PostalAddress/PostCode] and [PostalAddress/TownName] and [PostalAddress/TownLocationName] and [PostalAddress/DistrictName] and [PostalAddress/CountrySubDivision] and [PostalAddress/Country] must be absent

- **on camt.106.001.03/Charges/PerType/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress**

– **CBPR_StructuredvsUnstructured_FormalRule:**

If PostalAddress is used and if AddressLine is present, then all other optional elements in PostalAddress must be absent.

For each [Full Message/Document/ChargesPaymentRequestV03/Charges/PerType/ChargeAccountAgent/FinancialInstitutionIdentification/PostalAddress], if
at least one occurrence of the following element(s) [PostalAddress/AddressLine] is (are) present
, then
the following element(s) [PostalAddress/Department] and [PostalAddress/Sub-Department] and [PostalAddress/StreetName] and [PostalAddress/BuildingNumber] and [PostalAddress/BuildingName] and [PostalAddress/Floor] and [PostalAddress/PostBox] and [PostalAddress/Room] and [PostalAddress/PostCode] and [PostalAddress/TownName] and [PostalAddress/TownLocationName] and [PostalAddress/DistrictName] and [PostalAddress/CountrySubDivision] and [PostalAddress/Country] must be absent

- **on camt.106.001.03/Charges/PerType/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress**

– **CBPR_TownNameAndCountry_FormalRule:**

If Postal Address is used, and if Address Line is absent, then Town Name and Country must be present.

For each [Full Message/Document/ChargesPaymentRequestV03/Charges/PerType/ChargeAccountAgent/FinancialInstitutionIdentification/PostalAddress], if the following element(s) [PostalAddress/AddressLine] is (are) absent, then at least one occurrence of the following element(s) [PostalAddress/TownName] and [PostalAddress/Country] must be present

- on camt.106.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress

– **CBPR_StructuredvsUnstructured_FormalRule:**

If PostalAddress is used and if AddressLine is present, then all other optional elements in PostalAddress must be absent.

For each [Full Message/Document/ChargesPaymentRequestV03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress], if at least one occurrence of the following element(s) [PostalAddress/AddressLine] is (are) present, then the following element(s) [PostalAddress/Department] and [PostalAddress/Sub-Department] and [PostalAddress/StreetName] and [PostalAddress/BuildingNumber] and [PostalAddress/BuildingName] and [PostalAddress/Floor] and [PostalAddress/PostBox] and [PostalAddress/Room] and [PostalAddress/PostCode] and [PostalAddress/TownName] and [PostalAddress/TownLocationName] and [PostalAddress/DistrictName] and [PostalAddress/CountrySubDivision] and [PostalAddress/Country] must be absent

- on camt.106.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress

– **CBPR_TownNameAndCountry_FormalRule:**

If Postal Address is used, and if Address Line is absent, then Town Name and Country must be present.

For each [Full Message/Document/ChargesPaymentRequestV03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress], if the following element(s) [PostalAddress/AddressLine] is (are) absent, then at least one occurrence of the following element(s) [PostalAddress/TownName] and [PostalAddress/Country] must be present

5.41.6 Other

XML Tag: Othr

Presence: [0..1]

Definition: Unique identification of an agent, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericFinancialIdentification1](#)" on page 147 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		147
	SchemeName	<SchmeNm>		[0..1]		147
	Issuer	<Issr>		[0..1]		148

Usage Guideline details

- This element(camt.106.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/Other) is removed.
- This element(camt.106.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/Other) is removed.
- This element(camt.106.001.03/Charges/PerTransaction/Record/ChargesAccountAgent/FinancialInstitutionIdentification/Other) is removed.
- This element(camt.106.001.03/Charges/PerType/ChargesAccountAgent/FinancialInstitutionIdentification/Other) is removed.
- This element(camt.106.001.03/Charges/Single/ChargesAccountAgent/FinancialInstitutionIdentification/Other) is removed.

5.42 FinancialInstitutionIdentification23__3

Definition: Specifies the details to identify a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		135
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		136
	LEI	<LEI>		[0..1]		136
	Name	<Nm>		[0..1]		136
	PostalAddress	<PstlAdr>		[0..1]		136
	Other	<Othr>		[0..1]		138

Used in element(s)

"FinancialInstitutionIdentification" on page 36

5.42.1 BICFI

XML Tag: BICFI

Presence: [0..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: "BICFIDec2014Identifier" on page 262

5.42.2 ClearingSystemMemberIdentification

XML Tag: ClrSysMmbld

Presence: [0..1]

Definition: Information used to identify a member within a clearing system.

The **ClrSysMmbld** block contains the following elements (see datatype "ClearingSystemMemberIdentification2__1" on page 105 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]		106
	MemberIdentification	<Mmbld>		[1..1]		107

5.42.3 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identifier of the financial institution.

Datatype: "LEIIdentifier" on page 281

5.42.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "Max140Text" on page 282

5.42.5 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress27__2" on page 204 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		204
	CareOf	<CareOf>		[0..1]		205
	Department	<Dept>		[0..1]		205
	SubDepartment	<SubDept>		[0..1]		206
	StreetName	<StrtNm>		[0..1]		207
	BuildingNumber	<BldgNb>		[0..1]		207
	BuildingName	<BldgNm>		[0..1]		208
	Floor	<Flr>		[0..1]		209
	UnitNumber	<UnitNb>		[0..1]		209
	PostBox	<PstBx>		[0..1]		210
	Room	<Room>		[0..1]		210
	PostCode	<PstCd>		[0..1]		211
	TownName	<TwnNm>		[0..1]		212
	TownLocationName	<TwnLctnNm>		[0..1]		212
	DistrictName	<DstrctNm>		[0..1]		213
	CountrySubDivision	<CtrySubDvsn>		[0..1]		214
	Country	<Ctry>		[0..1]		214
	AddressLine	<AdrLine>		[0..7]	 R[0..3]	215

Usage Guideline details

- on camt.106.001.03/Charges/PerTransaction/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress

- CBPR_TownNameAndCountry_FormalRule:

If Postal Address is used, and if Address Line is absent, then Town Name and Country must be present.

For each [Full Message/Document/ChargesPaymentRequestV03/Charges/PerTransaction/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress], if the following element(s) [PostalAddress/AddressLine] is (are) absent, then at least one occurrence of the following element(s) [PostalAddress/TownName] and [PostalAddress/Country] must be present

- on camt.106.001.03/Charges/PerTransaction/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress

- CBPR_StructuredvsUnstructured_FormalRule:

If PostalAddress is used and if AddressLine is present, then all other optional elements in PostalAddress must be absent.

For each [Full Message/Document/ChargesPaymentRequestV03/Charges/PerTransaction/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress], if at least one occurrence of the following element(s) [PostalAddress/AddressLine] is (are) present, then the following element(s) [PostalAddress/Department] and [PostalAddress/Sub-Department] and [PostalAddress/StreetName] and [PostalAddress/BuildingNumber] and [PostalAddress/BuildingName] and [PostalAddress/Floor] and [PostalAddress/PostBox] and [PostalAddress/Room] and [PostalAddress/PostCode] and [PostalAddress/TownName] and [PostalAddress/TownLocationName] and [PostalAddress/DistrictName] and [PostalAddress/CountrySubDivision] and [PostalAddress/Country] must be absent

5.42.6 Other

XML Tag: Othr

Presence: [0..1]

Definition: Unique identification of an agent, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericFinancialIdentification1](#)" on page 147 for details)

🚫 Removed - 🚫 Partial Removed - ⬡ Ignored - ⬡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		147
	SchemeName	<SchmeNm>		[0..1]		147
	Issuer	<Issr>		[0..1]		148

Usage Guideline details

- This element([camt.106.001.03/Charges/PerTransaction/ChargesAccountAgent/FinancialInstitutionIdentification/Other](#)) is removed.

5.43 FinancialInstitutionIdentification23__4

Definition: Specifies the details to identify a financial institution.

🚫 Removed - 🚫 Partial Removed - ⬡ Ignored - ⬡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		139

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		139
	LEI	<LEI>		[0..1]		139
	Name	<Nm>		[0..1]	⚠	139
	PostalAddress	<PstlAdr>		[0..1]	⚠	140
	Other	<Othr>		[0..1]	🚫	141

Used in element(s)

"FinancialInstitutionIdentification" on page 38

5.43.1 BICFI

XML Tag: BICFI

Presence: [0..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: "BICFIDec2014Identifier" on page 262

5.43.2 ClearingSystemMemberIdentification

XML Tag: ClrSysMmbld

Presence: [0..1]

Definition: Information used to identify a member within a clearing system.

The **ClrSysMmbld** block contains the following elements (see datatype "ClearingSystemMemberIdentification2__1" on page 105 for details)

🚫 Removed - 🚫 Partial Removed - ⚠ Ignored - ⚠ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]	M	106
	MemberIdentification	<Mmbld>		[1..1]	⚠	107

5.43.3 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identifier of the financial institution.

Datatype: "LEIIdentifier" on page 281

5.43.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "CBPR_RestrictedFINXMax140Text_Extended" on page 266

Usage Guideline details

- on camt.106.001.03/Charges/PerType/Record/ChargesAccountAgent/FinancialInstitutionIdentification/Name

Type changed to: CBPR_RestrictedFINXMax140Text_Extended on page 266

5.43.5 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress27__4" on page 222 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		223
	CareOf	<CareOf>		[0..1]		223
	Department	<Dept>		[0..1]		224
	SubDepartment	<SubDept>		[0..1]		224
	StreetName	<StrtNm>		[0..1]		224
	BuildingNumber	<BldgNb>		[0..1]		225
	BuildingName	<BldgNm>		[0..1]		225
	Floor	<Flr>		[0..1]		225
	UnitNumber	<UnitNb>		[0..1]		225
	PostBox	<PstBx>		[0..1]		226
	Room	<Room>		[0..1]		226
	PostCode	<PstCd>		[0..1]		226
	TownName	<TwnNm>		[0..1]		226
	TownLocationName	<TwnLctnNm>		[0..1]		227
	DistrictName	<DstrctNm>		[0..1]		227
	CountrySubDivision	<CtrySubDvsn>		[0..1]		227

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Country	<Ctry>		[0..1]		227
	AddressLine	<AdrLine>		[0..7]	 R[0..3]	228

Usage Guideline details

- on **camt.106.001.03/Charges/PerType/Record/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress**

- **CBPR_TownNameAndCountry_FormalRule:**

If Postal Address is used, and if Address Line is absent, then Town Name and Country must be present.

For each [Full Message/Document/ChargesPaymentRequestV03/Charges/PerType/Record/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress], if the following element(s) [PostalAddress/AddressLine] is (are) absent, then at least one occurrence of the following element(s) [PostalAddress/TownName] and [PostalAddress/Country] must be present

- on **camt.106.001.03/Charges/PerType/Record/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress**

- **CBPR_StructuredvsUnstructured_FormalRule:**

If PostalAddress is used and if AddressLine is present, then all other optional elements in PostalAddress must be absent.

For each [Full Message/Document/ChargesPaymentRequestV03/Charges/PerType/Record/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress], if at least one occurrence of the following element(s) [PostalAddress/AddressLine] is (are) present, then the following element(s) [PostalAddress/Department] and [PostalAddress/Sub-Department] and [PostalAddress/StreetName] and [PostalAddress/BuildingNumber] and [PostalAddress/BuildingName] and [PostalAddress/Floor] and [PostalAddress/PostBox] and [PostalAddress/Room] and [PostalAddress/PostCode] and [PostalAddress/TownName] and [PostalAddress/TownLocationName] and [PostalAddress/DistrictName] and [PostalAddress/CountrySubDivision] and [PostalAddress/Country] must be absent

5.43.6 Other

XML Tag: Othr

Presence: [0..1]

Definition: Unique identification of an agent, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericFinancialIdentification1](#)" on page 147 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		147
	SchemeName	<SchmeNm>		[0..1]		147
	Issuer	<Issr>		[0..1]		148

Usage Guideline details

- This element([camt.106.001.03/Charges/PerType/Record/ChargesAccountAgent/FinancialInstitutionIdentification/Other](#)) is removed.

5.44 GenericAccountIdentification1

Definition: Information related to a generic account identification.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		142
	SchemeName	<SchmeNm>		[0..1]		142
	Issuer	<Issr>		[0..1]		143

Used in element(s)

"Other" on [page 20](#)

5.44.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: ["Max34Text"](#) on [page 283](#)

5.44.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype ["AccountSchemeName1Choice"](#) on [page 22](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		23
	Proprietary	<Prtry>	Or}	[1..1]		23

5.44.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 284

5.45 GenericAccountIdentification1__1

Definition: Information related to a generic account identification.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		143
	SchemeName	<SchmeNm>		[0..1]		144
	Issuer	<Issr>		[0..1]		145

Used in element(s)

"Other" on page 21

5.45.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: "CBPR_RestrictedFINXMax34Text" on page 268

Usage Guideline details

- on camt.106.001.03/Charges/PerTransaction/Record/DebtorAgentAccount/Identification/Other/Identification
Type changed to: CBPR_RestrictedFINXMax34Text on page 268
- on camt.106.001.03/GroupHeader/ChargesAccountAgentAccount/Identification/Other/Identification

Type changed to: [CBPR_RestrictedFINXMax34Text on page 268](#)

- on camt.106.001.03/Charges/PerType/Record/DebtorAgentAccount/Identification/Other/Identification

Type changed to: [CBPR_RestrictedFINXMax34Text on page 268](#)

- on camt.106.001.03/Charges/Single/ChargesAccountAgentAccount/Identification/Other/Identification

Type changed to: [CBPR_RestrictedFINXMax34Text on page 268](#)

- on camt.106.001.03/Charges/PerType/ChargesAccountAgentAccount/Identification/Other/Identification

Type changed to: [CBPR_RestrictedFINXMax34Text on page 268](#)

- on camt.106.001.03/Charges/PerTransaction/Record/ChargesAccountAgentAccount/Identification/Other/Identification

Type changed to: [CBPR_RestrictedFINXMax34Text on page 268](#)

- on camt.106.001.03/Charges/PerType/Record/ChargesAccountAgentAccount/Identification/Other/Identification

Type changed to: [CBPR_RestrictedFINXMax34Text on page 268](#)

- on camt.106.001.03/Charges/PerTransaction/ChargesAccountAgentAccount/Identification/Other/Identification

Type changed to: [CBPR_RestrictedFINXMax34Text on page 268](#)

- on camt.106.001.03/Charges/PerTransaction/Record/DebtorAccount/Identification/Other/Identification

Type changed to: [CBPR_RestrictedFINXMax34Text on page 268](#)

- on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAgentAccount/Identification/Other/Identification

Type changed to: [CBPR_RestrictedFINXMax34Text on page 268](#)

- on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAccount/Identification/Other/Identification

Type changed to: [CBPR_RestrictedFINXMax34Text on page 268](#)

5.45.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "AccountScheme-Name1Choice__1" on page 23 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		23
	Proprietary	<Prtry>	Or}	[1..1]		23

5.45.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 268

Usage Guideline details

- on camt.106.001.03/Charges/PerTransaction/Record/ChargesAccountAgentAccount/Identification/Other/Issuer
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on camt.106.001.03/GroupHeader/ChargesAccountAgentAccount/Identification/Other/Issuer
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on camt.106.001.03/Charges/PerType/Record/ChargesAccountAgentAccount/Identification/Other/Issuer
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on camt.106.001.03/Charges/Single/ChargesAccountAgentAccount/Identification/Other/Issuer
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on camt.106.001.03/Charges/PerTransaction/ChargesAccountAgentAccount/Identification/Other/Issuer
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on camt.106.001.03/Charges/PerTransaction/Record/DebtorAgentAccount/Identification/Other/Issuer
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on camt.106.001.03/Charges/PerType/Record/DebtorAgentAccount/Identification/Other/Issuer
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on camt.106.001.03/Charges/PerType/ChargesAccountAgentAccount/Identification/Other/Issuer
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on camt.106.001.03/Charges/PerTransaction/Record/DebtorAccount/Identification/Other/Issuer
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAgentAccount/Identification/Other/Issuer

Type changed to: [CBPR_RestrictedFINXMax35Text](#) on page 268

- on [camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAccount/Identification/Other/Issuer](#)

Type changed to: [CBPR_RestrictedFINXMax35Text](#) on page 268

5.46 GenericAccountIdentification1__2

Definition: Information related to a generic account identification.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		146
	SchemeName	<SchmeNm>		[0..1]		146
	Issuer	<Issr>		[0..1]		146

Used in element(s)

["Other" on page 22](#)

5.46.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: ["Max34Text" on page 283](#)

5.46.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype ["AccountSchemeName1Choice_1" on page 23](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		23
	Proprietary	<Prtry>	Or}	[1..1]		23

5.46.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 268

Usage Guideline details

- on **camt.106.001.03/Charges/Single/DebtorAgentAccount/Identification/Other/Issuer**
Type changed to: CBPR_RestrictedFINXMax35Text on page 268

5.47 GenericFinancialIdentification1

Definition: Information related to an identification of a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		147
	SchemeName	<SchmeNm>		[0..1]		147
	Issuer	<Issr>		[0..1]		148

Used in element(s)

"Other" on page 124, "Other" on page 121, "Other" on page 128, "Other" on page 134, "Other" on page 138, "Other" on page 141

5.47.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: "Max35Text" on page 284

5.47.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "FinancialIdentificationScheme-Name1Choice" on page 118 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		118
	Proprietary	<Prtry>	Or}	[1..1]		118

5.47.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 284

5.48 GenericIdentification3

Definition: Information related to an identification, for example, party identification or account identification.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		148
	Issuer	<Issr>		[0..1]		148

Used in element(s)

"Proprietary" on page 59

5.48.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Name or number assigned by an entity to enable recognition of that entity, for example, account identifier.

Datatype: "Max35Text" on page 284

5.48.2 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 284

5.49 GenericIdentification30

Definition: Information related to an identification, for example, party identification or account identification.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - 🟡 Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		149
	Issuer	<Issr>		[1..1]		149
	SchemeName	<SchmeNm>		[0..1]		149

Used in element(s)

"Proprietary" on page 25

5.49.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Proprietary information, often a code, issued by the data source scheme issuer.

Datatype: "Exact4AlphaNumericText" on page 273

5.49.2 Issuer

XML Tag: Issr

Presence: [1..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 284

5.49.3 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Short textual description of the scheme.

Datatype: "Max35Text" on page 284

5.50 GenericOrganisationIdentification1

Definition: Information related to an identification of an organisation.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - 🟡 Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		150

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	SchemeName	<SchmeNm>		[0..1]		150
	Issuer	<Issr>		[0..1]		150

Used in element(s)

"Other" on page 163

5.50.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: "Max35Text" on page 284

5.50.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "OrganisationIdentificationSchemeName1Choice" on page 166 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		166
	Proprietary	<Prtry>	Or}	[1..1]		166

5.50.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 284

5.51 GenericOrganisationIdentification3

Definition: Information related to an identification of an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		151
	SchemeName	<SchmeNm>		[0..1]		151
	Issuer	<Issr>		[0..1]		151

Used in element(s)

"Other" on page 165

5.51.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: "Max256Text" on page 283

5.51.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "[OrganisationIdentificationSchemeName1Choice](#)" on page 166 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		166
	Proprietary	<Prtry>	Or}	[1..1]		166

5.51.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 284

5.52 GenericOrganisationIdentification3__1

Definition: Information related to an identification of an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		152
	SchemeName	<SchmeNm>		[0..1]		152
	Issuer	<Issr>		[0..1]		153

Used in element(s)

"Other" on page 166

5.52.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 268

Usage Guideline details

- on camt.106.001.03/Charges/PerTransaction/Record/Debtor/Identification/OrganisationIdentification/Other/Identification

Type changed to: CBPR_RestrictedFINXMax35Text on page 268

5.52.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "OrganisationIdentificationSchemeName1Choice" on page 166 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		166
	Proprietary	<Prtry>	Or}	[1..1]		166

Usage Guideline details

- on camt.106.001.03/Charges/PerTransaction/Record/Debtor/Identification/OrganisationIdentification/Other/SchemeName

This element is now mandatory, the minimum occurrence has been changed to : 1

5.52.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 268

Usage Guideline details

- on camt.106.001.03/Charges/PerTransaction/Record/Debtor/Identification/OrganisationIdentification/Other/Issuer

Type changed to: CBPR_RestrictedFINXMax35Text on page 268

5.53 GenericPersonIdentification1

Definition: Information related to an identification of a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		153
	SchemeName	<SchmeNm>		[0..1]		153
	Issuer	<Issr>		[0..1]		154

Used in element(s)

"Other" on page 180

5.53.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: "Max35Text" on page 284

5.53.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "PersonIdentificationScheme-Name1Choice" on page 183 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		183
	Proprietary	<Prtry>	Or}	[1..1]		184

5.53.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 284

5.54 GenericPersonIdentification2

Definition: Information related to an identification of a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		154
	SchemeName	<SchmeNm>		[0..1]		154
	Issuer	<Issr>		[0..1]		155

Used in element(s)

"Other" on page 181

5.54.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: "Max256Text" on page 283

5.54.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "PersonIdentificationScheme-Name1Choice" on page 183 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		183
	Proprietary	<Prtry>	Or}	[1..1]		184

5.54.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 284

5.55 GenericPersonIdentification2__1

Definition: Information related to an identification of a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		155
	SchemeName	<SchmeNm>		[0..1]		155
	Issuer	<Issr>		[0..1]		156

Used in element(s)

"Other" on page 183

5.55.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 268

Usage Guideline details

- on camt.106.001.03/Charges/PerTransaction/Record/Debtor/Identification/PrivateIdentification/Other/Identification

Type changed to: CBPR_RestrictedFINXMax35Text on page 268

5.55.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "[PersonIdentificationScheme-Name1Choice](#)" on page 183 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		183
	Proprietary	<Prtry>	Or}	[1..1]	🚫	184

Usage Guideline details

- on [camt.106.001.03/Charges/PerTransaction/Record/Debtor/Identification/PrivateIdentification/Other/SchemeName](#)

This element is now mandatory, the minimum occurrence has been changed to : 1

5.55.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "[CBPR_RestrictedFINXMax35Text](#)" on page 268

Usage Guideline details

- on [camt.106.001.03/Charges/PerTransaction/Record/Debtor/Identification/PrivateIdentification/Other/Issuer](#)

Type changed to: [CBPR_RestrictedFINXMax35Text](#) on page 268

5.56 GroupHeader130__1

Definition: Set of characteristics shared by all individual charges records included in the message.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	MessageIdentification	<MsgId>		[1..1]	⚠	157
	CreationDateTime	<CreDtTm>		[1..1]	⚠	157
	ChargesRequestor	<ChrgsRqstr>		[0..1]	🚫	157
	SettlementInstruction	<SttlmInstr>		[0..1]	🚫	158
	TotalCharges	<TtlChrgs>		[0..1]	M	158

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ChargesAccountAgent	<ChrgsAcctAgt>		[0..1]		159
	ChargesAccountAgentAccount	<ChrgsAcctAgtAcct>		[0..1]		160

Used in element(s)

"GroupHeader" on page 17

5.56.1 MessageIdentification

XML Tag: MsgId

Presence: [1..1]

Definition: Point to point reference, as assigned by the instructing party, and sent to the next party in the chain to unambiguously identify the message.

Usage: The instructing party has to make sure that MessageIdentification is unique per instructed party for a pre-agreed period.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 268

Usage Guideline details

- on camt.106.001.03/GroupHeader/MessageIdentification
Type changed to: CBPR_RestrictedFINXMax35Text on page 268

5.56.2 CreationDateTime

XML Tag: CreDtTm

Presence: [1..1]

Definition: Date and time at which the message was created.

Datatype: "CBPR_DateTime" on page 265

Usage Guideline details

- on camt.106.001.03/GroupHeader/CreationDateTime
Type changed to: CBPR_DateTime on page 265

5.56.3 ChargesRequestor

XML Tag: ChrgsRqstr

Presence: [0..1]

Definition: Agent that requests the charges, if other than the sender.

The **ChrgsRqstr** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification8" on page 27 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		27
	BranchIdentification	<BrnchId>		[0..1]		28

Usage Guideline details

- This element([camt.106.001.03/GroupHeader/ChargesRequestor](#)) is removed.

5.56.4 SettlementInstruction

XML Tag: SttlmInstr

Presence: [0..1]

Definition: Specifies the details on how the settlement of the subsequent transaction(s) is completed.

Usage: this agent and party data should be mapped as-is onto the resulting message for the payment of the charges.

The **SttlmInstr** block contains the following elements (see datatype "[SettlementInstruction19](#)" on page 234 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	RequestedSettlementDate	<ReqdSttlmDt>		[0..1]		234
	CreditorAgent	<CdtrAgt>		[1..1]		234
	CreditorAgentAccount	<CdtrAgtAcct>		[0..1]		235
	Creditor	<Cdtr>		[0..1]		235
	CreditorAccount	<CdtrAcct>		[0..1]		235

Usage Guideline details

- This element([camt.106.001.03/GroupHeader/SettlementInstruction](#)) is removed.

5.56.5 TotalCharges

XML Tag: TtlChrgs

Presence: [0..1]

Definition: Total charges claimed through this message.

The **TtlChrgs** block contains the following elements (see datatype "TotalCharges7__1" on page 241 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NumberOfChargesRecords	<NbOfChrgsRcrds>		[1..1]		242
	ControlSum	<CtrlSum>		[0..1]	🚫	242
	TotalChargesAmount	<TtlChrgsAmt>		[0..1]	M ⚠	242
	CreditDebitIndicator	<CdtDbtInd>		[0..1]	M	243

Usage Guideline details

- on camt.106.001.03/GroupHeader/TotalCharges

This element is now mandatory, the minimum occurrence has been changed to : 1

5.56.6 ChargesAccountAgent

XML Tag: ChrgsAcctAgt

Presence: [0..1]

Definition: Agent that services the charges account.

Usage: this element should be used where the charge being claimed does not relate to the processing of a payment transaction e.g. it relates to an investigation or other process. This identifies the agent that services the account from which charges are to be settled from.

The **ChrgsAcctAgt** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification8__1" on page 28 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]	⚠	29
	BranchIdentification	<BrnchId>		[0..1]	🚫	31

Usage Guideline details

- on camt.106.001.03/GroupHeader/ChargesAccountAgent

– CBPR_Agent_Option_3_TextualRule:

Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country]). It is recommended to also add the post code when available

- on camt.106.001.03/GroupHeader/ChargesAccountAgent
 - CBPR_Agent_Option_1_TextualRule:

BICFI, complemented optionally with a LEI (preferred option)
- on camt.106.001.03/GroupHeader/ChargesAccountAgent
 - CBPR_Agent_National_only_TextualRule:

Whenever all agents in the chain are located within the same country, the clearing code only may be used.
- on camt.106.001.03/GroupHeader/ChargesAccountAgent
 - CBPR_Agent_Option_2_TextualRule:

(Clearing Code OR LEI) AND (Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country])). It is recommended to also add the post code when available

5.56.7 ChargesAccountAgentAccount

XML Tag: ChrgsAcctAgtAcct

Presence: [0..1]

Definition: Account of the agent that services the charges account.

Usage: this element should be used where the charge being claimed does not relate to the processing of a payment transaction e.g. it relates to an investigation or other process. This identifies the account from which charges are to be settled from.

The **ChrgsAcctAgtAcct** block contains the following elements (see datatype "CashAccount40__1" on page 50 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		50
	Type	<Tp>		[0..1]		51
	Currency	<Ccy>		[0..1]		52
	Name	<Nm>		[0..1]		52
	Proxy	<Prxy>		[0..1]		53

5.57 ImplementationSpecification1

Definition: Identifies the implementation specification to which the ISO 20022 message conforms.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Registry	<Regy>		[1..1]		161
	Identification	<Id>		[1..1]		161

Used in element(s)

"MarketPractice" on page 13

5.57.1 Registry

XML Tag: Regy

Presence: [1..1]

Definition: Name of the implementation specification registry in which the implementation specification of the ISO 20022 message is maintained.

For example, "MyStandards".

Datatype: "Max350Text" on page 283

5.57.2 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identifier which unambiguously identifies, within the implementation specification registry, the implementation specification to which the ISO 20022 message is compliant. This can be done via a URN. It can also contain a version number or date.

For instance, "2018-01-01 - Version 2" or "urn:uuid:6e8bc430-9c3a-11d9-9669-0800200c9a66".

Datatype: "Max2048Text" on page 283

5.58 InstructionForInstructedAgent1

Definition: Further information related to the processing of the charges instruction that may need to be acted upon by the instructed agent. The instruction may relate to an instruction that has to be executed by the instructed agent, or may be information required by the instructed agent.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>		[0..1]		162
	InstructionInformation	<InstrInf>		[0..1]		162

Used in element(s)

"InstructionForInstructedAgent" on page 102, "InstructionForInstructedAgent" on page 93

5.58.1 Code

XML Tag: Cd

Presence: [0..1]

Definition: Coded information related to the processing of the payment instruction, provided by the initiating party, and intended for the instructed agent.

Datatype: "ExternalInstructedAgentInstruction1Code" on page 277

5.58.2 InstructionInformation

XML Tag: InstrInf

Presence: [0..1]

Definition: Further information complementing the coded instruction or instruction to the instructed agent that is bilaterally agreed or specific to a user community.

Datatype: "Max140Text" on page 282

5.59 InstructionForInstructedAgent1__1

Definition: Further information related to the processing of the charges instruction that may need to be acted upon by the instructed agent. The instruction may relate to an instruction that has to be executed by the instructed agent, or may be information required by the instructed agent.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>		[0..1]		162
	InstructionInformation	<InstrInf>		[0..1]		163

Used in element(s)

"InstructionForInstructedAgent" on page 80

5.59.1 Code

XML Tag: Cd

Presence: [0..1]

Definition: Coded information related to the processing of the payment instruction, provided by the initiating party, and intended for the instructed agent.

Datatype: "ExternalInstructedAgentInstruction1Code" on page 277

Usage Guideline details

- on camt.106.001.03/Charges/PerTransaction/Record/InstructionForInstructedAgent/Code**
 This element is now mandatory, the minimum occurrence has been changed to : 1

5.59.2 InstructionInformation

XML Tag: InstrInf

Presence: [0..1]

Definition: Further information complementing the coded instruction or instruction to the instructed agent that is bilaterally agreed or specific to a user community.

Datatype: "CBPR_RestrictedFINXMax140Text" on page 265

Usage Guideline details

- on camt.106.001.03/Charges/PerTransaction/Record/InstructionForInstructedAgent/InstructionInformation

Type changed to: CBPR_RestrictedFINXMax140Text on page 265

5.60 OrganisationIdentification29

Definition: Unique and unambiguous way to identify an organisation.

🔴 Removed - 🔴 Partial Removed - 🔹 Ignored - 🔹 Partial Ignored - ⚠ Details below -

📌 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AnyBIC	<AnyBIC>		[0..1]		163
	LEI	<LEI>		[0..1]		163
	Other	<Othr>		[0..*]		163

Used in element(s)

"OrganisationIdentification" on page 168

5.60.1 AnyBIC

XML Tag: AnyBIC

Presence: [0..1]

Definition: Business identification code of the organisation.

Datatype: "AnyBICDec2014Identifier" on page 262

5.60.2 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identification as an alternate identification for a party.

Datatype: "LEIIdentifier" on page 281

5.60.3 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of an organisation, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericOrganisationIdentification1](#)" on page 149 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		150
	SchemeName	<SchmeNm>		[0..1]		150
	Issuer	<Issr>		[0..1]		150

5.61 OrganisationIdentification39

Definition: Unique and unambiguous way to identify an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AnyBIC	<AnyBIC>		[0..1]		164
	LEI	<LEI>		[0..1]		164
	Other	<Othr>		[0..*]		165

Used in element(s)

"[OrganisationIdentification](#)" on page 170

5.61.1 AnyBIC

XML Tag: AnyBIC

Presence: [0..1]

Definition: Business identification code of the organisation.

Datatype: "[AnyBICDec2014Identifier](#)" on page 262

5.61.2 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identification as an alternate identification for a party.

Datatype: "[LEIIdentifier](#)" on page 281

5.61.3 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of an organisation, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericOrganisationIdentification3](#)" on page 150 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		151
	SchemeName	<SchmeNm>		[0..1]		151
	Issuer	<Issr>		[0..1]		151

5.62 OrganisationIdentification39__1

Definition: Unique and unambiguous way to identify an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AnyBIC	<AnyBIC>		[0..1]		165
	LEI	<LEI>		[0..1]		165
	Other	<Othr>		[0..*]		166

Used in element(s)

["OrganisationIdentification"](#) on page 171

5.62.1 AnyBIC

XML Tag: AnyBIC

Presence: [0..1]

Definition: Business identification code of the organisation.

Datatype: "[AnyBICDec2014Identifier](#)" on page 262

5.62.2 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identification as an alternate identification for a party.

Datatype: "LEIIdentifier" on page 281

5.62.3 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of an organisation, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "GenericOrganisationIdentification3__1" on page 151 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]	⚠	152
	SchemeName	<SchmeNm>		[0..1]	M	152
	Issuer	<Issr>		[0..1]	⚠	153

5.63 OrganisationIdentificationSchemeName1Choice

Definition: Sets of elements to identify a name of the organisation identification scheme.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		166
	Proprietary	<Prtry>	Or}	[1..1]	🚫	166

Used in element(s)

"SchemeName" on page 150, "SchemeName" on page 151, "SchemeName" on page 152

5.63.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalOrganisationIdentification1Code" on page 278

5.63.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 284

Usage Guideline details

- This element([camt.106.001.03/Charges/PerTransaction/Record/Debtor/Identification/OrganisationIdentification/Other/SchemeName/Proprietary](#)) is removed.

5.64 OtherContact1

Definition: Communication device number or electronic address used for communication.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ChannelType	<ChanTp>		[1..1]		167
	Identification	<Id>		[0..1]		167

Used in element(s)

"Other" on page 111, "Other" on page 114

5.64.1 ChannelType

XML Tag: ChanTp

Presence: [1..1]

Definition: Method used to contact the financial institution's contact for the specific tax region.

Datatype: "Max4Text" on page 284

5.64.2 Identification

XML Tag: Id

Presence: [0..1]

Definition: Communication value such as phone number or email address.

Datatype: "Max128Text" on page 281

5.65 Party38Choice

Definition: Nature or use of the account.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		168
	PrivateIdentification	<PrvtId>	Or}	[1..1]		168

Used in element(s)

"Identification" on page 173

5.65.1 OrganisationIdentification

XML Tag: OrgId

Presence: [1..1]

Definition: Unique and unambiguous way to identify an organisation.

The **OrgId** block contains the following elements (see datatype "OrganisationIdentification29" on page 163 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AnyBIC	<AnyBIC>		[0..1]		163
	LEI	<LEI>		[0..1]		163
	Other	<Othr>		[0..*]		163

5.65.2 PrivateIdentification

XML Tag: PrvtId

Presence: [1..1]

Definition: Unique and unambiguous identification of a person, for example a passport.

The **PrvtId** block contains the following elements (see datatype "PersonIdentification13" on page 180 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		180
	Other	<Othr>		[0..*]		180

5.66 Party44Choice__1

Definition: Identification of a person, an organisation or a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		169
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		169

Used in element(s)

"From" on page 11, "From" on page 43, "To" on page 12, "To" on page 44

5.66.1 OrganisationIdentification

XML Tag: OrgId

Presence: [1..1]

Definition: Identification of a person or an organisation.

The **OrgId** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 172 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		172
	PostalAddress	<PstlAdr>		[0..1]		172
	Identification	<Id>		[0..1]		173
	CountryOfResidence	<CtryOfRes>		[0..1]		173
	ContactDetails	<CtctDtls>		[0..1]		173

Usage Guideline details

- This element([camt.106.001.03/.header/Related/From/OrganisationIdentification](#)) is removed.
- This element([camt.106.001.03/.header/To/OrganisationIdentification](#)) is removed.
- This element([camt.106.001.03/.header/Related/To/OrganisationIdentification](#)) is removed.
- This element([camt.106.001.03/.header/From/OrganisationIdentification](#)) is removed.

5.66.2 FinancialInstitutionIdentification

XML Tag: FIId

Presence: [1..1]

Definition: Identification of a financial institution.

The **FIId** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6__1](#)" on page 25 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		26
	BranchIdentification	<BrnchId>		[0..1]		26

5.67 Party52Choice

Definition: Specifies the identification of a person or an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		170
	PrivateIdentification	<PrvtId>	Or}	[1..1]		170

Used in element(s)

"Identification" on page 175

5.67.1 OrganisationIdentification

XML Tag: OrgId

Presence: [1..1]

Definition: Unique and unambiguous way to identify an organisation.

The **OrgId** block contains the following elements (see datatype "[OrganisationIdentification39](#)" on page 164 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AnyBIC	<AnyBIC>		[0..1]		164
	LEI	<LEI>		[0..1]		164
	Other	<Othr>		[0..*]		165

5.67.2 PrivateIdentification

XML Tag: PrvtId

Presence: [1..1]

Definition: Unique and unambiguous identification of a person, for example a passport.

The **PrvtId** block contains the following elements (see datatype "[PersonIdentification18](#)" on page 181 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		181
	Other	<Othr>		[0..*]		181

5.68 Party52Choice__1

Definition: Specifies the identification of a person or an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		171
	PrivateIdentification	<PrvtId>	Or}	[1..1]		171

Used in element(s)

"Identification" on page 178

5.68.1 OrganisationIdentification

XML Tag: OrgId

Presence: [1..1]

Definition: Unique and unambiguous way to identify an organisation.

The **OrgId** block contains the following elements (see datatype "OrganisationIdentification39__1" on page 165 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AnyBIC	<AnyBIC>		[0..1]		165
	LEI	<LEI>		[0..1]		165
	Other	<Othr>		[0..*]		166

5.68.2 PrivateIdentification

XML Tag: PrvtId

Presence: [1..1]

Definition: Unique and unambiguous identification of a person, for example a passport.

The **PrvtId** block contains the following elements (see datatype "PersonIdentification18__1" on page 182 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		182
	Other	<Othr>		[0..*]	R[0..2]	183

5.69 PartyIdentification135

Definition: Specifies the identification of a person or an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		172
	PostalAddress	<PstlAdr>		[0..1]		172
	Identification	<Id>		[0..1]		173
	CountryOfResidence	<CtryOfRes>		[0..1]		173
	ContactDetails	<CtctDtls>		[0..1]		173

Used in element(s)

"OrganisationIdentification" on page 169

5.69.1 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: "Max140Text" on page 282

5.69.2 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24" on page 184 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		185
	Department	<Dept>		[0..1]		185
	SubDepartment	<SubDept>		[0..1]		185
	StreetName	<StrtNm>		[0..1]		185
	BuildingNumber	<BldgNb>		[0..1]		185
	BuildingName	<BldgNm>		[0..1]		185

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Floor	<Flr>		[0..1]		186
	PostBox	<PstBx>		[0..1]		186
	Room	<Room>		[0..1]		186
	PostCode	<PstCd>		[0..1]		186
	TownName	<TwnNm>		[0..1]		186
	TownLocationName	<TwnLctnNm>		[0..1]		186
	DistrictName	<DstrctNm>		[0..1]		187
	CountrySubDivision	<CtrySubDvsn>		[0..1]		187
	Country	<Ctry>		[0..1]		187
	AddressLine	<AdrLine>		[0..7]		187

5.69.3 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a party.

The **Id** block contains the following elements (see datatype "[Party38Choice](#)" on page 167 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		168
	PrivateIdentification	<PrvtId>	Or}	[1..1]		168

5.69.4 CountryOfResidence

XML Tag: CtryOfRes

Presence: [0..1]

Definition: Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.

Datatype: "[CountryCode](#)" on page 271

5.69.5 ContactDetails

XML Tag: CtctDtls

Presence: [0..1]

Definition: Set of elements used to indicate how to contact the party.

The **CtctDtls** block contains the following elements (see datatype "[Contact4](#)" on page 112 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NamePrefix	<NmPrfx>		[0..1]		112
	Name	<Nm>		[0..1]		112
	PhoneNumber	<PhneNb>		[0..1]		113
	MobileNumber	<MobNb>		[0..1]		113
	FaxNumber	<FaxNb>		[0..1]		113
	EmailAddress	<EmailAdr>		[0..1]		113
	EmailPurpose	<EmailPurp>		[0..1]		113
	JobTitle	<JobTitl>		[0..1]		113
	Responsibility	<Rspnsblty>		[0..1]		114
	Department	<Dept>		[0..1]		114
	Other	<Othr>		[0..*]		114
	PreferredMethod	<PrefrdMtd>		[0..1]		114

5.70 PartyIdentification272

Definition: Specifies the identification of a person or an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		174
	PostalAddress	<PstlAdr>		[0..1]		175
	Identification	<Id>		[0..1]		175
	CountryOfResidence	<CtryOfRes>		[0..1]		176
	ContactDetails	<CtctDtls>		[0..1]		176

Used in element(s)

"Debtor" on page 97, "Debtor" on page 88

5.70.1 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: "Max140Text" on page 282

5.70.2 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress27" on page 187 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		188
	CareOf	<CareOf>		[0..1]		188
	Department	<Dept>		[0..1]		189
	SubDepartment	<SubDept>		[0..1]		189
	StreetName	<StrtNm>		[0..1]		189
	BuildingNumber	<BldgNb>		[0..1]		189
	BuildingName	<BldgNm>		[0..1]		189
	Floor	<Flr>		[0..1]		189
	UnitNumber	<UnitNb>		[0..1]		190
	PostBox	<PstBx>		[0..1]		190
	Room	<Room>		[0..1]		190
	PostCode	<PstCd>		[0..1]		190
	TownName	<TwnNm>		[0..1]		190
	TownLocationName	<TwnLctnNm>		[0..1]		190
	DistrictName	<DstrctNm>		[0..1]		191
	CountrySubDivision	<CtrySubDvsn>		[0..1]		191
	Country	<Ctry>		[0..1]		191
	AddressLine	<AdrLine>		[0..7]		191

5.70.3 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a party.

The **Id** block contains the following elements (see datatype "Party52Choice" on page 170 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		170
	PrivateIdentification	<PrvtId>	Or}	[1..1]		170

5.70.4 CountryOfResidence

XML Tag: CtryOfRes

Presence: [0..1]

Definition: Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.

Datatype: "CountryCode" on page 271

5.70.5 ContactDetails

XML Tag: CtctDtls

Presence: [0..1]

Definition: Set of elements used to indicate how to contact the party.

The **CtctDtls** block contains the following elements (see datatype "Contact13" on page 109 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NamePrefix	<NmPrfx>		[0..1]		109
	Name	<Nm>		[0..1]		110
	PhoneNumber	<PhneNb>		[0..1]		110
	MobileNumber	<MobNb>		[0..1]		110
	FaxNumber	<FaxNb>		[0..1]		110
	URLAddress	<URLAdr>		[0..1]		110
	EmailAddress	<EmailAdr>		[0..1]		110
	EmailPurpose	<EmailPurp>		[0..1]		111
	JobTitle	<JobTitt>		[0..1]		111
	Responsibility	<Rspnsblty>		[0..1]		111
	Department	<Dept>		[0..1]		111
	Other	<Othr>		[0..*]		111
	PreferredMethod	<PrefrdMtd>		[0..1]		111

5.71 PartyIdentification272__1

Definition: Specifies the identification of a person or an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		177
	PostalAddress	<PstlAdr>		[0..1]		177
	Identification	<Id>		[0..1]		178
	CountryOfResidence	<CtryOfRes>		[0..1]		179
	ContactDetails	<CtctDtls>		[0..1]		179

Used in element(s)

"Debtor" on page 74

5.71.1 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: "CBPR_RestrictedFINXMax140Text_Extended" on page 266

Usage Guideline details

- on camt.106.001.03/Charges/PerTransaction/Record/Debtor/Name
 Type changed to: CBPR_RestrictedFINXMax140Text_Extended on page 266

5.71.2 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress27__3" on page 216 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		217
	CareOf	<CareOf>		[0..1]		217

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Department	<Dept>		[0..1]		217
	SubDepartment	<SubDept>		[0..1]		218
	StreetName	<StrtNm>		[0..1]		218
	BuildingNumber	<BldgNb>		[0..1]		218
	BuildingName	<BldgNm>		[0..1]		218
	Floor	<Flr>		[0..1]		219
	UnitNumber	<UnitNb>		[0..1]		219
	PostBox	<PstBx>		[0..1]		219
	Room	<Room>		[0..1]		220
	PostCode	<PstCd>		[0..1]		220
	TownName	<TwnNm>		[0..1]	 	220
	TownLocationName	<TwnLctnNm>		[0..1]		221
	DistrictName	<DstrctNm>		[0..1]		221
	CountrySubDivision	<CtrySubDvsn>		[0..1]		221
	Country	<Ctry>		[0..1]		221
	AddressLine	<AdrLine>		[0..7]	 R[0..2]	222

Usage Guideline details

- on camt.106.001.03/Charges/PerTransaction/Record/Debtor/PostalAddress

- CBPR_Duplication_Postal_Address_TextualRule:

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.

5.71.3 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a party.

The **Id** block contains the following elements (see datatype "Party52Choice__1" on page 171 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		171
	PrivateIdentification	<PrvtId>	Or}	[1..1]		171

5.71.4 CountryOfResidence

XML Tag: CtryOfRes

Presence: [0..1]

Definition: Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.

Datatype: "CountryCode" on page 271

5.71.5 ContactDetails

XML Tag: CtctDtls

Presence: [0..1]

Definition: Set of elements used to indicate how to contact the party.

The **CtctDtls** block contains the following elements (see datatype "Contact13" on page 109 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NamePrefix	<NmPrfx>		[0..1]		109
	Name	<Nm>		[0..1]		110
	PhoneNumber	<PhneNb>		[0..1]		110
	MobileNumber	<MobNb>		[0..1]		110
	FaxNumber	<FaxNb>		[0..1]		110
	URLAddress	<URLAdr>		[0..1]		110
	EmailAddress	<EmailAdr>		[0..1]		110
	EmailPurpose	<EmailPurp>		[0..1]		111
	JobTitle	<JobTitl>		[0..1]		111
	Responsibility	<Rspnsblty>		[0..1]		111
	Department	<Dept>		[0..1]		111
	Other	<Othr>		[0..*]		111
	PreferredMethod	<PrefrdMtd>		[0..1]		111

Usage Guideline details

- This element([camt.106.001.03/Charges/PerTransaction/Record/Debtor/ContactDetails](#)) is removed.

5.72 PersonIdentification13

Definition: Unique and unambiguous way to identify a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		180
	Other	<Othr>		[0..*]		180

Used in element(s)

"PrivateIdentification" on page 168

5.72.1 DateAndPlaceOfBirth

XML Tag: DtAndPlcOfBirth

Presence: [0..1]

Definition: Date and place of birth of a person.

The **DtAndPlcOfBirth** block contains the following elements (see datatype "[DateAndPlaceOfBirth1](#)" on page 115 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BirthDate	<BirthDt>		[1..1]		116
	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		116
	CityOfBirth	<CityOfBirth>		[1..1]		116
	CountryOfBirth	<CtryOfBirth>		[1..1]		116

5.72.2 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of a person, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericPersonIdentification1](#)" on page 153 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		153
	SchemeName	<SchmeNm>		[0..1]		153
	Issuer	<Issr>		[0..1]		154

5.73 PersonIdentification18

Definition: Unique and unambiguous way to identify a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		181
	Other	<Othr>		[0..*]		181

Used in element(s)

"PrivateIdentification" on page 170

5.73.1 DateAndPlaceOfBirth

XML Tag: DtAndPlcOfBirth

Presence: [0..1]

Definition: Date and place of birth of a person.

The **DtAndPlcOfBirth** block contains the following elements (see datatype "[DateAndPlaceOfBirth1](#)" on page 115 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BirthDate	<BirthDt>		[1..1]		116
	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		116
	CityOfBirth	<CityOfBirth>		[1..1]		116
	CountryOfBirth	<CtryOfBirth>		[1..1]		116

5.73.2 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of a person, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericPersonIdentification2](#)" on [page 154](#) for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		154
	SchemeName	<SchmeNm>		[0..1]		154
	Issuer	<Issr>		[0..1]		155

5.74 PersonIdentification18__1

Definition: Unique and unambiguous way to identify a person.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		182
	Other	<Othr>		[0..*]	R[0..2]	183

Used in element(s)

["PrivateIdentification"](#) on [page 171](#)

5.74.1 DateAndPlaceOfBirth

XML Tag: DtAndPlcOfBirth

Presence: [0..1]

Definition: Date and place of birth of a person.

The **DtAndPlcOfBirth** block contains the following elements (see datatype "[DateAndPlaceOfBirth1__1](#)" on [page 116](#) for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BirthDate	<BirthDt>		[1..1]	⚠	117
	ProvinceOfBirth	<PrvcOfBirth>		[0..1]	⚠	117
	CityOfBirth	<CityOfBirth>		[1..1]	⚠	117
	CountryOfBirth	<CtryOfBirth>		[1..1]		117

5.74.2 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of a person, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericPersonIdentification2__1](#)" on page 155 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		155
	SchemeName	<SchmeNm>		[0..1]		155
	Issuer	<Issr>		[0..1]		156

Usage Guideline details

- on [camt.106.001.03/Charges/PerTransaction/Record/Debtor/Identification/PrivateIdentification/Other](#)

This element has change repeatability, the maximum occurrence has been changed to : 2

5.75 PersonIdentificationSchemeName1Choice

Definition: Sets of elements to identify a name of the identification scheme.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		183
	Proprietary	<Prtry>	Or}	[1..1]		184

Used in element(s)

["SchemeName" on page 153](#), ["SchemeName" on page 154](#), ["SchemeName" on page 155](#)

5.75.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "[ExternalPersonIdentification1Code](#)" on page 278

5.75.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 284

Usage Guideline details

- This element(camt.106.001.03/Charges/PerTransaction/Record/Debtor/Identification/PrivateIdentification/Other/SchemeName/Proprietary) is removed.

5.76 PostalAddress24

Definition: Information that locates and identifies a specific address, as defined by postal services.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		185
	Department	<Dept>		[0..1]		185
	SubDepartment	<SubDept>		[0..1]		185
	StreetName	<StrtNm>		[0..1]		185
	BuildingNumber	<BldgNb>		[0..1]		185
	BuildingName	<BldgNm>		[0..1]		185
	Floor	<Flr>		[0..1]		186
	PostBox	<PstBx>		[0..1]		186
	Room	<Room>		[0..1]		186
	PostCode	<PstCd>		[0..1]		186
	TownName	<TwnNm>		[0..1]		186
	TownLocationName	<TwnLctnNm>		[0..1]		186
	DistrictName	<DstrctNm>		[0..1]		187
	CountrySubDivision	<CtrySubDvsn>		[0..1]		187
	Country	<Ctry>		[0..1]		187
	AddressLine	<AdrLine>		[0..7]		187

Used in element(s)

"PostalAddress" on page 40, "PostalAddress" on page 172, "PostalAddress" on page 120

5.76.1 AddressType

XML Tag: AdrTp

Presence: [0..1]

Definition: Identifies the nature of the postal address.

The **AdrTp** block contains the following elements (see datatype "[AddressType3Choice](#)" on page 25 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		25
	Proprietary	<Prtry>	Or}	[1..1]		25

5.76.2 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: "[Max70Text](#)" on page 285

5.76.3 SubDepartment

XML Tag: SubDept

Presence: [0..1]

Definition: Identification of a sub-division of a large organisation or building.

Datatype: "[Max70Text](#)" on page 285

5.76.4 StreetName

XML Tag: StrtNm

Presence: [0..1]

Definition: Name of a street or thoroughfare.

Datatype: "[Max70Text](#)" on page 285

5.76.5 BuildingNumber

XML Tag: BldgNb

Presence: [0..1]

Definition: Number that identifies the position of a building on a street.

Datatype: "[Max16Text](#)" on page 282

5.76.6 BuildingName

XML Tag: BldgNm

Presence: [0..1]

Definition: Name of the building or house.

Datatype: "Max35Text" on page 284

5.76.7 Floor

XML Tag: Flr

Presence: [0..1]

Definition: Floor or storey within a building.

Datatype: "Max70Text" on page 285

5.76.8 PostBox

XML Tag: PstBx

Presence: [0..1]

Definition: Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for.

Datatype: "Max16Text" on page 282

5.76.9 Room

XML Tag: Room

Presence: [0..1]

Definition: Building room number.

Datatype: "Max70Text" on page 285

5.76.10 PostCode

XML Tag: PstCd

Presence: [0..1]

Definition: Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.

Datatype: "Max16Text" on page 282

5.76.11 TownName

XML Tag: TwnNm

Presence: [0..1]

Definition: Name of a built-up area, with defined boundaries, and a local government.

Datatype: "Max35Text" on page 284

5.76.12 TownLocationName

XML Tag: TwnLctnNm

Presence: [0..1]

Definition: Specific location name within the town.

Datatype: ["Max35Text" on page 284](#)

5.76.13 DistrictName

XML Tag: DstrctNm

Presence: [0..1]

Definition: Identifies a subdivision within a country sub-division.

Datatype: ["Max35Text" on page 284](#)

5.76.14 CountrySubDivision

XML Tag: CtrySubDvsn

Presence: [0..1]

Definition: Identifies a subdivision of a country such as state, region, county.

Datatype: ["Max35Text" on page 284](#)

5.76.15 Country

XML Tag: Ctry

Presence: [0..1]

Definition: Nation with its own government.

Datatype: ["CountryCode" on page 271](#)

5.76.16 AddressLine

XML Tag: AdrLine

Presence: [0..7]

Definition: Information that locates and identifies a specific address, as defined by postal services, presented in free format text.

Datatype: ["Max70Text" on page 285](#)

5.77 PostalAddress27

Definition: Information that locates and identifies a specific address, as defined by postal services.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		188
	CareOf	<CareOf>		[0..1]		188
	Department	<Dept>		[0..1]		189

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	SubDepartment	<SubDept>		[0..1]		189
	StreetName	<StrtNm>		[0..1]		189
	BuildingNumber	<BldgNb>		[0..1]		189
	BuildingName	<BldgNm>		[0..1]		189
	Floor	<Flr>		[0..1]		189
	UnitNumber	<UnitNb>		[0..1]		190
	PostBox	<PstBx>		[0..1]		190
	Room	<Room>		[0..1]		190
	PostCode	<PstCd>		[0..1]		190
	TownName	<TwnNm>		[0..1]		190
	TownLocationName	<TwnLctnNm>		[0..1]		190
	DistrictName	<DstrctNm>		[0..1]		191
	CountrySubDivision	<CtrySubDvsn>		[0..1]		191
	Country	<Ctry>		[0..1]		191
	AddressLine	<AdrLine>		[0..7]		191

Used in element(s)

["PostalAddress" on page 42](#), ["PostalAddress" on page 123](#), ["PostalAddress" on page 175](#)

5.77.1 AddressType

XML Tag: AdrTp

Presence: [0..1]

Definition: Identifies the nature of the postal address.

The **AdrTp** block contains the following elements (see datatype ["AddressType3Choice" on page 25](#) for details)

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below -

📌 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		25
	Proprietary	<Prtry>	Or}	[1..1]		25

5.77.2 CareOf

XML Tag: CareOf

Presence: [0..1]

Definition: Identifies an addressee that is accepting the correspondence for the intended recipient. Using care of ensures the correspondence reaches the right recipient rather than getting returned to the sender.

Datatype: "Max140Text" on page 282

5.77.3 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: "Max70Text" on page 285

5.77.4 SubDepartment

XML Tag: SubDept

Presence: [0..1]

Definition: Identification of a sub-division of a large organisation or building.

Datatype: "Max70Text" on page 285

5.77.5 StreetName

XML Tag: StrtNm

Presence: [0..1]

Definition: Name of a street or thoroughfare.

Datatype: "Max140Text" on page 282

5.77.6 BuildingNumber

XML Tag: BldgNb

Presence: [0..1]

Definition: Number that identifies the position of a building on a street.

Datatype: "Max16Text" on page 282

5.77.7 BuildingName

XML Tag: BldgNm

Presence: [0..1]

Definition: Name of the building or house.

Datatype: "Max140Text" on page 282

5.77.8 Floor

XML Tag: Flr

Presence: [0..1]

Definition: Floor or storey within a building.

Datatype: "Max70Text" on page 285

5.77.9 UnitNumber

XML Tag: UnitNb

Presence: [0..1]

Definition: Identifies a flat or dwelling within the building.

Datatype: "Max16Text" on page 282

5.77.10 PostBox

XML Tag: PstBx

Presence: [0..1]

Definition: Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for.

Datatype: "Max16Text" on page 282

5.77.11 Room

XML Tag: Room

Presence: [0..1]

Definition: Building room number.

Datatype: "Max70Text" on page 285

5.77.12 PostCode

XML Tag: PstCd

Presence: [0..1]

Definition: Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.

Datatype: "Max16Text" on page 282

5.77.13 TownName

XML Tag: TwnNm

Presence: [0..1]

Definition: Name of a built-up area, with defined boundaries, and a local government.

Datatype: "Max140Text" on page 282

5.77.14 TownLocationName

XML Tag: TwnLctnNm

Presence: [0..1]

Definition: Specific location name within the town.

Datatype: "Max140Text" on page 282

5.77.15 DistrictName

XML Tag: DstrctNm

Presence: [0..1]

Definition: Identifies a subdivision within a country sub-division.

Datatype: "Max140Text" on page 282

5.77.16 CountrySubDivision

XML Tag: CtrySubDvsn

Presence: [0..1]

Definition: Identifies a subdivision of a country such as state, region, county.

Datatype: "Max35Text" on page 284

5.77.17 Country

XML Tag: Ctry

Presence: [0..1]

Definition: Nation with its own government.

Datatype: "CountryCode" on page 271

5.77.18 AddressLine

XML Tag: AdrLine

Presence: [0..7]

Definition: Information that locates and identifies a specific address, as defined by postal services, presented in free format text.

Datatype: "Max70Text" on page 285

5.78 PostalAddress27__1

Definition: Information that locates and identifies a specific address, as defined by postal services.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -

📌 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]	🚫	192
	CareOf	<CareOf>		[0..1]	🚫	193
	Department	<Dept>		[0..1]	⚠	193
	SubDepartment	<SubDept>		[0..1]	⚠	194
	StreetName	<StrtNm>		[0..1]	⚠	194
	BuildingNumber	<BldgNb>		[0..1]	⚠	195

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BuildingName	<BldgNm>		[0..1]		196
	Floor	<Flr>		[0..1]		196
	UnitNumber	<UnitNb>		[0..1]		197
	PostBox	<PstBx>		[0..1]		197
	Room	<Room>		[0..1]		198
	PostCode	<PstCd>		[0..1]		199
	TownName	<TwnNm>		[0..1]	 	199
	TownLocationName	<TwnLctnNm>		[0..1]		200
	DistrictName	<DstrctNm>		[0..1]		201
	CountrySubDivision	<CtrySubDvsn>		[0..1]		201
	Country	<Ctry>		[0..1]		202
	AddressLine	<AdrLine>		[0..7]	 R[0..2] R[0..2] R[0..2] R[0..2] R[0..2] R[0..2] R[0..2]	203

Used in element(s)

"PostalAddress" on page 126

5.78.1 AddressType

XML Tag: AdrTp

Presence: [0..1]

Definition: Identifies the nature of the postal address.

The **AdrTp** block contains the following elements (see datatype "AddressType3Choice" on page 25 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		25
	Proprietary	<Prtry>	Or}	[1..1]		25

Usage Guideline details

- This element(camt.106.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/PostalAddress/AddressType) is removed.
- This element(camt.106.001.03/GroupHeader/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/AddressType) is removed.
- This element(camt.106.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/AddressType) is removed.

- This element([camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/Creditor-Agent/FinancialInstitutionIdentification/PostalAddress/AddressType](#)) is removed.
- This element([camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/Creditor/FinancialInstitutionIdentification/PostalAddress/AddressType](#)) is removed.

5.78.2 CareOf

XML Tag: CareOf

Presence: [0..1]

Definition: Identifies an addressee that is accepting the correspondence for the intended recipient. Using care of ensures the correspondence reaches the right recipient rather than getting returned to the sender.

Datatype: ["Max140Text"](#) on page 282

Usage Guideline details

- This element([camt.106.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/PostalAddress/CareOf](#)) is removed.
- This element([camt.106.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/CareOf](#)) is removed.
- This element([camt.106.001.03/GroupHeader/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/CareOf](#)) is removed.
- This element([camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/Creditor-Agent/FinancialInstitutionIdentification/PostalAddress/CareOf](#)) is removed.
- This element([camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/Creditor/FinancialInstitutionIdentification/PostalAddress/CareOf](#)) is removed.

5.78.3 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended"](#) on page 270

Usage Guideline details

- on [camt.106.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/PostalAddress/Department](#)
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 270
- on [camt.106.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/Department](#)
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 270

- on camt.106.001.03/GroupHeader/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/Department

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 270

- on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/Department

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 270

- on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/Creditor/FinancialInstitutionIdentification/PostalAddress/Department

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 270

5.78.4 SubDepartment

XML Tag: SubDept

Presence: [0..1]

Definition: Identification of a sub-division of a large organisation or building.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended"](#) on page 270

Usage Guideline details

- on camt.106.001.03/GroupHeader/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/SubDepartment

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 270

- on camt.106.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/PostalAddress/SubDepartment

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 270

- on camt.106.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/SubDepartment

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 270

- on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/SubDepartment

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 270

- on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/Creditor/FinancialInstitutionIdentification/PostalAddress/SubDepartment

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 270

5.78.5 StreetName

XML Tag: StrtNm

Presence: [0..1]

Definition: Name of a street or thoroughfare.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended"](#) on page 270

Usage Guideline details

- on **camt.106.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/StreetName**
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 270
- on **camt.106.001.03/GroupHeader/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/StreetName**
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 270
- on **camt.106.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/PostalAddress/StreetName**
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 270
- on **camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/StreetName**
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 270
- on **camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/Creditor/FinancialInstitutionIdentification/PostalAddress/StreetName**
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 270

5.78.6 BuildingNumber

XML Tag: BldgNb

Presence: [0..1]

Definition: Number that identifies the position of a building on a street.

Datatype: ["CBPR_RestrictedFINXMax16Text_Extended"](#) on page 266

Usage Guideline details

- on **camt.106.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/PostalAddress/BuildingNumber**
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended](#) on page 266
- on **camt.106.001.03/GroupHeader/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/BuildingNumber**
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended](#) on page 266
- on **camt.106.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/BuildingNumber**
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended](#) on page 266
- on **camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/BuildingNumber**
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended](#) on page 266
- on **camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/Creditor/FinancialInstitutionIdentification/PostalAddress/BuildingNumber**

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 266](#)

5.78.7 BuildingName

XML Tag: BldgNm

Presence: [0..1]

Definition: Name of the building or house.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 269](#)

Usage Guideline details

- **on camt.106.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/BuildingName**
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)
- **on camt.106.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/PostalAddress/BuildingName**
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)
- **on camt.106.001.03/GroupHeader/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/BuildingName**
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)
- **on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/BuildingName**
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)
- **on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/Creditor/FinancialInstitutionIdentification/PostalAddress/BuildingName**
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)

5.78.8 Floor

XML Tag: Flr

Presence: [0..1]

Definition: Floor or storey within a building.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended" on page 270](#)

Usage Guideline details

- **on camt.106.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/PostalAddress/Floor**
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 270](#)
- **on camt.106.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/Floor**

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 270](#)

- on [camt.106.001.03/GroupHeader/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/Floor](#)

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 270](#)

- on [camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/Floor](#)

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 270](#)

- on [camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/Creditor/FinancialInstitutionIdentification/PostalAddress/Floor](#)

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 270](#)

5.78.9 UnitNumber

XML Tag: UnitNb

Presence: [0..1]

Definition: Identifies a flat or dwelling within the building.

Datatype: ["Max16Text" on page 282](#)

Usage Guideline details

- This element([camt.106.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/PostalAddress/UnitNumber](#)) is removed.
- This element([camt.106.001.03/GroupHeader/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/UnitNumber](#)) is removed.
- This element([camt.106.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/UnitNumber](#)) is removed.
- This element([camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/UnitNumber](#)) is removed.
- This element([camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/Creditor/FinancialInstitutionIdentification/PostalAddress/UnitNumber](#)) is removed.

5.78.10 PostBox

XML Tag: PstBx

Presence: [0..1]

Definition: Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for.

Datatype: ["CBPR_RestrictedFINXMax16Text_Extended" on page 266](#)

Usage Guideline details

- on camt.106.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/PostBox
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended](#) on page 266
- on camt.106.001.03/GroupHeader/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/PostBox
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended](#) on page 266
- on camt.106.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/PostalAddress/PostBox
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended](#) on page 266
- on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/PostBox
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended](#) on page 266
- on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/Creditor/FinancialInstitutionIdentification/PostalAddress/PostBox
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended](#) on page 266

5.78.11 Room

XML Tag: Room

Presence: [0..1]

Definition: Building room number.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended"](#) on page 270

Usage Guideline details

- on camt.106.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/PostalAddress/Room
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 270
- on camt.106.001.03/GroupHeader/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/Room
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 270
- on camt.106.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/Room
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 270
- on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/Room
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 270
- on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/Creditor/FinancialInstitutionIdentification/PostalAddress/Room

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 270](#)

5.78.12 PostCode

XML Tag: PstCd

Presence: [0..1]

Definition: Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.

Datatype: ["CBPR_RestrictedFINXMax16Text_Extended" on page 266](#)

Usage Guideline details

- **on camt.106.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/PostCode**
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 266](#)
- **on camt.106.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/PostalAddress/PostCode**
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 266](#)
- **on camt.106.001.03/GroupHeader/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/PostCode**
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 266](#)
- **on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/PostCode**
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 266](#)
- **on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/Creditor/FinancialInstitutionIdentification/PostalAddress/PostCode**
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 266](#)

5.78.13 TownName

XML Tag: TwNm

Presence: [0..1]

Definition: Name of a built-up area, with defined boundaries, and a local government.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 269](#)

Usage Guideline details

- **on camt.106.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/TownName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on camt.106.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/PostalAddress/TownName**

This element is now mandatory, the minimum occurrence has been changed to : 1

- on camt.106.001.03/GroupHeader/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/TownName

This element is now mandatory, the minimum occurrence has been changed to : 1

- on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/TownName

This element is now mandatory, the minimum occurrence has been changed to : 1

- on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/Creditor/FinancialInstitutionIdentification/PostalAddress/TownName

This element is now mandatory, the minimum occurrence has been changed to : 1

- on camt.106.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/TownName

Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 269

- on camt.106.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/PostalAddress/TownName

Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 269

- on camt.106.001.03/GroupHeader/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/TownName

Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 269

- on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/TownName

Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 269

- on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/Creditor/FinancialInstitutionIdentification/PostalAddress/TownName

Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 269

5.78.14 TownLocationName

XML Tag: TwnLctnNm

Presence: [0..1]

Definition: Specific location name within the town.

Datatype: "CBPR_RestrictedFINXMax35Text_Extended" on page 269

Usage Guideline details

- on camt.106.001.03/GroupHeader/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/TownLocationName

Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 269

- on camt.106.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/PostalAddress/TownLocationName

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)

- on [camt.106.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/TownLocationName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)

- on [camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/TownLocationName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)

- on [camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/Creditor/FinancialInstitutionIdentification/PostalAddress/TownLocationName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)

5.78.15 DistrictName

XML Tag: DstrctNm

Presence: [0..1]

Definition: Identifies a subdivision within a country sub-division.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 269](#)

Usage Guideline details

- on [camt.106.001.03/GroupHeader/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/DistrictName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)

- on [camt.106.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/DistrictName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)

- on [camt.106.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/PostalAddress/DistrictName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)

- on [camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/DistrictName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)

- on [camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/Creditor/FinancialInstitutionIdentification/PostalAddress/DistrictName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)

5.78.16 CountrySubDivision

XML Tag: CtrySubDvsn

Presence: [0..1]

Definition: Identifies a subdivision of a country such as state, region, county.

Datatype: "CBPR_RestrictedFINXMax35Text_Extended" on page 269

Usage Guideline details

- on **camt.106.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision**
Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 269
- on **camt.106.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision**
Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 269
- on **camt.106.001.03/GroupHeader/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision**
Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 269
- on **camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision**
Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 269
- on **camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/Creditor/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision**
Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 269

5.78.17 Country

XML Tag: Ctry

Presence: [0..1]

Definition: Nation with its own government.

Datatype: "CountryCode" on page 271

Usage Guideline details

- on **camt.106.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/PostalAddress/Country**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **camt.106.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/Country**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **camt.106.001.03/GroupHeader/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/Country**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/Country**
This element is now mandatory, the minimum occurrence has been changed to : 1

- on **camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/Creditor/FinancialInstitutionIdentification/PostalAddress/Country**

This element is now mandatory, the minimum occurrence has been changed to : 1

5.78.18 AddressLine

XML Tag: AdrLine

Presence: [0..7]

Definition: Information that locates and identifies a specific address, as defined by postal services, presented in free format text.

Datatype: "CBPR_RestrictedFINXMax70Text_Extended" on page 270

Usage Guideline details

- on **camt.106.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/PostalAddress/AddressLine**

This element has change repeatability, the maximum occurrence has been changed to : 2

- on **camt.106.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine**

This element has change repeatability, the maximum occurrence has been changed to : 2

- on **camt.106.001.03/GroupHeader/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine**

This element has change repeatability, the maximum occurrence has been changed to : 2

- on **camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine**

This element has change repeatability, the maximum occurrence has been changed to : 2

- on **camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/Creditor/FinancialInstitutionIdentification/PostalAddress/AddressLine**

This element has change repeatability, the maximum occurrence has been changed to : 2

- on **camt.106.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/PostalAddress/AddressLine**

Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 270

- on **camt.106.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine**

Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 270

- on **camt.106.001.03/GroupHeader/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine**

Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 270

- on **camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine**

Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 270

- on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/Creditor/FinancialInstitutionIdentification/PostalAddress/AddressLine

Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 270

5.79 PostalAddress27__2

Definition: Information that locates and identifies a specific address, as defined by postal services.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		204
	CareOf	<CareOf>		[0..1]		205
	Department	<Dept>		[0..1]		205
	SubDepartment	<SubDept>		[0..1]		206
	StreetName	<StrtNm>		[0..1]		207
	BuildingNumber	<BldgNb>		[0..1]		207
	BuildingName	<BldgNm>		[0..1]		208
	Floor	<Flr>		[0..1]		209
	UnitNumber	<UnitNb>		[0..1]		209
	PostBox	<PstBx>		[0..1]		210
	Room	<Room>		[0..1]		210
	PostCode	<PstCd>		[0..1]		211
	TownName	<TwnNm>		[0..1]		212
	TownLocationName	<TwnLctnNm>		[0..1]		212
	DistrictName	<DstrctNm>		[0..1]		213
	CountrySubDivision	<CtrySubDvsn>		[0..1]		214
	Country	<Ctry>		[0..1]		214
	AddressLine	<AdrLine>		[0..7]	 R[0..3] R[0..3] R[0..3] R	215

Used in element(s)

"PostalAddress" on page 130, "PostalAddress" on page 136

5.79.1 AddressType

XML Tag: AdrTp

Presence: [0..1]

Definition: Identifies the nature of the postal address.

The **AdrTp** block contains the following elements (see datatype "[AddressType3Choice](#)" on page 25 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		25
	Proprietary	<Prtry>	Or}	[1..1]		25

Usage Guideline details

- This element([camt.106.001.03/Charges/PerTransaction/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/AddressType](#)) is removed.
- This element([camt.106.001.03/Charges/PerTransaction/Record/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/AddressType](#)) is removed.
- This element([camt.106.001.03/Charges/PerType/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/AddressType](#)) is removed.
- This element([camt.106.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/AddressType](#)) is removed.
- This element([camt.106.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/AddressType](#)) is removed.
- This element([camt.106.001.03/Charges/Single/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/AddressType](#)) is removed.

5.79.2 CareOf

XML Tag: CareOf

Presence: [0..1]

Definition: Identifies an addressee that is accepting the correspondence for the intended recipient. Using care of ensures the correspondence reaches the right recipient rather than getting returned to the sender.

Datatype: "[Max140Text](#)" on page 282

5.79.3 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: "[CBPR_RestrictedFINXMax70Text_Extended](#)" on page 270

Usage Guideline details

- on camt.106.001.03/Charges/PerTransaction/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/Department
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 270
- on camt.106.001.03/Charges/PerType/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/Department
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 270
- on camt.106.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/Department
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 270
- on camt.106.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/Department
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 270
- on camt.106.001.03/Charges/PerTransaction/Record/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/Department
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 270
- on camt.106.001.03/Charges/Single/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/Department
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 270

5.79.4 SubDepartment

XML Tag: SubDept

Presence: [0..1]

Definition: Identification of a sub-division of a large organisation or building.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended"](#) on page 270

Usage Guideline details

- on camt.106.001.03/Charges/PerType/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/SubDepartment
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 270
- on camt.106.001.03/Charges/Single/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/SubDepartment
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 270
- on camt.106.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/SubDepartment
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 270
- on camt.106.001.03/Charges/PerTransaction/Record/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/SubDepartment

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 270](#)

- on [camt.106.001.03/Charges/PerTransaction/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/SubDepartment](#)

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 270](#)

- on [camt.106.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/SubDepartment](#)

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 270](#)

5.79.5 StreetName

XML Tag: StrtNm

Presence: [0..1]

Definition: Name of a street or thoroughfare.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended" on page 270](#)

Usage Guideline details

- on [camt.106.001.03/Charges/Single/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/StreetName](#)

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 270](#)

- on [camt.106.001.03/Charges/PerTransaction/Record/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/StreetName](#)

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 270](#)

- on [camt.106.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/StreetName](#)

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 270](#)

- on [camt.106.001.03/Charges/PerTransaction/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/StreetName](#)

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 270](#)

- on [camt.106.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/StreetName](#)

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 270](#)

- on [camt.106.001.03/Charges/PerType/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/StreetName](#)

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 270](#)

5.79.6 BuildingNumber

XML Tag: BldgNb

Presence: [0..1]

Definition: Number that identifies the position of a building on a street.

Datatype: "CBPR_RestrictedFINXMax16Text_Extended" on page 266

Usage Guideline details

- on camt.106.001.03/Charges/Single/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/BuildingNumber
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 266](#)
- on camt.106.001.03/Charges/PerType/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/BuildingNumber
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 266](#)
- on camt.106.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/BuildingNumber
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 266](#)
- on camt.106.001.03/Charges/PerTransaction/Record/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/BuildingNumber
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 266](#)
- on camt.106.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/BuildingNumber
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 266](#)
- on camt.106.001.03/Charges/PerTransaction/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/BuildingNumber
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 266](#)

5.79.7 BuildingName

XML Tag: BldgNm

Presence: [0..1]

Definition: Name of the building or house.

Datatype: "CBPR_RestrictedFINXMax35Text_Extended" on page 269

Usage Guideline details

- on camt.106.001.03/Charges/PerType/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/BuildingName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)
- on camt.106.001.03/Charges/Single/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/BuildingName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)
- on camt.106.001.03/Charges/PerTransaction/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/BuildingName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)

- on camt.106.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/BuildingName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)
- on camt.106.001.03/Charges/PerTransaction/Record/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/BuildingName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)
- on camt.106.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/BuildingName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)

5.79.8 Floor

XML Tag: Flr

Presence: [0..1]

Definition: Floor or storey within a building.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended" on page 270](#)

Usage Guideline details

- on camt.106.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/Floor
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 270](#)
- on camt.106.001.03/Charges/Single/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/Floor
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 270](#)
- on camt.106.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/Floor
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 270](#)
- on camt.106.001.03/Charges/PerType/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/Floor
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 270](#)
- on camt.106.001.03/Charges/PerTransaction/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/Floor
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 270](#)
- on camt.106.001.03/Charges/PerTransaction/Record/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/Floor
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 270](#)

5.79.9 UnitNumber

XML Tag: UnitNb

Presence: [0..1]

Definition: Identifies a flat or dwelling within the building.

Datatype: "Max16Text" on page 282

5.79.10 PostBox

XML Tag: PstBx

Presence: [0..1]

Definition: Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for.

Datatype: "CBPR_RestrictedFINXMax16Text_Extended" on page 266

Usage Guideline details

- on camt.106.001.03/Charges/PerTransaction/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/PostBox
Type changed to: CBPR_RestrictedFINXMax16Text_Extended on page 266
- on camt.106.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/PostBox
Type changed to: CBPR_RestrictedFINXMax16Text_Extended on page 266
- on camt.106.001.03/Charges/Single/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/PostBox
Type changed to: CBPR_RestrictedFINXMax16Text_Extended on page 266
- on camt.106.001.03/Charges/PerType/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/PostBox
Type changed to: CBPR_RestrictedFINXMax16Text_Extended on page 266
- on camt.106.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/PostBox
Type changed to: CBPR_RestrictedFINXMax16Text_Extended on page 266
- on camt.106.001.03/Charges/PerTransaction/Record/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/PostBox
Type changed to: CBPR_RestrictedFINXMax16Text_Extended on page 266

5.79.11 Room

XML Tag: Room

Presence: [0..1]

Definition: Building room number.

Datatype: "CBPR_RestrictedFINXMax70Text_Extended" on page 270

Usage Guideline details

- on **camt.106.001.03/Charges/PerTransaction/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/Room**
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 270
- on **camt.106.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/Room**
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 270
- on **camt.106.001.03/Charges/Single/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/Room**
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 270
- on **camt.106.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/Room**
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 270
- on **camt.106.001.03/Charges/PerType/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/Room**
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 270
- on **camt.106.001.03/Charges/PerTransaction/Record/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/Room**
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 270

5.79.12 PostCode

XML Tag: PstCd

Presence: [0..1]

Definition: Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.

Datatype: "CBPR_RestrictedFINXMax16Text_Extended" on page 266

Usage Guideline details

- on **camt.106.001.03/Charges/PerTransaction/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/PostCode**
Type changed to: CBPR_RestrictedFINXMax16Text_Extended on page 266
- on **camt.106.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/PostCode**
Type changed to: CBPR_RestrictedFINXMax16Text_Extended on page 266
- on **camt.106.001.03/Charges/Single/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/PostCode**
Type changed to: CBPR_RestrictedFINXMax16Text_Extended on page 266
- on **camt.106.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/PostCode**

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 266](#)

- on [camt.106.001.03/Charges/PerType/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/PostCode](#)

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 266](#)

- on [camt.106.001.03/Charges/PerTransaction/Record/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/PostCode](#)

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 266](#)

5.79.13 TownName

XML Tag: TwnNm

Presence: [0..1]

Definition: Name of a built-up area, with defined boundaries, and a local government.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 269](#)

Usage Guideline details

- on [camt.106.001.03/Charges/Single/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/TownName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)

- on [camt.106.001.03/Charges/PerTransaction/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/TownName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)

- on [camt.106.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/TownName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)

- on [camt.106.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/TownName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)

- on [camt.106.001.03/Charges/PerTransaction/Record/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/TownName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)

- on [camt.106.001.03/Charges/PerType/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/TownName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)

5.79.14 TownLocationName

XML Tag: TwnLctnNm

Presence: [0..1]

Definition: Specific location name within the town.

Datatype: "CBPR_RestrictedFINXMax35Text_Extended" on page 269

Usage Guideline details

- on camt.106.001.03/Charges/Single/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/TownLocationName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)
- on camt.106.001.03/Charges/PerType/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/TownLocationName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)
- on camt.106.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/TownLocationName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)
- on camt.106.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/TownLocationName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)
- on camt.106.001.03/Charges/PerTransaction/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/TownLocationName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)
- on camt.106.001.03/Charges/PerTransaction/Record/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/TownLocationName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)

5.79.15 DistrictName

XML Tag: DstrctNm

Presence: [0..1]

Definition: Identifies a subdivision within a country sub-division.

Datatype: "CBPR_RestrictedFINXMax35Text_Extended" on page 269

Usage Guideline details

- on camt.106.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/DistrictName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)
- on camt.106.001.03/Charges/Single/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/DistrictName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)
- on camt.106.001.03/Charges/PerType/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/DistrictName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)

- on camt.106.001.03/Charges/PerTransaction/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/DistrictName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)
- on camt.106.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/DistrictName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)
- on camt.106.001.03/Charges/PerTransaction/Record/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/DistrictName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)

5.79.16 CountrySubDivision

XML Tag: CtrySubDvsn

Presence: [0..1]

Definition: Identifies a subdivision of a country such as state, region, county.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 269](#)

Usage Guideline details

- on camt.106.001.03/Charges/PerTransaction/Record/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)
- on camt.106.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)
- on camt.106.001.03/Charges/Single/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)
- on camt.106.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)
- on camt.106.001.03/Charges/PerTransaction/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)
- on camt.106.001.03/Charges/PerType/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)

5.79.17 Country

XML Tag: Ctry

Presence: [0..1]

Definition: Nation with its own government.

Datatype: "CountryCode" on page 271

5.79.18 AddressLine

XML Tag: AdrLine

Presence: [0..7]

Definition: Information that locates and identifies a specific address, as defined by postal services, presented in free format text.

Datatype: "CBPR_RestrictedFINXMax35Text_Extended" on page 269

Usage Guideline details

- **on camt.106.001.03/Charges/PerType/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine**
This element has change repeatability, the maximum occurrence has been changed to : 3
- **on camt.106.001.03/Charges/PerTransaction/Record/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine**
This element has change repeatability, the maximum occurrence has been changed to : 3
- **on camt.106.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine**
This element has change repeatability, the maximum occurrence has been changed to : 3
- **on camt.106.001.03/Charges/PerTransaction/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine**
This element has change repeatability, the maximum occurrence has been changed to : 3
- **on camt.106.001.03/Charges/Single/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine**
This element has change repeatability, the maximum occurrence has been changed to : 3
- **on camt.106.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine**
This element has change repeatability, the maximum occurrence has been changed to : 3
- **on camt.106.001.03/Charges/PerType/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine**
Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 269
- **on camt.106.001.03/Charges/PerTransaction/Record/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine**
Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 269
- **on camt.106.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine**
Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 269

- on camt.106.001.03/Charges/PerTransaction/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine
Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 269
- on camt.106.001.03/Charges/Single/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine
Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 269
- on camt.106.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine
Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 269

5.80 PostalAddress27__3

Definition: Information that locates and identifies a specific address, as defined by postal services.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		217
	CareOf	<CareOf>		[0..1]		217
	Department	<Dept>		[0..1]		217
	SubDepartment	<SubDept>		[0..1]		218
	StreetName	<StrtNm>		[0..1]		218
	BuildingNumber	<BldgNb>		[0..1]		218
	BuildingName	<BldgNm>		[0..1]		218
	Floor	<Flr>		[0..1]		219
	UnitNumber	<UnitNb>		[0..1]		219
	PostBox	<PstBx>		[0..1]		219
	Room	<Room>		[0..1]		220
	PostCode	<PstCd>		[0..1]		220
	TownName	<TwnNm>		[0..1]	 	220
	TownLocationName	<TwnLctnNm>		[0..1]		221
	DistrictName	<DstrctNm>		[0..1]		221
	CountrySubDivision	<CtrySubDvsn>		[0..1]		221
	Country	<Ctry>		[0..1]		221
	AddressLine	<AdrLine>		[0..7]	 R[0..2]	222

Used in element(s)

"PostalAddress" on page 177

5.80.1 AddressType

XML Tag: AdrTp

Presence: [0..1]

Definition: Identifies the nature of the postal address.

The **AdrTp** block contains the following elements (see datatype "AddressType3Choice" on page 25 for details)

❌ Removed - ❌ Partial Removed - ♦ Ignored - ♦ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		25
	Proprietary	<Prtry>	Or}	[1..1]		25

Usage Guideline details

- This element(camt.106.001.03/Charges/PerTransaction/Record/Debtor/PostalAddress/AddressType) is removed.

5.80.2 CareOf

XML Tag: CareOf

Presence: [0..1]

Definition: Identifies an addressee that is accepting the correspondence for the intended recipient. Using care of ensures the correspondence reaches the right recipient rather than getting returned to the sender.

Datatype: "Max140Text" on page 282

Usage Guideline details

- This element(camt.106.001.03/Charges/PerTransaction/Record/Debtor/PostalAddress/CareOf) is removed.

5.80.3 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: "CBPR_RestrictedFINXMax70Text_Extended" on page 270

Usage Guideline details

- on **camt.106.001.03/Charges/PerTransaction/Record/Debtor/PostalAddress/Department**
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 270

5.80.4 SubDepartment

XML Tag: SubDept

Presence: [0..1]

Definition: Identification of a sub-division of a large organisation or building.

Datatype: "CBPR_RestrictedFINXMax70Text_Extended" on page 270

Usage Guideline details

- on **camt.106.001.03/Charges/PerTransaction/Record/Debtor/PostalAddress/SubDepartment**
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 270

5.80.5 StreetName

XML Tag: StrtNm

Presence: [0..1]

Definition: Name of a street or thoroughfare.

Datatype: "CBPR_RestrictedFINXMax140Text_Extended" on page 266

Usage Guideline details

- on **camt.106.001.03/Charges/PerTransaction/Record/Debtor/PostalAddress/StreetName**
Type changed to: CBPR_RestrictedFINXMax140Text_Extended on page 266

5.80.6 BuildingNumber

XML Tag: BldgNb

Presence: [0..1]

Definition: Number that identifies the position of a building on a street.

Datatype: "CBPR_RestrictedFINXMax16Text_Extended" on page 266

Usage Guideline details

- on **camt.106.001.03/Charges/PerTransaction/Record/Debtor/PostalAddress/BuildingNumber**
Type changed to: CBPR_RestrictedFINXMax16Text_Extended on page 266

5.80.7 BuildingName

XML Tag: BldgNm

Presence: [0..1]

Definition: Name of the building or house.

Datatype: "CBPR_RestrictedFINXMax140Text_Extended" on page 266

Usage Guideline details

- on **camt.106.001.03/Charges/PerTransaction/Record/Debtor/PostalAddress/BuildingName**
Type changed to: CBPR_RestrictedFINXMax140Text_Extended on page 266

5.80.8 Floor

XML Tag: Flr

Presence: [0..1]

Definition: Floor or storey within a building.

Datatype: "CBPR_RestrictedFINXMax70Text_Extended" on page 270

Usage Guideline details

- on **camt.106.001.03/Charges/PerTransaction/Record/Debtor/PostalAddress/Floor**
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 270

5.80.9 UnitNumber

XML Tag: UnitNb

Presence: [0..1]

Definition: Identifies a flat or dwelling within the building.

Datatype: "Max16Text" on page 282

Usage Guideline details

- This element(**camt.106.001.03/Charges/PerTransaction/Record/Debtor/PostalAddress/Unit-Number**) is removed.

5.80.10 PostBox

XML Tag: PstBx

Presence: [0..1]

Definition: Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for.

Datatype: "CBPR_RestrictedFINXMax16Text_Extended" on page 266

Usage Guideline details

- on **camt.106.001.03/Charges/PerTransaction/Record/Debtor/PostalAddress/PostBox**
Type changed to: CBPR_RestrictedFINXMax16Text_Extended on page 266

5.80.11 Room

XML Tag: Room

Presence: [0..1]

Definition: Building room number.

Datatype: "CBPR_RestrictedFINXMax70Text_Extended" on page 270

Usage Guideline details

- on **camt.106.001.03/Charges/PerTransaction/Record/Debtor/PostalAddress/Room**
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 270

5.80.12 PostCode

XML Tag: PstCd

Presence: [0..1]

Definition: Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.

Datatype: "CBPR_RestrictedFINXMax16Text_Extended" on page 266

Usage Guideline details

- on **camt.106.001.03/Charges/PerTransaction/Record/Debtor/PostalAddress/PostCode**
Type changed to: CBPR_RestrictedFINXMax16Text_Extended on page 266

5.80.13 TownName

XML Tag: TwnNm

Presence: [0..1]

Definition: Name of a built-up area, with defined boundaries, and a local government.

Datatype: "CBPR_RestrictedFINXMax140Text_Extended" on page 266

Usage Guideline details

- on **camt.106.001.03/Charges/PerTransaction/Record/Debtor/PostalAddress/TownName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **camt.106.001.03/Charges/PerTransaction/Record/Debtor/PostalAddress/TownName**

Type changed to: [CBPR_RestrictedFINXMax140Text_Extended on page 266](#)

5.80.14 TownLocationName

XML Tag: TwnLctnNm

Presence: [0..1]

Definition: Specific location name within the town.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 269](#)

Usage Guideline details

- on [camt.106.001.03/Charges/PerTransaction/Record/Debtor/PostalAddress/TownLocation-Name](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)

5.80.15 DistrictName

XML Tag: DstrctNm

Presence: [0..1]

Definition: Identifies a subdivision within a country sub-division.

Datatype: ["CBPR_RestrictedFINXMax140Text_Extended" on page 266](#)

Usage Guideline details

- on [camt.106.001.03/Charges/PerTransaction/Record/Debtor/PostalAddress/DistrictName](#)

Type changed to: [CBPR_RestrictedFINXMax140Text_Extended on page 266](#)

5.80.16 CountrySubDivision

XML Tag: CtrySubDvsn

Presence: [0..1]

Definition: Identifies a subdivision of a country such as state, region, county.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 269](#)

Usage Guideline details

- on [camt.106.001.03/Charges/PerTransaction/Record/Debtor/PostalAddress/CountrySubDivision](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)

5.80.17 Country

XML Tag: Ctry

Presence: [0..1]

Definition: Nation with its own government.

Datatype: "CountryCode" on page 271

Usage Guideline details

- **on camt.106.001.03/Charges/PerTransaction/Record/Debtor/PostalAddress/Country**
This element is now mandatory, the minimum occurrence has been changed to : 1

5.80.18 AddressLine

XML Tag: AdrLine

Presence: [0..7]

Definition: Information that locates and identifies a specific address, as defined by postal services, presented in free format text.

Datatype: "CBPR_RestrictedFINXMax70Text_Extended" on page 270

Usage Guideline details

- **on camt.106.001.03/Charges/PerTransaction/Record/Debtor/PostalAddress/AddressLine**
This element has change repeatability, the maximum occurrence has been changed to : 2
- **on camt.106.001.03/Charges/PerTransaction/Record/Debtor/PostalAddress/AddressLine**
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 270

5.81 PostalAddress27__4

Definition: Information that locates and identifies a specific address, as defined by postal services.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]	🚫	223
	CareOf	<CareOf>		[0..1]		223
	Department	<Dept>		[0..1]	⚠	224
	SubDepartment	<SubDept>		[0..1]	⚠	224
	StreetName	<StrtNm>		[0..1]	⚠	224
	BuildingNumber	<BldgNb>		[0..1]	⚠	225
	BuildingName	<BldgNm>		[0..1]	⚠	225
	Floor	<Flr>		[0..1]	⚠	225

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	UnitNumber	<UnitNb>		[0..1]		225
	PostBox	<PstBx>		[0..1]		226
	Room	<Room>		[0..1]		226
	PostCode	<PstCd>		[0..1]		226
	TownName	<TwnNm>		[0..1]		226
	TownLocationName	<TwnLctnNm>		[0..1]		227
	DistrictName	<DstrctNm>		[0..1]		227
	CountrySubDivision	<CtrySubDvsn>		[0..1]		227
	Country	<Ctry>		[0..1]		227
	AddressLine	<AdrLine>		[0..7]	 R[0..3]	228

Used in element(s)

"PostalAddress" on page 140

5.81.1 AddressType

XML Tag: AdrTp

Presence: [0..1]

Definition: Identifies the nature of the postal address.

The **AdrTp** block contains the following elements (see datatype "AddressType3Choice" on page 25 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		25
	Proprietary	<Prtry>	Or}	[1..1]		25

Usage Guideline details

- This element(camt.106.001.03/Charges/PerType/Record/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/AddressType) is removed.

5.81.2 CareOf

XML Tag: CareOf

Presence: [0..1]

Definition: Identifies an addressee that is accepting the correspondence for the intended recipient. Using care of ensures the correspondence reaches the right recipient rather than getting returned to the sender.

Datatype: ["Max140Text" on page 282](#)

5.81.3 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended" on page 270](#)

Usage Guideline details

- on [camt.106.001.03/Charges/PerType/Record/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/Department](#)

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 270](#)

5.81.4 SubDepartment

XML Tag: SubDept

Presence: [0..1]

Definition: Identification of a sub-division of a large organisation or building.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended" on page 270](#)

Usage Guideline details

- on [camt.106.001.03/Charges/PerType/Record/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/SubDepartment](#)

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 270](#)

5.81.5 StreetName

XML Tag: StrtNm

Presence: [0..1]

Definition: Name of a street or thoroughfare.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended" on page 270](#)

Usage Guideline details

- on [camt.106.001.03/Charges/PerType/Record/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/StreetName](#)

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 270](#)

5.81.6 BuildingNumber

XML Tag: BldgNb

Presence: [0..1]

Definition: Number that identifies the position of a building on a street.

Datatype: "CBPR_RestrictedFINXMax16Text_Extended" on page 266

Usage Guideline details

- on camt.106.001.03/Charges/PerType/Record/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/BuildingNumber

Type changed to: CBPR_RestrictedFINXMax16Text_Extended on page 266

5.81.7 BuildingName

XML Tag: BldgNm

Presence: [0..1]

Definition: Name of the building or house.

Datatype: "CBPR_RestrictedFINXMax35Text_Extended" on page 269

Usage Guideline details

- on camt.106.001.03/Charges/PerType/Record/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/BuildingName

Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 269

5.81.8 Floor

XML Tag: Flr

Presence: [0..1]

Definition: Floor or storey within a building.

Datatype: "CBPR_RestrictedFINXMax70Text_Extended" on page 270

Usage Guideline details

- on camt.106.001.03/Charges/PerType/Record/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/Floor

Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 270

5.81.9 UnitNumber

XML Tag: UnitNb

Presence: [0..1]

Definition: Identifies a flat or dwelling within the building.

Datatype: ["Max16Text" on page 282](#)

5.81.10 PostBox

XML Tag: PstBx

Presence: [0..1]

Definition: Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for.

Datatype: ["Max16Text" on page 282](#)

5.81.11 Room

XML Tag: Room

Presence: [0..1]

Definition: Building room number.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended" on page 270](#)

Usage Guideline details

- on [camt.106.001.03/Charges/PerType/Record/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/Room](#)

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 270](#)

5.81.12 PostCode

XML Tag: PstCd

Presence: [0..1]

Definition: Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.

Datatype: ["Max16Text" on page 282](#)

5.81.13 TownName

XML Tag: TwnNm

Presence: [0..1]

Definition: Name of a built-up area, with defined boundaries, and a local government.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 269](#)

Usage Guideline details

- on [camt.106.001.03/Charges/PerType/Record/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/TownName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)

5.81.14 TownLocationName

XML Tag: TwnLctnNm

Presence: [0..1]

Definition: Specific location name within the town.

Datatype: "CBPR_RestrictedFINXMax35Text_Extended" on page 269

Usage Guideline details

- on camt.106.001.03/Charges/PerType/Record/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/TownLocationName

Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 269

5.81.15 DistrictName

XML Tag: DstrctNm

Presence: [0..1]

Definition: Identifies a subdivision within a country sub-division.

Datatype: "CBPR_RestrictedFINXMax35Text_Extended" on page 269

Usage Guideline details

- on camt.106.001.03/Charges/PerType/Record/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/DistrictName

Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 269

5.81.16 CountrySubDivision

XML Tag: CtrySubDvsn

Presence: [0..1]

Definition: Identifies a subdivision of a country such as state, region, county.

Datatype: "CBPR_RestrictedFINXMax35Text_Extended" on page 269

Usage Guideline details

- on camt.106.001.03/Charges/PerType/Record/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision

Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 269

5.81.17 Country

XML Tag: Ctry

Presence: [0..1]

Definition: Nation with its own government.

Datatype: ["CountryCode" on page 271](#)

5.81.18 AddressLine

XML Tag: AdrLine

Presence: [0..7]

Definition: Information that locates and identifies a specific address, as defined by postal services, presented in free format text.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 269](#)

Usage Guideline details

- on [camt.106.001.03/Charges/PerType/Record/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine](#)

This element has change repeatability, the maximum occurrence has been changed to : 3

- on [camt.106.001.03/Charges/PerType/Record/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 269](#)

5.82 ProprietaryReference1

Definition: Set of elements to identify a proprietary reference.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[1..1]		228
	Reference	<Ref>		[1..1]		228

Used in element(s)

["Proprietary" on page 251](#), ["Proprietary" on page 258](#)

5.82.1 Type

XML Tag: Tp

Presence: [1..1]

Definition: Identifies the type of reference reported.

Datatype: ["Max35Text" on page 284](#)

5.82.2 Reference

XML Tag: Ref

Presence: [1..1]

Definition: Proprietary reference specification related to the underlying transaction.

Datatype: ["Max35Text" on page 284](#)

5.83 ProxyAccountIdentification1

Definition: Information related to a proxy identification of the account.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		229
	Identification	<Id>		[1..1]		229

Used in element(s)

["Proxy" on page 49](#)

5.83.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Type of the proxy identification.

The **Tp** block contains the following elements (see datatype ["ProxyAccountType1Choice" on page 232](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		232
	Proprietary	<Prtry>	Or}	[1..1]		232

5.83.2 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification used to indicate the account identification under another specified name.

Datatype: ["Max2048Text" on page 283](#)

5.84 ProxyAccountIdentification1__1

Definition: Information related to a proxy identification of the account.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		230
	Identification	<Id>		[1..1]		230

Used in element(s)

"Proxy" on page 53, "Proxy" on page 56

5.84.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Type of the proxy identification.

The **Tp** block contains the following elements (see datatype "ProxyAccountType1Choice_1" on page 232 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		232
	Proprietary	<Prtry>	Or}	[1..1]		233

Usage Guideline details

- on camt.106.001.03/GroupHeader/ChargesAccountAgentAccount/Proxy/Type**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAgentAccount/Proxy/Type**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAccount/Proxy/Type**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.106.001.03/Charges/PerTransaction/Record/DebtorAccount/Proxy/Type**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.106.001.03/Charges/PerTransaction/Record/DebtorAgentAccount/Proxy/Type**
This element is now mandatory, the minimum occurrence has been changed to : 1

5.84.2 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification used to indicate the account identification under another specified name.

Datatype: "CBPR_RestrictedFINXMax320Text_Extended" on page 267

Usage Guideline details

- on camt.106.001.03/Charges/PerType/Record/ChargesAccountAgentAccount/Proxy/Identification
Type changed to: [CBPR_RestrictedFINXMax320Text_Extended on page 267](#)
- on camt.106.001.03/Charges/PerTransaction/ChargesAccountAgentAccount/Proxy/Identification
Type changed to: [CBPR_RestrictedFINXMax320Text_Extended on page 267](#)
- on camt.106.001.03/Charges/Single/DebtorAgentAccount/Proxy/Identification
Type changed to: [CBPR_RestrictedFINXMax320Text_Extended on page 267](#)
- on camt.106.001.03/GroupHeader/ChargesAccountAgentAccount/Proxy/Identification
Type changed to: [CBPR_RestrictedFINXMax320Text_Extended on page 267](#)
- on camt.106.001.03/Charges/PerTransaction/Record/DebtorAgentAccount/Proxy/Identification
Type changed to: [CBPR_RestrictedFINXMax320Text_Extended on page 267](#)
- on camt.106.001.03/Charges/PerType/Record/DebtorAgentAccount/Proxy/Identification
Type changed to: [CBPR_RestrictedFINXMax320Text_Extended on page 267](#)
- on camt.106.001.03/Charges/PerType/ChargesAccountAgentAccount/Proxy/Identification
Type changed to: [CBPR_RestrictedFINXMax320Text_Extended on page 267](#)
- on camt.106.001.03/Charges/PerTransaction/Record/ChargesAccountAgentAccount/Proxy/Identification
Type changed to: [CBPR_RestrictedFINXMax320Text_Extended on page 267](#)
- on camt.106.001.03/Charges/Single/ChargesAccountAgentAccount/Proxy/Identification
Type changed to: [CBPR_RestrictedFINXMax320Text_Extended on page 267](#)
- on camt.106.001.03/Charges/PerTransaction/Record/DebtorAccount/Proxy/Identification
Type changed to: [CBPR_RestrictedFINXMax320Text_Extended on page 267](#)
- on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAgentAccount/Proxy/Identification
Type changed to: [CBPR_RestrictedFINXMax320Text_Extended on page 267](#)
- on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAccount/Proxy/Identification
Type changed to: [CBPR_RestrictedFINXMax320Text_Extended on page 267](#)

5.85 ProxyAccountType1Choice

Definition: Specifies the scheme used for the identification of an account alias.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		232
	Proprietary	<Prtry>	Or}	[1..1]		232

Used in element(s)

"Type" on page 229

5.85.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalProxyAccountType1Code" on page 279

5.85.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 284

5.86 ProxyAccountType1Choice__1

Definition: Specifies the scheme used for the identification of an account alias.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		232
	Proprietary	<Prtry>	Or}	[1..1]		233

Used in element(s)

"Type" on page 230

5.86.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: ["ExternalProxyAccountType1Code" on page 279](#)

5.86.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 268](#)

Usage Guideline details

- on [camt.106.001.03/Charges/PerTransaction/ChargesAccountAgentAccount/Proxy/Type/Proprietary](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on [camt.106.001.03/GroupHeader/ChargesAccountAgentAccount/Proxy/Type/Proprietary](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on [camt.106.001.03/Charges/Single/ChargesAccountAgentAccount/Proxy/Type/Proprietary](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on [camt.106.001.03/Charges/PerTransaction/Record/DebtorAgentAccount/Proxy/Type/Proprietary](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on [camt.106.001.03/Charges/Single/DebtorAgentAccount/Proxy/Type/Proprietary](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on [camt.106.001.03/Charges/PerType/ChargesAccountAgentAccount/Proxy/Type/Proprietary](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on [camt.106.001.03/Charges/PerType/Record/DebtorAgentAccount/Proxy/Type/Proprietary](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on [camt.106.001.03/Charges/PerType/Record/ChargesAccountAgentAccount/Proxy/Type/Proprietary](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on [camt.106.001.03/Charges/PerTransaction/Record/ChargesAccountAgentAccount/Proxy/Type/Proprietary](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on [camt.106.001.03/Charges/PerTransaction/Record/DebtorAccount/Proxy/Type/Proprietary](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on [camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAgentAccount/Proxy/Type/Proprietary](#)

Type changed to: [CBPR_RestrictedFINXMax35Text](#) on page 268

- on [camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAccount/Proxy/Type/Proprietary](#)

Type changed to: [CBPR_RestrictedFINXMax35Text](#) on page 268

5.87 SettlementInstruction19

Definition: Provides further details on the settlement of the instruction.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	RequestedSettlementDate	<ReqdSttlmDt>		[0..1]		234
	CreditorAgent	<CdtrAgt>		[1..1]		234
	CreditorAgentAccount	<CdtrAgtAcct>		[0..1]		235
	Creditor	<Cdtr>		[0..1]		235
	CreditorAccount	<CdtrAcct>		[0..1]		235

Used in element(s)

["SettlementInstruction" on page 158](#),
 ["SettlementInstruction" on page 95](#),
 ["SettlementInstruction" on page 86](#)

5.87.1 RequestedSettlementDate

XML Tag: ReqdSttlmDt

Presence: [0..1]

Definition: Date at which the message sender or ChargesRequestor where this element is present expects to be credited for the payment of the charges.

Datatype: ["ISODate" on page 280](#)

5.87.2 CreditorAgent

XML Tag: CdtrAgt

Presence: [1..1]

Definition: Financial institution servicing an account for the creditor.

The **CdtrAgt** block contains the following elements (see datatype ["BranchAndFinancialInstitutionIdentification8" on page 27](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		27
	BranchIdentification	<BrnchId>		[0..1]		28

5.87.3 CreditorAgentAccount

XML Tag: CdtrAgtAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction.

The **CdtrAgtAcct** block contains the following elements (see datatype "CashAccount40" on page 47 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		48
	Type	<Tp>		[0..1]		48
	Currency	<Ccy>		[0..1]		49
	Name	<Nm>		[0..1]		49
	Proxy	<Prxy>		[0..1]		49

5.87.4 Creditor

XML Tag: Cdtr

Presence: [0..1]

Definition: Financial institution that receives an amount of money from the financial institutional debtor.

Usage: where used this party must be the same as the message sender or ChargesRequestor where this element is present.

The **Cdtr** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification8" on page 27 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		27
	BranchIdentification	<BrnchId>		[0..1]		28

5.87.5 CreditorAccount

XML Tag: CdtrAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction.

Usage: where used this account should be owned by the message sender or ChargesRequestor where this element is present.

The **CdtrAcct** block contains the following elements (see datatype "CashAccount40" on page 47 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		48
	Type	<Tp>		[0..1]		48
	Currency	<Ccy>		[0..1]		49
	Name	<Nm>		[0..1]		49
	Proxy	<Prxy>		[0..1]		49

5.88 SettlementInstruction19__1

Definition: Provides further details on the settlement of the instruction.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	RequestedSettlementDate	<ReqdSttlmDt>		[0..1]		236
	CreditorAgent	<CdtrAgt>		[1..1]		237
	CreditorAgentAccount	<CdtrAgtAcct>		[0..1]		238
	Creditor	<Cdtr>		[0..1]		238
	CreditorAccount	<CdtrAcct>		[0..1]		239

Used in element(s)

"SettlementInstruction" on page 71

5.88.1 RequestedSettlementDate

XML Tag: ReqdSttlmDt

Presence: [0..1]

Definition: Date at which the message sender or ChargesRequestor where this element is present expects to be credited for the payment of the charges.

Datatype: "CBPR_Date" on page 264

Usage Guideline details

- on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/RequestedSettlementDate

Type changed to: CBPR_Date on page 264

5.88.2 CreditorAgent

XML Tag: CdtrAgt

Presence: [1..1]

Definition: Financial institution servicing an account for the creditor.

The **CdtrAgt** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification8_1" on page 28 for details)

❌ Removed - ❌ Partial Removed - ◆ Ignored - ◆ Partial Ignored - ⚠️ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]	⚠️	29
	BranchIdentification	<BrnchId>		[0..1]	❌	31

Usage Guideline details

- on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAgent
 - CBPR_Agent_Option_1_TextualRule:

BICFI, complemented optionally with a LEI (preferred option)
- on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAgent
 - CBPR_Agent_National_only_TextualRule:

Whenever Debtor Agent, Creditor Agent and all agents in between are located within the same country, the clearing code only may be used.
- on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAgent
 - CBPR_Agent_Option_2_TextualRule:

(Clearing Code OR LEI) AND (Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.
- on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/CreditorAgent
 - CBPR_Agent_Option_3_TextualRule:

Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country]). It is recommended to also add the post code when available.

5.88.3 CreditorAgentAccount

XML Tag: CdtrAgtAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction.

The **CdtrAgtAcct** block contains the following elements (see datatype "CashAccount40__1" on page 50 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]	M	50
	Type	<Tp>		[0..1]		51
	Currency	<Ccy>		[0..1]		52
	Name	<Nm>		[0..1]	⚠	52
	Proxy	<Prxy>		[0..1]		53

5.88.4 Creditor

XML Tag: Cdtr

Presence: [0..1]

Definition: Financial institution that receives an amount of money from the financial institutional debtor.

Usage: where used this party must be the same as the message sender or ChargesRequestor where this element is present.

The **Cdtr** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification8__1" on page 28 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]	⚠	29
	BranchIdentification	<BrnchId>		[0..1]	🚫	31

Usage Guideline details

- on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/Creditor

– **CBPR_Agent_National_only_TextualRule:**

Whenever Debtor Agent, Creditor Agent and all agents in between are located within the same country, the clearing code only may be used.

• **on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/Creditor**

– **CBPR_Agent_Option_1_TextualRule:**

BICFI, complemented optionally with a LEI (preferred option)

• **on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/Creditor**

– **CBPR_Agent_Option_2_TextualRule:**

(Clearing Code OR LEI) AND (Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.

• **on camt.106.001.03/Charges/PerTransaction/Record/SettlementInstruction/Creditor**

– **CBPR_Agent_Option_3_TextualRule:**

Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.

5.88.5 CreditorAccount

XML Tag: CdtrAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction.

Usage: where used this account should be owned by the message sender or ChargesRequestor where this element is present.

The **CdtrAcct** block contains the following elements (see datatype "CashAccount40__1" on page 50 for details)

🚫 Removed - 🚫 Partial Removed - 💡 Ignored - 💡 Partial Ignored - ⚠️ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]	M	50
	Type	<Tp>		[0..1]		51
	Currency	<Ccy>		[0..1]		52
	Name	<Nm>		[0..1]	⚠️	52
	Proxy	<Prxy>		[0..1]		53

5.89 SupplementaryData1

Definition: Additional information that can not be captured in the structured fields and/or any other specific block.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
 M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PlaceAndName	<PlcAndNm>		[0..1]		240
	Envelope	<Envlp>		[1..1]		240

Rules

R19 SupplementaryDataRule

This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

Error handling: Undefined

Used in element(s)

"SupplementaryData" on page 18

5.89.1 PlaceAndName

XML Tag: PlcAndNm

Presence: [0..1]

Definition: Unambiguous reference to the location where the supplementary data must be inserted in the message instance.

In the case of XML, this is expressed by a valid XPath.

Datatype: "Max350Text" on page 283

5.89.2 Envelope

XML Tag: Envlp

Presence: [1..1]

Definition: Technical element wrapping the supplementary data.

5.90 TotalCharges7

Definition: Specifies the total amount of records and charges included in the block.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
 M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NumberOfChargesRecords	<NbOfChrgsRcrds>		[1..1]		241

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ControlSum	<CtrlSum>		[0..1]		241
	TotalChargesAmount	<TtlChrgsAmt>		[0..1]		241
	CreditDebitIndicator	<CdtDbtInd>		[0..1]		241

Used in element(s)

"TotalChargesPerTransaction" on page 65

5.90.1 NumberOfChargesRecords

XML Tag: NbOfChrgsRcrds

Presence: [1..1]

Definition: Number of individual charges records.

Datatype: "Max15NumericText" on page 282

5.90.2 ControlSum

XML Tag: CtrlSum

Presence: [0..1]

Definition: Total of all individual amounts included, irrespective of currencies.

Datatype: "DecimalNumber" on page 272

5.90.3 TotalChargesAmount

XML Tag: TtlChrgsAmt

Presence: [0..1]

Definition: Total amount of charges claimed.

Datatype: "ActiveCurrencyAndAmount" on page 259

5.90.4 CreditDebitIndicator

XML Tag: CdtDbtInd

Presence: [0..1]

Definition: Indicates whether the total charges amount is a credit or a debit amount.

Usage: A zero amount is considered to be a credit.

Datatype: "CreditDebitCode" on page 272

5.91 TotalCharges7__1

Definition: Specifies the total amount of records and charges included in the block.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NumberOfChargesRecords	<NbOfChrgsRcrds>		[1..1]		242
	ControlSum	<CtrlSum>		[0..1]		242
	TotalChargesAmount	<TtlChrgsAmt>		[0..1]	 	242
	CreditDebitIndicator	<CdtDbtInd>		[0..1]		243

Used in element(s)

"TotalCharges" on page 158, "TotalChargesPerChargeType" on page 81

5.91.1 NumberOfChargesRecords

XML Tag: NbOfChrgsRcrds

Presence: [1..1]

Definition: Number of individual charges records.

Datatype: "Max15NumericText" on page 282

5.91.2 ControlSum

XML Tag: CtrlSum

Presence: [0..1]

Definition: Total of all individual amounts included, irrespective of currencies.

Datatype: "DecimalNumber" on page 272

Usage Guideline details

- This element(camt.106.001.03/GroupHeader/TotalCharges/ControlSum) is removed.

5.91.3 TotalChargesAmount

XML Tag: TtlChrgsAmt

Presence: [0..1]

Definition: Total amount of charges claimed.

Datatype: "CBPR_Amount__1" on page 264

Usage Guideline details

- on camt.106.001.03/GroupHeader/TotalCharges/TotalChargesAmount
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.106.001.03/Charges/PerType/TotalChargesPerChargeType/TotalChargesAmount
Type changed to: CBPR_Amount on page 263
- on camt.106.001.03/GroupHeader/TotalCharges/TotalChargesAmount

Type changed to: [CBPR_Amount on page 263](#)

5.91.4 CreditDebitIndicator

XML Tag: CdtDbtInd

Presence: [0..1]

Definition: Indicates whether the total charges amount is a credit or a debit amount.

Usage: A zero amount is considered to be a credit.

Datatype: ["CreditDebitCode" on page 272](#)

Usage Guideline details

- on [camt.106.001.03/GroupHeader/TotalCharges/CreditDebitIndicator](#)
This element is now mandatory, the minimum occurrence has been changed to : 1

5.92 TotalCharges8__1

Definition: Specifies the total amount of records and charges included in the block.

🚫 Removed - 🚫 Partial Removed - ✨ Ignored - ✨ Partial Ignored - ⚠️ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NumberOfChargesBreak-downItems	<NbOfChrgsBrkdwnItms>		[1..1]		243
	ControlSum	<CtrlSum>		[0..1]	🚫	243
	TotalChargesAmount	<TtlChrgsAmt>		[0..1]	M ⚠️	244
	CreditDebitIndicator	<CdtDbtInd>		[0..1]	M	244

Used in element(s)

["TotalChargesPerRecord" on page 73](#)

5.92.1 NumberOfChargesBreakdownItems

XML Tag: NbOfChrgsBrkdwnItms

Presence: [1..1]

Definition: Number of individual charges breakdown items contained in the record.

Datatype: ["Max15NumericText" on page 282](#)

5.92.2 ControlSum

XML Tag: CtrlSum

Presence: [0..1]

Definition: Total of all individual charges breakdown amounts, irrespective of currencies.

Datatype: ["DecimalNumber" on page 272](#)

Usage Guideline details

- This element([camt.106.001.03/Charges/PerTransaction/Record/TotalChargesPerRecord/ControlSum](#)) is removed.

5.92.3 TotalChargesAmount

XML Tag: TtlChrgsAmt

Presence: [0..1]

Definition: Total amount of charges claimed through the charges breakdown items.

Datatype: ["CBPR_Amount__1" on page 264](#)

Usage Guideline details

- on [camt.106.001.03/Charges/PerTransaction/Record/TotalChargesPerRecord/TotalChargesAmount](#)
This element is now mandatory, the minimum occurrence has been changed to : 1
- on [camt.106.001.03/Charges/PerTransaction/Record/TotalChargesPerRecord/TotalChargesAmount](#)
Type changed to: [CBPR_Amount on page 263](#)

5.92.4 CreditDebitIndicator

XML Tag: CdtDbtInd

Presence: [0..1]

Definition: Indicates whether the total charges amount is a credit or a debit amount.

Usage: A zero amount is considered to be a credit.

Datatype: ["CreditDebitCode" on page 272](#)

Usage Guideline details

- on [camt.106.001.03/Charges/PerTransaction/Record/TotalChargesPerRecord/CreditDebitIndicator](#)
This element is now mandatory, the minimum occurrence has been changed to : 1

5.93 TransactionReferences7__1

Definition: Identifies the underlying transaction.

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	MessageIdentification	<MsgId>		[0..1]		245
	MessageNameIdentification	<MsgNmId>		[0..1]	M	246
	AccountServicerReference	<AcctSvcrRef>		[0..1]		246
	PaymentInformationIdentification	<PmtInfId>		[0..1]		246
	InstructionIdentification	<InstrId>		[0..1]	M	247
	EndToEndIdentification	<EndToEndId>		[0..1]		247
	UETR	<UETR>		[0..1]	M	248
	TransactionIdentification	<TxId>		[0..1]		248
	MandatIdentification	<MndtId>		[0..1]		249
	ChequeNumber	<ChqNb>		[0..1]		249
	ClearingSystemReference	<ClrSysRef>		[0..1]		249
	AccountOwnerTransactionIdentification	<AcctOwnrTxId>		[0..1]		250
	AccountServicerTransactionIdentification	<AcctSvcrTxId>		[0..1]		250
	MarketInfrastructureTransactionIdentification	<MktInfstrctrTxId>		[0..1]		251
	ProcessingIdentification	<PrcgId>		[0..1]		251
	Proprietary	<Prtry>		[0..*]		251

Used in element(s)

"UnderlyingTransaction" on page 96, "UnderlyingTransaction" on page 87

5.93.1 MessageIdentification

XML Tag: MsgId

Presence: [0..1]

Definition: Point to point reference, as assigned by the instructing party of the underlying message.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 268

Usage Guideline details

- on camt.106.001.03/Charges/PerType/Record/UnderlyingTransaction/MessageIdentification
Type changed to: CBPR_RestrictedFINXMax35Text on page 268
- on camt.106.001.03/Charges/Single/UnderlyingTransaction/MessageIdentification

Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)

5.93.2 MessageNameIdentification

XML Tag: MsgNmId

Presence: [0..1]

Definition: Specifies the original message name identifier to which the message refers.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 268](#)

Usage Guideline details

- **on camt.106.001.03/Charges/Single/UnderlyingTransaction/MessageNameIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on camt.106.001.03/Charges/PerType/Record/UnderlyingTransaction/MessageNameIdentification**
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- **on camt.106.001.03/Charges/Single/UnderlyingTransaction/MessageNameIdentification**
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)

5.93.3 AccountServicerReference

XML Tag: AcctSvcrRef

Presence: [0..1]

Definition: Unique reference, as assigned by the account servicing institution, to unambiguously identify the instruction.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 268](#)

Usage Guideline details

- **on camt.106.001.03/Charges/PerType/Record/UnderlyingTransaction/AccountServicerReference**
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- **on camt.106.001.03/Charges/Single/UnderlyingTransaction/AccountServicerReference**
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)

5.93.4 PaymentInformationIdentification

XML Tag: PmtInfId

Presence: [0..1]

Definition: Unique identification, as assigned by a sending party, to unambiguously identify the payment information group within the message.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 268](#)

Usage Guideline details

- on **camt.106.001.03/Charges/PerType/Record/UnderlyingTransaction/PaymentInformationIdentification**
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on **camt.106.001.03/Charges/Single/UnderlyingTransaction/PaymentInformationIdentification**
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)

5.93.5 InstructionIdentification

XML Tag: InstrId

Presence: [0..1]

Definition: Unique identification, as assigned by an instructing party for an instructed party, to unambiguously identify the instruction.

Usage: The instruction identification is a point to point reference that can be used between the instructing party and the instructed party to refer to the individual instruction. It can be included in several messages related to the instruction.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 268](#)

Usage Guideline details

- on **camt.106.001.03/Charges/Single/UnderlyingTransaction/InstructionIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **camt.106.001.03/Charges/PerType/Record/UnderlyingTransaction/InstructionIdentification**
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on **camt.106.001.03/Charges/Single/UnderlyingTransaction/InstructionIdentification**
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)

5.93.6 EndToEndIdentification

XML Tag: EndToEndId

Presence: [0..1]

Definition: Unique identification, as assigned by the initiating party, to unambiguously identify the transaction. This identification is passed on, unchanged, throughout the entire end-to-end chain.

Usage: The end-to-end identification can be used for reconciliation or to link tasks relating to the transaction. It can be included in several messages related to the transaction.

Usage: In case there are technical limitations to pass on multiple references, the end-to-end identification must be passed on throughout the entire end-to-end chain.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 268

Usage Guideline details

- on **camt.106.001.03/Charges/PerType/Record/UnderlyingTransaction/EndToEndIdentification**
Type changed to: CBPR_RestrictedFINXMax35Text on page 268
- on **camt.106.001.03/Charges/Single/UnderlyingTransaction/EndToEndIdentification**
Type changed to: CBPR_RestrictedFINXMax35Text on page 268

5.93.7 UETR

XML Tag: UETR

Presence: [0..1]

Definition: Universally unique identifier to provide an end-to-end reference of a payment transaction.

Datatype: "UUIDv4Identifier" on page 289

Usage Guideline details

- on **camt.106.001.03/Charges/PerType/Record/UnderlyingTransaction/UETR**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **camt.106.001.03/Charges/Single/UnderlyingTransaction/UETR**
This element is now mandatory, the minimum occurrence has been changed to : 1

5.93.8 TransactionIdentification

XML Tag: TxId

Presence: [0..1]

Definition: Unique identification, as assigned by the first instructing agent, to unambiguously identify the transaction that is passed on, unchanged, throughout the entire interbank chain.

Usage: The transaction identification can be used for reconciliation, tracking or to link tasks relating to the transaction on the interbank level.

Usage: The instructing agent has to make sure that the transaction identification is unique for a pre-agreed period.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 268

Usage Guideline details

- on **camt.106.001.03/Charges/PerType/Record/UnderlyingTransaction/TransactionIdentification**
Type changed to: CBPR_RestrictedFINXMax35Text on page 268

- on **camt.106.001.03/Charges/Single/UnderlyingTransaction/TransactionIdentification**
Type changed to: CBPR_RestrictedFINXMax35Text on page 268

5.93.9 MandateIdentification

XML Tag: MndtId

Presence: [0..1]

Definition: Unique identification, as assigned by the creditor, to unambiguously identify the mandate.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 268

Usage Guideline details

- on **camt.106.001.03/Charges/PerType/Record/UnderlyingTransaction/MandateIdentification**
Type changed to: CBPR_RestrictedFINXMax35Text on page 268
- on **camt.106.001.03/Charges/Single/UnderlyingTransaction/MandateIdentification**
Type changed to: CBPR_RestrictedFINXMax35Text on page 268

5.93.10 ChequeNumber

XML Tag: ChqNb

Presence: [0..1]

Definition: Unique and unambiguous identifier for a cheque as assigned by the agent.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 268

Usage Guideline details

- on **camt.106.001.03/Charges/Single/UnderlyingTransaction/ChequeNumber**
Type changed to: CBPR_RestrictedFINXMax35Text on page 268
- on **camt.106.001.03/Charges/PerType/Record/UnderlyingTransaction/ChequeNumber**
Type changed to: CBPR_RestrictedFINXMax35Text on page 268

5.93.11 ClearingSystemReference

XML Tag: ClrSysRef

Presence: [0..1]

Definition: Unique reference, as assigned by a clearing system, to unambiguously identify the instruction.

Usage: In case there are technical limitations to pass on multiple references, the end-to-end identification must be passed on throughout the entire end-to-end chain.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 268

Usage Guideline details

- on camt.106.001.03/Charges/Single/UnderlyingTransaction/ClearingSystemReference
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on camt.106.001.03/Charges/PerType/Record/UnderlyingTransaction/ClearingSystemReference
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)

5.93.12 AccountOwnerTransactionIdentification

XML Tag: AcctOwnrTxId

Presence: [0..1]

Definition: Unambiguous identification of the securities transaction as known by the securities account owner (or the instructing party managing the account).

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 268](#)

Usage Guideline details

- on camt.106.001.03/Charges/Single/UnderlyingTransaction/AccountOwnerTransactionIdentification
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on camt.106.001.03/Charges/PerType/Record/UnderlyingTransaction/AccountOwnerTransactionIdentification
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)

5.93.13 AccountServicerTransactionIdentification

XML Tag: AcctSvcrTxId

Presence: [0..1]

Definition: Unambiguous identification of the securities transaction as known by the securities account servicer.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 268](#)

Usage Guideline details

- on camt.106.001.03/Charges/Single/UnderlyingTransaction/AccountServicerTransactionIdentification
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on camt.106.001.03/Charges/PerType/Record/UnderlyingTransaction/AccountServicerTransactionIdentification
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)

5.93.14 MarketInfrastructureTransactionIdentification

XML Tag: MktInfrstrctrTxId

Presence: [0..1]

Definition: Identification of a securities transaction assigned by a market infrastructure other than a central securities depository, for example, Target2-Securities.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 268](#)

Usage Guideline details

- on [camt.106.001.03/Charges/Single/UnderlyingTransaction/MarketInfrastructureTransactionIdentification](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on [camt.106.001.03/Charges/PerType/Record/UnderlyingTransaction/MarketInfrastructureTransactionIdentification](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)

5.93.15 ProcessingIdentification

XML Tag: PrcgId

Presence: [0..1]

Definition: Identification of the securities transaction assigned by the processor of the instruction other than the securities account owner, the securities account servicer and the market infrastructure.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 268](#)

Usage Guideline details

- on [camt.106.001.03/Charges/PerType/Record/UnderlyingTransaction/ProcessingIdentification](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)
- on [camt.106.001.03/Charges/Single/UnderlyingTransaction/ProcessingIdentification](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)

5.93.16 Proprietary

XML Tag: Prtry

Presence: [0..*]

Definition: Proprietary reference related to the underlying transaction.

The **Prtry** block contains the following elements (see datatype ["ProprietaryReference1" on page 228](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[1..1]		228
	Reference	<Ref>		[1..1]		228

Usage Guideline details

- This element(camt.106.001.03/Charges/Single/UnderlyingTransaction/Proprietary) is removed.
- This element(camt.106.001.03/Charges/PerType/Record/UnderlyingTransaction/Proprietary) is removed.

5.94 TransactionReferences7__2

Definition: Identifies the underlying transaction.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	MessageIdentification	<MsgId>		[0..1]		253
	MessageNameIdentification	<MsgNmId>		[0..1]	 	253
	AccountServicerReference	<AcctSvcrRef>		[0..1]		253
	PaymentInformationIdentification	<PmtInfId>		[0..1]		254
	InstructionIdentification	<InstrId>		[0..1]		254
	EndToEndIdentification	<EndToEndId>		[0..1]		255
	UETR	<UETR>		[0..1]		255
	TransactionIdentification	<TxId>		[0..1]		255
	MandateIdentification	<MndtId>		[0..1]		256
	ChequeNumber	<ChqNb>		[0..1]		256
	ClearingSystemReference	<ClrSysRef>		[0..1]		256
	AccountOwnerTransactionIdentification	<AcctOwnrTxId>		[0..1]		257
	AccountServicerTransactionIdentification	<AcctSvcrTxId>		[0..1]		257
	MarketInfrastructureTransactionIdentification	<MktInfstrctrTxId>		[0..1]		257
	ProcessingIdentification	<PrcgId>		[0..1]		258
	Proprietary	<Prtry>		[0..*]		258

Used in element(s)

["UnderlyingTransaction" on page 72](#)

5.94.1 MessageIdentification

XML Tag: MsgId

Presence: [0..1]

Definition: Point to point reference, as assigned by the instructing party of the underlying message.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 268](#)

Usage Guideline details

- on [camt.106.001.03/Charges/PerTransaction/Record/UnderlyingTransaction/MessageIdentification](#)

Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)

5.94.2 MessageNameIdentification

XML Tag: MsgNmId

Presence: [0..1]

Definition: Specifies the original message name identifier to which the message refers.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 268](#)

Usage Guideline details

- on [camt.106.001.03/Charges/PerTransaction/Record/UnderlyingTransaction/MessageNameIdentification](#)

This element is now mandatory, the minimum occurrence has been changed to : 1

- on [camt.106.001.03/Charges/PerTransaction/Record/UnderlyingTransaction/MessageNameIdentification](#)

Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)

5.94.3 AccountServicerReference

XML Tag: AcctSvcrRef

Presence: [0..1]

Definition: Unique reference, as assigned by the account servicing institution, to unambiguously identify the instruction.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 268](#)

Usage Guideline details

- on [camt.106.001.03/Charges/PerTransaction/Record/UnderlyingTransaction/AccountServicerReference](#)

Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)

5.94.4 PaymentInformationIdentification

XML Tag: PmtInfId

Presence: [0..1]

Definition: Unique identification, as assigned by a sending party, to unambiguously identify the payment information group within the message.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 268](#)

Usage Guideline details

- on [camt.106.001.03/Charges/PerTransaction/Record/UnderlyingTransaction/PaymentInformationIdentification](#)

Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)

5.94.5 InstructionIdentification

XML Tag: InstrId

Presence: [0..1]

Definition: Unique identification, as assigned by an instructing party for an instructed party, to unambiguously identify the instruction.

Usage: The instruction identification is a point to point reference that can be used between the instructing party and the instructed party to refer to the individual instruction. It can be included in several messages related to the instruction.

Datatype: ["CBPR_RestrictedFINXMax16Text" on page 266](#)

Usage Guideline details

- on [camt.106.001.03/Charges/PerTransaction/Record/UnderlyingTransaction/InstructionIdentification](#)

Type changed to: [CBPR_RestrictedFINXMax16Text on page 266](#)

- on [camt.106.001.03/Charges/PerTransaction/Record/UnderlyingTransaction/InstructionIdentification](#)

– CBPR_Instruction_Identification_FormaRule:

This element must not start or end with a slash '/' and must not contain two consecutive slashes '//'.

For each [Full Message/Document/ChargesPaymentRequestV03/Charges/PerTransaction/Record/UnderlyingTransaction/InstructionIdentification],

the value of every occurrence of [InstructionIdentification] must not comply with the following XML pattern : `'(/.*)|(.*/)|(.*/.*)'`

5.94.6 EndToEndIdentification

XML Tag: EndToEndId

Presence: [0..1]

Definition: Unique identification, as assigned by the initiating party, to unambiguously identify the transaction. This identification is passed on, unchanged, throughout the entire end-to-end chain.

Usage: The end-to-end identification can be used for reconciliation or to link tasks relating to the transaction. It can be included in several messages related to the transaction.

Usage: In case there are technical limitations to pass on multiple references, the end-to-end identification must be passed on throughout the entire end-to-end chain.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 268

Usage Guideline details

- on **camt.106.001.03/Charges/PerTransaction/Record/UnderlyingTransaction/EndToEndIdentification**

Type changed to: CBPR_RestrictedFINXMax35Text on page 268

5.94.7 UETR

XML Tag: UETR

Presence: [0..1]

Definition: Universally unique identifier to provide an end-to-end reference of a payment transaction.

Datatype: "UUIDv4Identifier" on page 289

5.94.8 TransactionIdentification

XML Tag: TxId

Presence: [0..1]

Definition: Unique identification, as assigned by the first instructing agent, to unambiguously identify the transaction that is passed on, unchanged, throughout the entire interbank chain.

Usage: The transaction identification can be used for reconciliation, tracking or to link tasks relating to the transaction on the interbank level.

Usage: The instructing agent has to make sure that the transaction identification is unique for a pre-agreed period.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 268

Usage Guideline details

- on **camt.106.001.03/Charges/PerTransaction/Record/UnderlyingTransaction/TransactionIdentification**

Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)

5.94.9 MandateIdentification

XML Tag: MndtId

Presence: [0..1]

Definition: Unique identification, as assigned by the creditor, to unambiguously identify the mandate.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 268](#)

Usage Guideline details

- on **camt.106.001.03/Charges/PerTransaction/Record/UnderlyingTransaction/MandateIdentification**

Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)

5.94.10 ChequeNumber

XML Tag: ChqNb

Presence: [0..1]

Definition: Unique and unambiguous identifier for a cheque as assigned by the agent.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 268](#)

Usage Guideline details

- on **camt.106.001.03/Charges/PerTransaction/Record/UnderlyingTransaction/ChequeNumber**

Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)

5.94.11 ClearingSystemReference

XML Tag: ClrSysRef

Presence: [0..1]

Definition: Unique reference, as assigned by a clearing system, to unambiguously identify the instruction.

Usage: In case there are technical limitations to pass on multiple references, the end-to-end identification must be passed on throughout the entire end-to-end chain.

Datatype: ["Max35Text" on page 284](#)

Usage Guideline details

- This element([camt.106.001.03/Charges/PerTransaction/Record/UnderlyingTransaction/ClearingSystemReference](#)) is removed.

5.94.12 AccountOwnerTransactionIdentification

XML Tag: AcctOwnrTxId

Presence: [0..1]

Definition: Unambiguous identification of the securities transaction as known by the securities account owner (or the instructing party managing the account).

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 268](#)

Usage Guideline details

- on [camt.106.001.03/Charges/PerTransaction/Record/UnderlyingTransaction/AccountOwner-TransactionIdentification](#)

Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)

5.94.13 AccountServicerTransactionIdentification

XML Tag: AcctSvcrTxId

Presence: [0..1]

Definition: Unambiguous identification of the securities transaction as known by the securities account servicer.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 268](#)

Usage Guideline details

- on [camt.106.001.03/Charges/PerTransaction/Record/UnderlyingTransaction/AccountServicer-TransactionIdentification](#)

Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)

5.94.14 MarketInfrastructureTransactionIdentification

XML Tag: MktInfrstrctrTxId

Presence: [0..1]

Definition: Identification of a securities transaction assigned by a market infrastructure other than a central securities depository, for example, Target2-Securities.

Datatype: ["Max35Text" on page 284](#)

Usage Guideline details

- This element([camt.106.001.03/Charges/PerTransaction/Record/UnderlyingTransaction/MarketInfrastructureTransactionIdentification](#)) is removed.

5.94.15 ProcessingIdentification

XML Tag: PrcgId

Presence: [0..1]

Definition: Identification of the securities transaction assigned by the processor of the instruction other than the securities account owner, the securities account servicer and the market infrastructure.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 268](#)

Usage Guideline details

- on [camt.106.001.03/Charges/PerTransaction/Record/UnderlyingTransaction/ProcessingIdentification](#)

Type changed to: [CBPR_RestrictedFINXMax35Text on page 268](#)

5.94.16 Proprietary

XML Tag: Prtry

Presence: [0..*]

Definition: Proprietary reference related to the underlying transaction.

The **Prtry** block contains the following elements (see datatype ["ProprietaryReference1" on page 228](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[1..1]		228
	Reference	<Ref>		[1..1]		228

Usage Guideline details

- This element([camt.106.001.03/Charges/PerTransaction/Record/UnderlyingTransaction/Proprietary](#)) is removed.

6 Message Datatypes

Note The following chapter identifies the datatypes that are used in the message.

6.1 ActiveCurrencyAndAmount

Definition: A number of monetary units specified in an active currency where the unit of currency is explicit and compliant with ISO 4217.

Type: Amount

This data type must be used with the following XML Attributes:

Attribute	Tag	Datatype
Currency	Ccy	"ActiveCurrencyCode" on page 259

Format

fractionDigits	5
minInclusive	0
totalDigits	18

Rules

R20 CurrencyAmount ✓

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00007
- *Error Text:* Invalid currency code or too many decimal digits.

Used in element(s)

"TotalChargesAmount" on page 241

6.2 ActiveCurrencyCode

Definition: A code allocated to a currency by a Maintenance Agency under an international identification scheme as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds".

Type: CodeSet

Format

pattern	[A-Z]{3,3}
---------	------------

Rules

R2 ActiveCurrency ✓

The currency code must be a valid active currency code, not yet withdrawn on the day the message containing the currency is exchanged. Valid active currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and are not yet withdrawn on the day the message containing the Currency is exchanged.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00005
- *Error Text:* Invalid currency code

Used in attribute(s)

"CBPR_Amount" on page 263, "ActiveCurrencyAndAmount" on page 259, "CBPR_Amount__1" on page 264

Restricts

"ParentCurrencyCode" on page 286

6.3 ActiveOrHistoricCurrencyCode

Definition: A code allocated to a currency by a Maintenance Agency under an international identification scheme, as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds".

Type: CodeSet

Format

pattern	[A-Z]{3,3}
---------	------------

Rules

R15 ActiveOrHistoricCurrency ✓

The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00006
- *Error Text:* Invalid currency code.

Used in element(s)

"Currency" on page 49, "Currency" on page 52, "Currency" on page 55

Restricts

["ParentCurrencyCode" on page 286](#)

6.4 AddressType2Code

Definition: Specifies the type of address.

Type: CodeSet

Code	Name	Definition
ADDR	Postal	Address is the complete postal address.
BIZZ	Business	Address is the business address.
DLVY	DeliveryTo	Address is the address to which delivery is to take place.
HOME	Residential	Address is the home address.
MLTO	MailTo	Address is the address to which mail is sent.
PBOX	POBox	Address is a postal office (PO) box.

Used in element(s)

["Code" on page 25](#)

Restricts

["AddressTypeCode" on page 261](#)

6.5 AddressTypeCode

Definition: Specifies the type of address.

Type: CodeSet

Code	Name	Definition
ADDR	Postal	Address is the complete postal address.
BIZZ	Business	Address is the business address.
DLVY	DeliveryTo	Address is the address to which delivery is to take place.
HOME	Residential	Address is the home address.
MLTO	MailTo	Address is the address to which mail is sent.
PBOX	POBox	Address is a postal office (PO) box.

Is restricted by

["AddressType2Code" on page 261](#)

6.6 AmountDirectionCode

Definition: Specifies if an operation is an increase or a decrease or the result of a reversal operation.

Type: CodeSet

Code	Name	Definition
CRDT	Credit	Operation is an increase.
DBIT	Debit	Operation is a decrease.
RVCD	ReversalCredit	Debit entry used to reverse a previously booked credit entry.
RVDB	ReversalDebit	Credit entry used to reverse a previously booked debit entry.

Is restricted by

"CreditDebitCode" on page 272

6.7 AnyBICDec2014Identifier

Definition: Code allocated to a financial or non-financial institution by the ISO 9362 Registration Authority, as described in ISO 9362: 2014 - "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Type: IdentifierSet

Format

pattern [A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}([A-Z0-9]{3,3}){0,1}

Rules

R18 AnyBIC ✓

Only a valid Business identifier code is allowed. Business identifier codes for financial or non-financial institutions are registered and published by the ISO 9362 Registration Authority in the ISO directory of BICs, and consists of eight (8) or eleven (11) contiguous characters.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00008
- *Error Text:* Invalid BIC.

Used in element(s)

"AnyBIC" on page 163, "AnyBIC" on page 164, "AnyBIC" on page 165

6.8 BICFIDec2014Identifier

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362: 2014 - "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Type: IdentifierSet

Format

pattern [A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}([A-Z0-9]{3,3}){0,1}

Rules**R17 BICFI ✓**

Valid BICs for financial institutions are registered and published by the ISO 9362 Registration Authority in the ISO directory of BICs, and consist of eight (8) or eleven (11) contiguous characters.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00001
- *Error Text:* Invalid FI BIC.

Used in element(s)

"BICFI" on page 122, "BICFI" on page 119, "BICFI" on page 125, "BICFI" on page 129, "BICFI" on page 135, "BICFI" on page 139

6.9 CBPR_Amount

Definition:

This datatype has been created by the Publisher of this Usage Guideline.

Type: Amount

This data type must be used with the following XML Attributes:

Attribute	Tag	Datatype
Currency	Ccy	"ActiveCurrencyCode" on page 259

Format

fractionDigits 5
 minInclusive 0
 totalDigits 14

Rules**R1 CurrencyAmount**

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00007

- *Error Text:* Invalid currency code or too many decimal digits

6.10 CBPR_Amount__1

Definition:

Type: Amount

This data type must be used with the following XML Attributes:

Attribute	Tag	Datatype
Currency	Ccy	"ActiveCurrencyCode" on page 259

Format

fractionDigits	5
minInclusive	0
totalDigits	14

Rules

R21 CurrencyAmount

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00007
- *Error Text:* Invalid currency code or too many decimal digits

Used in element(s)

"Amount" on page 96, "Amount" on page 62, "Amount" on page 88, "TotalChargesAmount" on page 242, "TotalChargesAmount" on page 244

6.11 CBPR_Date

Definition: This Type restricts the base ISODate to YYYY (exactly 4 digits for the Year) and does not allow use of UTC offset or Zulu indicator with a date.

This datatype has been created by the Publisher of this Usage Guideline.

Type: Date

Format

pattern	[0-9]{4}-[0-9]{2}-[0-9]{2}
---------	----------------------------

Used in element(s)

"BirthDate" on page 117, "RequestedSettlementDate" on page 236

6.12 CBPR_DateTime

Definition: A particular point in the progression of time defined by a mandatory date and a mandatory time component, expressed in local time with UTC offset format (YYYY-MM-DDThh:mm:ss.sss+/-hh:mm-m).

This representation is defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Note on the time format:

1) beginning / end of calendar day

00:00:00 = the beginning of a calendar day

24:00:00 = the end of a calendar day

2) fractions of second in time format

Decimal fractions of seconds may be included. In this case, the involved parties shall agree on the maximum number of digits that are allowed.

Example: 2020-07-16T19:20:30.45+01:00

This datatype has been created by the Publisher of this Usage Guideline.

Type: DateTime

Format

pattern `.*(\+|-)((0[0-9]))(1[0-4])):[0-5][0-9]`

Used in element(s)

"CreationDate" on page 46, "CreationDateTime" on page 157, "DateTime" on page 115

6.13 CBPR_RestrictedFINXMax140Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 140 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength 140

minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,'+]+

Used in element(s)

"InstructionInformation" on page 163

6.14 CBPR_RestrictedFINXMax140Text_Extended

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 140 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . that is extended to support the following additional characters !#\$%&*='^_`{|}~";<>@[\\]

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	140
minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,'+ !#\$%&!*='^_`{ }~";<>@[\\]]+

Used in element(s)

"BuildingName" on page 218, "DistrictName" on page 221, "Name" on page 126, "Name" on page 130, "Name" on page 177, "Name" on page 139, "StreetName" on page 218, "TownName" on page 220

6.15 CBPR_RestrictedFINXMax16Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 16 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	16
minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,'+]+

Used in element(s)

"ChargesIdentification" on page 64, "InstructionIdentification" on page 254

6.16 CBPR_RestrictedFINXMax16Text_Extended

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 16 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . that is extended to support the following additional characters !#\$%&*='^_`{|}~";<>@[\\]

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	16
minLength	1
pattern	[0-9a-zA-Z/\-!\?:(\)\.,\'+ !#\$%&!*='^_`{ }\}~";<>@[\\]]+

Used in element(s)

["BuildingNumber" on page 195](#), ["BuildingNumber" on page 207](#), ["BuildingNumber" on page 218](#), ["BuildingNumber" on page 225](#), ["PostBox" on page 197](#), ["PostBox" on page 210](#), ["PostBox" on page 219](#), ["PostCode" on page 199](#), ["PostCode" on page 211](#), ["PostCode" on page 220](#)

6.17 CBPR_RestrictedFINXMax28Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 28 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	28
minLength	1
pattern	[0-9a-zA-Z/\-!\?:(\)\.,\'+]+

Used in element(s)

["MemberIdentification" on page 107](#)

6.18 CBPR_RestrictedFINXMax320Text_Extended

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 320 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . that is extended to support the following additional characters !#\$%&*='^_`{|}~";<>@[\\]

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	320
minLength	1
pattern	[0-9a-zA-Z/\-!\?:(\)\.,'+ !#\$%&!*^_`{ }\}~";<>@[\\]]+

Used in element(s)

["Identification" on page 230](#)

6.19 CBPR_RestrictedFINXMax34Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 34 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . and disable the use of slash "/" at the beginning and end of line and double slash "/" within the line.

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	34
minLength	1
pattern	(([0-9a-zA-Z/\-!\?:(\)\.,'+]([0-9a-zA-Z/\-!\?:(\)\.,'+])*([0-9a-zA-Z/\-!\?:(\)\.,'+])?*))

Used in element(s)

["Identification" on page 143](#)

6.20 CBPR_RestrictedFINXMax35Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 35 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	35
minLength	1
pattern	[0-9a-zA-Z/\-!\?:(\)\.,'+]+

Used in element(s)

["AccountOwnerTransactionIdentification" on page 250](#), ["AccountOwnerTransactionIdentification" on page 257](#), ["AccountServicerReference" on page 246](#), ["AccountServicerReference" on page 253](#), ["AccountServicerTransactionIdentification" on page 250](#), ["AccountServicerTransactionIdentification" on](#)

page 257, "BusinessMessageIdentifier" on page 44, "BusinessService" on page 45, "ChargesIdentification" on page 94, "ChargesIdentification" on page 81, "ChequeNumber" on page 249, "ChequeNumber" on page 256, "ClearingSystemReference" on page 249, "EndToEndIdentification" on page 247, "EndToEndIdentification" on page 255, "Identification" on page 152, "Identification" on page 155, "InstructionIdentification" on page 247, "Issuer" on page 145, "Issuer" on page 146, "Issuer" on page 153, "Issuer" on page 156, "MandatIdentification" on page 249, "MandatIdentification" on page 256, "MarketInfrastructureTransactionIdentification" on page 251, "MessageDefinitionIdentifier" on page 45, "MessageIdentification" on page 157, "MessageIdentification" on page 245, "MessageIdentification" on page 253, "MessageNameIdentification" on page 246, "MessageNameIdentification" on page 253, "PaymentInformationIdentification" on page 246, "PaymentInformationIdentification" on page 254, "ProcessingIdentification" on page 251, "ProcessingIdentification" on page 258, "Proprietary" on page 23, "Proprietary" on page 57, "Proprietary" on page 233, "RecordIdentification" on page 94, "RecordIdentification" on page 70, "TransactionIdentification" on page 248, "TransactionIdentification" on page 255

6.21 CBPR_RestrictedFINXMax35Text_Extended

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 35 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . that is extended to support the following additional characters !#\$%&*='^_`{|}~";<>@[\\]

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	35
minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,'\+ !#\$%&!*='^_`{ }~";<>@[\\]]+

Used in element(s)

"AddressLine" on page 215, "AddressLine" on page 228, "BuildingName" on page 196, "BuildingName" on page 208, "BuildingName" on page 225, "CityOfBirth" on page 117, "CountrySubDivision" on page 201, "CountrySubDivision" on page 214, "CountrySubDivision" on page 221, "CountrySubDivision" on page 227, "DistrictName" on page 201, "DistrictName" on page 213, "DistrictName" on page 227, "ProvinceOfBirth" on page 117, "TownLocationName" on page 200, "TownLocationName" on page 212, "TownLocationName" on page 221, "TownLocationName" on page 227, "TownName" on page 199, "TownName" on page 212, "TownName" on page 226

6.22 CBPR_RestrictedFINXMax70Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 70 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	70
-----------	----

minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,'+]+

Used in element(s)

["Name" on page 52](#), ["Name" on page 55](#)

6.23 CBPR_RestrictedFINXMax70Text_Extended

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 70 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . that is extended to support the following additional characters !#\$%&*='^_`{|}~";<>@[\\]

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	70
minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,'+ !#\$%&!*='^_`{ }~";<>@[\\]]+

Used in element(s)

["AddressLine" on page 203](#), ["AddressLine" on page 222](#), ["Department" on page 193](#), ["Department" on page 205](#), ["Department" on page 217](#), ["Department" on page 224](#), ["Floor" on page 196](#), ["Floor" on page 209](#), ["Floor" on page 219](#), ["Floor" on page 225](#), ["Room" on page 198](#), ["Room" on page 210](#), ["Room" on page 220](#), ["Room" on page 226](#), ["StreetName" on page 194](#), ["StreetName" on page 207](#), ["StreetName" on page 224](#), ["SubDepartment" on page 194](#), ["SubDepartment" on page 206](#), ["SubDepartment" on page 218](#), ["SubDepartment" on page 224](#)

6.24 CopyDuplicate1Code

Definition: Specifies if this document is a copy, a duplicate, or a duplicate of a copy.

Type: CodeSet

Code	Name	Definition
CODU	CopyDuplicate	Message is being sent as a copy to a party other than the account owner, for information purposes and the message is a duplicate of a message previously sent.
COPY	Copy	Message is being sent as a copy to a party other than the account owner, for information purposes.
DUPL	Duplicate	Message is for information/confirmation purposes. It is a duplicate of a message previously sent.

Used in element(s)

["CopyDuplicate" on page 46](#)

Restricts

["CopyDuplicateCode" on page 271](#)

6.25 CopyDuplicateCode

Definition: Specifies if this document is a copy, a duplicate, or a duplicate of a copy.

Type: CodeSet

Code	Name	Definition
CODU	CopyDuplicate	Message is being sent as a copy to a party other than the account owner, for information purposes and the message is a duplicate of a message previously sent.
COPY	Copy	Message is being sent as a copy to a party other than the account owner, for information purposes.
DUPL	Duplicate	Message is for information/confirmation purposes. It is a duplicate of a message previously sent.

Is restricted by

["CopyDuplicate1Code" on page 270](#)

6.26 CountryCode

Definition: Code to identify a country, a dependency, or another area of particular geopolitical interest, on the basis of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

Type: CodeSet

Format

pattern [A-Z]{2,2}

Rules**R16 Country ✓**

The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00004
- *Error Text:* Invalid Country Code.

Used in element(s)

["Country" on page 187](#), ["Country" on page 191](#), ["Country" on page 202](#), ["Country" on page 214](#), ["Country" on page 221](#), ["Country" on page 227](#), ["CountryOfBirth" on page 116](#), ["CountryOfBirth" on page 117](#), ["CountryOfResidence" on page 173](#), ["CountryOfResidence" on page 176](#), ["CountryOfResidence" on page 179](#)

6.27 CreditDebitCode

Definition: Specifies if an operation is an increase or a decrease.

Type: CodeSet

Code	Name	Definition
CRDT	Credit	Operation is an increase. Usage Guideline restrictions for this code • This code(camt.106.001.03/Group-Header/TotalCharges/CreditDebitIndicator/Credit) is removed. • This code(camt.106.001.03/Charges/PerTransaction/Record/ChargesBreakdown/CreditDebitIndicator/Credit) is removed. • This code(camt.106.001.03/Charges/PerTransaction/Record/TotalChargesPerRecord/CreditDebitIndicator/Credit) is removed.
DBIT	Debit	Operation is a decrease.

Used in element(s)

["CreditDebitIndicator" on page 241](#), ["CreditDebitIndicator" on page 243](#), ["CreditDebitIndicator" on page 97](#), ["CreditDebitIndicator" on page 244](#), ["CreditDebitIndicator" on page 62](#), ["CreditDebitIndicator" on page 88](#)

Restricts

["AmountDirectionCode" on page 261](#)

6.28 DecimalNumber

Definition: Number of objects represented as a decimal number, for example 0.75 or 45.6.

Type: Quantity

Format

fractionDigits	17
totalDigits	18

Used in element(s)

["ControlSum" on page 241](#), ["ControlSum" on page 242](#), ["ControlSum" on page 243](#)

6.29 Exact4AlphaNumericText

Definition: Specifies an alphanumeric string with a length of 4 characters.

Type: Text

Format

pattern	[a-zA-Z0-9]{4}
---------	----------------

Used in element(s)

["Identification" on page 149](#)

6.30 ExternalAccountIdentification1Code

Definition: Specifies the external account identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

["Code" on page 23](#), ["Code" on page 23](#)

Restricts

["ExternalAccountIdentificationCode" on page 273](#)

6.31 ExternalAccountIdentificationCode

Definition: Specifies the external account identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalAccountIdentification1Code" on page 273

6.32 ExternalCashAccountType1Code

Definition: Specifies the nature, or use, of the cash account in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 56, "Code" on page 57

Restricts

"ExternalCashAccountTypeCode" on page 274

6.33 ExternalCashAccountTypeCode

Definition: Specifies the nature, or use, of the cash account in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalCashAccountType1Code" on page 274

6.34 ExternalChargeType1Code

Definition: Specifies the nature, or use, of the charges in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 58

Restricts

"ExternalChargeTypeCode" on page 275

6.35 ExternalChargeTypeCode

Definition: Specifies the nature, or use, of the charges in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code set published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalChargeType1Code" on page 275

6.36 ExternalClearingSystemIdentification1Code

Definition: Specifies the clearing system identification code, as published in an external clearing system identification code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	5
minLength	1

Used in element(s)

"Code" on page 103

Restricts

"ExternalClearingSystemIdentificationCode" on page 276

6.37 ExternalClearingSystemIdentificationCode

Definition: Specifies the clearing system identification code, as published in an external clearing system identification code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	5
minLength	1

Is restricted by

"ExternalClearingSystemIdentification1Code" on page 275

6.38 ExternalFinancialInstitutionIdentification1Code

Definition: Specifies the external financial institution identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 118

Restricts

"ExternalFinancialInstitutionIdentificationCode" on page 277

6.39 ExternalFinancialInstitutionIdentificationCode

Definition: Specifies the external financial institution identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalFinancialInstitutionIdentification1Code" on page 276

6.40 ExternalInstructedAgentInstruction1Code

Definition: Specifies further instructions concerning the processing of a payment instruction or adjustment, as provided to the instructed agent.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 162, "Code" on page 162

Restricts

"ExternalInstructedAgentInstructionCode" on page 277

6.41 ExternalInstructedAgentInstructionCode

Definition: Specifies further instructions concerning the processing of a payment instruction or adjustment, as provided to the instructed agent.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalInstructedAgentInstruction1Code" on page 277

6.42 ExternalOrganisationIdentification1Code

Definition: Specifies the external organisation identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 166

Restricts

"ExternalOrganisationIdentificationCode" on page 278

6.43 ExternalOrganisationIdentificationCode

Definition: Specifies the external organisation identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalOrganisationIdentification1Code" on page 278

6.44 ExternalPersonIdentification1Code

Definition: Specifies the external person identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

["Code" on page 183](#)

Restricts

["ExternalPersonIdentificationCode" on page 279](#)

6.45 ExternalPersonIdentificationCode

Definition: Specifies the external person identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

["ExternalPersonIdentification1Code" on page 278](#)

6.46 ExternalProxyAccountType1Code

Definition: Specifies the external proxy account type code, as published in the proxy account type external code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

["Code" on page 232](#), ["Code" on page 232](#)

Restricts

["ExternalProxyAccountTypeCode" on page 280](#)

6.47 ExternalProxyAccountTypeCode

Definition: Specifies the external proxy account type code, as published in the proxy account type external code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalProxyAccountType1Code" on page 279

6.48 IBAN2007Identifier

Definition: The International Bank Account Number is a code used internationally by financial institutions to uniquely identify the account of a customer at a financial institution as described in the 2007 edition of the ISO 13616 standard "Banking and related financial services - International Bank Account Number (IBAN)" and replaced by the more recent edition of the standard.

Type: IdentifierSet

Format

pattern	[A-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}
---------	---------------------------------------

Rules

R13 IBAN ✓

A valid IBAN consists of all three of the following components: Country Code, check digits and BBAN.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00003
- *Error Text:* Invalid IBAN format or invalid check digits.

Used in element(s)

"IBAN" on page 20, "IBAN" on page 21, "IBAN" on page 22

6.49 ISODate

Definition: A particular point in the progression of time in a calendar year expressed in the YYYY-MM-DD format. This representation is defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Type: Date

Used in element(s)

["BirthDate" on page 116](#), ["Date" on page 115](#), ["RequestedSettlementDate" on page 234](#)

6.50 ISODateTime

Definition: A particular point in the progression of time defined by a mandatory date and a mandatory time component, expressed in either UTC time format (YYYY-MM-DDThh:mm:ss.sssZ), local time with UTC offset format (YYYY-MM-DDThh:mm:ss.sss+/-hh:mm), or local time format (YYYY-MM-DDThh:mm:ss.sss). These representations are defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Note on the time format:

1) beginning / end of calendar day

00:00:00 = the beginning of a calendar day

24:00:00 = the end of a calendar day

2) fractions of second in time format

Decimal fractions of seconds may be included. In this case, the involved parties shall agree on the maximum number of digits that are allowed.

Type: DateTime

6.51 LEIIdentifier

Definition: Legal Entity Identifier is a code allocated to a party as described in ISO 17442 "Financial Services - Legal Entity Identifier (LEI)".

Type: IdentifierSet

Format

pattern	[A-Z0-9]{18,18}[0-9]{2,2}
---------	---------------------------

Used in element(s)

["LEI" on page 40](#), ["LEI" on page 41](#), ["LEI" on page 123](#), ["LEI" on page 163](#), ["LEI" on page 164](#), ["LEI" on page 120](#), ["LEI" on page 125](#), ["LEI" on page 129](#), ["LEI" on page 136](#), ["LEI" on page 165](#), ["LEI" on page 139](#)

6.52 Max128Text

Definition: Specifies a character string with a maximum length of 128 characters.

Type: Text

Format

maxLength	128
minLength	1

Used in element(s)

["Identification" on page 167](#)

6.53 Max140Text

Definition: Specifies a character string with a maximum length of 140 characters.

Type: Text

Format

maxLength	140
minLength	1

Used in element(s)

["AdditionalInformation" on page 102](#), ["AdditionalInformation" on page 69](#), ["AdditionalInformation" on page 80](#), ["AdditionalInformation" on page 85](#), ["AdditionalInformation" on page 93](#), ["BuildingName" on page 189](#), ["CareOf" on page 188](#), ["CareOf" on page 193](#), ["CareOf" on page 205](#), ["CareOf" on page 217](#), ["CareOf" on page 223](#), ["DistrictName" on page 191](#), ["InstructionInformation" on page 162](#), ["Name" on page 40](#), ["Name" on page 42](#), ["Name" on page 110](#), ["Name" on page 112](#), ["Name" on page 123](#), ["Name" on page 172](#), ["Name" on page 174](#), ["Name" on page 120](#), ["Name" on page 136](#), ["StreetName" on page 189](#), ["TownLocationName" on page 190](#), ["TownName" on page 190](#)

6.54 Max15NumericText

Definition: Specifies a numeric string with a maximum length of 15 digits.

Type: Text

Format

pattern	[0-9]{1,15}
---------	-------------

Used in element(s)

["NumberOfChargesBreakdownItems" on page 243](#), ["NumberOfChargesRecords" on page 241](#), ["NumberOfChargesRecords" on page 242](#)

6.55 Max16Text

Definition: Specifies a character string with a maximum length of 16 characters.

Type: Text

Format

maxLength	16
minLength	1

Used in element(s)

["BuildingNumber" on page 185](#), ["BuildingNumber" on page 189](#), ["PostBox" on page 186](#), ["PostBox" on page 190](#), ["PostBox" on page 226](#), ["PostCode" on page 186](#), ["PostCode" on page 190](#), ["PostCode" on](#)

[page 226](#), ["UnitNumber" on page 190](#), ["UnitNumber" on page 197](#), ["UnitNumber" on page 209](#), ["Unit-Number" on page 219](#), ["UnitNumber" on page 225](#)

6.56 Max2048Text

Definition: Specifies a character string with a maximum length of 2048 characters.

Type: Text

Format

maxLength	2048
minLength	1

Used in element(s)

["EmailAddress" on page 113](#), ["Identification" on page 161](#), ["Identification" on page 229](#), ["URLAddress" on page 110](#)

6.57 Max256Text

Definition: Specifies a character string with a maximum length of 256 characters.

Type: Text

Format

maxLength	256
minLength	1

Used in element(s)

["EmailAddress" on page 110](#), ["Identification" on page 151](#), ["Identification" on page 154](#)

6.58 Max34Text

Definition: Specifies a character string with a maximum length of 34 characters.

Type: Text

Format

maxLength	34
minLength	1

Used in element(s)

["Identification" on page 142](#), ["Identification" on page 146](#)

6.59 Max350Text

Definition: Specifies a character string with a maximum length of 350 characters.

Type: Text

Format

maxLength	350
minLength	1

Used in element(s)

"PlaceAndName" on page 240, "Registry" on page 161

6.60 Max35Text

Definition: Specifies a character string with a maximum length of 35 characters.

Type: Text

Format

maxLength	35
minLength	1

Used in element(s)

"BuildingName" on page 185, "CityOfBirth" on page 116, "ClearingSystemReference" on page 256, "CountrySubDivision" on page 187, "CountrySubDivision" on page 191, "DistrictName" on page 187, "EmailPurpose" on page 111, "EmailPurpose" on page 113, "Identification" on page 40, "Identification" on page 41, "Identification" on page 147, "Identification" on page 148, "Identification" on page 150, "Identification" on page 153, "Issuer" on page 143, "Issuer" on page 148, "Issuer" on page 148, "Issuer" on page 149, "Issuer" on page 150, "Issuer" on page 151, "Issuer" on page 154, "Issuer" on page 155, "JobTitle" on page 111, "JobTitle" on page 113, "MarketInfrastructureTransaction-Identification" on page 257, "MemberIdentification" on page 105, "Proprietary" on page 23, "Proprietary" on page 56, "Proprietary" on page 103, "Proprietary" on page 118, "Proprietary" on page 166, "Proprietary" on page 184, "Proprietary" on page 232, "ProvinceOfBirth" on page 116, "RecordIdentification" on page 86, "Reference" on page 228, "Responsibility" on page 111, "Responsibility" on page 114, "SchemeName" on page 149, "TownLocationName" on page 186, "TownName" on page 186, "Type" on page 228

6.61 Max4Text

Definition: Specifies a character string with a maximum length of 4 characters.

Type: Text

Format

maxLength	4
minLength	1

Used in element(s)

"ChannelType" on page 167

6.62 Max70Text

Definition: Specifies a character string with a maximum length of 70characters.

Type: Text

Format

maxLength	70
minLength	1

Used in element(s)

"AddressLine" on page 187, "AddressLine" on page 191, "Department" on page 111, "Department" on page 114, "Department" on page 185, "Department" on page 189, "Floor" on page 186, "Floor" on page 189, "Name" on page 49, "Room" on page 186, "Room" on page 190, "StreetName" on page 185, "SubDepartment" on page 185, "SubDepartment" on page 189

6.63 NamePrefix2Code

Definition: Specifies the terms used to formally address a person.

Type: CodeSet

Code	Name	Definition
DOCT	Doctor	Title of the person is Doctor or Dr.
MADM	Madam	Title of the person is Madam.
MIKS	GenderNeutral	Title of the person is gender neutral (Mx).
MISS	Miss	Title of the person is Miss.
MIST	Mister	Title of the person is Mister or Mr.

Used in element(s)

"NamePrefix" on page 109, "NamePrefix" on page 112

Restricts

"NamePrefixCode" on page 285

6.64 NamePrefixCode

Definition: Specifies the terms used to formally address a person.

Type: CodeSet

Code	Name	Definition
DOCT	Doctor	Title of the person is Doctor or Dr.
MADM	Madam	Title of the person is Madam.
MIKS	GenderNeutral	Title of the person is gender neutral (Mx).

Code	Name	Definition
MISS	Miss	Title of the person is Miss.
MIST	Mister	Title of the person is Mister or Mr.

Is restricted by

["NamePrefix2Code" on page 285](#)

6.65 ParentCurrencyCode

Definition: Code allocated to a currency, by a maintenance agency, under an international identification scheme as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds". Valid currency codes are registered with the ISO 4217 Maintenance Agency, and consist of three contiguous letters.

Type: CodeSet

Format

pattern [A-Z]{3,3}

Is restricted by

["ActiveCurrencyCode" on page 259](#), ["ActiveOrHistoricCurrencyCode" on page 260](#)

6.66 PhoneNumber

Definition: The collection of information which identifies a specific phone or FAX number as defined by telecom services.

It consists of a "+" followed by the country code (from 1 to 3 characters) then a "-" and finally, any combination of numbers, "(", ")", "+", and "-" (up to 30 characters).

Type: Text

Format

pattern \+[0-9]{1,3}-[0-9()+\-]{1,30}

Used in element(s)

["FaxNumber" on page 110](#), ["FaxNumber" on page 113](#), ["MobileNumber" on page 110](#), ["MobileNumber" on page 113](#), ["PhoneNumber" on page 110](#), ["PhoneNumber" on page 113](#)

6.67 PreferredContactMethod1Code

Definition: Preferred method used to reach the individual contact within an organisation.

Type: CodeSet

Code	Name	Definition
CELL	MobileOrCellPhone	Preferred method used to reach the contact is per mobile or cell phone.

Code	Name	Definition
FAXX	Fax	Preferred method used to reach the contact is per fax.
LETT	Letter	Preferred method used to reach the contact is per letter.
MAIL	Email	Preferred method used to reach the contact is per email.
PHON	Phone	Preferred method used to reach the contact is per phone.

Used in element(s)

["PreferredMethod" on page 114](#)

Restricts

["PreferredContactMethodCode" on page 287](#)

6.68 PreferredContactMethod2Code

Definition: Preferred method used to reach the individual contact within an organisation.

Type: CodeSet

Code	Name	Definition
CELL	MobileOrCellPhone	Preferred method used to reach the contact is per mobile or cell phone.
FAXX	Fax	Preferred method used to reach the contact is per fax.
LETT	Letter	Preferred method used to reach the contact is per letter.
MAIL	Email	Preferred method used to reach the contact is per email.
ONLI	Online	Preferred method used to reach the contact is online.
PHON	Phone	Preferred method used to reach the contact is per phone.

Used in element(s)

["PreferredMethod" on page 111](#)

Restricts

["PreferredContactMethodCode" on page 287](#)

6.69 PreferredContactMethodCode

Definition: Preferred method used to reach the individual contact within an organisation.

Type: CodeSet

Code	Name	Definition
CELL	MobileOrCellPhone	Preferred method used to reach the contact is per mobile or cell phone.
FAXX	Fax	Preferred method used to reach the contact is per fax.
LETT	Letter	Preferred method used to reach the contact is per letter.
MAIL	Email	Preferred method used to reach the contact is per email.
ONLI	Online	Preferred method used to reach the contact is online.
PHON	Phone	Preferred method used to reach the contact is per phone.

Is restricted by

"PreferredContactMethod1Code" on page 286, "PreferredContactMethod2Code" on page 287

6.70 Priority2Code

Definition: Specifies the priority level of an event.

Type: CodeSet

Code	Name	Definition
HIGH	High	Priority level is high.
NORM	Normal	Priority level is normal.

Used in element(s)

"Priority" on page 47

Restricts

"PriorityCode" on page 288

6.71 PriorityCode

Definition: Specifies the priority level of an event.

Type: CodeSet

Code	Name	Definition
HIGH	High	Priority level is high.
LOWW	Low	Priority level is low.
NORM	Normal	Priority level is normal.
URGT	Urgent	Priority level is urgent (highest priority possible).

Is restricted by

["Priority2Code" on page 288](#)

6.72 UUIDv4Identifier

Definition: Universally Unique Identifier (UUID) version 4, as described in IETF RFC 4122 "Universally Unique Identifier (UUID) URN Namespace".

Type: IdentifierSet

Format

pattern [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}

Used in element(s)

["UETR" on page 248](#), ["UETR" on page 255](#)

6.73 UnicodeChartsCode

*Definition:*odelist containing the names of the UNICODE code block name as specified on <http://unicode.org/Public/UNIDATA/Blocks.txt>.

Type: CodeSet

Rules

R4 ValidationByTable

Error handling: Undefined

Used in element(s)

["CharacterSet" on page 43](#)

6.74 YesNoIndicator

Definition: Indicates a "Yes" or "No" type of answer for an element.

Type: Indicator

Meaning When True: Yes

Meaning When False: No

Used in element(s)

["PossibleDuplicate" on page 46](#)

Legal Notices

Copyright

S.W.I.F.T. SC © 2026. All rights reserved.

This material is a component of MyStandards, the Swift collaborative Web application used to manage standards definitions and industry usage. It can only be used and distributed in accordance with MyStandards Terms of Use.

Unless otherwise agreed in writing with S.W.I.F.T. SC, you have no right to:

- authorise external end users to use this component for other purposes than their internal use.
- remove, alter, cover, obfuscate or cancel from view any copyright or other proprietary rights notices appearing in this physical medium.
- re-sell or authorise another party e.g. software and service providers, to re-sell this component.

Confidentiality

This publication may contain Swift or third-party confidential information. Only disclose it outside your organisation in accordance with MyStandards Terms of Use and your related license rights.

This component is provided 'AS IS'. Swift does not give and excludes any express or implied warranties with respect to this component such as but not limited to any guarantee as to its quality, supply or availability.

Any and all rights, including title, ownership rights, copyright, trademark, patents, and any other intellectual property rights of whatever nature in this component will remain the exclusive property of Swift or its licensors.

Trademarks and Patents

Swift is the trade name of S.W.I.F.T. SC. The following are registered trademarks of Swift: 3SKey, Innotribe, MyStandards, Sibos, Swift, SwiftNet, the Standards Forum logo, the Swift logo, Swift GPI with logo, the Swift GPI logo, and UETR. Other product, service, or company names in this publication are trade names, trademarks, or registered trademarks of their respective owners.