



Usage Guideline

CBPRPlus-camt.109.001.01_Cheque-CancellationOrStopReport

CBPRPlus SR2026 (Combined)

This document describes a usage guideline restricting the base message **MX camt.109.001.01**. You can also consult [this information online](#).

Published by Cross Border Payments and Reporting Plus (CBPR+) and generated by [MyStandards](#).

20 February 2026

Table of Contents

Message Functionality	3
1 Restriction summary	5
2 Structure	6
3 ISO 20022 Rules	8
4 Message Building Blocks	9
5 Message Components	17
6 Message Datatypes	105
Legal Notices	132

Message Functionality

This Usage Guideline is based on the camt.109.001.01 message definition. In addition, Cross Border Payments and Reporting Plus (CBPR+) has defined usage of BusinessApplicationHeaderV02 as mandatory. The following section will be dealing with the camt.109.001.01 only.

Overview

Principles:

1A) AGENTS IDENTIFICATION - Textual Rules

-> If BICFI is present, then (Name & Postal Address) is NOT allowed (ClearingSystemMemberIdentification and LEI may complement) - However, in case of conflicting information, the BICFI will always take precedence.

-> If BICFI is absent, (Name & Postal Address) OR [(Name & Postal Address) and ClearingSystemMemberIdentification] must be present.

Exception: If BICFI is absent, whenever Debtor Agent, Creditor Agent and all agents in between are located within the same country, the clearing code only may be used.

1B. PARTY IDENTIFICATION - Textual Rules

-> If AnyBIC is present, then (Name and Postal Address) is NOT allowed (other elements remain optional) - However, in case of conflicting information, AnyBIC will always take precedence.

-> If Name is present, it is recommended to use Postal Address.

2) Character Set:

All proprietary and Text fields EXCLUDING Name and Address for all actors and Related Remittance Information and Remittance are limited to the FIN-X-Character set.

All Name and Address for all actors, Related Remittance Information and Remittance Information (structured and unstructured), Email Address where included as part of a proxy element are extended to support the following additional characters:

!#\$%&*='^_`{|}~";<>@[\]

< is replaced with <

> is replaced with >

Collection Description

This is the Cross Border Payment and Reporting Collection for SR2026.

These are FINAL usage guidelines.

The usage guidelines are available on the CBPR+ SR2026 Readiness Portal for testing.

The Collection contains:

30 Usage Guidelines that will be live on the network as of November 2026.

Outline

The CBPRPlus SR2026 (Combined) / CBPRPlus-camt.109.001.01_ChequeCancellationOrStopReport message is composed of 3 building blocks

a. GroupHeader

Set of characteristics shared by all individual cheques included in the message.

b. Cheque

Specifies the details of the cheque.

c. SupplementaryData

Additional information that cannot be captured in the structured elements and/or any other specific block.

1 Restriction summary

This Usage Guideline restricts the camt.109.001.01 message. This also includes the BusinessApplicationHeaderV02.

Restriction Type	See page
Removed elements	12, 13, 16, 22, 24, 24, 24, 24, 30, 30, 42, 43, 45, 45, 45, 45, 51, 57, 58, 58, 58, 58, 59, 59, 59, 59, 60, 60, 60, 60, 71, 73, 73, 73, 73, 76, 78, 78, 78, 78, 80, 80, 80, 80, 85, 89, 94, 94
Make mandatory	11, 38, 46, 46, 46, 46, 46, 57, 57, 57, 58, 66, 69, 72, 72, 72, 72, 83, 84, 98, 98, 99, 99, 101
Reduce Multiplicity	14, 16, 74, 88, 100, 100
Ignore	n.a.
Text rules	14, 28, 28, 29, 38, 40, 40, 40, 44, 56, 84
Conditional rules	n.a.
Formal rules	9, 15, 22, 38, 70
Fixed values	11, 11
Truncates	n.a.
Comments	n.a.
Annotations	n.a.
Changed datatypes	10, 12, 13, 20, 28, 28, 29, 29, 30, 35, 36, 37, 38, 38, 39, 39, 39, 43, 44, 47, 47, 47, 47, 47, 50, 52, 53, 53, 55, 62, 62, 66, 67, 68, 69, 70, 70, 76, 83, 89, 94, 94, 95, 95, 95, 95, 95, 96, 96, 96, 96, 96, 97, 97, 97, 97, 98, 98, 98, 98, 98, 98, 99, 99, 100, 100, 102, 103
Extensions	n.a.
Synonyms	n.a.

2 Structure

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	<i>BusinessApplicationHeaderV02</i>	<AppHdr>		[1..1]		
	CharacterSet	<CharSet>		[0..1]		9
	From	<Fr>		[1..1]		9
	OrganisationIdentification	<OrgId>	{Or	[1..1]		79
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		80
	To	<To>		[1..1]		10
	OrganisationIdentification	<OrgId>	{Or	[1..1]		79
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		80
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]		10
	MessageDefinitionIdentifier	<MsgDefIdr>		[1..1]		10
	BusinessService	<BizSvc>		[0..1]		11
	MarketPractice	<MktPrctc>		[0..1]		11
	Registry	<Regy>		[1..1]		71
	Identification	<Id>		[1..1]		71
	CreationDate	<CreDt>		[1..1]		12
	BusinessProcessingDate	<BizPrctgDt>		[0..1]		12
	CopyDuplicate	<CpyDplct>		[0..1]		12
	PossibleDuplicate	<PssblDplct>		[0..1]		12
	Priority	<Prty>		[0..1]		13
	Signature	<Sgntr>		[0..1]		13
	Related	<Rltd>		[0..*]	R[0..1]	13
	CharacterSet	<CharSet>		[0..1]		26
	From	<Fr>		[1..1]		26
	To	<To>		[1..1]		27
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]		27
	MessageDefinitionIdentifier	<MsgDefIdr>		[1..1]		28
	BusinessService	<BizSvc>		[0..1]		28
	CreationDate	<CreDt>		[1..1]		29

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CopyDuplicate	<CpyDplct>		[0..1]		29
	PossibleDuplicate	<PssblDplct>		[0..1]		29
	Priority	<Prty>		[0..1]		30
	Signature	<Sgntr>		[0..1]		30
	<i>ChequeCancellationOrStopReportV01</i>	<ChqCxlOrStopRpt>		[1..1]		14
	GroupHeader	<GrpHdr>		[1..1]		15
	MessageIdentification	<MsgId>		[1..1]		69
	CreationDateTime	<CreDtTm>		[1..1]		70
	NumberOfCheques	<NbOfChqs>		[1..1]		70
	ControlSum	<CtrlSum>		[0..1]		70
	Cheque	<Chq>		[1..*]	R[1..1]	15
	InstructionIdentification	<InstrId>		[0..1]		37
	OriginalInstructionIdentification	<OrgnlInstrId>		[0..1]	 	38
	ChequeNumber	<ChqNb>		[1..1]		38
	IssueDate	<IssDt>		[1..1]		38
	StaleDate	<StlDt>		[0..1]		39
	Amount	<Amt>		[1..1]		39
	EffectiveDate	<FctvDt>		[0..1]		39
	DrawerAgent	<DrwrAgt>		[0..1]		40
	DrawerAgentAccount	<DrwrAgtAcct>		[0..1]		40
	Payee	<Pyee>		[0..1]		41
	PayeeAccount	<PyeeAcct>		[0..1]		41
	ChequeCancellationOrStopStatus	<ChqCxlOrStopSts>		[1..1]		42
	SupplementaryData	<SplmtryData>		[0..*]		16
	PlaceAndName	<PlcAndNm>		[0..1]		104
	Envelope	<Envlp>		[1..1]		104

3 ISO 20022 Rules

R3 RelatedPresentWhenCopyDupl ✓

Related MUST contain the relevant BusinessMessageHeader elements of the BusinessMessage to which this BusinessMessage relates.

If CopyDuplicate is present, then Related MUST be present.

Error handling:

- *Error severity:* Warning
- *Error Code:* H00001
- *Error Text:* Element Related is missing

4 Message Building Blocks

Note The following chapter identifies the building blocks of the CBPRPlus SR2026 (Combined) / CBPRPlus-camt.109.001.01_ChequeCancellationOrStopReport message definition.

Usage Guideline on Root Node

- on camt.109.001.01/fullmessage

- **CBPR_BusinessMessageIdentifier_FormalRule:**

The Business Message Identifier must match the Message Identification in the Group Header.

For each [Full Message], every occurrence of [Full Message/BusinessApplication-HeaderV02/BusinessMessageIdentifier] value must be equal to every occurrence of [Full Message/Document/ChequeCancellationOrStopReportV01/GroupHeader/MessageIdentification] value

4.1 Header Building Blocks

Note The following chapter identifies the building blocks of the BusinessApplicationHeaderV02 definition.

4.1.1 CharSet

XML Tag: CharSet

Presence: [0..1]

Definition: Contains the character set of the text-based elements used in the Business Message.

Datatype: ["UnicodeChartsCode" on page 131](#)

4.1.2 From

XML Tag: Fr

Presence: [1..1]

Definition: The sending MessagingEndpoint that has created this Business Message for the receiving MessagingEndpoint that will process this Business Message.

Note the sending MessagingEndpoint might be different from the sending address potentially contained in the transport header (as defined in the transport layer).

The **Fr** block contains the following elements (see datatype ["Party44Choice__1" on page 79](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		79
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		80

4.1.3 To

XML Tag: To

Presence: [1..1]

Definition: The MessagingEndpoint designated by the sending MessagingEndpoint to be the recipient who will ultimately process this Business Message.

Note the receiving MessagingEndpoint might be different from the receiving address potentially contained in the transport header (as defined in the transport layer).

The **To** block contains the following elements (see datatype "[Party44Choice__1](#)" on page 79 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		79
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		80

4.1.4 BusinessMessageIdentifier

XML Tag: BizMsgIdr

Presence: [1..1]

Definition: Unambiguously identifies the Business Message to the MessagingEndpoint that has created the Business Message.

Datatype: "[CBPR_RestrictedFINXMax35Text](#)" on page 113

Usage Guideline details

- on [camt.109.001.01/header/BusinessMessageIdentifier](#)
Type changed to: [CBPR_RestrictedFINXMax35Text](#) on page 113

4.1.5 MessageDefinitionIdentifier

XML Tag: MsgDefIdr

Presence: [1..1]

Definition: Contains the MessageIdentifier that defines the BusinessMessage.

It must contain a MessageIdentifier published on the ISO 20022 website.

example camt.001.001.03.

Datatype: "Max35Text" on page 127

Usage Guideline details

- on camt.109.001.01/.header/MessageDefinitionIdentifier
Single value: camt.109.001.01

4.1.6 BusinessService

XML Tag: BizSvc

Presence: [0..1]

Definition: Specifies the business service agreed between the two MessagingEndpoints under which rules this Business Message is exchanged.

To be used when there is a choice of processing services or processing service levels.

Example: E&I.

Datatype: "Max35Text" on page 127

Usage Guideline details

- on camt.109.001.01/.header/BusinessService
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.109.001.01/.header/BusinessService
Single value: swift.cbprplus.04

4.1.7 MarketPractice

XML Tag: MktPrctc

Presence: [0..1]

Definition: Specifies the market practice to which the message conforms. The market practices are a set of rules agreed between parties that restricts the usage of the messages in order to achieve better STP (Straight Through Processing) rates.

A market practice specification may also extend the underlying message specification by using extensions or supplementary data of this underlying message.

The **MktPrctc** block contains the following elements (see datatype "[ImplementationSpecification1](#)" on page 71 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Registry	<Regy>		[1..1]		71
	Identification	<Id>		[1..1]		71

4.1.8 CreationDate

XML Tag: CreDt

Presence: [1..1]

Definition: Date and time when this Business Message (header) was created.

Datatype: "CBPR_DateTime" on page 109

Usage Guideline details

- **on camt.109.001.01/.header/CreationDate**
Type changed to: CBPR_DateTime on page 109

4.1.9 BusinessProcessingDate

XML Tag: BizPrcgDt

Presence: [0..1]

Definition: Processing date and time indicated by the sender for the receiver of the business message. This date may be different from the date and time provided in the CreationDate.

Usage: Market practice or bilateral agreement should specify how this element should be used.

Datatype: "ISODatetime" on page 124

Usage Guideline details

- **This element(camt.109.001.01/.header/BusinessProcessingDate) is removed.**

4.1.10 CopyDuplicate

XML Tag: CpyDplct

Presence: [0..1]

Definition: Indicates whether the message is a Copy, a Duplicate or a copy of a duplicate of a previously sent ISO 20022 Message.

Datatype: "CopyDuplicate1Code" on page 115

4.1.11 PossibleDuplicate

XML Tag: PssblDplct

Presence: [0..1]

Definition: Flag indicating if the Business Message exchanged between the MessagingEndpoints is possibly a duplicate.

If the receiving MessagingEndpoint did not receive the original, then this Business Message should be processed as if it were the original.

If the receiving MessagingEndpoint did receive the original, then it should perform necessary actions to avoid processing this Business Message again.

This will guarantee business idempotent behaviour.

NOTE: this is named "PossResend" in FIX - this is an application level resend not a network level re-transmission.

Datatype: ["YesNoIndicator" on page 131](#)

4.1.12 Priority

XML Tag: Prty

Presence: [0..1]

Definition: Relative indication of the processing precedence of the message over a (set of) Business Messages with assigned priorities.

Datatype: ["Priority2Code" on page 130](#)

Usage Guideline details

- **on [camt.109.001.01/header/Priority](#)**
Type changed to: [Priority2Code on page 130](#)

4.1.13 Signature

XML Tag: Sgntr

Presence: [0..1]

Definition: Contains the digital signature of the Business Entity authorised to sign this Business Message.

Usage Guideline details

- **This element([camt.109.001.01/header/Signature](#)) is removed.**

4.1.14 Related

XML Tag: Rltd

Presence: [0..*]

Definition: Specifies the Business Application Header(s) of the Business Message(s) to which this Business Message relates.

Can be used when replying to a query; can also be used when canceling or amending.

The **Rltd** block contains the following elements (see datatype "BusinessApplicationHeader5__1" on page 26 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CharacterSet	<CharSet>		[0..1]		26
	From	<Fr>		[1..1]		26
	To	<To>		[1..1]		27
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]		27
	MessageDefinitionIdentifier	<MsgDefIdr>		[1..1]		28
	BusinessService	<BizSvc>		[0..1]		28
	CreationDate	<CreDt>		[1..1]		29
	CopyDuplicate	<CpyDplct>		[0..1]		29
	PossibleDuplicate	<PssblDplct>		[0..1]		29
	Priority	<Prty>		[0..1]		30
	Signature	<Sgntr>		[0..1]		30

Usage Guideline details

- on **camt.109.001.01/.header/Related**

This element has change repeatability, the maximum occurrence has been changed to : 1

- on **camt.109.001.01/.header/Related**

- **CBPR_Related_Business_Application_Header_TextualRule:**

If used, the Related BAH must transport the exact same information as in the BAH of the related message.

4.2 Payload Building Blocks

Note The following chapter identifies the building blocks of the CBPRPlus SR2026 (Combined) / CBPRPlus-camt.109.001.01_ChequeCancellationOrStopReport payload definition.

Usage Guideline on Root Node

- on **camt.109.001.01/**

– CBPR_Cheque_Rejected_AdditionalInformation_FormalRule:

If Status/Code = Rejected, then a reason code must be populated in the element "Additional Information".

For each [Full Message/Document/ChequeCancellationOrStopReportV01], if every occurrence of [ChequeCancellationOrStopReportV01/Cheque/ChequeCancellationOrStopStatus/Status/Code] has value included in the following list 'RJCR', then
at least one occurrence of the following element(s) [ChequeCancellationOrStopReportV01/Cheque/ChequeCancellationOrStopStatus/AdditionalInformation] must be present

4.2.1 GroupHeader

XML Tag: GrpHdr

Presence: [1..1]

Definition: Set of characteristics shared by all individual cheques included in the message.

The **GrpHdr** block contains the following elements (see datatype "GroupHeader103__1" on page 69 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	MessageIdentification	<MsgId>		[1..1]	⚠	69
	CreationDateTime	<CreDtTm>		[1..1]	⚠	70
	NumberOfCheques	<NbOfChqs>		[1..1]		70
	ControlSum	<CtrlSum>		[0..1]	🚫	70

4.2.2 Cheque

XML Tag: Chq

Presence: [1..*]

Definition: Specifies the details of the cheque.

The **Chq** block contains the following elements (see datatype "Cheque14__1" on page 37 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	InstructionIdentification	<InstrId>		[0..1]	⚠	37
	OriginalInstructionIdentification	<OrgnlInstrId>		[0..1]	M ⚠	38

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ChequeNumber	<ChqNb>		[1..1]	⚠	38
	IssueDate	<IsseDt>		[1..1]	⚠	38
	StaleDate	<StlDt>		[0..1]	⚠	39
	Amount	<Amt>		[1..1]	⚠	39
	EffectiveDate	<FctvDt>		[0..1]		39
	DrawerAgent	<DrwrAgt>		[0..1]	⚠	40
	DrawerAgentAccount	<DrwrAgtAcct>		[0..1]		40
	Payee	<Pyee>		[0..1]		41
	PayeeAccount	<PyeeAcct>		[0..1]	🚫	41
	ChequeCancellationOrStopStatus	<ChqCxlOrStopSts>		[1..1]		42

Usage Guideline details

- on camt.109.001.01/Cheque

This element has change repeatability, the maximum occurrence has been changed to : 1

4.2.3 SupplementaryData

XML Tag: SplmtryData

Presence: [0..*]

Definition: Additional information that cannot be captured in the structured elements and/or any other specific block.

The **SplmtryData** block contains the following elements (see datatype "SupplementaryData1" on page 103 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PlaceAndName	<PlcAndNm>		[0..1]		104
	Envelope	<Envlp>		[1..1]		104

Usage Guideline details

- This element(camt.109.001.01/SupplementaryData) is removed.

5 Message Components

Note The following chapter identifies the message components.

5.1 AccountIdentification4Choice

Definition: Specifies the unique identification of an account as assigned by the account servicer.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	IBAN	<IBAN>	{Or	[1..1]		17
	Other	<Othr>	Or}	[1..1]		17

Used in element(s)

"Identification" on page 31

5.1.1 IBAN

XML Tag: IBAN

Presence: [1..1]

Definition: International Bank Account Number (IBAN) - identifier used internationally by financial institutions to uniquely identify the account of a customer. Further specifications of the format and content of the IBAN can be found in the standard ISO 13616 "Banking and related financial services - International Bank Account Number (IBAN)" version 1997-10-01, or later revisions.

Datatype: "IBAN2007Identifier" on page 123

5.1.2 Other

XML Tag: Othr

Presence: [1..1]

Definition: Unique identification of an account, as assigned by the account servicer, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericAccountIdentification1](#)" on page 60 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		61
	SchemeName	<SchmeNm>		[0..1]		61
	Issuer	<Issr>		[0..1]		61

5.2 AccountIdentification4Choice__1

Definition: Specifies the unique identification of an account as assigned by the account servicer.

🚫 Removed - 🚫 Partial Removed - ⬡ Ignored - ⬡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	IBAN	<IBAN>	{Or	[1..1]		18
	Other	<Othr>	Or}	[1..1]		18

Used in element(s)

"Identification" on page 33

5.2.1 IBAN

XML Tag: IBAN

Presence: [1..1]

Definition: International Bank Account Number (IBAN) - identifier used internationally by financial institutions to uniquely identify the account of a customer. Further specifications of the format and content of the IBAN can be found in the standard ISO 13616 "Banking and related financial services - International Bank Account Number (IBAN)" version 1997-10-01, or later revisions.

Datatype: "IBAN2007Identifier" on page 123

5.2.2 Other

XML Tag: Othr

Presence: [1..1]

Definition: Unique identification of an account, as assigned by the account servicer, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericAccountIdentification1__1](#)" on page 61 for details)

🚫 Removed - 🚫 Partial Removed - ⬡ Ignored - ⬡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]	⚠	62
	SchemeName	<SchmeNm>		[0..1]		62
	Issuer	<Issr>		[0..1]	⚠	62

5.3 AccountSchemeName1Choice

Definition: Sets of elements to identify a name of the identification scheme.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		19
	Proprietary	<Prtry>	Or}	[1..1]		19

Used in element(s)

"SchemeName" on page 61

5.3.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalAccountIdentification1Code" on page 117

5.3.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 127

5.4 AccountSchemeName1Choice__1

Definition: Sets of elements to identify a name of the identification scheme.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		19
	Proprietary	<Prtry>	Or}	[1..1]		20

Used in element(s)

"SchemeName" on page 62

5.4.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalAccountIdentification1Code" on page 117

5.4.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 113](#)

Usage Guideline details

- on [camt.109.001.01/Cheque/DrawerAgentAccount/Identification/Other/SchemeName/Proprietary](#)

Type changed to: [CBPR_RestrictedFINXMax35Text on page 113](#)

5.5 AddressType3Choice

Definition: Choice of formats for the type of address.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		20
	Proprietary	<Prtry>	Or}	[1..1]		20

Used in element(s)

["AddressType" on page 90](#), ["AddressType" on page 94](#)

5.5.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Type of address expressed as a code.

Datatype: ["AddressType2Code" on page 106](#)

5.5.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Type of address expressed as a proprietary code.

The **Prtry** block contains the following elements (see datatype ["GenericIdentification30" on page 63](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		64
	Issuer	<Issr>		[1..1]		64
	SchemeName	<SchmeNm>		[0..1]		64

5.6 BranchAndFinancialInstitutionIdentification6__1

Definition: Unique and unambiguous identification of a financial institution or a branch of a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		21
	BranchIdentification	<BrnchId>		[0..1]		22

Used in element(s)

"DrawerAgent" on page 40

5.6.1 FinancialInstitutionIdentification

XML Tag: FinInstnId

Presence: [1..1]

Definition: Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

The **FinInstnId** block contains the following elements (see datatype "FinancialInstitutionIdentification18__1" on page 54 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		54
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		54
	LEI	<LEI>		[0..1]		55
	Name	<Nm>		[0..1]		55
	PostalAddress	<PstlAdr>		[0..1]		55
	Other	<Othr>		[0..1]		56

Usage Guideline details

- on camt.109.001.01/Cheque/DrawerAgent/FinancialInstitutionIdentification

- CBPR_Agent_Name_Postal_Address_FormaRule:

Name and Address must always be present together.

```
For each [Full Message/Document/ChequeCancellationOrStopReportV01/Cheque/Drawer-
Agent/FinancialInstitutionIdentification],
  for each [FinancialInstitutionIdentification], if
    at least one occurrence of the following element(s) [FinancialInstitu-
tionIdentification/Name] is (are) present
  then
    at least one occurrence of the following element(s) [FinancialInstitu-
tionIdentification/PostalAddress] must be present
  and for each [FinancialInstitutionIdentification], if
    at least one occurrence of the following element(s) [FinancialInstitu-
tionIdentification/PostalAddress] is (are) present
  then
    at least one occurrence of the following element(s) [FinancialInstitu-
tionIdentification/Name] must be present
```

5.6.2 BranchIdentification

XML Tag: BrnchId

Presence: [0..1]

Definition: Identifies a specific branch of a financial institution.

Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

The **BrnchId** block contains the following elements (see datatype "BranchData3" on page 24 for details)

❌ Removed -
⊗ Partial Removed -
◆ Ignored -
⊗ Partial Ignored -
⚠ Details below -
M Mandatory -
R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		24
	LEI	<LEI>		[0..1]		25
	Name	<Nm>		[0..1]		25
	PostalAddress	<PstAdr>		[0..1]		25

Usage Guideline details

- This element(camt.109.001.01/Cheque/DrawerAgent/BranchIdentification) is removed.

5.7 BranchAndFinancialInstitutionIdentification6__2

Definition: Unique and unambiguous identification of a financial institution or a branch of a financial institution.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		23
	BranchIdentification	<BrnchId>		[0..1]	🚫	23

Used in element(s)

"FinancialInstitutionIdentification" on page 80

5.7.1 FinancialInstitutionIdentification

XML Tag: FinInstnId

Presence: [1..1]

Definition: Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

The **FinInstnId** block contains the following elements (see datatype "FinancialInstitutionIdentification18__2" on page 57 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]	M	57
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		58
	LEI	<LEI>		[0..1]		58
	Name	<Nm>		[0..1]	🚫	58
	PostalAddress	<PstlAdr>		[0..1]	🚫	59
	Other	<Othr>		[0..1]	🚫	60

5.7.2 BranchIdentification

XML Tag: BrnchId

Presence: [0..1]

Definition: Identifies a specific branch of a financial institution.

Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

The **BrnchId** block contains the following elements (see datatype "[BranchData3](#)" on page 24 for details)

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		24
	LEI	<LEI>		[0..1]		25
	Name	<Nm>		[0..1]		25
	PostalAddress	<PstAdr>		[0..1]		25

Usage Guideline details

- This element([camt.109.001.01/.header/Related/To/FinancialInstitutionIdentification/BranchIdentification](#)) is removed.
- This element([camt.109.001.01/.header/To/FinancialInstitutionIdentification/BranchIdentification](#)) is removed.
- This element([camt.109.001.01/.header/Related/From/FinancialInstitutionIdentification/BranchIdentification](#)) is removed.
- This element([camt.109.001.01/.header/From/FinancialInstitutionIdentification/BranchIdentification](#)) is removed.

5.8 BranchData3

Definition: Information that locates and identifies a specific branch of a financial institution.

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		24
	LEI	<LEI>		[0..1]		25
	Name	<Nm>		[0..1]		25
	PostalAddress	<PstAdr>		[0..1]		25

Used in element(s)

["BranchIdentification"](#) on page 23, ["BranchIdentification"](#) on page 22

5.8.1 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a branch of a financial institution.

Datatype: "Max35Text" on page 127

5.8.2 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identification for the branch of the financial institution.

Datatype: "LEIIdentifier" on page 124

5.8.3 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "Max140Text" on page 125

5.8.4 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24" on page 89 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		90
	Department	<Dept>		[0..1]		90
	SubDepartment	<SubDept>		[0..1]		91
	StreetName	<StrtNm>		[0..1]		91
	BuildingNumber	<BldgNb>		[0..1]		91
	BuildingName	<BldgNm>		[0..1]		91
	Floor	<Flr>		[0..1]		91
	PostBox	<PstBx>		[0..1]		91
	Room	<Room>		[0..1]		92
	PostCode	<PstCd>		[0..1]		92
	TownName	<TwnNm>		[0..1]		92
	TownLocationName	<TwnLctnNm>		[0..1]		92

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DistrictName	<DstrctNm>		[0..1]		92
	CountrySubDivision	<CtrySubDvsn>		[0..1]		92
	Country	<Ctry>		[0..1]		92
	AddressLine	<AdrLine>		[0..7]		93

5.9 BusinessApplicationHeader5__1

Definition: Specifies the Business Application Header of the Business Message.

Can be used when replying to a query; can also be used when canceling or amending.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CharacterSet	<CharSet>		[0..1]		26
	From	<Fr>		[1..1]		26
	To	<To>		[1..1]		27
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]		27
	MessageDefinitionIdentifier	<MsgDefldr>		[1..1]		28
	BusinessService	<BizSvc>		[0..1]		28
	CreationDate	<CreDt>		[1..1]		29
	CopyDuplicate	<CpyDplct>		[0..1]		29
	PossibleDuplicate	<PssblDplct>		[0..1]		29
	Priority	<Prty>		[0..1]		30
	Signature	<Sgntr>		[0..1]		30

Used in element(s)

"Related" on page 13

5.9.1 CharacterSet

XML Tag: CharSet

Presence: [0..1]

Definition: Contains the character set of the text-based elements used in the Business Message.

Datatype: "UnicodeChartsCode" on page 131

5.9.2 From

XML Tag: Fr

Presence: [1..1]

Definition: The sending MessagingEndpoint that has created this Business Message for the receiving MessagingEndpoint that will process this Business Message.

Note the sending MessagingEndpoint might be different from the sending address potentially contained in the transport header (as defined in the transport layer).

The **Fr** block contains the following elements (see datatype "[Party44Choice__1](#)" on page 79 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]	🚫	79
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		80

5.9.3 To

XML Tag: To

Presence: [1..1]

Definition: The MessagingEndpoint designated by the sending MessagingEndpoint to be the recipient who will ultimately process this Business Message.

Note the receiving MessagingEndpoint might be different from the receiving address potentially contained in the transport header (as defined in the transport layer).

The **To** block contains the following elements (see datatype "[Party44Choice__1](#)" on page 79 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]	🚫	79
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		80

5.9.4 BusinessMessageIdentifier

XML Tag: BizMsgIdr

Presence: [1..1]

Definition: Unambiguously identifies the Business Message to the MessagingEndpoint that has created the Business Message.

Datatype: "[CBPR_RestrictedFINXMax35Text](#)" on page 113

Usage Guideline details

- on **camt.109.001.01/.header/Related/BusinessMessageIdentifier**

Type changed to: [CBPR_RestrictedFINXMax35Text on page 113](#)

- on **camt.109.001.01/.header/Related/BusinessMessageIdentifier**

- **CBPR_BusinessMessageIdentifier_TextualRule:**

The Business Message Identifier is the unique identifier of the Business Message instance that is being transported with this header, as defined by the sending application or system.

Must contain the Message Identification element from the Group Header of the underlying message, where available (as is typically the case with pacs, pain, and camt messages, for example). If Message Identification is not available in the underlying message, then this element must contain the unique identifier of the Business Message instance.

5.9.5 MessageDefinitionIdentifier

XML Tag: MsgDefIdr

Presence: [1..1]

Definition: Contains the MessageIdentifier that defines the BusinessMessage.

It must contain a MessageIdentifier published on the ISO 20022 website.

example camt.001.001.03.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 113](#)

Usage Guideline details

- on **camt.109.001.01/.header/Related/MessageDefinitionIdentifier**

Type changed to: [CBPR_RestrictedFINXMax35Text on page 113](#)

- on **camt.109.001.01/.header/Related/MessageDefinitionIdentifier**

- **CBPR_MessageDefinitionIdentifier_TextualRule:**

The Message Definition Identifier of the Business Message instance that is being transported with this header. In general, it must be formatted exactly as it appears in the namespace of the Business Message instance.

5.9.6 BusinessService

XML Tag: BizSvc

Presence: [0..1]

Definition: Specifies the business service agreed between the two MessagingEndpoints under which rules this Business Message is exchanged.

To be used when there is a choice of processing services or processing service levels.

Example: E&I.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 113](#)

Usage Guideline details

- **on [camt.109.001.01/.header/Related/BusinessService](#)**
Type changed to: [CBPR_RestrictedFINXMax35Text on page 113](#)
- **on [camt.109.001.01/.header/Related/BusinessService](#)**
 - **CBPR_RelatedBAHBusinessService_TextualRule:**
 If related BAH is present, then it is recommended to transport the element Business Service.

5.9.7 CreationDate

XML Tag: CreDt

Presence: [1..1]

Definition: Date and time when this Business Message (header) was created.

Note Times must be normalized, using the "Z" annotation.

Datatype: ["CBPR_DateTime" on page 109](#)

Usage Guideline details

- **on [camt.109.001.01/.header/Related/CreationDate](#)**
Type changed to: [CBPR_DateTime on page 109](#)

5.9.8 CopyDuplicate

XML Tag: CpyDplct

Presence: [0..1]

Definition: Indicates whether the message is a Copy, a Duplicate or a copy of a duplicate of a previously sent ISO 20022 Message.

Datatype: ["CopyDuplicate1Code" on page 115](#)

5.9.9 PossibleDuplicate

XML Tag: PssblDplct

Presence: [0..1]

Definition: Flag indicating if the Business Message exchanged between the MessagingEndpoints is possibly a duplicate.

If the receiving MessagingEndpoint did not receive the original, then this Business Message should be processed as if it were the original.

If the receiving MessagingEndpoint did receive the original, then it should perform necessary actions to avoid processing this Business Message again.

This will guarantee business idempotent behaviour.

NOTE: this is named "PossResend" in FIX - this is an application level resend not a network level re-transmission.

Datatype: ["YesNoIndicator" on page 131](#)

Usage Guideline details

- This element([camt.109.001.01/.header/Related/PossibleDuplicate](#)) is removed.

5.9.10 Priority

XML Tag: Prty

Presence: [0..1]

Definition: Relative indication of the processing precedence of the message over a (set of) Business Messages with assigned priorities.

Datatype: ["Priority2Code" on page 130](#)

Usage Guideline details

- on [camt.109.001.01/.header/Related/Priority](#)
Type changed to: [Priority2Code on page 130](#)

5.9.11 Signature

XML Tag: Sgntr

Presence: [0..1]

Definition: Contains the digital signature of the Business Entity authorised to sign this Business Message.

Usage Guideline details

- This element([camt.109.001.01/.header/Related/Signature](#)) is removed.

5.10 CashAccount40

Definition: Provides the details to identify an account.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		31
	Type	<Tp>		[0..1]		32
	Currency	<Ccy>		[0..1]		32
	Name	<Nm>		[0..1]		32
	Proxy	<Prxy>		[0..1]		32

Rules

R7 IdentificationOrProxyPresenceRule ✓

Identification must be present or Proxy must be present. Both may be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00498
- *Error Text:* Missing account identification or account proxy.

Guidelines

1. IdentificationAndProxyGuideline

If the account identification is not defined through a conventional identification such as an email address or a mobile number, then the proxy element should be used for the identification of the account.

Used in element(s)

"PayeeAccount" on page 41

5.10.1 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification for the account between the account owner and the account servicer.

The **Id** block contains the following elements (see datatype "[AccountIdentification4Choice](#)" on page 17 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	IBAN	<IBAN>	{Or	[1..1]		17
	Other	<Othr>	Or}	[1..1]		17

5.10.2 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the nature, or use of the account.

The **Tp** block contains the following elements (see datatype "[CashAccountType2Choice](#)" on page 35 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		35
	Proprietary	<Prtry>	Or}	[1..1]		36

5.10.3 Currency

XML Tag: Ccy

Presence: [0..1]

Definition: Identification of the currency in which the account is held.

Usage: Currency should only be used in case one and the same account number covers several currencies

and the initiating party needs to identify which currency needs to be used for settlement on the account.

Datatype: "[ActiveOrHistoricCurrencyCode](#)" on page 105

5.10.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name of the account, as assigned by the account servicing institution, in agreement with the account owner in order to provide an additional means of identification of the account.

Usage: The account name is different from the account owner name. The account name is used in certain user communities to provide a means of identifying the account, in addition to the account owner's identity and the account number.

Datatype: "[Max70Text](#)" on page 127

5.10.5 Proxy

XML Tag: Prxy

Presence: [0..1]

Definition: Specifies an alternate assumed name for the identification of the account.

The **Prxy** block contains the following elements (see datatype "[ProxyAccountIdentification1](#)" on [page 100](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		100
	Identification	<Id>		[1..1]		101

5.11 CashAccount40__1

Definition: Provides the details to identify an account.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		33
	Type	<Tp>		[0..1]		34
	Currency	<Ccy>		[0..1]		34
	Name	<Nm>		[0..1]		34
	Proxy	<Prxy>		[0..1]		35

Rules

R13 IdentificationOrProxyPresenceRule ✓

Identification must be present or Proxy must be present. Both may be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00498
- *Error Text:* Missing account identification or account proxy.

Guidelines

1. IdentificationAndProxyGuideline

If the account identification is not defined through a conventional identification such as an email address or a mobile number, then the proxy element should be used for the identification of the account.

Used in element(s)

"[DrawerAgentAccount](#)" on [page 40](#)

5.11.1 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification for the account between the account owner and the account servicer.

The **Id** block contains the following elements (see datatype "[AccountIdentification4Choice__1](#)" on [page 18](#) for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	IBAN	<IBAN>	{Or	[1..1]		18
	Other	<Othr>	Or}	[1..1]		18

5.11.2 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the nature, or use of the account.

The **Tp** block contains the following elements (see datatype "[CashAccountType2Choice__1](#)" on [page 36](#) for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		36
	Proprietary	<Prtry>	Or}	[1..1]		36

5.11.3 Currency

XML Tag: Ccy

Presence: [0..1]

Definition: Identification of the currency in which the account is held.

Usage: Currency should only be used in case one and the same account number covers several currencies

and the initiating party needs to identify which currency needs to be used for settlement on the account.

Datatype: "[ActiveOrHistoricCurrencyCode](#)" on [page 105](#)

5.11.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name of the account, as assigned by the account servicing institution, in agreement with the account owner in order to provide an additional means of identification of the account.

Usage: The account name is different from the account owner name. The account name is used in certain user communities to provide a means of identifying the account, in addition to the account owner's identity and the account number.

Datatype: "CBPR_RestrictedFINXMax70Text" on page 114

Usage Guideline details

- on **camt.109.001.01/Cheque/DrawerAgentAccount/Name**
Type changed to: CBPR_RestrictedFINXMax70Text on page 114

5.11.5 Proxy

XML Tag: Prxy

Presence: [0..1]

Definition: Specifies an alternate assumed name for the identification of the account.

The **Prxy** block contains the following elements (see datatype "ProxyAccountIdentification1__1" on page 101 for details)

⊘ Removed - ⊘ Partial Removed - ◇ Ignored - ◇ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]	M	101
	Identification	<Id>		[1..1]	⚠	101

5.12 CashAccountType2Choice

Definition: Nature or use of the account.

⊘ Removed - ⊘ Partial Removed - ◇ Ignored - ◇ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		35
	Proprietary	<Prtry>	Or}	[1..1]		36

Used in element(s)

"Type" on page 32

5.12.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Account type, in a coded form.

Datatype: ["ExternalCashAccountType1Code" on page 118](#)

5.12.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Nature or use of the account in a proprietary form.

Datatype: ["Max35Text" on page 127](#)

5.13 CashAccountType2Choice__1

Definition: Nature or use of the account.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		36
	Proprietary	<Prtry>	Or}	[1..1]		36

Used in element(s)

["Type" on page 34](#)

5.13.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Account type, in a coded form.

Datatype: ["ExternalCashAccountType1Code" on page 118](#)

5.13.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Nature or use of the account in a proprietary form.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 113](#)

Usage Guideline details

- on [camt.109.001.01/Cheque/DrawerAgentAccount/Type/Proprietary](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 113](#)

5.14 Cheque14__1

Definition: Characteristics of a cheque instruction, such as cheque type or cheque number.

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	InstructionIdentification	<InstrId>		[0..1]		37
	OriginalInstructionIdentification	<OrgnInstrId>		[0..1]		38
	ChequeNumber	<ChqNb>		[1..1]		38
	IssueDate	<IssDt>		[1..1]		38
	StaleDate	<StlDt>		[0..1]		39
	Amount	<Amt>		[1..1]		39
	EffectiveDate	<FctvDt>		[0..1]		39
	DrawerAgent	<DrwrAgt>		[0..1]		40
	DrawerAgentAccount	<DrwrAgtAcct>		[0..1]		40
	Payee	<Pyee>		[0..1]		41
	PayeeAccount	<PyeeAcct>		[0..1]		41
	ChequeCancellationOrStopStatus	<ChqCxlOrStopSts>		[1..1]		42

Used in element(s)

"Cheque" on page 15

5.14.1 InstructionIdentification

XML Tag: InstrId

Presence: [0..1]

Definition: Unique identification, as assigned by an instructing party for an instructed party, to unambiguously identify the instruction.

Usage: The instruction identification is a point to point reference that can be used between the instructing party and the instructed party to refer to the individual instruction. It can be included in several messages related to the instruction.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 113

Usage Guideline details

- on camt.109.001.01/Cheque/InstructionIdentification
 Type changed to: CBPR_RestrictedFINXMax35Text on page 113

5.14.2 OriginalInstructionIdentification

XML Tag: OrgnlInstrId

Presence: [0..1]

Definition: Unique identification, as assigned by the original instructing party for the original instructed party, to unambiguously identify the original instruction.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 113

Usage Guideline details

- on **camt.109.001.01/Cheque/OriginalInstructionIdentification**

This element is now mandatory, the minimum occurrence has been changed to : 1

- on **camt.109.001.01/Cheque/OriginalInstructionIdentification**

Type changed to: CBPR_RestrictedFINXMax35Text on page 113

- on **camt.109.001.01/Cheque/OriginalInstructionIdentification**

– CBPR_OriginalInstructionIdentification_TextualRule:

OriginalInstructionIdentification is required in follow-up of a camt.108, otherwise "NOTPROVIDED" if Originator is Drawee Agent.

5.14.3 ChequeNumber

XML Tag: ChqNb

Presence: [1..1]

Definition: Unique and unambiguous identifier for a cheque as assigned by the agent.

Datatype: "CBPR_RestrictedFINXMax16Text" on page 111

Usage Guideline details

- on **camt.109.001.01/Cheque/ChequeNumber**

Type changed to: CBPR_RestrictedFINXMax16Text on page 111

- on **camt.109.001.01/Cheque/ChequeNumber**

– CBPR_Cheque_Number_FormalRule:

This element must not start or end with a slash '/' and must not contain two consecutive slashes '//'.

For each [Full Message/Document/ChequeCancellationOrStopReportV01/Cheque/ChequeNumber],
the value of every occurrence of [ChequeNumber] must not comply with the following XML pattern : `'(/.*)|(.*/)|(.*/.*)'`

5.14.4 IssueDate

XML Tag: IsseDt

Presence: [1..1]

Definition: Date when the cheque has been issued by the payer.

Datatype: "CBPR_Date" on page 109

Usage Guideline details

- on camt.109.001.01/Cheque/IssueDate
Type changed to: CBPR_Date on page 109

5.14.5 StaleDate

XML Tag: StlDt

Presence: [0..1]

Definition: Date after which a cheque is no longer valid. The validity period of a cheque is calculated from the issue date on the face of the cheque. The period may be indicated on the face of the cheque itself such as "Valid for 90 days" or may be determined in accordance with domestic banking practice.

Not all countries will have a validity period.

Datatype: "CBPR_Date" on page 109

Usage Guideline details

- on camt.109.001.01/Cheque/StaleDate
Type changed to: CBPR_Date on page 109

5.14.6 Amount

XML Tag: Amt

Presence: [1..1]

Definition: Specifies the amount of the cheque to be paid to the payee.

Datatype: "CBPR_Amount" on page 108

Usage Guideline details

- on camt.109.001.01/Cheque/Amount
Type changed to: CBPR_Amount on page 108

5.14.7 EffectiveDate

XML Tag: FctvDt

Presence: [0..1]

Definition: Date and time at which the cheque amount becomes available on the payee account.

The **FctvDt** block contains the following elements (see datatype "[DateAndDateTime2Choice__1](#)" on [page 50](#) for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Date	<Dt>	{Or	[1..1]	⚠	50
	DateTime	<DtTm>	Or}	[1..1]	🚫	51

5.14.8 DrawerAgent

XML Tag: DrwrAgt

Presence: [0..1]

Definition: Specifies the agent servicing the account of the cheque payer.

The **DrwrAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6__1](#)" on [page 21](#) for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]	⚠	21
	BranchIdentification	<BrnchId>		[0..1]	🚫	22

Usage Guideline details

- on **camt.109.001.01/Cheque/DrawerAgent**
 - **CBPR_Agent_Option_3_TextualRule:**
Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country]). It is recommended to also add the post code when available
- on **camt.109.001.01/Cheque/DrawerAgent**
 - **CBPR_Agent_Option_1_TextualRule:**
BICFI, complemented optionally with a LEI (preferred option)
- on **camt.109.001.01/Cheque/DrawerAgent**
 - **CBPR_Agent_Option_2_TextualRule:**
(Clearing Code OR LEI) AND (Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country]). It is recommended to also add the post code when available

5.14.9 DrawerAgentAccount

XML Tag: DrwrAgtAcct

Presence: [0..1]

Definition: Specifies the cash account of the drawer agent.

The **DrwrAgtAcct** block contains the following elements (see datatype "CashAccount40__1" on page 33 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		33
	Type	<Tp>		[0..1]		34
	Currency	<Ccy>		[0..1]		34
	Name	<Nm>		[0..1]	⚠	34
	Proxy	<Prxy>		[0..1]		35

5.14.10 Payee

XML Tag: Pyee

Presence: [0..1]

Definition: Party that receives an amount of money as specified in the cheque.

The **Pyee** block contains the following elements (see datatype "PartyIdentification135__1" on page 82 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]	M ⚠	83
	PostalAddress	<PstlAdr>		[0..1]	M ⚠	83
	Identification	<Id>		[0..1]		84
	CountryOfResidence	<CtryOfRes>		[0..1]		85
	ContactDetails	<CtctDtls>		[0..1]	🚫	85

5.14.11 PayeeAccount

XML Tag: PyeeAcct

Presence: [0..1]

Definition: Specifies the cash account of the payee.

The **PyeeAcct** block contains the following elements (see datatype "CashAccount40" on page 30 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		31
	Type	<Tp>		[0..1]		32
	Currency	<Ccy>		[0..1]		32
	Name	<Nm>		[0..1]		32
	Proxy	<Prxy>		[0..1]		32

Usage Guideline details

- This element([camt.109.001.01/Cheque/PayeeAccount](#)) is removed.

5.14.12 ChequeCancellationOrStopStatus

XML Tag: ChqCxlOrStopSts

Presence: [1..1]

Definition: Specifies the status of the cancellation or stop request.

The **ChqCxlOrStopSts** block contains the following elements (see datatype "[ChequeCancellationStatus1__1](#)" on page 43 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Originator	<Orgtr>		[0..1]		43
	Status	<Sts>		[1..1]		44
	AdditionalInformation	<AddtlInf>		[0..1]		44

5.15 ChequeCancellationStatus1Choice__1

Definition: Specifies the status for the cancellation request of a cheque presentment.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		43
	Proprietary	<Prtry>	Or}	[1..1]		43

Used in element(s)

["Status" on page 44](#)

5.15.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Status, in a coded form, as published in an external code set.

Datatype: ["CBPR_ChequeCancellationOrStopStatusCode" on page 109](#)

Usage Guideline details

- on [camt.109.001.01/Cheque/ChequeCancellationOrStopStatus/Status/Code](#)
Type changed to: [CBPR_ChequeCancellationOrStopStatusCode on page 109](#)

5.15.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Status, in a proprietary form.

Datatype: ["Max35Text" on page 127](#)

Usage Guideline details

- This element([camt.109.001.01/Cheque/ChequeCancellationOrStopStatus/Status/Proprietary](#)) is removed.

5.16 ChequeCancellationStatus1__1

Definition: Provides further details on the status of the cheque presentment cancellation request.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Originator	<Orgtr>		[0..1]		43
	Status	<Sts>		[1..1]		44
	AdditionalInformation	<AddtlInf>		[0..1]		44

Used in element(s)

["ChequeCancellationOrStopStatus" on page 42](#)

5.16.1 Originator

XML Tag: Orgtr

Presence: [0..1]

Definition: Party that issues the cancellation request.

Datatype: "ChequePartyRole1Code" on page 114

5.16.2 Status

XML Tag: Sts

Presence: [1..1]

Definition: Specifies the status for the cancellation request.

The **Sts** block contains the following elements (see datatype "ChequeCancellationStatus1Choice__1" on page 42 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		43
	Proprietary	<Prtry>	Or}	[1..1]		43

5.16.3 AdditionalInformation

XML Tag: AddtlInf

Presence: [0..1]

Definition: Further details on the cancellation request reason.

Datatype: "CBPR_RestrictedFINXMax140Text" on page 110

Usage Guideline details

- on camt.109.001.01/Cheque/ChequeCancellationOrStopStatus/AdditionalInformation
Type changed to: CBPR_RestrictedFINXMax140Text on page 110
- on camt.109.001.01/Cheque/ChequeCancellationOrStopStatus/AdditionalInformation
 - **CBPR_Rejected_Status_Reason_TextualRule:**

The element "Additional Information" should be used to populate rejection reasons such as:

 - CLEA (Cheque already settled)
 - NCHQ (No cheque found)

5.17 ClearingSystemIdentification2Choice

Definition: Choice of a clearing system identifier.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		45
	Proprietary	<Prtry>	Or}	[1..1]		45

Used in element(s)

["ClearingSystemIdentification" on page 46](#)

5.17.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Identification of a clearing system, in a coded form as published in an external list.

Datatype: ["ExternalClearingSystemIdentification1Code" on page 119](#)

5.17.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Identification code for a clearing system, that has not yet been identified in the list of clearing systems.

Datatype: ["Max35Text" on page 127](#)

Usage Guideline details

- This element([camt.109.001.01/header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary](#)) is removed.
- This element([camt.109.001.01/header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary](#)) is removed.
- This element([camt.109.001.01/header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary](#)) is removed.
- This element([camt.109.001.01/header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary](#)) is removed.
- This element([camt.109.001.01/Cheque/DrawerAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary](#)) is removed.

5.18 ClearingSystemMemberIdentification2__1

Definition: Unique identification, as assigned by a clearing system, to unambiguously identify a member of the clearing system.

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]		46
	MemberIdentification	<MmbId>		[1..1]		47

Used in element(s)

"ClearingSystemMemberIdentification" on page 58, "ClearingSystemMemberIdentification" on page 54

5.18.1 ClearingSystemIdentification

XML Tag: ClrSysId

Presence: [0..1]

Definition: Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed.

The **ClrSysId** block contains the following elements (see datatype "ClearingSystemIdentification2Choice" on page 44 for details)

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		45
	Proprietary	<Prtry>	Or}	[1..1]		45

Usage Guideline details

- on camt.109.001.01/header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.109.001.01/header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.109.001.01/header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.109.001.01/header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.109.001.01/Cheque/DrawerAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**

This element is now mandatory, the minimum occurrence has been changed to : 1

5.18.2 MemberIdentification

XML Tag: Mmbld

Presence: [1..1]

Definition: Identification of a member of a clearing system.

Datatype: "CBPR_RestrictedFINXMax28Text" on page 112

Usage Guideline details

- on camt.109.001.01/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 112](#)
- on camt.109.001.01/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 112](#)
- on camt.109.001.01/Cheque/DrawerAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 112](#)
- on camt.109.001.01/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 112](#)
- on camt.109.001.01/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 112](#)

5.19 Contact4

Definition: Specifies the details of the contact person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NamePrefix	<NmPrfx>		[0..1]		48
	Name	<Nm>		[0..1]		48
	PhoneNumber	<PhneNb>		[0..1]		48
	MobileNumber	<MobNb>		[0..1]		48
	FaxNumber	<FaxNb>		[0..1]		49

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	EmailAddress	<EmailAdr>		[0..1]		49
	EmailPurpose	<EmailPurp>		[0..1]		49
	JobTitle	<JobTitl>		[0..1]		49
	Responsibility	<Rspnsblty>		[0..1]		49
	Department	<Dept>		[0..1]		49
	Other	<Othr>		[0..*]		49
	PreferredMethod	<PrefrdMtd>		[0..1]		50

Used in element(s)

"ContactDetails" on page 82, "ContactDetails" on page 85

5.19.1 NamePrefix

XML Tag: NmPrfx

Presence: [0..1]

Definition: Specifies the terms used to formally address a person.

Datatype: "NamePrefix2Code" on page 128

5.19.2 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: "Max140Text" on page 125

5.19.3 PhoneNumber

XML Tag: PhneNb

Presence: [0..1]

Definition: Collection of information that identifies a phone number, as defined by telecom services.

Datatype: "PhoneNumber" on page 129

5.19.4 MobileNumber

XML Tag: MobNb

Presence: [0..1]

Definition: Collection of information that identifies a mobile phone number, as defined by telecom services.

Datatype: "PhoneNumber" on page 129

5.19.5 FaxNumber

XML Tag: FaxNb

Presence: [0..1]

Definition: Collection of information that identifies a FAX number, as defined by telecom services.

Datatype: "PhoneNumber" on page 129

5.19.6 EmailAddress

XML Tag: EmailAdr

Presence: [0..1]

Definition: Address for electronic mail (e-mail).

Datatype: "Max2048Text" on page 126

5.19.7 EmailPurpose

XML Tag: EmailPurp

Presence: [0..1]

Definition: Purpose for which an email address may be used.

Datatype: "Max35Text" on page 127

5.19.8 JobTitle

XML Tag: JobTitl

Presence: [0..1]

Definition: Title of the function.

Datatype: "Max35Text" on page 127

5.19.9 Responsibility

XML Tag: Rspnsblty

Presence: [0..1]

Definition: Role of a person in an organisation.

Datatype: "Max35Text" on page 127

5.19.10 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: "Max70Text" on page 127

5.19.11 Other

XML Tag: Othr

Presence: [0..*]

Definition: Contact details in another form.

The **Othr** block contains the following elements (see datatype "OtherContact1" on page 76 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ChannelType	<ChanlTp>		[1..1]		76
	Identification	<Id>		[0..1]		76

5.19.12 PreferredMethod

XML Tag: PrefrdMtd

Presence: [0..1]

Definition: Preferred method used to reach the contact.

Datatype: "PreferredContactMethod1Code" on page 129

5.20 DateAndDateTime2Choice__1

Definition: Choice between a date or a date and time format.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Date	<Dt>	{Or	[1..1]		50
	DateTime	<DtTm>	Or}	[1..1]		51

Used in element(s)

"EffectiveDate" on page 39

5.20.1 Date

XML Tag: Dt

Presence: [1..1]

Definition: Specified date.

Datatype: "CBPR_Date" on page 109

Usage Guideline details

- on camt.109.001.01/Cheque/EffectiveDate/Date
Type changed to: CBPR_Date on page 109

5.20.2 DateTime

XML Tag: DtTm

Presence: [1..1]

Definition: Specified date and time.

Datatype: ["ISODateTime" on page 124](#)

Usage Guideline details

- This element([camt.109.001.01/Cheque/EffectiveDate/DateTime](#)) is removed.

5.21 DateAndPlaceOfBirth1

Definition: Date and place of birth of a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BirthDate	<BirthDt>		[1..1]		51
	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		51
	CityOfBirth	<CityOfBirth>		[1..1]		51
	CountryOfBirth	<CtryOfBirth>		[1..1]		52

Used in element(s)

["DateAndPlaceOfBirth" on page 86](#)

5.21.1 BirthDate

XML Tag: BirthDt

Presence: [1..1]

Definition: Date on which a person is born.

Datatype: ["ISODate" on page 124](#)

5.21.2 ProvinceOfBirth

XML Tag: PrvcOfBirth

Presence: [0..1]

Definition: Province where a person was born.

Datatype: ["Max35Text" on page 127](#)

5.21.3 CityOfBirth

XML Tag: CityOfBirth

Presence: [1..1]

Definition: City where a person was born.

Datatype: ["Max35Text" on page 127](#)

5.21.4 CountryOfBirth

XML Tag: CtryOfBirth

Presence: [1..1]

Definition: Country where a person was born.

Datatype: ["CountryCode" on page 116](#)

5.22 DateAndPlaceOfBirth1__1

Definition: Date and place of birth of a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BirthDate	<BirthDt>		[1..1]		52
	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		52
	CityOfBirth	<CityOfBirth>		[1..1]		53
	CountryOfBirth	<CtryOfBirth>		[1..1]		53

Used in element(s)

["DateAndPlaceOfBirth" on page 87](#)

5.22.1 BirthDate

XML Tag: BirthDt

Presence: [1..1]

Definition: Date on which a person is born.

Datatype: ["CBPR_Date" on page 109](#)

Usage Guideline details

- on [camt.109.001.01/Cheque/Payee/Identification/PrivateIdentification/DateAndPlaceOfBirth/BirthDate](#)

Type changed to: [CBPR_Date on page 109](#)

5.22.2 ProvinceOfBirth

XML Tag: PrvcOfBirth

Presence: [0..1]

Definition: Province where a person was born.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 113](#)

Usage Guideline details

- on [camt.109.001.01/Cheque/Payee/Identification/PrivateIdentification/DateAndPlaceOf-Birth/ProvinceOfBirth](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 113](#)

5.22.3 CityOfBirth

XML Tag: CityOfBirth

Presence: [1..1]

Definition: City where a person was born.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 113](#)

Usage Guideline details

- on [camt.109.001.01/Cheque/Payee/Identification/PrivateIdentification/DateAndPlaceOf-Birth/CityOfBirth](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 113](#)

5.22.4 CountryOfBirth

XML Tag: CtryOfBirth

Presence: [1..1]

Definition: Country where a person was born.

Datatype: ["CountryCode" on page 116](#)

5.23 FinancialIdentificationSchemeName1Choice

Definition: Sets of elements to identify a name of the organisation identification scheme.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		53
	Proprietary	<Prtry>	Or}	[1..1]		54

Used in element(s)

["SchemeName" on page 63](#)

5.23.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalFinancialInstitutionIdentification1Code" on page 120

5.23.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 127

5.24 FinancialInstitutionIdentification18__1

Definition: Specifies the details to identify a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		54
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		54
	LEI	<LEI>		[0..1]		55
	Name	<Nm>		[0..1]		55
	PostalAddress	<PstlAdr>		[0..1]		55
	Other	<Othr>		[0..1]		56

Used in element(s)

"FinancialInstitutionIdentification" on page 21

5.24.1 BICFI

XML Tag: BICFI

Presence: [0..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: "BICFIDec2014Identifier" on page 107

5.24.2 ClearingSystemMemberIdentification

XML Tag: ClrSysMmbld

Presence: [0..1]

Definition: Information used to identify a member within a clearing system.

The **ClrSysMmbld** block contains the following elements (see datatype "[ClearingSystemMemberIdentification2__1](#)" on page 45 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]		46
	MemberIdentification	<Mmbld>		[1..1]		47

5.24.3 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identifier of the financial institution.

Datatype: "[LEIIdentifier](#)" on page 124

5.24.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "[CBPR_RestrictedFINXMax140Text_Extended](#)" on page 110

Usage Guideline details

- on [camt.109.001.01/Cheque/DrawerAgent/FinancialInstitutionIdentification/Name](#)
Type changed to: [CBPR_RestrictedFINXMax140Text_Extended](#) on page 110

5.24.5 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "[PostalAddress24__1](#)" on page 93 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		94
	Department	<Dept>		[0..1]		94
	SubDepartment	<SubDept>		[0..1]		94

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	StreetName	<StrtNm>		[0..1]	⚠	95
	BuildingNumber	<BldgNb>		[0..1]	⚠	95
	BuildingName	<BldgNm>		[0..1]	⚠	96
	Floor	<Flr>		[0..1]	⚠	96
	PostBox	<PstBx>		[0..1]	⚠	96
	Room	<Room>		[0..1]	⚠	97
	PostCode	<PstCd>		[0..1]	⚠	97
	TownName	<TwnNm>		[0..1]	M ⚠	97
	TownLocationName	<TwnLctnNm>		[0..1]	⚠	98
	DistrictName	<DstrctNm>		[0..1]	⚠	98
	CountrySubDivision	<CtrySubDvsn>		[0..1]	⚠	99
	Country	<Ctry>		[0..1]	M	99
	AddressLine	<AdrLine>		[0..7]	⚠ R[0..2]	99

Usage Guideline details

- on camt.109.001.01/Cheque/DrawerAgent/FinancialInstitutionIdentification/PostalAddress
 - CBPR_Duplication_Postal_Address_TextualRule:

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.

5.24.6 Other

XML Tag: Othr

Presence: [0..1]

Definition: Unique identification of an agent, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "GenericFinancialIdentification1" on page 62 for details)

ⓧ Removed - ⓧ Partial Removed - ⬠ Ignored - ⬠ Partial Ignored - ⚠ Details below -
 M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		63
	SchemeName	<SchmeNm>		[0..1]		63
	Issuer	<Issr>		[0..1]		63

Usage Guideline details

- This element([camt.109.001.01/Cheque/DrawerAgent/FinancialInstitutionIdentification/Other](#)) is removed.

5.25 FinancialInstitutionIdentification18__2

Definition: Specifies the details to identify a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		57
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		58
	LEI	<LEI>		[0..1]		58
	Name	<Nm>		[0..1]		58
	PostalAddress	<PstlAdr>		[0..1]		59
	Other	<Othr>		[0..1]		60

Used in element(s)

"[FinancialInstitutionIdentification](#)" on page 23

5.25.1 BICFI

XML Tag: BICFI

Presence: [0..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: "[BICFIDec2014Identifier](#)" on page 107

Usage Guideline details

- on [camt.109.001.01/header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI](#)
This element is now mandatory, the minimum occurrence has been changed to : 1
- on [camt.109.001.01/header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI](#)
This element is now mandatory, the minimum occurrence has been changed to : 1
- on [camt.109.001.01/header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI](#)
This element is now mandatory, the minimum occurrence has been changed to : 1

- on **camt.109.001.01/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI**

This element is now mandatory, the minimum occurrence has been changed to : 1

5.25.2 ClearingSystemMemberIdentification

XML Tag: **ClrSysMmbld**

Presence: [0..1]

Definition: Information used to identify a member within a clearing system.

The **ClrSysMmbld** block contains the following elements (see datatype "[ClearingSystemMemberIdentification2_1](#)" on page 45 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]		46
	MemberIdentification	<Mmbld>		[1..1]		47

5.25.3 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identifier of the financial institution.

Datatype: "[LEIIdentifier](#)" on page 124

5.25.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "[Max140Text](#)" on page 125

Usage Guideline details

- This element(**camt.109.001.01/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name**) is removed.
- This element(**camt.109.001.01/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name**) is removed.
- This element(**camt.109.001.01/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name**) is removed.
- This element(**camt.109.001.01/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name**) is removed.

5.25.5 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24" on page 89 for details)

❌ Removed - ❌ Partial Removed - ❖ Ignored - ❖ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		90
	Department	<Dept>		[0..1]		90
	SubDepartment	<SubDept>		[0..1]		91
	StreetName	<StrtNm>		[0..1]		91
	BuildingNumber	<BldgNb>		[0..1]		91
	BuildingName	<BldgNm>		[0..1]		91
	Floor	<Flr>		[0..1]		91
	PostBox	<PstBx>		[0..1]		91
	Room	<Room>		[0..1]		92
	PostCode	<PstCd>		[0..1]		92
	TownName	<TwnNm>		[0..1]		92
	TownLocationName	<TwnLctnNm>		[0..1]		92
	DistrictName	<DstrctNm>		[0..1]		92
	CountrySubDivision	<CtrySubDvsn>		[0..1]		92
	Country	<Ctry>		[0..1]		92
	AddressLine	<AdrLine>		[0..7]		93

Usage Guideline details

- This element(camt.109.001.01/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress) is removed.
- This element(camt.109.001.01/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress) is removed.
- This element(camt.109.001.01/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress) is removed.
- This element(camt.109.001.01/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress) is removed.

5.25.6 Other

XML Tag: Othr

Presence: [0..1]

Definition: Unique identification of an agent, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericFinancialIdentification1](#)" on page 62 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		63
	SchemeName	<SchmeNm>		[0..1]		63
	Issuer	<Issr>		[0..1]		63

Usage Guideline details

- This element(camt.109.001.01/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other) is removed.
- This element(camt.109.001.01/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other) is removed.
- This element(camt.109.001.01/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other) is removed.
- This element(camt.109.001.01/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other) is removed.

5.26 GenericAccountIdentification1

Definition: Information related to a generic account identification.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		61
	SchemeName	<SchmeNm>		[0..1]		61
	Issuer	<Issr>		[0..1]		61

Used in element(s)

"Other" on page 17

5.26.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: "Max34Text" on page 126

5.26.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "AccountSchemeName1Choice" on page 18 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		19
	Proprietary	<Prtry>	Or}	[1..1]		19

5.26.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 127

5.27 GenericAccountIdentification1__1

Definition: Information related to a generic account identification.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		62
	SchemeName	<SchmeNm>		[0..1]		62
	Issuer	<Issr>		[0..1]		62

Used in element(s)

"Other" on page 18

5.27.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: ["CBPR_RestrictedFINXMax34Text" on page 112](#)

Usage Guideline details

- on [camt.109.001.01/Cheque/DrawerAgentAccount/Identification/Other/Identification](#)
Type changed to: [CBPR_RestrictedFINXMax34Text on page 112](#)

5.27.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype ["AccountScheme-Name1Choice__1" on page 19](#) for details)

❌ Removed - ❌ Partial Removed - ◆ Ignored - ◆ Partial Ignored - ⚠️ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		19
	Proprietary	<Prtry>	Or}	[1..1]	⚠️	20

5.27.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 113](#)

Usage Guideline details

- on [camt.109.001.01/Cheque/DrawerAgentAccount/Identification/Other/Issuer](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 113](#)

5.28 GenericFinancialIdentification1

Definition: Information related to an identification of a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		63
	SchemeName	<SchmeNm>		[0..1]		63
	Issuer	<Issr>		[0..1]		63

Used in element(s)

"Other" on page 60, "Other" on page 56

5.28.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: "Max35Text" on page 127

5.28.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "FinancialIdentificationScheme-Name1Choice" on page 53 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		53
	Proprietary	<Prtry>	Or}	[1..1]		54

5.28.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 127

5.29 GenericIdentification30

Definition: Information related to an identification, for example, party identification or account identification.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		64
	Issuer	<Issr>		[1..1]		64
	SchemeName	<SchmeNm>		[0..1]		64

Used in element(s)

"Proprietary" on page 20

5.29.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Proprietary information, often a code, issued by the data source scheme issuer.

Datatype: "Exact4AlphaNumericText" on page 117

5.29.2 Issuer

XML Tag: Issr

Presence: [1..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 127

5.29.3 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Short textual description of the scheme.

Datatype: "Max35Text" on page 127

5.30 GenericOrganisationIdentification1

Definition: Information related to an identification of an organisation.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		65
	SchemeName	<SchmeNm>		[0..1]		65
	Issuer	<Issr>		[0..1]		65

Used in element(s)

"Other" on page 73

5.30.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: "Max35Text" on page 127

5.30.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "[OrganisationIdentificationSchemeName1Choice](#)" on page 74 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		75
	Proprietary	<Prtry>	Or}	[1..1]		75

5.30.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 127

5.31 GenericOrganisationIdentification1__1

Definition: Information related to an identification of an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		66
	SchemeName	<SchmeNm>		[0..1]		66
	Issuer	<Issr>		[0..1]		66

Used in element(s)

"Other" on page 74

5.31.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 113

Usage Guideline details

- on camt.109.001.01/Cheque/Payee/Identification/OrganisationIdentification/Other/Identification
- Type changed to: CBPR_RestrictedFINXMax35Text on page 113

5.31.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "OrganisationIdentificationSchemeName1Choice_1" on page 75 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		75
	Proprietary	<Prtry>	Or}	[1..1]	 	76

Usage Guideline details

- on camt.109.001.01/Cheque/Payee/Identification/OrganisationIdentification/Other/SchemeName
- This element is now mandatory, the minimum occurrence has been changed to : 1*

5.31.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 113

Usage Guideline details

- on [camt.109.001.01/Cheque/Payee/Identification/OrganisationIdentification/Other/Issuer](#)
Type changed to: [CBPR_RestrictedFINXMax35Text](#) on page 113

5.32 GenericPersonIdentification1

Definition: Information related to an identification of a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		67
	SchemeName	<SchmeNm>		[0..1]		67
	Issuer	<Issr>		[0..1]		67

Used in element(s)

"Other" on page 86

5.32.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: "Max35Text" on page 127

5.32.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "[PersonIdentificationScheme-Name1Choice](#)" on page 88 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		88
	Proprietary	<Prtry>	Or}	[1..1]		88

5.32.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 127

5.33 GenericPersonIdentification1__1

Definition: Information related to an identification of a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		68
	SchemeName	<SchmeNm>		[0..1]		68
	Issuer	<Issr>		[0..1]		69

Used in element(s)

"Other" on page 87

5.33.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 113

Usage Guideline details

- on camt.109.001.01/Cheque/Payee/Identification/PrivateIdentification/Other/Identification
Type changed to: CBPR_RestrictedFINXMax35Text on page 113

5.33.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "PersonIdentificationScheme-Name1Choice__1" on page 88 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		89
	Proprietary	<Prtry>	Or}	[1..1]		89

Usage Guideline details

- on camt.109.001.01/Cheque/Payee/Identification/PrivateIdentification/Other/SchemeName
This element is now mandatory, the minimum occurrence has been changed to : 1

5.33.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 113

Usage Guideline details

- on camt.109.001.01/Cheque/Payee/Identification/PrivateIdentification/Other/Issuer
Type changed to: CBPR_RestrictedFINXMax35Text on page 113

5.34 GroupHeader103__1

Definition: Set of characteristics shared by all individual cheques included in the message.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	MessageIdentification	<MsgId>		[1..1]		69
	CreationDateTime	<CreDtTm>		[1..1]		70
	NumberOfCheques	<NbOfChqs>		[1..1]		70
	ControlSum	<CtrlSum>		[0..1]		70

Used in element(s)

"GroupHeader" on page 15

5.34.1 MessageIdentification

XML Tag: MsgId

Presence: [1..1]

Definition: Point to point reference, as assigned by the instructing party, and sent to the next party in the chain to unambiguously identify the message.

Usage: The instructing party has to make sure that MessageIdentification is unique per instructed party for a pre-agreed period.

Datatype: "CBPR_RestrictedFINXMax16Text" on page 111

Usage Guideline details

- on **camt.109.001.01/GroupHeader/MessageIdentification**
Type changed to: CBPR_RestrictedFINXMax16Text on page 111

- on **camt.109.001.01/GroupHeader/MessageIdentification**

- **CBPR_Message_Identification_FormalRule:**

This element must not start or end with a slash '/' and must not contain two consecutive slashes '//'.

For each [Full Message/Document/ChequeCancellationOrStopReportV01/GroupHeader/MessageIdentification],
the value of every occurrence of [MessageIdentification] must not comply with the following XML pattern : '(/.*)|(./)|(.*/.*)'

5.34.2 CreationDateTime

XML Tag: CreDtTm

Presence: [1..1]

Definition: Date and time at which the message was created.

Datatype: "CBPR_DateTime" on page 109

Usage Guideline details

- on **camt.109.001.01/GroupHeader/CreationDateTime**
Type changed to: CBPR_DateTime on page 109

5.34.3 NumberOfCheques

XML Tag: NbOfChqs

Presence: [1..1]

Definition: Number of individual cheques contained in the message.

Datatype: "Max15NumericText" on page 125

5.34.4 ControlSum

XML Tag: CtrlSum

Presence: [0..1]

Definition: Total of all individual amounts included in the message, irrespective of currencies.

Datatype: "DecimalNumber" on page 117

Usage Guideline details

- This element(**camt.109.001.01/GroupHeader/ControlSum**) is removed.

5.35 ImplementationSpecification1

Definition: Identifies the implementation specification to which the ISO 20022 message conforms.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Registry	<Regy>		[1..1]		71
	Identification	<Id>		[1..1]		71

Used in element(s)

"MarketPractice" on page 11

5.35.1 Registry

XML Tag: Regy

Presence: [1..1]

Definition: Name of the implementation specification registry in which the implementation specification of the ISO 20022 message is maintained.

For example, "MyStandards".

Datatype: "Max350Text" on page 126

5.35.2 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identifier which unambiguously identifies, within the implementation specification registry, the implementation specification to which the ISO 20022 message is compliant. This can be done via a URN. It can also contain a version number or date.

For instance, "2018-01-01 - Version 2" or "urn:uuid:6e8bc430-9c3a-11d9-9669-0800200c9a66".

Datatype: "Max2048Text" on page 126

5.36 OrganisationIdentification29

Definition: Unique and unambiguous way to identify an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AnyBIC	<AnyBIC>		[0..1]		72
	LEI	<LEI>		[0..1]		72
	Other	<Othr>		[0..*]		73

Used in element(s)

"OrganisationIdentification" on page 77

5.36.1 AnyBIC

XML Tag: AnyBIC

Presence: [0..1]

Definition: Business identification code of the organisation.

Datatype: "AnyBICDec2014Identifier" on page 107

Usage Guideline details

- on camt.109.001.01/header/Related/From/OrganisationIdentification/Identification/OrganisationIdentification/AnyBIC**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.109.001.01/header/From/OrganisationIdentification/Identification/OrganisationIdentification/AnyBIC**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.109.001.01/header/Related/To/OrganisationIdentification/Identification/OrganisationIdentification/AnyBIC**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.109.001.01/header/To/OrganisationIdentification/Identification/OrganisationIdentification/AnyBIC**
This element is now mandatory, the minimum occurrence has been changed to : 1

5.36.2 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identification as an alternate identification for a party.

Datatype: "LEIIdentifier" on page 124

5.36.3 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of an organisation, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericOrganisationIdentification1](#)" on page 64 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		65
	SchemeName	<SchmeNm>		[0..1]		65
	Issuer	<Issr>		[0..1]		65

Usage Guideline details

- This element([camt.109.001.01/.header/From/OrganisationIdentification/Identification/OrganisationIdentification/Other](#)) is removed.
- This element([camt.109.001.01/.header/Related/To/OrganisationIdentification/Identification/OrganisationIdentification/Other](#)) is removed.
- This element([camt.109.001.01/.header/To/OrganisationIdentification/Identification/OrganisationIdentification/Other](#)) is removed.
- This element([camt.109.001.01/.header/Related/From/OrganisationIdentification/Identification/OrganisationIdentification/Other](#)) is removed.

5.37 OrganisationIdentification29__1

Definition: Unique and unambiguous way to identify an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AnyBIC	<AnyBIC>		[0..1]		74
	LEI	<LEI>		[0..1]		74
	Other	<Othr>		[0..*]	R[0..2]	74

Used in element(s)

"[OrganisationIdentification](#)" on page 78

5.37.1 AnyBIC

XML Tag: AnyBIC

Presence: [0..1]

Definition: Business identification code of the organisation.

Datatype: "AnyBICDec2014Identifier" on page 107

5.37.2 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identification as an alternate identification for a party.

Datatype: "LEIIdentifier" on page 124

5.37.3 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of an organisation, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "GenericOrganisationIdentification1__1" on page 65 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		66
	SchemeName	<SchmeNm>		[0..1]		66
	Issuer	<Issr>		[0..1]		66

Usage Guideline details

- on camt.109.001.01/Cheque/Payee/Identification/OrganisationIdentification/Other
This element has change repeatability, the maximum occurrence has been changed to : 2

5.38 OrganisationIdentificationSchemeName1Choice

Definition: Sets of elements to identify a name of the organisation identification scheme.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		75
	Proprietary	<Prtry>	Or}	[1..1]		75

Used in element(s)

"SchemeName" on page 65

5.38.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalOrganisationIdentification1Code" on page 121

5.38.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 127

5.39 OrganisationIdentificationScheme-Name1Choice__1

Definition: Sets of elements to identify a name of the organisation identification scheme.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		75
	Proprietary	<Prtry>	Or}	[1..1]	 	76

Used in element(s)

"SchemeName" on page 66

5.39.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalOrganisationIdentification1Code" on page 121

5.39.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 113

Usage Guideline details

- This element([camt.109.001.01/Cheque/Payee/Identification/OrganisationIdentification/Other/SchemeName/Proprietary](#)) is removed.
- on [camt.109.001.01/Cheque/Payee/Identification/OrganisationIdentification/Other/SchemeName/Proprietary](#)
Type changed to: CBPR_RestrictedFINXMax35Text on page 113

5.40 OtherContact1

Definition: Communication device number or electronic address used for communication.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ChannelType	<ChanTp>		[1..1]		76
	Identification	<Id>		[0..1]		76

Used in element(s)

"Other" on page 49

5.40.1 ChannelType

XML Tag: ChanTp

Presence: [1..1]

Definition: Method used to contact the financial institution's contact for the specific tax region.

Datatype: "Max4Text" on page 127

5.40.2 Identification

XML Tag: Id

Presence: [0..1]

Definition: Communication value such as phone number or email address.

Datatype: "Max128Text" on page 125

5.41 Party38Choice

Definition: Nature or use of the account.

🚫 Removed - 🚫 Partial Removed - ⬡ Ignored - ⬡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		77
	PrivateIdentification	<PrvtId>	Or}	[1..1]	🚫	77

Used in element(s)

"Identification" on page 81

5.41.1 OrganisationIdentification

XML Tag: OrgId

Presence: [1..1]

Definition: Unique and unambiguous way to identify an organisation.

The **OrgId** block contains the following elements (see datatype "[OrganisationIdentification29](#)" on page 71 for details)

🚫 Removed - 🚫 Partial Removed - ⬡ Ignored - ⬡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AnyBIC	<AnyBIC>		[0..1]	M	72
	LEI	<LEI>		[0..1]		72
	Other	<Othr>		[0..*]	🚫	73

5.41.2 PrivateIdentification

XML Tag: PrvtId

Presence: [1..1]

Definition: Unique and unambiguous identification of a person, for example a passport.

The **PrvtId** block contains the following elements (see datatype "[PersonIdentification13](#)" on page 86 for details)

🚫 Removed - 🚫 Partial Removed - ⬡ Ignored - ⬡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		86
	Other	<Othr>		[0..*]		86

Usage Guideline details

- This element(`camt.109.001.01/.header/Related/From/OrganisationIdentification/Identification/Privateldentification`) is removed.
- This element(`camt.109.001.01/.header/From/OrganisationIdentification/Identification/Privateldentification`) is removed.
- This element(`camt.109.001.01/.header/To/OrganisationIdentification/Identification/Privateldentification`) is removed.
- This element(`camt.109.001.01/.header/Related/To/OrganisationIdentification/Identification/Privateldentification`) is removed.

5.42 Party38Choice__1

Definition: Nature or use of the account.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		78
	Privateldentification	<PrvtId>	Or}	[1..1]		78

Used in element(s)

"Identification" on page 84

5.42.1 OrganisationIdentification

XML Tag: OrgId

Presence: [1..1]

Definition: Unique and unambiguous way to identify an organisation.

The **OrgId** block contains the following elements (see datatype "OrganisationIdentification29__1" on page 73 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AnyBIC	<AnyBIC>		[0..1]		74
	LEI	<LEI>		[0..1]		74
	Other	<Othr>		[0..*]	R[0..2]	74

5.42.2 Privateldentification

XML Tag: PrvtId

Presence: [1..1]

Definition: Unique and unambiguous identification of a person, for example a passport.

The **PrvtId** block contains the following elements (see datatype "[PersonIdentification13__1](#)" on page 87 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		87
	Other	<Othr>		[0..*]	R[0..2]	87

5.43 Party44Choice__1

Definition: Identification of a person, an organisation or a financial institution.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]	🚫	79
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		80

Used in element(s)

"From" on page 9, "From" on page 26, "To" on page 10, "To" on page 27

5.43.1 OrganisationIdentification

XML Tag: OrgId

Presence: [1..1]

Definition: Identification of a person or an organisation.

The **OrgId** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 80 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		80
	PostalAddress	<PstlAdr>		[0..1]		81
	Identification	<Id>		[0..1]		81
	CountryOfResidence	<CtryOfRes>		[0..1]		82
	ContactDetails	<CtctDtls>		[0..1]		82

Usage Guideline details

- This element(`camt.109.001.01/.header/Related/From/OrganisationIdentification`) is removed.
- This element(`camt.109.001.01/.header/To/OrganisationIdentification`) is removed.
- This element(`camt.109.001.01/.header/From/OrganisationIdentification`) is removed.
- This element(`camt.109.001.01/.header/Related/To/OrganisationIdentification`) is removed.

5.43.2 FinancialInstitutionIdentification

XML Tag: FIId

Presence: [1..1]

Definition: Identification of a financial institution.

The **FIId** block contains the following elements (see datatype "`BranchAndFinancialInstitutionIdentification6_2`" on page 23 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		23
	BranchIdentification	<BrnchId>		[0..1]		23

5.44 PartyIdentification135

Definition: Specifies the identification of a person or an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		80
	PostalAddress	<PstlAdr>		[0..1]		81
	Identification	<Id>		[0..1]		81
	CountryOfResidence	<CtryOfRes>		[0..1]		82
	ContactDetails	<CtctDtls>		[0..1]		82

Used in element(s)

"OrganisationIdentification" on page 79

5.44.1 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: "Max140Text" on page 125

5.44.2 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24" on page 89 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		90
	Department	<Dept>		[0..1]		90
	SubDepartment	<SubDept>		[0..1]		91
	StreetName	<StrtNm>		[0..1]		91
	BuildingNumber	<BldgNb>		[0..1]		91
	BuildingName	<BldgNm>		[0..1]		91
	Floor	<Flr>		[0..1]		91
	PostBox	<PstBx>		[0..1]		91
	Room	<Room>		[0..1]		92
	PostCode	<PstCd>		[0..1]		92
	TownName	<TwnNm>		[0..1]		92
	TownLocationName	<TwnLctnNm>		[0..1]		92
	DistrictName	<DstrctNm>		[0..1]		92
	CountrySubDivision	<CtrySubDvsn>		[0..1]		92
	Country	<Ctry>		[0..1]		92
	AddressLine	<AdrLine>		[0..7]		93

5.44.3 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a party.

The **Id** block contains the following elements (see datatype "Party38Choice" on page 77 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		77
	PrivateIdentification	<PrvtId>	Or}	[1..1]		77

5.44.4 CountryOfResidence

XML Tag: CtryOfRes

Presence: [0..1]

Definition: Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.

Datatype: ["CountryCode" on page 116](#)

5.44.5 ContactDetails

XML Tag: CtctDtls

Presence: [0..1]

Definition: Set of elements used to indicate how to contact the party.

The **CtctDtls** block contains the following elements (see datatype ["Contact4" on page 47](#) for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NamePrefix	<NmPrfx>		[0..1]		48
	Name	<Nm>		[0..1]		48
	PhoneNumber	<PhneNb>		[0..1]		48
	MobileNumber	<MobNb>		[0..1]		48
	FaxNumber	<FaxNb>		[0..1]		49
	EmailAddress	<EmailAdr>		[0..1]		49
	EmailPurpose	<EmailPurp>		[0..1]		49
	JobTitle	<JobTitl>		[0..1]		49
	Responsibility	<Rspnsblty>		[0..1]		49
	Department	<Dept>		[0..1]		49
	Other	<Othr>		[0..*]		49
	PreferredMethod	<PrefrdMtd>		[0..1]		50

5.45 PartyIdentification135__1

Definition: Specifies the identification of a person or an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]	 	83
	PostalAddress	<PstlAdr>		[0..1]	 	83
	Identification	<Id>		[0..1]		84
	CountryOfResidence	<CtryOfRes>		[0..1]		85
	ContactDetails	<CtctDtls>		[0..1]		85

Used in element(s)

"Payee" on page 41

5.45.1 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: "CBPR_RestrictedFINXMax140Text_Extended" on page 110

Usage Guideline details

- on camt.109.001.01/Cheque/Payee/Name
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.109.001.01/Cheque/Payee/Name
Type changed to: CBPR_RestrictedFINXMax140Text_Extended on page 110

5.45.2 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24__1" on page 93 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		94

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Department	<Dept>		[0..1]		94
	SubDepartment	<SubDept>		[0..1]		94
	StreetName	<StrtNm>		[0..1]		95
	BuildingNumber	<BldgNb>		[0..1]		95
	BuildingName	<BldgNm>		[0..1]		96
	Floor	<Flr>		[0..1]		96
	PostBox	<PstBx>		[0..1]		96
	Room	<Room>		[0..1]		97
	PostCode	<PstCd>		[0..1]		97
	TownName	<TwnNm>		[0..1]	 	97
	TownLocationName	<TwnLctnNm>		[0..1]		98
	DistrictName	<DstrctNm>		[0..1]		98
	CountrySubDivision	<CtrySubDvsn>		[0..1]		99
	Country	<Ctry>		[0..1]		99
	AddressLine	<AdrLine>		[0..7]	 R[0..2]	99

Usage Guideline details

- on camt.109.001.01/Cheque/Payee/PostalAddress

This element is now mandatory, the minimum occurrence has been changed to : 1

- on camt.109.001.01/Cheque/Payee/PostalAddress

- CBPR_Duplication_Postal_Address_TextualRule:

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.

5.45.3 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a party.

The **Id** block contains the following elements (see datatype "Party38Choice__1" on page 78 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		78
	PrivateIdentification	<PrvtId>	Or}	[1..1]		78

5.45.4 CountryOfResidence

XML Tag: CtryOfRes

Presence: [0..1]

Definition: Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.

Datatype: "CountryCode" on page 116

5.45.5 ContactDetails

XML Tag: CtctDtls

Presence: [0..1]

Definition: Set of elements used to indicate how to contact the party.

The **CtctDtls** block contains the following elements (see datatype "Contact4" on page 47 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NamePrefix	<NmPrfx>		[0..1]		48
	Name	<Nm>		[0..1]		48
	PhoneNumber	<PhneNb>		[0..1]		48
	MobileNumber	<MobNb>		[0..1]		48
	FaxNumber	<FaxNb>		[0..1]		49
	EmailAddress	<EmailAdr>		[0..1]		49
	EmailPurpose	<EmailPurp>		[0..1]		49
	JobTitle	<JobTitt>		[0..1]		49
	Responsibility	<Rspnsblty>		[0..1]		49
	Department	<Dept>		[0..1]		49
	Other	<Othr>		[0..*]		49
	PreferredMethod	<PrefrdMtd>		[0..1]		50

Usage Guideline details

- This element(camt.109.001.01/Cheque/Payee/ContactDetails) is removed.

5.46 PersonIdentification13

Definition: Unique and unambiguous way to identify a person.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		86
	Other	<Othr>		[0..*]		86

Used in element(s)

"PrivateIdentification" on page 77

5.46.1 DateAndPlaceOfBirth

XML Tag: DtAndPlcOfBirth

Presence: [0..1]

Definition: Date and place of birth of a person.

The **DtAndPlcOfBirth** block contains the following elements (see datatype "DateAndPlaceOfBirth1" on page 51 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BirthDate	<BirthDt>		[1..1]		51
	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		51
	CityOfBirth	<CityOfBirth>		[1..1]		51
	CountryOfBirth	<CtryOfBirth>		[1..1]		52

5.46.2 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of a person, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "GenericPersonIdentification1" on page 67 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		67

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	SchemeName	<SchmeNm>		[0..1]		67
	Issuer	<Issr>		[0..1]		67

5.47 PersonIdentification13__1

Definition: Unique and unambiguous way to identify a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		87
	Other	<Othr>		[0..*]	R[0..2]	87

Used in element(s)

"PrivateIdentification" on page 78

5.47.1 DateAndPlaceOfBirth

XML Tag: DtAndPlcOfBirth

Presence: [0..1]

Definition: Date and place of birth of a person.

The **DtAndPlcOfBirth** block contains the following elements (see datatype "[DateAndPlaceOfBirth1__1](#)" on page 52 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BirthDate	<BirthDt>		[1..1]		52
	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		52
	CityOfBirth	<CityOfBirth>		[1..1]		53
	CountryOfBirth	<CtryOfBirth>		[1..1]		53

5.47.2 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of a person, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericPersonIdentification1__1](#)" on page 68 for details)

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		68
	SchemeName	<SchmeNm>		[0..1]		68
	Issuer	<Issr>		[0..1]		69

Usage Guideline details

- on camt.109.001.01/Cheque/Payee/Identification/PrivateIdentification/Other
This element has change repeatability, the maximum occurrence has been changed to : 2

5.48 PersonIdentificationSchemeName1Choice

Definition: Sets of elements to identify a name of the identification scheme.

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		88
	Proprietary	<Prtry>	Or}	[1..1]		88

Used in element(s)

"SchemeName" on page 67

5.48.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalPersonIdentification1Code" on page 122

5.48.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 127

5.49 PersonIdentificationSchemeName1Choice__1

Definition: Sets of elements to identify a name of the identification scheme.

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		89
	Proprietary	<Prtry>	Or}	[1..1]	🚫 ⚠	89

Used in element(s)

"SchemeName" on page 68

5.49.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalPersonIdentification1Code" on page 122

5.49.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 113

Usage Guideline details

- This element(camt.109.001.01/Cheque/Payee/Identification/PrivateIdentification/Other/SchemeName/Proprietary) is removed.
- on camt.109.001.01/Cheque/Payee/Identification/PrivateIdentification/Other/SchemeName/Proprietary
 Type changed to: CBPR_RestrictedFINXMax35Text on page 113

5.50 PostalAddress24

Definition: Information that locates and identifies a specific address, as defined by postal services.

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		90
	Department	<Dept>		[0..1]		90

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	SubDepartment	<SubDept>		[0..1]		91
	StreetName	<StrtNm>		[0..1]		91
	BuildingNumber	<BldgNb>		[0..1]		91
	BuildingName	<BldgNm>		[0..1]		91
	Floor	<Flr>		[0..1]		91
	PostBox	<PstBx>		[0..1]		91
	Room	<Room>		[0..1]		92
	PostCode	<PstCd>		[0..1]		92
	TownName	<TwnNm>		[0..1]		92
	TownLocationName	<TwnLctnNm>		[0..1]		92
	DistrictName	<DstrctNm>		[0..1]		92
	CountrySubDivision	<CtrySubDvsn>		[0..1]		92
	Country	<Ctry>		[0..1]		92
	AddressLine	<AdrLine>		[0..7]		93

Used in element(s)

"PostalAddress" on page 25, "PostalAddress" on page 81, "PostalAddress" on page 59

5.50.1 AddressType

XML Tag: AdrTp

Presence: [0..1]

Definition: Identifies the nature of the postal address.

The **AdrTp** block contains the following elements (see datatype "AddressType3Choice" on page 20 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		20
	Proprietary	<Prtry>	Or}	[1..1]		20

5.50.2 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: ["Max70Text" on page 127](#)

5.50.3 SubDepartment

XML Tag: SubDept

Presence: [0..1]

Definition: Identification of a sub-division of a large organisation or building.

Datatype: ["Max70Text" on page 127](#)

5.50.4 StreetName

XML Tag: StrtNm

Presence: [0..1]

Definition: Name of a street or thoroughfare.

Datatype: ["Max70Text" on page 127](#)

5.50.5 BuildingNumber

XML Tag: BldgNb

Presence: [0..1]

Definition: Number that identifies the position of a building on a street.

Datatype: ["Max16Text" on page 125](#)

5.50.6 BuildingName

XML Tag: BldgNm

Presence: [0..1]

Definition: Name of the building or house.

Datatype: ["Max35Text" on page 127](#)

5.50.7 Floor

XML Tag: Flr

Presence: [0..1]

Definition: Floor or storey within a building.

Datatype: ["Max70Text" on page 127](#)

5.50.8 PostBox

XML Tag: PstBx

Presence: [0..1]

Definition: Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for.

Datatype: ["Max16Text" on page 125](#)

5.50.9 Room

XML Tag: Room

Presence: [0..1]

Definition: Building room number.

Datatype: "Max70Text" on page 127

5.50.10 PostCode

XML Tag: PstCd

Presence: [0..1]

Definition: Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.

Datatype: "Max16Text" on page 125

5.50.11 TownName

XML Tag: TwnNm

Presence: [0..1]

Definition: Name of a built-up area, with defined boundaries, and a local government.

Datatype: "Max35Text" on page 127

5.50.12 TownLocationName

XML Tag: TwnLctnNm

Presence: [0..1]

Definition: Specific location name within the town.

Datatype: "Max35Text" on page 127

5.50.13 DistrictName

XML Tag: DstrctNm

Presence: [0..1]

Definition: Identifies a subdivision within a country sub-division.

Datatype: "Max35Text" on page 127

5.50.14 CountrySubDivision

XML Tag: CtrySubDvsn

Presence: [0..1]

Definition: Identifies a subdivision of a country such as state, region, county.

Datatype: "Max35Text" on page 127

5.50.15 Country

XML Tag: Ctry

Presence: [0..1]

Definition: Nation with its own government.

Datatype: "CountryCode" on page 116

5.50.16 AddressLine

XML Tag: AdrLine

Presence: [0..7]

Definition: Information that locates and identifies a specific address, as defined by postal services, presented in free format text.

Datatype: "Max70Text" on page 127

5.51 PostalAddress24__1

Definition: Information that locates and identifies a specific address, as defined by postal services.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		94
	Department	<Dept>		[0..1]		94
	SubDepartment	<SubDept>		[0..1]		94
	StreetName	<StrtNm>		[0..1]		95
	BuildingNumber	<BldgNb>		[0..1]		95
	BuildingName	<BldgNm>		[0..1]		96
	Floor	<Flr>		[0..1]		96
	PostBox	<PstBx>		[0..1]		96
	Room	<Room>		[0..1]		97
	PostCode	<PstCd>		[0..1]		97
	TownName	<TwnNm>		[0..1]	 	97
	TownLocationName	<TwnLctnNm>		[0..1]		98
	DistrictName	<DstrctNm>		[0..1]		98
	CountrySubDivision	<CtrySubDvsn>		[0..1]		99
	Country	<Ctry>		[0..1]		99
	AddressLine	<AdrLine>		[0..7]	 R[0..2] R[0..2]	99

Used in element(s)

["PostalAddress" on page 55](#), ["PostalAddress" on page 83](#)

5.51.1 AddressType

XML Tag: AdrTp

Presence: [0..1]

Definition: Identifies the nature of the postal address.

The **AdrTp** block contains the following elements (see datatype ["AddressType3Choice" on page 20](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		20
	Proprietary	<Prtry>	Or}	[1..1]		20

Usage Guideline details

- This element([camt.109.001.01/Cheque/Payee/PostalAddress/AddressType](#)) is removed.
- This element([camt.109.001.01/Cheque/DrawerAgent/FinancialInstitutionIdentification/PostalAddress/AddressType](#)) is removed.

5.51.2 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended" on page 114](#)

Usage Guideline details

- on [camt.109.001.01/Cheque/DrawerAgent/FinancialInstitutionIdentification/PostalAddress/Department](#)
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 114](#)
- on [camt.109.001.01/Cheque/Payee/PostalAddress/Department](#)
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 114](#)

5.51.3 SubDepartment

XML Tag: SubDept

Presence: [0..1]

Definition: Identification of a sub-division of a large organisation or building.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended" on page 114](#)

Usage Guideline details

- **on camt.109.001.01/Cheque/Payee/PostalAddress/SubDepartment**
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 114](#)
- **on camt.109.001.01/Cheque/DrawerAgent/FinancialInstitutionIdentification/PostalAddress/SubDepartment**
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 114](#)

5.51.4 StreetName

XML Tag: StrtNm

Presence: [0..1]

Definition: Name of a street or thoroughfare.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended" on page 114](#)

Usage Guideline details

- **on camt.109.001.01/Cheque/DrawerAgent/FinancialInstitutionIdentification/PostalAddress/StreetName**
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 114](#)
- **on camt.109.001.01/Cheque/Payee/PostalAddress/StreetName**
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 114](#)

5.51.5 BuildingNumber

XML Tag: BldgNb

Presence: [0..1]

Definition: Number that identifies the position of a building on a street.

Datatype: ["CBPR_RestrictedFINXMax16Text_Extended" on page 111](#)

Usage Guideline details

- **on camt.109.001.01/Cheque/DrawerAgent/FinancialInstitutionIdentification/PostalAddress/BuildingNumber**
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 111](#)
- **on camt.109.001.01/Cheque/Payee/PostalAddress/BuildingNumber**
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 111](#)

5.51.6 BuildingName

XML Tag: BldgNm

Presence: [0..1]

Definition: Name of the building or house.

Datatype: "CBPR_RestrictedFINXMax35Text_Extended" on page 113

Usage Guideline details

- on **camt.109.001.01/Cheque/DrawerAgent/FinancialInstitutionIdentification/PostalAddress/BuildingName**

Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 113

- on **camt.109.001.01/Cheque/Payee/PostalAddress/BuildingName**

Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 113

5.51.7 Floor

XML Tag: Flr

Presence: [0..1]

Definition: Floor or storey within a building.

Datatype: "CBPR_RestrictedFINXMax70Text_Extended" on page 114

Usage Guideline details

- on **camt.109.001.01/Cheque/DrawerAgent/FinancialInstitutionIdentification/PostalAddress/Floor**

Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 114

- on **camt.109.001.01/Cheque/Payee/PostalAddress/Floor**

Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 114

5.51.8 PostBox

XML Tag: PstBx

Presence: [0..1]

Definition: Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for.

Datatype: "CBPR_RestrictedFINXMax16Text_Extended" on page 111

Usage Guideline details

- on **camt.109.001.01/Cheque/Payee/PostalAddress/PostBox**

Type changed to: CBPR_RestrictedFINXMax16Text_Extended on page 111

- on **camt.109.001.01/Cheque/DrawerAgent/FinancialInstitutionIdentification/PostalAddress/PostBox**

Type changed to: CBPR_RestrictedFINXMax16Text_Extended on page 111

5.51.9 Room

XML Tag: Room

Presence: [0..1]

Definition: Building room number.

Datatype: "CBPR_RestrictedFINXMax70Text_Extended" on page 114

Usage Guideline details

- on **camt.109.001.01/Cheque/Payee/PostalAddress/Room**
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 114
- on **camt.109.001.01/Cheque/DrawerAgent/FinancialInstitutionIdentification/PostalAddress/Room**
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 114

5.51.10 PostCode

XML Tag: PstCd

Presence: [0..1]

Definition: Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.

Datatype: "CBPR_RestrictedFINXMax16Text_Extended" on page 111

Usage Guideline details

- on **camt.109.001.01/Cheque/DrawerAgent/FinancialInstitutionIdentification/PostalAddress/PostCode**
Type changed to: CBPR_RestrictedFINXMax16Text_Extended on page 111
- on **camt.109.001.01/Cheque/Payee/PostalAddress/PostCode**
Type changed to: CBPR_RestrictedFINXMax16Text_Extended on page 111

5.51.11 TownName

XML Tag: TwnNm

Presence: [0..1]

Definition: Name of a built-up area, with defined boundaries, and a local government.

Datatype: "CBPR_RestrictedFINXMax35Text_Extended" on page 113

Usage Guideline details

- on camt.109.001.01/Cheque/DrawerAgent/FinancialInstitutionIdentification/PostalAddress/TownName

This element is now mandatory, the minimum occurrence has been changed to : 1

- on camt.109.001.01/Cheque/Payee/PostalAddress/TownName

This element is now mandatory, the minimum occurrence has been changed to : 1

- on camt.109.001.01/Cheque/DrawerAgent/FinancialInstitutionIdentification/PostalAddress/TownName

Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 113

- on camt.109.001.01/Cheque/Payee/PostalAddress/TownName

Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 113

5.51.12 TownLocationName

XML Tag: TwnLctnNm

Presence: [0..1]

Definition: Specific location name within the town.

Datatype: "CBPR_RestrictedFINXMax35Text_Extended" on page 113

Usage Guideline details

- on camt.109.001.01/Cheque/Payee/PostalAddress/TownLocationName

Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 113

- on camt.109.001.01/Cheque/DrawerAgent/FinancialInstitutionIdentification/PostalAddress/TownLocationName

Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 113

5.51.13 DistrictName

XML Tag: DstrctNm

Presence: [0..1]

Definition: Identifies a subdivision within a country sub-division.

Datatype: "CBPR_RestrictedFINXMax35Text_Extended" on page 113

Usage Guideline details

- on camt.109.001.01/Cheque/DrawerAgent/FinancialInstitutionIdentification/PostalAddress/DistrictName

Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 113

- on camt.109.001.01/Cheque/Payee/PostalAddress/DistrictName

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 113](#)

5.51.14 CountrySubDivision

XML Tag: CtrySubDvsn

Presence: [0..1]

Definition: Identifies a subdivision of a country such as state, region, county.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 113](#)

Usage Guideline details

- **on camt.109.001.01/Cheque/DrawerAgent/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision**

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 113](#)

- **on camt.109.001.01/Cheque/Payee/PostalAddress/CountrySubDivision**

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 113](#)

5.51.15 Country

XML Tag: Ctry

Presence: [0..1]

Definition: Nation with its own government.

Datatype: ["CountryCode" on page 116](#)

Usage Guideline details

- **on camt.109.001.01/Cheque/DrawerAgent/FinancialInstitutionIdentification/PostalAddress/Country**

This element is now mandatory, the minimum occurrence has been changed to : 1

- **on camt.109.001.01/Cheque/Payee/PostalAddress/Country**

This element is now mandatory, the minimum occurrence has been changed to : 1

5.51.16 AddressLine

XML Tag: AdrLine

Presence: [0..7]

Definition: Information that locates and identifies a specific address, as defined by postal services, presented in free format text.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended" on page 114](#)

Usage Guideline details

- **on camt.109.001.01/Cheque/Payee/PostalAddress/AddressLine**
This element has change repeatability, the maximum occurrence has been changed to : 2
- **on camt.109.001.01/Cheque/DrawerAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine**
This element has change repeatability, the maximum occurrence has been changed to : 2
- **on camt.109.001.01/Cheque/Payee/PostalAddress/AddressLine**
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 114
- **on camt.109.001.01/Cheque/DrawerAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine**
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 114

5.52 ProxyAccountIdentification1

Definition: Information related to a proxy identification of the account.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		100
	Identification	<Id>		[1..1]		101

Used in element(s)

"Proxy" on page 32

5.52.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Type of the proxy identification.

The **Tp** block contains the following elements (see datatype "ProxyAccountType1Choice" on page 102 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		102
	Proprietary	<Prtry>	Or}	[1..1]		102

5.52.2 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification used to indicate the account identification under another specified name.

Datatype: "Max2048Text" on page 126

5.53 ProxyAccountIdentification1__1

Definition: Information related to a proxy identification of the account.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		101
	Identification	<Id>		[1..1]		101

Used in element(s)

"Proxy" on page 35

5.53.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Type of the proxy identification.

The **Tp** block contains the following elements (see datatype "ProxyAccountType1Choice__1" on page 102 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		103
	Proprietary	<Prtry>	Or}	[1..1]		103

Usage Guideline details

- on camt.109.001.01/Cheque/DrawerAgentAccount/Proxy/Type

This element is now mandatory, the minimum occurrence has been changed to : 1

5.53.2 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification used to indicate the account identification under another specified name.

Datatype: "CBPR_RestrictedFINXMax320Text_Extended" on page 112

Usage Guideline details

- on **camt.109.001.01/Cheque/DrawerAgentAccount/Proxy/Identification**
Type changed to: CBPR_RestrictedFINXMax320Text_Extended on page 112

5.54 ProxyAccountType1Choice

Definition: Specifies the scheme used for the identification of an account alias.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		102
	Proprietary	<Prtry>	Or}	[1..1]		102

Used in element(s)

"Type" on page 100

5.54.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalProxyAccountType1Code" on page 122

5.54.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 127

5.55 ProxyAccountType1Choice__1

Definition: Specifies the scheme used for the identification of an account alias.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		103
	Proprietary	<Prtry>	Or}	[1..1]		103

Used in element(s)

"Type" on page 101

5.55.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalProxyAccountType1Code" on page 122

5.55.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 113

Usage Guideline details

- on camt.109.001.01/Cheque/DrawerAgentAccount/Proxy/Type/Proprietary
Type changed to: CBPR_RestrictedFINXMax35Text on page 113

5.56 SupplementaryData1

Definition: Additional information that can not be captured in the structured fields and/or any other specific block.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PlaceAndName	<PlcAndNm>		[0..1]		104
	Envelope	<Envlp>		[1..1]		104

Rules

R11 SupplementaryDataRule

This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

Error handling: Undefined

Used in element(s)

"SupplementaryData" on page 16

5.56.1 PlaceAndName

XML Tag: PlcAndNm

Presence: [0..1]

Definition: Unambiguous reference to the location where the supplementary data must be inserted in the message instance.

In the case of XML, this is expressed by a valid XPath.

Datatype: "Max350Text" on page 126

5.56.2 Envelope

XML Tag: Envlp

Presence: [1..1]

Definition: Technical element wrapping the supplementary data.

6 Message Datatypes

Note The following chapter identifies the datatypes that are used in the message.

6.1 ActiveCurrencyCode

Definition: A code allocated to a currency by a Maintenance Agency under an international identification scheme as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds".

Type: CodeSet

Format

pattern [A-Z]{3,3}

Rules

R2 ActiveCurrency ✓

The currency code must be a valid active currency code, not yet withdrawn on the day the message containing the currency is exchanged. Valid active currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and are not yet withdrawn on the day the message containing the Currency is exchanged.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00005
- *Error Text:* Invalid currency code

Used in attribute(s)

"CBPR_Amount" on page 108

Restricts

"ParentCurrencyCode" on page 128

6.2 ActiveOrHistoricCurrencyCode

Definition: A code allocated to a currency by a Maintenance Agency under an international identification scheme, as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds".

Type: CodeSet

Format

pattern [A-Z]{3,3}

Rules**R8 ActiveOrHistoricCurrency ✓**

The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00006
- *Error Text:* Invalid currency code.

Used in element(s)

["Currency" on page 32](#), ["Currency" on page 34](#)

Restricts

["ParentCurrencyCode" on page 128](#)

6.3 AddressType2Code

Definition: Specifies the type of address.

Type: CodeSet

Code	Name	Definition
ADDR	Postal	Address is the complete postal address.
BIZZ	Business	Address is the business address.
DLVY	DeliveryTo	Address is the address to which delivery is to take place.
HOME	Residential	Address is the home address.
MLTO	MailTo	Address is the address to which mail is sent.
PBOX	POBox	Address is a postal office (PO) box.

Used in element(s)

["Code" on page 20](#)

Restricts

["AddressTypeCode" on page 106](#)

6.4 AddressTypeCode

Definition: Specifies the type of address.

Type: CodeSet

Code	Name	Definition
ADDR	Postal	Address is the complete postal address.
BIZZ	Business	Address is the business address.
DLVY	DeliveryTo	Address is the address to which delivery is to take place.
HOME	Residential	Address is the home address.
MLTO	MailTo	Address is the address to which mail is sent.
PBOX	POBox	Address is a postal office (PO) box.

Is restricted by

["AddressType2Code" on page 106](#)

6.5 AnyBICDec2014Identifier

Definition: Code allocated to a financial or non-financial institution by the ISO 9362 Registration Authority, as described in ISO 9362: 2014 - "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Type: IdentifierSet

Format

pattern [A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}([A-Z0-9]{3,3}){0,1}

Rules

R10 AnyBIC ✓

Only a valid Business identifier code is allowed. Business identifier codes for financial or non-financial institutions are registered and published by the ISO 9362 Registration Authority in the ISO directory of BICs, and consists of eight (8) or eleven (11) contiguous characters.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00008
- *Error Text:* Invalid BIC.

Used in element(s)

["AnyBIC" on page 72](#), ["AnyBIC" on page 74](#)

6.6 BICFIDec2014Identifier

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362: 2014 - "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Type: IdentifierSet

Format

pattern [A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}([A-Z0-9]{3,3}){0,1}

Rules**R12 BICFI ✓**

Valid BICs for financial institutions are registered and published by the ISO 9362 Registration Authority in the ISO directory of BICs, and consist of eight (8) or eleven (11) contiguous characters.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00001
- *Error Text:* Invalid FI BIC.

Used in element(s)

"BICFI" on page 57, "BICFI" on page 54

6.7 CBPR_Amount

Definition:

This datatype has been created by the Publisher of this Usage Guideline.

Type: Amount

This data type must be used with the following XML Attributes:

Attribute	Tag	Datatype
Currency	Ccy	"ActiveCurrencyCode" on page 105

Format

fractionDigits 5
 minInclusive 0
 totalDigits 14

Rules**R1 CurrencyAmount**

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00007

– *Error Text:* Invalid currency code or too many decimal digits

Used in element(s)

"Amount" on page 39

6.8 CBPR_ChequeCancellationOrStopStatusCode

Definition: Status, in a coded form, as published in an external code set.

This datatype has been created by the Publisher of this Usage Guideline.

Type: CodeSet

Code	Name	Definition
ACCR	AcceptedCancellationOrStopChequeRequest	Cheque cancellation request or request to stop the cheque is accepted.
RJCR	RejectedCancellationOrStopChequeRequest	Cheque cancellation request or request to stop the cheque is rejected.

Used in element(s)

"Code" on page 43

6.9 CBPR_Date

Definition: This Type restricts the base ISODate to YYYY (exactly 4 digits for the Year) and does not allow use of UTC offset or Zulu indicator with a date.

This datatype has been created by the Publisher of this Usage Guideline.

Type: Date

Format

pattern [0-9]{4}-[0-9]{2}-[0-9]{2}

Used in element(s)

"BirthDate" on page 52, "Date" on page 50, "IssueDate" on page 38, "StaleDate" on page 39

6.10 CBPR_DateTime

Definition: A particular point in the progression of time defined by a mandatory date and a mandatory time component, expressed in local time with UTC offset format (YYYY-MM-DDThh:mm:ss.sss+/-hh:mm).

This representation is defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Note on the time format:

1) beginning / end of calendar day

00:00:00 = the beginning of a calendar day

24:00:00 = the end of a calendar day

2) fractions of second in time format

Decimal fractions of seconds may be included. In this case, the involved parties shall agree on the maximum number of digits that are allowed.

Example: 2020-07-16T19:20:30.45+01:00

This datatype has been created by the Publisher of this Usage Guideline.

Type: DateTime

Format

pattern `.*(\+|-)((0[0-9])|(1[0-4])):[0-5][0-9]`

Used in element(s)

["CreationDate" on page 29](#), ["CreationDateTime" on page 70](#)

6.11 CBPR_RestrictedFINXMax140Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 140 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	140
minLength	1
pattern	<code>[0-9a-zA-Z/\-!\?:\(\)\.,'\+]+</code>

Used in element(s)

["AdditionalInformation" on page 44](#)

6.12 CBPR_RestrictedFINXMax140Text_Extended

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 140 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . that is extended to support the following additional characters `!#$%&*='^_`{}~";<>@[\]`

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	140
minLength	1
pattern	[0-9a-zA-Z/\-!\?:(\)\.,\'+ !#\$%&!*^_`{ }\~";<>@[\\]]+

Used in element(s)

"Name" on page 55, "Name" on page 83

6.13 CBPR_RestrictedFINXMax16Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 16 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	16
minLength	1
pattern	[0-9a-zA-Z/\-!\?:(\)\.,\'+]+

Used in element(s)

"ChequeNumber" on page 38, "MessageIdentification" on page 69

6.14 CBPR_RestrictedFINXMax16Text_Extended

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 16 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . that is extended to support the following additional characters !#\$%&!*^_`{|}\~";<>@[\\]

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	16
minLength	1
pattern	[0-9a-zA-Z/\-!\?:(\)\.,\'+ !#\$%&!*^_`{ }\~";<>@[\\]]+

Used in element(s)

"BuildingNumber" on page 95, "PostBox" on page 96, "PostCode" on page 97

6.15 CBPR_RestrictedFINXMax28Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 28 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	28
minLength	1
pattern	[0-9a-zA-Z/\-?:(\)\.,'+]+

Used in element(s)

"MemberIdentification" on page 47

6.16 CBPR_RestrictedFINXMax320Text_Extended

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 320 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . that is extended to support the following additional characters !#\$%&*^_`{|}~";<>@[\\]

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	320
minLength	1
pattern	[0-9a-zA-Z/\-?:(\)\.,'+ !#\$%&*^_`{ }~";<>@[\\]]+

Used in element(s)

"Identification" on page 101

6.17 CBPR_RestrictedFINXMax34Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 34 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . and disable the use of slash "/" at the beginning and end of line and double slash "/" within the line.

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	34
minLength	1
pattern	<code>([0-9a-zA-Z\-\!\?:\(\)\.,\'+]([0-9a-zA-Z\-\!\?:\(\)\.,\'+]*([0-9a-zA-Z\-\!\?:\(\)\.,\'+])?)*)</code>

Used in element(s)

["Identification" on page 62](#)

6.18 CBPR_RestrictedFINXMax35Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 35 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	35
minLength	1
pattern	<code>[0-9a-zA-Z\-\!\?:\(\)\.,\'+]+</code>

Used in element(s)

["BusinessMessageIdentifier" on page 27](#), ["BusinessService" on page 28](#), ["Identification" on page 66](#), ["Identification" on page 68](#), ["InstructionIdentification" on page 37](#), ["Issuer" on page 62](#), ["Issuer" on page 66](#), ["Issuer" on page 69](#), ["MessageDefinitionIdentifier" on page 28](#), ["OriginalInstructionIdentification" on page 38](#), ["Proprietary" on page 20](#), ["Proprietary" on page 36](#), ["Proprietary" on page 103](#), ["Proprietary" on page 76](#), ["Proprietary" on page 89](#)

6.19 CBPR_RestrictedFINXMax35Text_Extended

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 35 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . that is extended to support the following additional characters `!#$%&*^_`{}~";<>@[]`

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	35
minLength	1

pattern [0-9a-zA-Z/\-!\?:\(\)\.,'+ !#\$%&!*^_`{|}\}~";<>@\[\]\]]+

Used in element(s)

"BuildingName" on page 96, "CityOfBirth" on page 53, "CountrySubDivision" on page 99, "DistrictName" on page 98, "ProvinceOfBirth" on page 52, "TownLocationName" on page 98, "TownName" on page 97

6.20 CBPR_RestrictedFINXMax70Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 70 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	70
minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,'+]+

Used in element(s)

"Name" on page 34

6.21 CBPR_RestrictedFINXMax70Text_Extended

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 70 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . that is extended to support the following additional characters !#\$%&*^_`{|}\}~";<>@[

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	70
minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,'+ !#\$%&*^_`{ }\}~";<>@\[\]\]]+

Used in element(s)

"AddressLine" on page 99, "Department" on page 94, "Floor" on page 96, "Room" on page 97, "Street-Name" on page 95, "SubDepartment" on page 94

6.22 ChequePartyRole1Code

Definition: Specifies the roles of the parties linked to a cheque.

Type: CodeSet

Code	Name	Definition
DWEA	DraweeAgent	Specifies the agent on which a cheque is drawn, that is the financial institution that services the account of the payee that issued the cheque.
DWRA	DrawerAgent	Specifies the agent servicing the account of the cheque payer.
PAYE	Payee	Party that receives an amount of money as specified in the cheque.
PAYR	Payer	Party that issues a cheque ordering the drawee agent to pay a specific amount, upon demand, to the payee.

Used in element(s)

["Originator" on page 43](#)

Restricts

["ChequePartyRoleCode" on page 115](#)

6.23 ChequePartyRoleCode

Definition: Specifies the roles of the parties linked to a cheque.

Type: CodeSet

Format

maxLength	4
minLength	1

Code	Name	Definition
DWEA	DraweeAgent	Specifies the agent on which a cheque is drawn, that is the financial institution that services the account of the payee that issued the cheque.
DWRA	DrawerAgent	Specifies the agent servicing the account of the cheque payer.
PAYE	Payee	Party that receives an amount of money as specified in the cheque.
PAYR	Payer	Party that issues a cheque ordering the drawee agent to pay a specific amount, upon demand, to the payee.

Is restricted by

["ChequePartyRole1Code" on page 114](#)

6.24 CopyDuplicate1Code

Definition: Specifies if this document is a copy, a duplicate, or a duplicate of a copy.

Type: CodeSet

Code	Name	Definition
CODU	CopyDuplicate	Message is being sent as a copy to a party other than the account owner, for information purposes and the message is a duplicate of a message previously sent.
COPY	Copy	Message is being sent as a copy to a party other than the account owner, for information purposes.
DUPL	Duplicate	Message is for information/confirmation purposes. It is a duplicate of a message previously sent.

Used in element(s)

"CopyDuplicate" on page 29

Restricts

"CopyDuplicateCode" on page 116

6.25 CopyDuplicateCode

Definition: Specifies if this document is a copy, a duplicate, or a duplicate of a copy.

Type: CodeSet

Code	Name	Definition
CODU	CopyDuplicate	Message is being sent as a copy to a party other than the account owner, for information purposes and the message is a duplicate of a message previously sent.
COPY	Copy	Message is being sent as a copy to a party other than the account owner, for information purposes.
DUPL	Duplicate	Message is for information/confirmation purposes. It is a duplicate of a message previously sent.

Is restricted by

"CopyDuplicate1Code" on page 115

6.26 CountryCode

Definition: Code to identify a country, a dependency, or another area of particular geopolitical interest, on the basis of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

Type: CodeSet

Format

pattern [A-Z]{2,2}

Rules

R9 Country ✓

The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00004
- *Error Text:* Invalid Country Code.

Used in element(s)

"Country" on page 92, "Country" on page 99, "CountryOfBirth" on page 52, "CountryOfBirth" on page 53, "CountryOfResidence" on page 82, "CountryOfResidence" on page 85

6.27 DecimalNumber

Definition: Number of objects represented as a decimal number, for example 0.75 or 45.6.

Type: Quantity

Format

fractionDigits	17
totalDigits	18

Used in element(s)

"ControlSum" on page 70

6.28 Exact4AlphaNumericText

Definition: Specifies an alphanumeric string with a length of 4 characters.

Type: Text

Format

pattern [a-zA-Z0-9]{4}

Used in element(s)

"Identification" on page 64

6.29 ExternalAccountIdentification1Code

Definition: Specifies the external account identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

["Code" on page 19](#), ["Code" on page 19](#)

Restricts

["ExternalAccountIdentificationCode" on page 118](#)

6.30 ExternalAccountIdentificationCode

Definition: Specifies the external account identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

["ExternalAccountIdentification1Code" on page 117](#)

6.31 ExternalCashAccountType1Code

Definition: Specifies the nature, or use, of the cash account in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

["Code" on page 35](#), ["Code" on page 36](#)

Restricts

["ExternalCashAccountTypeCode" on page 119](#)

6.32 ExternalCashAccountTypeCode

Definition: Specifies the nature, or use, of the cash account in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

["ExternalCashAccountType1Code" on page 118](#)

6.33 ExternalClearingSystemIdentification1Code

Definition: Specifies the clearing system identification code, as published in an external clearing system identification code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	5
minLength	1

Used in element(s)

["Code" on page 45](#)

Restricts

["ExternalClearingSystemIdentificationCode" on page 120](#)

6.34 ExternalClearingSystemIdentificationCode

Definition: Specifies the clearing system identification code, as published in an external clearing system identification code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	5
minLength	1

Is restricted by

"ExternalClearingSystemIdentification1Code" on page 119

6.35 ExternalFinancialInstitutionIdentification1Code

Definition: Specifies the external financial institution identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 53

Restricts

"ExternalFinancialInstitutionIdentificationCode" on page 120

6.36 ExternalFinancialInstitutionIdentificationCode

Definition: Specifies the external financial institution identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalFinancialInstitutionIdentification1Code" on page 120

6.37 ExternalOrganisationIdentification1Code

Definition: Specifies the external organisation identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 75, "Code" on page 75

Restricts

"ExternalOrganisationIdentificationCode" on page 121

6.38 ExternalOrganisationIdentificationCode

Definition: Specifies the external organisation identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalOrganisationIdentification1Code" on page 121

6.39 ExternalPersonIdentification1Code

Definition: Specifies the external person identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

["Code" on page 88](#), ["Code" on page 89](#)

Restricts

["ExternalPersonIdentificationCode" on page 122](#)

6.40 ExternalPersonIdentificationCode

Definition: Specifies the external person identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

["ExternalPersonIdentification1Code" on page 122](#)

6.41 ExternalProxyAccountType1Code

Definition: Specifies the external proxy account type code, as published in the proxy account type external code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

["Code" on page 102](#), ["Code" on page 103](#)

Restricts

["ExternalProxyAccountTypeCode" on page 123](#)

6.42 ExternalProxyAccountTypeCode

Definition: Specifies the external proxy account type code, as published in the proxy account type external code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

["ExternalProxyAccountType1Code" on page 122](#)

6.43 IBAN2007Identifier

Definition: The International Bank Account Number is a code used internationally by financial institutions to uniquely identify the account of a customer at a financial institution as described in the 2007 edition of the ISO 13616 standard "Banking and related financial services - International Bank Account Number (IBAN)" and replaced by the more recent edition of the standard.

Type: IdentifierSet

Format

pattern	[A-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}
---------	---------------------------------------

Rules
R6 IBAN ✓

A valid IBAN consists of all three of the following components: Country Code, check digits and BBAN.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00003

– *Error Text:* Invalid IBAN format or invalid check digits.

Used in element(s)

"IBAN" on page 17, "IBAN" on page 18

6.44 ISODate

Definition: A particular point in the progression of time in a calendar year expressed in the YYYY-MM-DD format. This representation is defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Type: Date

Used in element(s)

"BirthDate" on page 51

6.45 ISODateTime

Definition: A particular point in the progression of time defined by a mandatory date and a mandatory time component, expressed in either UTC time format (YYYY-MM-DDThh:mm:ss.sssZ), local time with UTC offset format (YYYY-MM-DDThh:mm:ss.sss+/-hh:mm), or local time format (YYYY-MM-DDThh:mm:ss.sss). These representations are defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Note on the time format:

1) beginning / end of calendar day

00:00:00 = the beginning of a calendar day

24:00:00 = the end of a calendar day

2) fractions of second in time format

Decimal fractions of seconds may be included. In this case, the involved parties shall agree on the maximum number of digits that are allowed.

Type: DateTime

Used in element(s)

"DateTime" on page 51

6.46 LEIIdentifier

Definition: Legal Entity Identifier is a code allocated to a party as described in ISO 17442 "Financial Services - Legal Entity Identifier (LEI)".

Type: IdentifierSet

Format

pattern [A-Z0-9]{18,18}[0-9]{2,2}

Used in element(s)

["LEI" on page 25](#), ["LEI" on page 72](#), ["LEI" on page 58](#), ["LEI" on page 55](#), ["LEI" on page 74](#)

6.47 Max128Text

Definition: Specifies a character string with a maximum length of 128 characters.

Type: Text

Format

maxLength	128
minLength	1

Used in element(s)

["Identification" on page 76](#)

6.48 Max140Text

Definition: Specifies a character string with a maximum length of 140 characters.

Type: Text

Format

maxLength	140
minLength	1

Used in element(s)

["Name" on page 25](#), ["Name" on page 48](#), ["Name" on page 80](#), ["Name" on page 58](#)

6.49 Max15NumericText

Definition: Specifies a numeric string with a maximum length of 15 digits.

Type: Text

Format

pattern	[0-9]{1,15}
---------	-------------

Used in element(s)

["NumberOfCheques" on page 70](#)

6.50 Max16Text

Definition: Specifies a character string with a maximum length of 16 characters.

Type: Text

Format

maxLength	16
minLength	1

Used in element(s)

"BuildingNumber" on page 91, "PostBox" on page 91, "PostCode" on page 92

6.51 Max2048Text

Definition: Specifies a character string with a maximum length of 2048 characters.

Type: Text

Format

maxLength	2048
minLength	1

Used in element(s)

"EmailAddress" on page 49, "Identification" on page 71, "Identification" on page 101

6.52 Max34Text

Definition: Specifies a character string with a maximum length of 34 characters.

Type: Text

Format

maxLength	34
minLength	1

Used in element(s)

"Identification" on page 61

6.53 Max350Text

Definition: Specifies a character string with a maximum length of 350 characters.

Type: Text

Format

maxLength	350
minLength	1

Used in element(s)

"PlaceAndName" on page 104, "Registry" on page 71

6.54 Max35Text

Definition: Specifies a character string with a maximum length of 35 characters.

Type: Text

Format

maxLength	35
minLength	1

Used in element(s)

"BuildingName" on page 91, "CityOfBirth" on page 51, "CountrySubDivision" on page 92, "DistrictName" on page 92, "EmailPurpose" on page 49, "Identification" on page 24, "Identification" on page 63, "Identification" on page 65, "Identification" on page 67, "Issuer" on page 61, "Issuer" on page 63, "Issuer" on page 64, "Issuer" on page 65, "Issuer" on page 67, "JobTitle" on page 49, "Proprietary" on page 19, "Proprietary" on page 36, "Proprietary" on page 45, "Proprietary" on page 54, "Proprietary" on page 75, "Proprietary" on page 88, "Proprietary" on page 102, "Proprietary" on page 43, "ProvinceOfBirth" on page 51, "Responsibility" on page 49, "SchemeName" on page 64, "TownLocationName" on page 92, "TownName" on page 92

6.55 Max4Text

Definition: Specifies a character string with a maximum length of 4 characters.

Type: Text

Format

maxLength	4
minLength	1

Used in element(s)

"ChannelType" on page 76

6.56 Max70Text

Definition: Specifies a character string with a maximum length of 70characters.

Type: Text

Format

maxLength	70
minLength	1

Used in element(s)

"AddressLine" on page 93, "Department" on page 49, "Department" on page 90, "Floor" on page 91, "Name" on page 32, "Room" on page 92, "StreetName" on page 91, "SubDepartment" on page 91

6.57 NamePrefix2Code

Definition: Specifies the terms used to formally address a person.

Type: CodeSet

Code	Name	Definition
DOCT	Doctor	Title of the person is Doctor or Dr.
MADM	Madam	Title of the person is Madam.
MIKS	GenderNeutral	Title of the person is gender neutral (Mx).
MISS	Miss	Title of the person is Miss.
MIST	Mister	Title of the person is Mister or Mr.

Used in element(s)

["NamePrefix" on page 48](#)

Restricts

["NamePrefixCode" on page 128](#)

6.58 NamePrefixCode

Definition: Specifies the terms used to formally address a person.

Type: CodeSet

Code	Name	Definition
DOCT	Doctor	Title of the person is Doctor or Dr.
MADM	Madam	Title of the person is Madam.
MIKS	GenderNeutral	Title of the person is gender neutral (Mx).
MISS	Miss	Title of the person is Miss.
MIST	Mister	Title of the person is Mister or Mr.

Is restricted by

["NamePrefix2Code" on page 128](#)

6.59 ParentCurrencyCode

Definition: Code allocated to a currency, by a maintenance agency, under an international identification scheme as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds". Valid currency codes are registered with the ISO 4217 Maintenance Agency, and consist of three contiguous letters.

Type: CodeSet

Format

pattern [A-Z]{3,3}

Is restricted by

["ActiveCurrencyCode" on page 105](#), ["ActiveOrHistoricCurrencyCode" on page 105](#)

6.60 PhoneNumber

Definition: The collection of information which identifies a specific phone or FAX number as defined by telecom services.

It consists of a "+" followed by the country code (from 1 to 3 characters) then a "-" and finally, any combination of numbers, "(", ")", "+" and "-" (up to 30 characters).

Type: Text

Format

pattern \+[0-9]{1,3}-[0-9()+-]{1,30}

Used in element(s)

["FaxNumber" on page 49](#), ["MobileNumber" on page 48](#), ["PhoneNumber" on page 48](#)

6.61 PreferredContactMethod1Code

Definition: Preferred method used to reach the individual contact within an organisation.

Type: CodeSet

Code	Name	Definition
CELL	MobileOrCellPhone	Preferred method used to reach the contact is per mobile or cell phone.
FAXX	Fax	Preferred method used to reach the contact is per fax.
LETT	Letter	Preferred method used to reach the contact is per letter.
MAIL	Email	Preferred method used to reach the contact is per email.
PHON	Phone	Preferred method used to reach the contact is per phone.

Used in element(s)

["PreferredMethod" on page 50](#)

Restricts

["PreferredContactMethodCode" on page 129](#)

6.62 PreferredContactMethodCode

Definition: Preferred method used to reach the individual contact within an organisation.

Type: CodeSet

Code	Name	Definition
CELL	MobileOrCellPhone	Preferred method used to reach the contact is per mobile or cell phone.
FAXX	Fax	Preferred method used to reach the contact is per fax.
LETT	Letter	Preferred method used to reach the contact is per letter.
MAIL	Email	Preferred method used to reach the contact is per email.
ONLI	Online	Preferred method used to reach the contact is online.
PHON	Phone	Preferred method used to reach the contact is per phone.

Is restricted by

"PreferredContactMethod1Code" on page 129

6.63 Priority2Code

Definition: Specifies the priority level of an event.

Type: CodeSet

Code	Name	Definition
HIGH	High	Priority level is high.
NORM	Normal	Priority level is normal.

Used in element(s)

"Priority" on page 30

Restricts

"PriorityCode" on page 130

6.64 PriorityCode

Definition: Specifies the priority level of an event.

Type: CodeSet

Code	Name	Definition
HIGH	High	Priority level is high.
LOWW	Low	Priority level is low.
NORM	Normal	Priority level is normal.

Code	Name	Definition
URGT	Urgent	Priority level is urgent (highest priority possible).

Is restricted by

"Priority2Code" on page 130

6.65 UnicodeChartsCode

*Definition:*odelist containing the names of the UNICODE code block name as specified on <http://unicode.org/Public/UNIDATA/Blocks.txt>.

Type: CodeSet

Rules

R4 ValidationByTable

Error handling: Undefined

Used in element(s)

"CharacterSet" on page 26

6.66 YesNoIndicator

Definition: Indicates a "Yes" or "No" type of answer for an element.

Type: Indicator

Meaning When True: Yes

Meaning When False: No

Used in element(s)

"PossibleDuplicate" on page 29

Legal Notices

Copyright

S.W.I.F.T. SC © 2026. All rights reserved.

This material is a component of MyStandards, the Swift collaborative Web application used to manage standards definitions and industry usage. It can only be used and distributed in accordance with MyStandards Terms of Use.

Unless otherwise agreed in writing with S.W.I.F.T. SC, you have no right to:

- authorise external end users to use this component for other purposes than their internal use.
- remove, alter, cover, obfuscate or cancel from view any copyright or other proprietary rights notices appearing in this physical medium.
- re-sell or authorise another party e.g. software and service providers, to re-sell this component.

Confidentiality

This publication may contain Swift or third-party confidential information. Only disclose it outside your organisation in accordance with MyStandards Terms of Use and your related license rights.

This component is provided 'AS IS'. Swift does not give and excludes any express or implied warranties with respect to this component such as but not limited to any guarantee as to its quality, supply or availability.

Any and all rights, including title, ownership rights, copyright, trademark, patents, and any other intellectual property rights of whatever nature in this component will remain the exclusive property of Swift or its licensors.

Trademarks and Patents

Swift is the trade name of S.W.I.F.T. SC. The following are registered trademarks of Swift: 3SKey, Innotribe, MyStandards, Sibos, Swift, SwiftNet, the Standards Forum logo, the Swift logo, Swift GPI with logo, the Swift GPI logo, and UETR. Other product, service, or company names in this publication are trade names, trademarks, or registered trademarks of their respective owners.