



Usage Guideline

CBPRPlus- pain.008.001.08_FIToFICustomer- DirectDebitInitiation

CBPRPlus SR2026 (Combined)

This document describes a usage guideline restricting the base message **MX pain.008.001.08**. You can also consult [this information online](#).

Published by Cross Border Payments and Reporting Plus (CBPR+) and generated by [MyStandards](#).

20 February 2026

Table of Contents

Message Functionality	3
1 Restriction summary	4
2 Structure	6
3 ISO 20022 Rules	9
4 Message Building Blocks	10
5 Message Components	19
6 Message Datatypes	192
Legal Notices	237

Message Functionality

This Usage Guideline is based on the pain.008.001.08 message definition. In addition, Cross Border Payments and Reporting Plus (CBPR+) has defined usage of BusinessApplicationHeaderV02 as mandatory. The following section will be dealing with the pain.008.001.08 only.

Overview

Principles:

1. The CustomerDirectDebitInitiation message is sent by the initiating party to the forwarding agent which acts as a concentrating financial institution. It will forward the CustomerDirectDebitInitiation message to the creditor agent.
2. Character Set:
All proprietary and Text fields EXCLUDING Name and Address for all actors and Related Remittance Information and Remittance are limited to the FIN-X-Character set.

All Name and Address for all actors, Related Remittance Information and Remittance Information (structured and unstructured), Email Address where included as part of a proxy element are extended to support the following additional characters:

!#\$%&*='^_`{|}~";<>@[\\]

< is replaced with <
> is replaced with >

Collection Description

This is the Cross Border Payment and Reporting Collection for SR2026.
These are FINAL usage guidelines.
The usage guidelines are available on the CBPR+ SR2026 Readiness Portal for testing.

The Collection contains:
30 Usage Guidelines that will be live on the network as of November 2026.

Outline

The CBPRPlus SR2026 (Combined) / CBPRPlus-pain.008.001.08_FIToFICustomerDirectDebitInitiation message is composed of 3 building blocks

- a. GroupHeader
Set of characteristics shared by all individual transactions included in the message.
- b. PaymentInformation
Set of characteristics that apply to the credit side of the payment transactions included in the direct debit transaction initiation.
- c. SupplementaryData
Additional information that cannot be captured in the structured elements and/or any other specific block.

1 Restriction summary

This Usage Guideline restricts the pain.008.001.08 message. This also includes the BusinessApplicationHeaderV02.

Restriction Type	See page
Removed elements	9, 13, 14, 18, 29, 29, 29, 29, 29, 29, 31, 31, 31, 31, 32, 32, 33, 37, 38, 39, 40, 40, 42, 43, 43, 43, 43, 43, 43, 67, 74, 74, 76, 77, 78, 78, 78, 78, 80, 80, 80, 80, 81, 81, 81, 81, 82, 82, 82, 82, 99, 109, 109, 109, 109, 111, 111, 111, 111, 111, 111, 112, 112, 112, 112, 112, 112, 114, 114, 114, 114, 116, 116, 116, 116, 119, 124, 124, 124, 124, 124, 124, 124, 124, 124, 128, 129, 129, 129, 132, 132, 134, 141, 141, 141, 141, 141, 141, 141, 141, 141, 141, 141, 142, 143, 143, 143, 143, 143, 143, 143, 143, 143, 143, 143, 143, 143, 144, 144, 144, 144, 144, 144, 149, 199
Make mandatory	12, 44, 44, 44, 45, 45, 45, 45, 50, 75, 79, 79, 79, 79, 92, 92, 94, 94, 94, 94, 94, 94, 94, 94, 94, 95, 95, 95, 96, 96, 96, 96, 96, 96, 96, 97, 97, 97, 97, 97, 100, 108, 108, 109, 109, 120, 146, 146, 146, 146, 146, 146, 146, 146, 146, 146, 146, 146, 146, 147, 147, 147, 147, 147, 148, 148, 148, 148, 148, 148, 148, 148, 148, 148, 148, 148, 149, 149, 149, 149, 149, 149, 152, 152, 152, 152, 152, 152, 152, 152
Reduce Multiplicity	15, 17, 110, 110, 110, 110, 110, 110, 110, 110, 110, 110, 136, 136, 138, 139, 139, 140, 140, 140, 140, 140, 140, 140, 149, 149, 150, 150, 150, 150, 150, 150, 150, 150, 150, 150, 150, 150, 150, 151, 151, 151, 164
Ignore	n.a.
Text rules	15, 35, 36, 36, 40, 61, 64, 75, 75, 77, 77, 77, 77, 78, 98, 121, 121, 121, 121, 121, 122, 122, 122, 122, 122, 122, 122, 125, 164
Conditional rules	n.a.
Formal rules	10, 16, 16, 18, 28, 28, 61, 62, 64, 86, 87, 100, 130, 171, 171
Fixed values	12, 12
Truncates	n.a.
Comments	n.a.
Annotations	n.a.

Restriction Type	See page
Changed datatypes	11, 13, 14, 25, 35, 36, 36, 37, 38, 46, 46, 46, 46, 53, 53, 53, 53, 53, 53, 53, 53, 53, 54, 54, 54, 55, 55, 55, 55, 55, 55, 55, 56, 58, 70, 87, 98, 103, 104, 105, 125, 130, 155, 168, 180, 183, 186, 187, 187, 187
Extensions	n.a.
Synonyms	n.a.

2 Structure

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	<i>BusinessApplicationHeaderV02</i>	<AppHdr>		[1..1]		
	CharacterSet	<CharSet>		[0..1]		10
	From	<Fr>		[1..1]		10
	OrganisationIdentification	<OrgId>	{Or	[1..1]		115
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		116
	To	<To>		[1..1]		11
	OrganisationIdentification	<OrgId>	{Or	[1..1]		115
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		116
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]		11
	MessageDefinitionIdentifier	<MsgDefIdr>		[1..1]		12
	BusinessService	<BizSvc>		[0..1]	 	12
	MarketPractice	<MktPrctc>		[0..1]		12
	Registry	<Regy>		[1..1]		101
	Identification	<Id>		[1..1]		101
	CreationDate	<CreDt>		[1..1]		13
	BusinessProcessingDate	<BizPrctgDt>		[0..1]		13
	CopyDuplicate	<CpyDplct>		[0..1]		13
	PossibleDuplicate	<PssblDplct>		[0..1]		14
	Priority	<Prty>		[0..1]		14
	Signature	<Sgntr>		[0..1]		14
	Related	<Rltd>		[0..*]	 R[0..1]	14
	CharacterSet	<CharSet>		[0..1]		34
	From	<Fr>		[1..1]		34
	To	<To>		[1..1]		34
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]		35
	MessageDefinitionIdentifier	<MsgDefIdr>		[1..1]		35
	BusinessService	<BizSvc>		[0..1]		36
	CreationDate	<CreDt>		[1..1]		36

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CopyDuplicate	<CpyDplct>		[0..1]		37
	PossibleDuplicate	<PssblDplct>		[0..1]		37
	Priority	<Prty>		[0..1]		37
	Signature	<Sgntr>		[0..1]		38
	<i>CustomerDirectDebitInitiationV08</i>	<CstmrDrctDbtInitn>		[1..1]		16
5.4.1	GroupHeader	<GrpHdr>		[1..1]		16
6.1.12.6.1	MessageIdentification	<MsgId>		[1..1]		98
6.1.12.6.2	CreationDateTime	<CreDtTm>		[1..1]		98
6.1.12.6.3	Authorisation	<Authstn>		[0..2]		98
6.1.12.6.4	NumberOfTransactions	<NbOfTx>		[1..1]		99
6.1.12.6.5	ControlSum	<CtrlSum>		[0..1]		99
6.1.12.6.6	InitiatingParty	<InitgPty>		[1..1]		99
6.1.12.6.7	ForwardingAgent	<FwdgAgt>		[0..1]		100
5.4.2	PaymentInformation	<PmtInf>		[1..*]	R[1..1]	17
6.1.15.5.1	PaymentInformationIdentification	<PmtInfId>		[1..1]		128
6.1.15.5.2	PaymentMethod	<PmtMtd>		[1..1]		128
6.1.15.5.3	BatchBooking	<BtchBookg>		[0..1]		128
6.1.15.5.4	NumberOfTransactions	<NbOfTx>		[0..1]		128
6.1.15.5.5	ControlSum	<CtrlSum>		[0..1]		129
6.1.15.5.6	PaymentTypeInformation	<PmtTpInf>		[0..1]		129
6.1.15.5.7	RequestedCollectionDate	<ReqdColltnDt>		[1..1]		129
6.1.15.5.8	Creditor	<Cdtr>		[1..1]		130
6.1.15.5.9	CreditorAccount	<CdtrAcct>		[1..1]		131
6.1.15.5.10	CreditorAgent	<CdtrAgt>		[1..1]		131
6.1.15.5.11	CreditorAgentAccount	<CdtrAgtAcct>		[0..1]		131
6.1.15.5.12	UltimateCreditor	<UltmtCdtr>		[0..1]		132
6.1.15.5.13	ChargeBearer	<ChrgBr>		[0..1]		132
6.1.15.5.14	ChargesAccount	<ChrgsAcct>		[0..1]		133
6.1.15.5.15	ChargesAccountAgent	<ChrgsAcctAgt>		[0..1]		133
6.1.15.5.16	CreditorSchemeIdentification	<CdtrSchmId>		[0..1]		133
6.1.15.5.17	DirectDebitTransactionInformation	<DrctDbtTxInf>		[1..*]		134

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.4.3	SupplementaryData	<SplmtryData>		[0..*]		18
6.1.12.1.1	PlaceAndName	<PlcAndNm>		[0..1]		174
6.1.12.1.2	Envelope	<Envlp>		[1..1]		174

3 ISO 20022 Rules

R1 **RelatedPresentWhenCopyDupl** ✓

Related MUST contain the relevant BusinessMessageHeader elements of the BusinessMessage to which this BusinessMessage relates.

If CopyDuplicate is present, then Related MUST be present.

Error handling:

- *Error severity:* Warning
- *Error Code:* H00001
- *Error Text:* Element Related is missing

R4 **SupplementaryDataRule**

The SupplementaryData building block at message level must not be used to provide additional information about a transaction. The SupplementaryData element at transaction level should be used for that purpose.

Error handling: Undefined

Usage Guideline restrictions for this element

- **This rule(pain.008.001.08/SupplementaryDataRule) is removed.**

4 Message Building Blocks

Note The following chapter identifies the building blocks of the CBPRPlus SR2026 (Combined) / CBPRPlus-pain.008.001.08_FIToFICustomerDirectDebitInitiation message definition.

Usage Guideline on Root Node

- on pain.008.001.08/.fullmessage

- CBPR_BusinessMessageIdentifier_FormalRule:

The Business Message Identifier must match the Message Identification in the Group Header.

For each [Full Message], every occurrence of [Full Message/BusinessApplication-HeaderV02/BusinessMessageIdentifier] value must be equal to every occurrence of [Full Message/Document/CustomerDirectDebitInitiationV08/GroupHeader/MessageIdentification] value

4.1 Header Building Blocks

Note The following chapter identifies the building blocks of the BusinessApplicationHeaderV02 definition.

4.1.1 CharSet

XML Tag: CharSet

Presence: [0..1]

Definition: Contains the character set of the text-based elements used in the Business Message.

Datatype: ["UnicodeChartsCode" on page 235](#)

4.1.2 From

XML Tag: Fr

Presence: [1..1]

Definition: The sending MessagingEndpoint that has created this Business Message for the receiving MessagingEndpoint that will process this Business Message.

Note the sending MessagingEndpoint might be different from the sending address potentially contained in the transport header (as defined in the transport layer).

The **Fr** block contains the following elements (see datatype ["Party44Choice__1" on page 115](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]	!🚫	115
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		116

!🚫 , 🚫 >> Note as not all **Fr** blocks have this element removed and/or ignored. Please refer to the page number next to the element for further details on which elements have been removed and/or ignored.

4.1.3 To

XML Tag: To

Presence: [1..1]

Definition: The MessagingEndpoint designated by the sending MessagingEndpoint to be the recipient who will ultimately process this Business Message.

Note the receiving MessagingEndpoint might be different from the receiving address potentially contained in the transport header (as defined in the transport layer).

The **To** block contains the following elements (see datatype "Party44Choice__1" on page 115 for details)

🚫 Removed - !🚫 Partial Removed - 🚫 Ignored - 🚫 Partial Ignored - ⚠️ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]	!🚫	115
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		116

!🚫 , 🚫 >> Note as not all **To** blocks have this element removed and/or ignored. Please refer to the page number next to the element for further details on which elements have been removed and/or ignored.

4.1.4 BusinessMessageIdentifier

XML Tag: BizMsgIdr

Presence: [1..1]

Definition: Unambiguously identifies the Business Message to the MessagingEndpoint that has created the Business Message.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 198

Usage Guideline details

- on pain.008.001.08/.header/BusinessMessageIdentifier
Type changed to: CBPR_RestrictedFINXMax35Text on page 198

4.1.5 MessageDefinitionIdentifier

XML Tag: MsgDefldr

Presence: [1..1]

Definition: Contains the MessageIdentifier that defines the BusinessMessage.

It must contain a MessageIdentifier published on the ISO 20022 website.

example camt.001.001.03.

Datatype: "Max35Text" on page 223

Usage Guideline details

- **on pain.008.001.08/.header/MessageDefinitionIdentifier**
Single value: pain.008.001.08

4.1.6 BusinessService

XML Tag: BizSvc

Presence: [0..1]

Definition: Specifies the business service agreed between the two MessagingEndpoints under which rules this Business Message is exchanged.

To be used when there is a choice of processing services or processing service levels.

Example: E&I.

Datatype: "Max35Text" on page 223

Usage Guideline details

- **on pain.008.001.08/.header/BusinessService**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pain.008.001.08/.header/BusinessService**
Single value: swift.cbprplus.03

4.1.7 MarketPractice

XML Tag: MktPrctc

Presence: [0..1]

Definition: Specifies the market practice to which the message conforms. The market practices are a set of rules agreed between parties that restricts the usage of the messages in order to achieve better STP (Straight Through Processing) rates.

A market practice specification may also extend the underlying message specification by using extensions or supplementary data of this underlying message.

The **MktPrctc** block contains the following elements (see datatype "[ImplementationSpecification1](#)" on [page 100](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[[details](#)]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Registry	<Regy>		[1..1]		101
	Identification	<Id>		[1..1]		101

4.1.8 CreationDate

XML Tag: CreDt

Presence: [1..1]

Definition: Date and time when this Business Message (header) was created.

Datatype: "[CBPR_DateTime](#)" on [page 197](#)

Usage Guideline details

- on [pain.008.001.08/header/CreationDate](#)
Type changed to: [CBPR_DateTime](#) on [page 197](#)

4.1.9 BusinessProcessingDate

XML Tag: BizPrcgDt

Presence: [0..1]

Definition: Processing date and time indicated by the sender for the receiver of the business message. This date may be different from the date and time provided in the [CreationDate](#).

Usage: Market practice or bilateral agreement should specify how this element should be used.

Datatype: "[ISODatetime](#)" on [page 220](#)

Usage Guideline details

- This element([pain.008.001.08/header/BusinessProcessingDate](#)) is removed.

4.1.10 CopyDuplicate

XML Tag: CpyDplct

Presence: [0..1]

Definition: Indicates whether the message is a Copy, a Duplicate or a copy of a duplicate of a previously sent ISO 20022 Message.

Datatype: "[CopyDuplicate1Code](#)" on [page 200](#)

4.1.11 PossibleDuplicate

XML Tag: PssblDplct

Presence: [0..1]

Definition: Flag indicating if the Business Message exchanged between the MessagingEndpoints is possibly a duplicate.

If the receiving MessagingEndpoint did not receive the original, then this Business Message should be processed as if it were the original.

If the receiving MessagingEndpoint did receive the original, then it should perform necessary actions to avoid processing this Business Message again.

This will guarantee business idempotent behaviour.

NOTE: this is named "PossResend" in FIX - this is an application level resend not a network level re-transmission.

Datatype: "YesNoIndicator" on page 235

4.1.12 Priority

XML Tag: Prty

Presence: [0..1]

Definition: Relative indication of the processing precedence of the message over a (set of) Business Messages with assigned priorities.

Datatype: "Priority2Code" on page 229

Usage Guideline details

- on **pain.008.001.08/.header/Priority**
Type changed to: Priority2Code on page 229

4.1.13 Signature

XML Tag: Sgntr

Presence: [0..1]

Definition: Contains the digital signature of the Business Entity authorised to sign this Business Message.

Usage Guideline details

- This element(**pain.008.001.08/.header/Signature**) is removed.

4.1.14 Related

XML Tag: Rltd

Presence: [0..*]

Definition: Specifies the Business Application Header(s) of the Business Message(s) to which this Business Message relates.

Can be used when replying to a query; can also be used when canceling or amending.

The **Rltd** block contains the following elements (see datatype "BusinessApplicationHeader5__1" on page 33 for details)

Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CharacterSet	<CharSet>		[0..1]		34
	From	<Fr>		[1..1]		34
	To	<To>		[1..1]		34
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]		35
	MessageDefinitionIdentifier	<MsgDefIdr>		[1..1]		35
	BusinessService	<BizSvc>		[0..1]		36
	CreationDate	<CreDt>		[1..1]		36
	CopyDuplicate	<CpyDplct>		[0..1]		37
	PossibleDuplicate	<PssblDplct>		[0..1]		37
	Priority	<Prty>		[0..1]		37
	Signature	<Sgntr>		[0..1]		38

, >> Note as not all **Rltd** blocks have this element removed and/or ignored. Please refer to the page number next to the element for further details on which elements have been removed and/or ignored.

Usage Guideline details

- on pain.008.001.08/.header/Related
This element has change repeatability, the maximum occurrence has been changed to : 1
- on pain.008.001.08/.header/Related
 - **CBPR_Related_Business_Application_Header_TextualRule:**
If used, the Related BAH must transport the exact same information as in the BAH of the related message.

4.2 Payload Building Blocks

Note The following chapter identifies the building blocks of the CBPRPlus SR2026 (Combined) / CBPRPlus-pain.008.001.08_FIToFICustomerDirectDebitInitiation payload definition.

Usage Guideline on Root Node

- on pain.008.001.08/

- **CBPR_NumberOfTransactions_FormalRule:**

The number of transactions must match the number of occurrences of Direct Debit Transaction Information.

For each [Full Message/Document/CustomerDirectDebitInitiationV08], every occurrence of [CustomerDirectDebitInitiationV08/GroupHeader/NumberOfTransactions] value must be equal to the number of occurrences of [CustomerDirectDebitInitiationV08/PaymentInformation/DirectDebitTransactionInformation]

- on pain.008.001.08/

- **CBPR_MessageIdentification_PaymentInformationIdentification_FormalRule:**

The Payment Information Identification must be the same as the Message Identification in the Group Header.

For each [Full Message/Document/CustomerDirectDebitInitiationV08], every occurrence of [CustomerDirectDebitInitiationV08/PaymentInformation/PaymentInformationIdentification] value must be equal to every occurrence of [CustomerDirectDebitInitiationV08/GroupHeader/MessageIdentification] value

4.2.1 GroupHeader

XML Tag: GrpHdr

Presence: [1..1]

Definition: Set of characteristics shared by all individual transactions included in the message.

The **GrpHdr** block contains the following elements (see datatype "GroupHeader83_1" on page 97 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.12.6.1	MessageIdentification	<MsgId>		[1..1]		98
6.1.12.6.2	CreationDateTime	<CreDtTm>		[1..1]		98
6.1.12.6.3	Authorisation	<Authstn>		[0..2]		98
6.1.12.6.4	NumberOfTransactions	<NbOfTx>		[1..1]		99
6.1.12.6.5	ControlSum	<CtrlSum>		[0..1]		99

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.12.6.6	InitiatingParty	<InitgPty>		[1..1]		99
6.1.12.6.7	ForwardingAgent	<FwdgAgt>		[0..1]		100

4.2.2 PaymentInformation

XML Tag: PmtInf

Presence: [1..*]

Definition: Set of characteristics that apply to the credit side of the payment transactions included in the direct debit transaction initiation.

The **PmtInf** block contains the following elements (see datatype "PaymentInstruction29__1" on page 126 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.15.5.1	PaymentInformationIdentification	<PmtInfId>		[1..1]		128
6.1.15.5.2	PaymentMethod	<PmtMtd>		[1..1]		128
6.1.15.5.3	BatchBooking	<BtchBookg>		[0..1]		128
6.1.15.5.4	NumberOfTransactions	<NbOfTxS>		[0..1]		128
6.1.15.5.5	ControlSum	<CtrlSum>		[0..1]		129
6.1.15.5.6	PaymentTypeInformation	<PmtTplnf>		[0..1]		129
6.1.15.5.7	RequestedCollectionDate	<ReqdColltnDt>		[1..1]		129
6.1.15.5.8	Creditor	<Cdtr>		[1..1]		130
6.1.15.5.9	CreditorAccount	<CdtrAcct>		[1..1]		131
6.1.15.5.10	CreditorAgent	<CdtrAgt>		[1..1]		131
6.1.15.5.11	CreditorAgentAccount	<CdtrAgtAcct>		[0..1]		131
6.1.15.5.12	UltimateCreditor	<UltmtCdtr>		[0..1]		132
6.1.15.5.13	ChargeBearer	<ChrgBr>		[0..1]		132
6.1.15.5.14	ChargesAccount	<ChrgsAcct>		[0..1]		133
6.1.15.5.15	ChargesAccountAgent	<ChrgsAcctAgt>		[0..1]		133
6.1.15.5.16	CreditorSchemeIdentification	<CdtrSchmId>		[0..1]		133
6.1.15.5.17	DirectDebitTransactionInformation	<DrctDbtTxInf>		[1..*]		134

Usage Guideline details

- on pain.008.001.08/PaymentInformation

This element has change repeatability, the maximum occurrence has been changed to : 1

- on pain.008.001.08/PaymentInformation

- CBPR_Remittance_Mutually_Exclusive_FormalRule:

Either Structured or Unstructured Remittance can be present, not both together.
Both may be absent.

For each [Full Message/Document/CustomerDirectDebitInitiationV08/PaymentInformation], the following elements are mutually exclusive: [PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Unstructured] , [PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured] and all may be absent

4.2.3 SupplementaryData

XML Tag: SplmtryData

Presence: [0..*]

Definition: Additional information that cannot be captured in the structured elements and/or any other specific block.

The **SplmtryData** block contains the following elements (see datatype "[SupplementaryData1](#)" on page 173 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.12.1.1	PlaceAndName	<PlcAndNm>		[0..1]		174
6.1.12.1.2	Envelope	<Envlp>		[1..1]		174

Usage Guideline details

- This element(pain.008.001.08/SupplementaryData) is removed.

5 Message Components

Note The following chapter identifies the message components.

5.1 AccountIdentification4Choice

Definition: Specifies the unique identification of an account as assigned by the account servicer.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.2.1.1	IBAN	<IBAN>	{Or	[1..1]		19
6.1.2.1.2	Other	<Othr>	Or}	[1..1]		19

Used in element(s)

"Identification" on page 38

5.1.1 IBAN

XML Tag: IBAN

Presence: [1..1]

Definition: International Bank Account Number (IBAN) - identifier used internationally by financial institutions to uniquely identify the account of a customer. Further specifications of the format and content of the IBAN can be found in the standard ISO 13616 "Banking and related financial services - International Bank Account Number (IBAN)" version 1997-10-01, or later revisions.

Datatype: "IBAN2007Identifier" on page 219

5.1.2 Other

XML Tag: Othr

Presence: [1..1]

Definition: Unique identification of an account, as assigned by the account servicer, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericAccountIdentification1](#)" on page 90 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.1.2.1	Identification	<Id>		[1..1]		90
6.1.1.2.2	SchemeName	<SchmeNm>		[0..1]		90
6.1.1.2.3	Issuer	<Issr>		[0..1]		90

5.2 AccountSchemeName1Choice

Definition: Sets of elements to identify a name of the identification scheme.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.1.2.2.1	Code	<Cd>	{Or	[1..1]		20
6.1.1.2.2.2	Proprietary	<Prtry>	Or}	[1..1]		20

Used in element(s)

"SchemeName" on page 90

5.2.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalAccountIdentification1Code" on page 206

5.2.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 223

5.3 AddressType3Choice

Definition: Choice of formats for the type of address.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.18.1.1.1	Code	<Cd>	{Or	[1..1]		20
6.1.18.1.1.2	Proprietary	<Prtry>	Or}	[1..1]		21

Used in element(s)

"AddressType" on page 142

5.3.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Type of address expressed as a code.

Datatype: "AddressType2Code" on page 193

5.3.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Type of address expressed as a proprietary code.

The **Prtry** block contains the following elements (see datatype "GenericIdentification30" on page 92 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.11.1.1	Identification	<Id>		[1..1]		92
6.1.11.1.2	Issuer	<Issr>		[1..1]		92
6.1.11.1.3	SchemeName	<SchmeNm>		[0..1]		93

5.4 AmendmentInformationDetails13__1

Definition: Provides further details on the list of direct debit mandate elements that have been modified when the amendment indicator has been set.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.8.1.1	OriginalMandateIdentification	<OrgnlMndtId>		[0..1]		22
6.1.8.1.2	OriginalCreditorSchemeIdentification	<OrgnlCdtrSchmeId>		[0..1]		22
6.1.8.1.3	OriginalCreditorAgent	<OrgnlCdtrAgt>		[0..1]		22
6.1.8.1.4	OriginalCreditorAgentAccount	<OrgnlCdtrAgtAcct>		[0..1]		23
6.1.8.1.5	OriginalDebtor	<OrgnlDbtr>		[0..1]		23
6.1.8.1.6	OriginalDebtorAccount	<OrgnlDbtrAcct>		[0..1]		23
6.1.8.1.7	OriginalDebtorAgent	<OrgnlDbtrAgt>		[0..1]		24
6.1.8.1.8	OriginalDebtorAgentAccount	<OrgnlDbtrAgtAcct>		[0..1]		24
6.1.8.1.9	OriginalFinalCollectionDate	<OrgnlFnlColltnDt>		[0..1]		25
6.1.8.1.10	OriginalFrequency	<OrgnlFrqcy>		[0..1]		25
6.1.8.1.11	OriginalReason	<OrgnlRsn>		[0..1]		25

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.8.1.12	OriginalTrackingDays	<OrgnlTrckgDays>		[0..1]		26

Used in element(s)

"AmendmentInformationDetails" on page 103

5.4.1 OriginalMandatIdentification

XML Tag: OrgnlMndtId

Presence: [0..1]

Definition: Unique identification, as assigned by the creditor, to unambiguously identify the original mandate.

Datatype: "Max35Text" on page 223

5.4.2 OriginalCreditorSchemeIdentification

XML Tag: OrgnlCdtrSchmeld

Presence: [0..1]

Definition: Original creditor scheme identification that has been modified.

The **OrgnlCdtrSchmeld** block contains the following elements (see datatype "[PartyIdentification135_1](#)" on page 119 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.14.1.1	Name	<Nm>		[0..1]		120
6.1.14.1.2	PostalAddress	<PstlAdr>		[0..1]		120
6.1.14.1.3	Identification	<Id>		[0..1]		122
6.1.14.1.4	CountryOfResidence	<CtryOfRes>		[0..1]		123
6.1.14.1.5	ContactDetails	<CtctDtls>		[0..1]		123

5.4.3 OriginalCreditorAgent

XML Tag: OrgnlCdtrAgt

Presence: [0..1]

Definition: Original creditor agent that has been modified.

The **OrgnlCdtrAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6](#)" on page 27 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.10.4.1	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		27
6.1.10.4.2	BranchIdentification	<BrnchId>		[0..1]		28

5.4.4 OriginalCreditorAgentAccount

XML Tag: OrgnlCdtrAgtAcct

Presence: [0..1]

Definition: Original creditor agent account that has been modified.

The **OrgnlCdtrAgtAcct** block contains the following elements (see datatype "[CashAccount38](#)" on page 38 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.1.4.1	Identification	<Id>		[1..1]		38
6.1.1.4.2	Type	<Tp>		[0..1]		39
6.1.1.4.3	Currency	<Ccy>		[0..1]		39
6.1.1.4.4	Name	<Nm>		[0..1]		40
6.1.1.4.5	Proxy	<Prxy>		[0..1]		40

5.4.5 OriginalDebtor

XML Tag: OrgnlDbtr

Presence: [0..1]

Definition: Original debtor that has been modified.

The **OrgnlDbtr** block contains the following elements (see datatype "[PartyIdentification135__1](#)" on page 119 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.14.1.1	Name	<Nm>		[0..1]		120
6.1.14.1.2	PostalAddress	<PstlAdr>		[0..1]		120
6.1.14.1.3	Identification	<Id>		[0..1]		122
6.1.14.1.4	CountryOfResidence	<CtryOfRes>		[0..1]		123
6.1.14.1.5	ContactDetails	<CtctDtls>		[0..1]		123

5.4.6 OriginalDebtorAccount

XML Tag: OrgnIDbtrAcct

Presence: [0..1]

Definition: Original debtor account that has been modified.

The **OrgnIDbtrAcct** block contains the following elements (see datatype "CashAccount38" on page 38 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.1.4.1	Identification	<Id>		[1..1]		38
6.1.1.4.2	Type	<Tp>		[0..1]	🚫	39
6.1.1.4.3	Currency	<Ccy>		[0..1]	🚫	39
6.1.1.4.4	Name	<Nm>		[0..1]	🚫	40
6.1.1.4.5	Proxy	<Prxy>		[0..1]		40

5.4.7 OriginalDebtorAgent

XML Tag: OrgnIDbtrAgt

Presence: [0..1]

Definition: Original debtor agent that has been modified.

The **OrgnIDbtrAgt** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification6" on page 27 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.10.4.1	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		27
6.1.10.4.2	BranchIdentification	<BrnchId>		[0..1]	🚫	28

5.4.8 OriginalDebtorAgentAccount

XML Tag: OrgnIDbtrAgtAcct

Presence: [0..1]

Definition: Original debtor agent account that has been modified.

The **OrgnIDbtrAgtAcct** block contains the following elements (see datatype "CashAccount38" on page 38 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.1.4.1	Identification	<Id>		[1..1]		38
6.1.1.4.2	Type	<Tp>		[0..1]		39
6.1.1.4.3	Currency	<Ccy>		[0..1]		39
6.1.1.4.4	Name	<Nm>		[0..1]		40
6.1.1.4.5	Proxy	<Prxy>		[0..1]		40

5.4.9 OriginalFinalCollectionDate

XML Tag: OrgnlFnlColltnDt

Presence: [0..1]

Definition: Original final collection date that has been modified.

Datatype: "CBPR_Date" on page 197

Usage Guideline details

- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/MandateRelatedInformation/AmendmentInformationDetails/OriginalFinalCollectionDate**
Type changed to: CBPR_Date on page 197

5.4.10 OriginalFrequency

XML Tag: OrgnlFrqcy

Presence: [0..1]

Definition: Original frequency that has been modified.

The **OrgnlFrqcy** block contains the following elements (see datatype "Frequency36Choice" on page 82 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.12.7.1	Type	<Tp>	{Or	[1..1]		82
6.1.12.7.2	Period	<Prd>	Or	[1..1]		83
6.1.12.7.3	PointInTime	<PtInTm>	Or}	[1..1]		83

5.4.11 OriginalReason

XML Tag: OrgnlRsn

Presence: [0..1]

Definition: Original reason for the mandate to allow the user to distinguish between different mandates for the same creditor.

The **OrgnlRsn** block contains the following elements (see datatype "[MandateSetupReason1Choice](#)" on [page 106](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.8.1.11.1 , 6.1.8.3.9.1	Code	<Cd>	{Or	[1..1]		106
6.1.8.1.11.2 , 6.1.8.3.9.2	Proprietary	<Prtry>	Or}	[1..1]		106

5.4.12 OriginalTrackingDays

XML Tag: OrgnlTrckgDays

Presence: [0..1]

Definition: Original number of tracking days that has been modified.

Datatype: "[Exact2NumericText](#)" on [page 205](#)

5.5 Authorisation1Choice

Definition: Provides the details on the user identification or any user key that allows to check if the initiating party is allowed to issue the transaction.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.12.10.1	Code	<Cd>	{Or	[1..1]		26
6.1.12.10.2	Proprietary	<Prtry>	Or}	[1..1]		26

Used in element(s)

"[Authorisation](#)" on [page 98](#)

5.5.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Specifies the authorisation, in a coded form.

Datatype: "[Authorisation1Code](#)" on [page 195](#)

5.5.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Specifies the authorisation, in a free text form.

Datatype: "Max128Text" on page 221

5.6 BranchAndFinancialInstitutionIdentification6

Definition: Unique and unambiguous identification of a financial institution or a branch of a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.10.4.1	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		27
6.1.10.4.2	BranchIdentification	<BrnchId>		[0..1]		28

Used in element(s)

["ChargesAccountAgent" on page 133](#),
 ["CreditorAgent" on page 131](#),
 ["DebtorAgent" on page 61](#),
 ["ForwardingAgent" on page 100](#),
 ["OriginalCreditorAgent" on page 22](#),
 ["OriginalDebtorAgent" on page 24](#)

5.6.1 FinancialInstitutionIdentification

XML Tag: FinInstnId

Presence: [1..1]

Definition: Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

The **FinInstnId** block contains the following elements (see datatype ["FinancialInstitutionIdentification18"](#) on page 74 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.10.2.1	BICFI	<BICFI>		[0..1]		75
6.1.10.2.2	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		75
6.1.10.2.3	LEI	<LEI>		[0..1]		76
6.1.10.2.4	Name	<Nm>		[0..1]		76
6.1.10.2.5	PostalAddress	<PstlAdr>		[0..1]	 	76
6.1.10.2.6	Other	<Othr>		[0..1]		78

 ,  >> Note as not all **FinInstnId** blocks have this element removed and/or ignored. Please refer to the page number next to the element for further details on which elements have been removed and/or ignored.

Usage Guideline details

- on pain.008.001.08/PaymentInformation/CreditorAgent/FinancialInstitutionIdentification

- CBPR_Agent_Name_Postal_Address_FormaRule:

Name and Address must always be present together.

For each [Full Message/Document/CustomerDirectDebitInitiationV08/PaymentInformation/CreditorAgent/FinancialInstitutionIdentification],
 for each [FinancialInstitutionIdentification], if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] must be present
 and for each [FinancialInstitutionIdentification], if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] must be present

- on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DebtorAgent/FinancialInstitutionIdentification

- CBPR_Agent_Name_Postal_Address_FormaRule:

Name and Address must always be present together.

For each [Full Message/Document/CustomerDirectDebitInitiationV08/PaymentInformation/DirectDebitTransactionInformation/DebtorAgent/FinancialInstitutionIdentification],
 for each [FinancialInstitutionIdentification], if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] must be present
 and for each [FinancialInstitutionIdentification], if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] must be present

5.6.2 BranchIdentification

XML Tag: BrnchId

Presence: [0..1]

Definition: Identifies a specific branch of a financial institution.

Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

The **BrnchId** block contains the following elements (see datatype "[BranchData3](#)" on page 31 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.10.3.1	Identification	<Id>		[0..1]		31
6.1.10.3.2	LEI	<LEI>		[0..1]	🚫	32
6.1.10.3.3	Name	<Nm>		[0..1]	🚫	32
6.1.10.3.4	PostalAddress	<PstlAdr>		[0..1]	🚫	32

🚫 , ⬜ >> Note as not all **BrnchId** blocks have this element removed and/or ignored. Please refer to the page number next to the element for further details on which elements have been removed and/or ignored.

Usage Guideline details

- This element(pain.008.001.08/PaymentInformation/CreditorAgent/BranchIdentification) is removed.
- This element(pain.008.001.08/PaymentInformation/ChargesAccountAgent/BranchIdentification) is removed.
- This element(pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DebtorAgent/BranchIdentification) is removed.
- This element(pain.008.001.08/GroupHeader/ForwardingAgent/BranchIdentification) is removed.
- This element(pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/MandateRelatedInformation/AmendmentInformationDetails/OriginalCreditorAgent/BranchIdentification) is removed.
- This element(pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/MandateRelatedInformation/AmendmentInformationDetails/OriginalDebtorAgent/BranchIdentification) is removed.

5.7 BranchAndFinancialInstitutionIdentification6__1

Definition: Unique and unambiguous identification of a financial institution or a branch of a financial institution.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.10.4.1	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		30
6.1.10.4.2	BranchIdentification	<BrnchId>		[0..1]		30

Used in element(s)

"FinancialInstitutionIdentification" on page 116

5.7.1 FinancialInstitutionIdentification

XML Tag: FinInstnId

Presence: [1..1]

Definition: Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

The **FinInstnId** block contains the following elements (see datatype "FinancialInstitutionIdentification18_1" on page 78 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.10.2.1	BICFI	<BICFI>		[0..1]		79
6.1.10.2.2	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		79
6.1.10.2.3	LEI	<LEI>		[0..1]		80
6.1.10.2.4	Name	<Nm>		[0..1]		80
6.1.10.2.5	PostalAddress	<PstlAdr>		[0..1]		80
6.1.10.2.6	Other	<Othr>		[0..1]		81

 ,  >> Note as not all **FinInstnId** blocks have this element removed and/or ignored. Please refer to the page number next to the element for further details on which elements have been removed and/or ignored.

5.7.2 BranchIdentification

XML Tag: BrnchId

Presence: [0..1]

Definition: Identifies a specific branch of a financial institution.

Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

The **BrnchId** block contains the following elements (see datatype "BranchData3" on page 31 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.10.3.1	Identification	<Id>		[0..1]		31
6.1.10.3.2	LEI	<LEI>		[0..1]		32
6.1.10.3.3	Name	<Nm>		[0..1]		32
6.1.10.3.4	PostalAddress	<PstlAdr>		[0..1]		32

Usage Guideline details

- This element(**pain.008.001.08/.header/Related/To/FinancialInstitutionIdentification/BranchIdentification**) is removed.
- This element(**pain.008.001.08/.header/To/FinancialInstitutionIdentification/BranchIdentification**) is removed.
- This element(**pain.008.001.08/.header/Related/From/FinancialInstitutionIdentification/BranchIdentification**) is removed.
- This element(**pain.008.001.08/.header/From/FinancialInstitutionIdentification/BranchIdentification**) is removed.

5.8 BranchData3

Definition: Information that locates and identifies a specific branch of a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.10.3.1	Identification	<Id>		[0..1]		31
6.1.10.3.2	LEI	<LEI>		[0..1]		32
6.1.10.3.3	Name	<Nm>		[0..1]		32
6.1.10.3.4	PostalAddress	<PstlAdr>		[0..1]		32

 ,  >> Note as not all **BranchData3** blocks have this element removed and/or ignored. Please refer to the page number next to the element for further details on which elements have been removed and/or ignored.

Used in element(s)

"BranchIdentification" on page 30, "BranchIdentification" on page 28

5.8.1 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a branch of a financial institution.

Datatype: "Max35Text" on page 223

5.8.2 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identification for the branch of the financial institution.

Datatype: "LEIIdentifier" on page 221

Usage Guideline details

- This element(**pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/Debtor-Agent/BranchIdentification/LEI**) is removed.

5.8.3 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "Max140Text" on page 222

Usage Guideline details

- This element(**pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/Debtor-Agent/BranchIdentification/Name**) is removed.

5.8.4 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24" on page 142 for details)

🚫 Removed - 🚫 Partial Removed - ✨ Ignored - ✨ Partial Ignored - ⚠ Details below -

📌 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.18.1.1	AddressType	<AdrTp>		[0..1]		142
6.1.18.1.2	Department	<Dept>		[0..1]		144

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.18.1.3	SubDepartment	<SubDept>		[0..1]		144
6.1.18.1.4	StreetName	<StrtNm>		[0..1]		144
6.1.18.1.5	BuildingNumber	<BldgNb>		[0..1]		144
6.1.18.1.6	BuildingName	<BldgNm>		[0..1]		145
6.1.18.1.7	Floor	<Flr>		[0..1]		145
6.1.18.1.8	PostBox	<PstBx>		[0..1]		145
6.1.18.1.9	Room	<Room>		[0..1]		145
6.1.18.1.10	PostCode	<PstCd>		[0..1]		145
6.1.18.1.11	TownName	<TwnNm>		[0..1]		145
6.1.18.1.12	TownLocationName	<TwnLctnNm>		[0..1]		147
6.1.18.1.13	DistrictName	<DstrctNm>		[0..1]		147
6.1.18.1.14	CountrySubDivision	<CtrySubDvsn>		[0..1]		147
6.1.18.1.15	Country	<Ctry>		[0..1]		147
6.1.18.1.16	AddressLine	<AdrLine>		[0..7]		149

Usage Guideline details

- This element(pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/Debtor-Agent/BranchIdentification/PostalAddress) is removed.

5.9 BusinessApplicationHeader5__1

Definition: Specifies the Business Application Header of the Business Message.

Can be used when replying to a query; can also be used when canceling or amending.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CharacterSet	<CharSet>		[0..1]		34
	From	<Fr>		[1..1]		34
	To	<To>		[1..1]		34
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]		35
	MessageDefinitionIdentifier	<MsgDefIdr>		[1..1]		35
	BusinessService	<BizSvc>		[0..1]		36

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CreationDate	<CreDt>		[1..1]		36
	CopyDuplicate	<CpyDplct>		[0..1]		37
	PossibleDuplicate	<PssblDplct>		[0..1]		37
	Priority	<Prty>		[0..1]		37
	Signature	<Sgntr>		[0..1]		38

Used in element(s)

"Related" on page 14

5.9.1 CharacterSet

XML Tag: CharSet

Presence: [0..1]

Definition: Contains the character set of the text-based elements used in the Business Message.

Datatype: "UnicodeChartsCode" on page 235

5.9.2 From

XML Tag: Fr

Presence: [1..1]

Definition: The sending MessagingEndpoint that has created this Business Message for the receiving MessagingEndpoint that will process this Business Message.

Note the sending MessagingEndpoint might be different from the sending address potentially contained in the transport header (as defined in the transport layer).

The **Fr** block contains the following elements (see datatype "Party44Choice__1" on page 115 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		115
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		116

 ,  >> Note as not all **Fr** blocks have this element removed and/or ignored. Please refer to the page number next to the element for further details on which elements have been removed and/or ignored.

5.9.3 To

XML Tag: To

Presence: [1..1]

Definition: The MessagingEndpoint designated by the sending MessagingEndpoint to be the recipient who will ultimately process this Business Message.

Note the receiving MessagingEndpoint might be different from the receiving address potentially contained in the transport header (as defined in the transport layer).

The **To** block contains the following elements (see datatype "[Party44Choice__1](#)" on page 115 for details)

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]	🚫	115
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		116

🚫 , ⚡ >> Note as not all **To** blocks have this element removed and/or ignored. Please refer to the page number next to the element for further details on which elements have been removed and/or ignored.

5.9.4 BusinessMessageIdentifier

XML Tag: BizMsgIdr

Presence: [1..1]

Definition: Unambiguously identifies the Business Message to the MessagingEndpoint that has created the Business Message.

Datatype: "[CBPR_RestrictedFINXMax35Text](#)" on page 198

Usage Guideline details

- on [pain.008.001.08/.header/Related/BusinessMessageIdentifier](#)

Type changed to: [CBPR_RestrictedFINXMax35Text](#) on page 198

- on [pain.008.001.08/.header/Related/BusinessMessageIdentifier](#)

– CBPR_Business_Message_Identifier_TextualRule:

The Business Message Identifier is the unique identifier of the Business Message instance that is being transported with this header, as defined by the sending application or system.

Must contain the Message Identification element from the Group Header of the underlying message, where available (as is typically the case with pacs, pain, and camt messages, for example). If Message Identification is not available in the underlying message, then this element must contain the unique identifier of the Business Message instance.

5.9.5 MessageDefinitionIdentifier

XML Tag: MsgDefIdr

Presence: [1..1]

Definition: Contains the MessageIdentifier that defines the BusinessMessage.

It must contain a MessageIdentifier published on the ISO 20022 website.

example camt.001.001.03.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 198

Usage Guideline details

- on **pain.008.001.08/.header/Related/MessageDefinitionIdentifier**

Type changed to: CBPR_RestrictedFINXMax35Text on page 198

- on **pain.008.001.08/.header/Related/MessageDefinitionIdentifier**

– **CBPR_Message_Definition_Identifier_TextualRule:**

The Message Definition Identifier of the Business Message instance that is being transported with this header. In general, it must be formatted exactly as it appears in the namespace of the Business Message instance.

5.9.6 BusinessService

XML Tag: BizSvc

Presence: [0..1]

Definition: Specifies the business service agreed between the two MessagingEndpoints under which rules this Business Message is exchanged.

To be used when there is a choice of processing services or processing service levels.

Example: E&I.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 198

Usage Guideline details

- on **pain.008.001.08/.header/Related/BusinessService**

Type changed to: CBPR_RestrictedFINXMax35Text on page 198

- on **pain.008.001.08/.header/Related/BusinessService**

– **CBPR_Related_BAH_Business_Service_TextualRule:**

If related BAH is present, it should transport the element Business Service.

5.9.7 CreationDate

XML Tag: CreDt

Presence: [1..1]

Definition: Date and time when this Business Message (header) was created.

Note Times must be normalized, using the "Z" annotation.

Datatype: ["CBPR_DateTime" on page 197](#)

Usage Guideline details

- **on pain.008.001.08/.header/Related/CreationDate**
Type changed to: [CBPR_DateTime on page 197](#)

5.9.8 CopyDuplicate

XML Tag: CpyDplct

Presence: [0..1]

Definition: Indicates whether the message is a Copy, a Duplicate or a copy of a duplicate of a previously sent ISO 20022 Message.

Datatype: ["CopyDuplicate1Code" on page 200](#)

5.9.9 PossibleDuplicate

XML Tag: PssblDplct

Presence: [0..1]

Definition: Flag indicating if the Business Message exchanged between the MessagingEndpoints is possibly a duplicate.

If the receiving MessagingEndpoint did not receive the original, then this Business Message should be processed as if it were the original.

If the receiving MessagingEndpoint did receive the original, then it should perform necessary actions to avoid processing this Business Message again.

This will guarantee business idempotent behaviour.

NOTE: this is named "PossResend" in FIX - this is an application level resend not a network level re-transmission.

Datatype: ["YesNoIndicator" on page 235](#)

Usage Guideline details

- **This element(pain.008.001.08/.header/Related/PossibleDuplicate) is removed.**

5.9.10 Priority

XML Tag: Prty

Presence: [0..1]

Definition: Relative indication of the processing precedence of the message over a (set of) Business Messages with assigned priorities.

Datatype: ["Priority2Code" on page 229](#)

Usage Guideline details

- on [pain.008.001.08/.header/Related/Priority](#)
Type changed to: [Priority2Code on page 229](#)

5.9.11 Signature

XML Tag: Sgntr

Presence: [0..1]

Definition: Contains the digital signature of the Business Entity authorised to sign this Business Message.

Usage Guideline details

- This element([pain.008.001.08/.header/Related/Signature](#)) is removed.

5.10 CashAccount38

Definition: Provides the details to identify an account.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.1.4.1	Identification	<Id>		[1..1]		38
6.1.1.4.2	Type	<Tp>		[0..1]	🚫	39
6.1.1.4.3	Currency	<Ccy>		[0..1]	🚫 ⚠	39
6.1.1.4.4	Name	<Nm>		[0..1]	🚫	40
6.1.1.4.5	Proxy	<Prxy>		[0..1]		40

Used in element(s)

"ChargesAccount" on [page 133](#), "CreditorAccount" on [page 131](#), "CreditorAgentAccount" on [page 131](#), "DebtorAccount" on [page 63](#), "DebtorAgentAccount" on [page 61](#), "OriginalCreditorAgentAccount" on [page 23](#), "OriginalDebtorAccount" on [page 23](#), "OriginalDebtorAgentAccount" on [page 24](#)

5.10.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification for the account between the account owner and the account servicer.

The **Id** block contains the following elements (see datatype "[AccountIdentification4Choice](#)" on page 19 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.2.1.1	IBAN	<IBAN>	{Or	[1..1]		19
6.1.2.1.2	Other	<Othr>	Or}	[1..1]		19

5.10.2 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the nature, or use of the account.

The **Tp** block contains the following elements (see datatype "[CashAccountType2Choice](#)" on page 40 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.1.1.1	Code	<Cd>	{Or	[1..1]		41
6.1.1.1.2	Proprietary	<Prtry>	Or}	[1..1]		41

Usage Guideline details

- This element(pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/MandateRelatedInformation/AmendmentInformationDetails/OriginalDebtorAccount/Type) is removed.

5.10.3 Currency

XML Tag: Ccy

Presence: [0..1]

Definition: Identification of the currency in which the account is held.

Usage: Currency should only be used in case one and the same account number covers several currencies

and the initiating party needs to identify which currency needs to be used for settlement on the account.

Datatype: "[ActiveOrHistoricCurrencyCode](#)" on page 192

Usage Guideline details

- This element(pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/MandateRelatedInformation/AmendmentInformationDetails/OriginalDebtorAccount/Currency) is removed.
 - on pain.008.001.08/PaymentInformation/CreditorAccount/Currency
 - CBPR_Account_Currency_TextualRule:
- Recommended

5.10.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name of the account, as assigned by the account servicing institution, in agreement with the account owner in order to provide an additional means of identification of the account.

Usage: The account name is different from the account owner name. The account name is used in certain user communities to provide a means of identifying the account, in addition to the account owner's identity and the account number.

Datatype: "Max70Text" on page 224

Usage Guideline details

- This element(pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/MandateRelatedInformation/AmendmentInformationDetails/OriginalDebtorAccount/Name) is removed.

5.10.5 Proxy

XML Tag: Prxy

Presence: [0..1]

Definition: Specifies an alternate assumed name for the identification of the account.

The **Prxy** block contains the following elements (see datatype "[ProxyAccountIdentification1](#)" on page 151 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.1.3.1	Type	<Tp>		[0..1]		151
6.1.1.3.2	Identification	<Id>		[1..1]		152

5.11 CashAccountType2Choice

Definition: Nature or use of the account.

Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.1.1.1	Code	<Cd>	{Or	[1..1]		41
6.1.1.1.2	Proprietary	<Prtry>	Or}	[1..1]		41

Used in element(s)

"Type" on page 39

5.11.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Account type, in a coded form.

Datatype: "ExternalCashAccountType1Code" on page 206

5.11.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Nature or use of the account in a proprietary form.

Datatype: "Max35Text" on page 223

5.12 CategoryPurpose1Choice

Definition: Specifies the high level purpose of the instruction based on a set of pre-defined categories.

Usage: This is used by the initiating party to provide information concerning the processing of the payment. It is likely to trigger special processing by any of the agents involved in the payment chain.

Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.16.2.5.1	Code	<Cd>	{Or	[1..1]		41
6.1.16.2.5.2	Proprietary	<Prtry>	Or}	[1..1]		42

Used in element(s)

"CategoryPurpose" on page 137

5.12.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Category purpose, as published in an external category purpose code list.

Datatype: ["ExternalCategoryPurpose1Code" on page 207](#)

5.12.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Category purpose, in a proprietary form.

Datatype: ["Max35Text" on page 223](#)

5.13 ClearingSystemIdentification2Choice

Definition: Choice of a clearing system identifier.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.23.1.1	Code	<Cd>	{Or	[1..1]		42
6.1.23.1.2	Proprietary	<Prtry>	Or}	[1..1]		42

Used in element(s)

["ClearingSystemIdentification" on page 45](#), ["ClearingSystemIdentification" on page 43](#)

5.13.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Identification of a clearing system, in a coded form as published in an external list.

Datatype: ["ExternalClearingSystemIdentification1Code" on page 208](#)

5.13.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Identification code for a clearing system, that has not yet been identified in the list of clearing systems.

Datatype: ["Max35Text" on page 223](#)

Usage Guideline details

- This element([pain.008.001.08/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary](#)) is removed.

- This element(`pain.008.001.08/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary`) is removed.
- This element(`pain.008.001.08/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary`) is removed.
- This element(`pain.008.001.08/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary`) is removed.
- This element(`pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary`) is removed.
- This element(`pain.008.001.08/GroupHeader/ForwardingAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary`) is removed.
- This element(`pain.008.001.08/PaymentInformation/CreditorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary`) is removed.

5.14 ClearingSystemMemberIdentification2

Definition: Unique identification, as assigned by a clearing system, to unambiguously identify a member of the clearing system.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.10.1.1	ClearingSystemIdentification	<ClrSysId>		[0..1]		43
6.1.10.1.2	MemberIdentification	<MmbId>		[1..1]		44

Used in element(s)

"ClearingSystemMemberIdentification" on page 75

5.14.1 ClearingSystemIdentification

XML Tag: ClrSysId

Presence: [0..1]

Definition: Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed.

The **ClrSysId** block contains the following elements (see datatype "ClearingSystemIdentification2Choice" on page 42 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.23.1.1	Code	<Cd>	{Or	[1..1]		42
6.1.23.1.2	Proprietary	<Prtry>	Or}	[1..1]	!⊘	42

!⊘, ⊠ >> Note as not all **ClrSysId** blocks have this element removed and/or ignored. Please refer to the page number next to the element for further details on which elements have been removed and/or ignored.

Usage Guideline details

- on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pain.008.001.08/PaymentInformation/CreditorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pain.008.001.08/GroupHeader/ForwardingAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification
This element is now mandatory, the minimum occurrence has been changed to : 1

5.14.2 MemberIdentification

XML Tag: Mmbld

Presence: [1..1]

Definition: Identification of a member of a clearing system.

Datatype: "Max35Text" on page 223

5.15 ClearingSystemMemberIdentification2__1

Definition: Unique identification, as assigned by a clearing system, to unambiguously identify a member of the clearing system.

⊘ Removed - !⊘ Partial Removed - ⊠ Ignored - ⊠ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.10.1.1	ClearingSystemIdentification	<ClrSysId>		[0..1]	M	45
6.1.10.1.2	MemberIdentification	<Mmbld>		[1..1]	⚠	45

Used in element(s)

"ClearingSystemMemberIdentification" on page 79

5.15.1 ClearingSystemIdentification

XML Tag: ClrSysId

Presence: [0..1]

Definition: Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed.

The **ClrSysId** block contains the following elements (see datatype "ClearingSystemIdentification2Choice" on page 42 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
 M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.23.1.1	Code	<Cd>	{Or	[1..1]		42
6.1.23.1.2	Proprietary	<Prtry>	Or}	[1..1]	🚫	42

🚫 , ⬜ >> Note as not all **ClrSysId** blocks have this element removed and/or ignored. Please refer to the page number next to the element for further details on which elements have been removed and/or ignored.

Usage Guideline details

- on pain.008.001.08/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pain.008.001.08/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pain.008.001.08/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pain.008.001.08/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification
This element is now mandatory, the minimum occurrence has been changed to : 1

5.15.2 MemberIdentification

XML Tag: Mmbld

Presence: [1..1]

Definition: Identification of a member of a clearing system.

Datatype: "CBPR_RestrictedFINXMax28Text" on page 198

Usage Guideline details

- on **pain.008.001.08/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification**
Type changed to: CBPR_RestrictedFINXMax28Text on page 198
- on **pain.008.001.08/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification**
Type changed to: CBPR_RestrictedFINXMax28Text on page 198
- on **pain.008.001.08/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification**
Type changed to: CBPR_RestrictedFINXMax28Text on page 198
- on **pain.008.001.08/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification**
Type changed to: CBPR_RestrictedFINXMax28Text on page 198

5.16 Contact4

Definition: Specifies the details of the contact person.

❌ Removed - ❌ Partial Removed - ❖ Ignored - ❖ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.17.2.1	NamePrefix	<NmPrfx>		[0..1]		47
6.1.17.2.2	Name	<Nm>		[0..1]		47
6.1.17.2.3	PhoneNumber	<PhneNb>		[0..1]		47
6.1.17.2.4	MobileNumber	<MobNb>		[0..1]		47
6.1.17.2.5	FaxNumber	<FaxNb>		[0..1]		47
6.1.17.2.6	EmailAddress	<EmailAdr>		[0..1]		47
6.1.17.2.7	EmailPurpose	<EmailPurp>		[0..1]		47
6.1.17.2.8	JobTitle	<JobTitt>		[0..1]		48
6.1.17.2.9	Responsibility	<Rspnsblty>		[0..1]		48
6.1.17.2.10	Department	<Dept>		[0..1]		48
6.1.17.2.11	Other	<Othr>		[0..*]		48
6.1.17.2.12	PreferredMethod	<PrefrdMtd>		[0..1]		48

Used in element(s)

"ContactDetails" on page 123, "ContactDetails" on page 118

5.16.1 **NamePrefix**

XML Tag: NmPrfx

Presence: [0..1]

Definition: Specifies the terms used to formally address a person.

Datatype: "NamePrefix2Code" on page 225

5.16.2 **Name**

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: "Max140Text" on page 222

5.16.3 **PhoneNumber**

XML Tag: PhneNb

Presence: [0..1]

Definition: Collection of information that identifies a phone number, as defined by telecom services.

Datatype: "PhoneNumber" on page 227

5.16.4 **MobileNumber**

XML Tag: MobNb

Presence: [0..1]

Definition: Collection of information that identifies a mobile phone number, as defined by telecom services.

Datatype: "PhoneNumber" on page 227

5.16.5 **FaxNumber**

XML Tag: FaxNb

Presence: [0..1]

Definition: Collection of information that identifies a FAX number, as defined by telecom services.

Datatype: "PhoneNumber" on page 227

5.16.6 **EmailAddress**

XML Tag: EmailAdr

Presence: [0..1]

Definition: Address for electronic mail (e-mail).

Datatype: "Max2048Text" on page 223

5.16.7 **EmailPurpose**

XML Tag: EmailPurp

Presence: [0..1]

Definition: Purpose for which an email address may be used.

Datatype: ["Max35Text" on page 223](#)

5.16.8 JobTitle

XML Tag: JobTitl

Presence: [0..1]

Definition: Title of the function.

Datatype: ["Max35Text" on page 223](#)

5.16.9 Responsibility

XML Tag: Rspnsblty

Presence: [0..1]

Definition: Role of a person in an organisation.

Datatype: ["Max35Text" on page 223](#)

5.16.10 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: ["Max70Text" on page 224](#)

5.16.11 Other

XML Tag: Othr

Presence: [0..*]

Definition: Contact details in another form.

The **Othr** block contains the following elements (see datatype ["OtherContact1" on page 112](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.17.2.11.1	ChannelType	<ChanlTp>		[1..1]		112
6.1.17.2.11.2	Identification	<Id>		[0..1]		112

5.16.12 PreferredMethod

XML Tag: PrefrdMtd

Presence: [0..1]

Definition: Preferred method used to reach the contact.

Datatype: ["PreferredContactMethod1Code" on page 228](#)

5.17 CreditorReferenceInformation2

Definition: Reference information provided by the creditor to allow the identification of the underlying documents.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.9.1.1	Type	<Tp>		[0..1]		49
6.1.9.1.2	Reference	<Ref>		[0..1]		49

Used in element(s)

["CreditorReferenceInformation" on page 170](#)

5.17.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the type of creditor reference.

The **Tp** block contains the following elements (see datatype ["CreditorReferenceType2" on page 50](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.9.1.1.1	CodeOrProprietary	<CdOrPrtry>		[1..1]		51
6.1.9.1.1.2	Issuer	<Issr>		[0..1]		51

5.17.2 Reference

XML Tag: Ref

Presence: [0..1]

Definition: Unique reference, as assigned by the creditor, to unambiguously refer to the payment transaction.

Usage: If available, the initiating party should provide this reference in the structured remittance information, to enable reconciliation by the creditor upon receipt of the amount of money.

If the business context requires the use of a creditor reference or a payment remit identification, and only one identifier can be passed through the end-to-end chain, the creditor's reference or payment remittance identification should be quoted in the end-to-end transaction identification.

Datatype: "Max35Text" on page 223

Usage Guideline details

- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/CreditorReferenceInformation/Reference**

This element is now mandatory, the minimum occurrence has been changed to : 1

5.18 CreditorReferenceType1Choice

Definition: Specifies the type of document referred by the creditor.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.9.1.1.1.1	Code	<Cd>	{Or	[1..1]		50
6.1.9.1.1.1.2	Proprietary	<Prtry>	Or}	[1..1]		50

Used in element(s)

"CodeOrProprietary" on page 51

5.18.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Type of creditor reference, in a coded form.

Datatype: "DocumentType3Code" on page 202

5.18.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Creditor reference type, in a proprietary form.

Datatype: "Max35Text" on page 223

5.19 CreditorReferenceType2

Definition: Specifies the type of creditor reference.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.9.1.1.1	CodeOrProprietary	<CdOrPrtry>		[1..1]		51
6.1.9.1.1.2	Issuer	<Issr>		[0..1]		51

Used in element(s)

"Type" on page 49

5.19.1 CodeOrProprietary

XML Tag: CdOrPrtry

Presence: [1..1]

Definition: Coded or proprietary format creditor reference type.

The **CdOrPrtry** block contains the following elements (see datatype "[CreditorReferenceType1Choice](#)" on page 50 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.9.1.1.1.1	Code	<Cd>	{Or	[1..1]		50
6.1.9.1.1.1.2	Proprietary	<Prtry>	Or}	[1..1]		50

5.19.2 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the credit reference type.

Datatype: "[Max35Text](#)" on page 223

5.20 DateAndPlaceOfBirth1

Definition: Date and place of birth of a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.17.1.1.1	BirthDate	<BirthDt>		[1..1]		52
6.1.17.1.1.2	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		52
6.1.17.1.1.3	CityOfBirth	<CityOfBirth>		[1..1]		52
6.1.17.1.1.4	CountryOfBirth	<CtryOfBirth>		[1..1]		52

Used in element(s)

"DateAndPlaceOfBirth" on page 137

5.20.1 BirthDate

XML Tag: BirthDt

Presence: [1..1]

Definition: Date on which a person is born.

Datatype: "ISODate" on page 220

5.20.2 ProvinceOfBirth

XML Tag: PrvcOfBirth

Presence: [0..1]

Definition: Province where a person was born.

Datatype: "Max35Text" on page 223

5.20.3 CityOfBirth

XML Tag: CityOfBirth

Presence: [1..1]

Definition: City where a person was born.

Datatype: "Max35Text" on page 223

5.20.4 CountryOfBirth

XML Tag: CtryOfBirth

Presence: [1..1]

Definition: Country where a person was born.

Datatype: "CountryCode" on page 201

5.21 DateAndPlaceOfBirth1__1

Definition: Date and place of birth of a person.

❌ Removed - !❌ Partial Removed - ♦ Ignored - !♦ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.17.1.1.1	BirthDate	<BirthDt>		[1..1]	⚠	53
6.1.17.1.1.2	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		54
6.1.17.1.1.3	CityOfBirth	<CityOfBirth>		[1..1]		54
6.1.17.1.1.4	CountryOfBirth	<CtryOfBirth>		[1..1]		54

Used in element(s)

["DateAndPlaceOfBirth" on page 139](#)

5.21.1 BirthDate

XML Tag: BirthDt

Presence: [1..1]

Definition: Date on which a person is born.

Datatype: ["CBPR_Date" on page 197](#)

Usage Guideline details

- on [pain.008.001.08/GroupHeader/InitiatingParty/Identification/PrivateIdentification/DateAndPlaceOfBirth/BirthDate](#)
Type changed to: [CBPR_Date on page 197](#)
- on [pain.008.001.08/PaymentInformation/Creditor/Identification/PrivateIdentification/DateAndPlaceOfBirth/BirthDate](#)
Type changed to: [CBPR_Date on page 197](#)
- on [pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/MandateRelatedInformation/AmendmentInformationDetails/OriginalCreditorSchemeIdentification/Identification/PrivateIdentification/DateAndPlaceOfBirth/BirthDate](#)
Type changed to: [CBPR_Date on page 197](#)
- on [pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/MandateRelatedInformation/AmendmentInformationDetails/OriginalDebtor/Identification/PrivateIdentification/DateAndPlaceOfBirth/BirthDate](#)
Type changed to: [CBPR_Date on page 197](#)
- on [pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/CreditorSchemeIdentification/Identification/PrivateIdentification/DateAndPlaceOfBirth/BirthDate](#)
Type changed to: [CBPR_Date on page 197](#)
- on [pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/UltimateCreditor/Identification/PrivateIdentification/DateAndPlaceOfBirth/BirthDate](#)
Type changed to: [CBPR_Date on page 197](#)
- on [pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/Debtor/Identification/PrivateIdentification/DateAndPlaceOfBirth/BirthDate](#)
Type changed to: [CBPR_Date on page 197](#)
- on [pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/UltimateDebtor/Identification/PrivateIdentification/DateAndPlaceOfBirth/BirthDate](#)
Type changed to: [CBPR_Date on page 197](#)
- on [pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/Invoicer/Identification/PrivateIdentification/DateAndPlaceOfBirth/BirthDate](#)
Type changed to: [CBPR_Date on page 197](#)

- on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/Invoicee/Identification/PrivateIdentification/DateAndPlaceOfBirth/BirthDate
Type changed to: CBPR_Date on page 197
- on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/GarnishmentRemittance/Garnishee/Identification/PrivateIdentification/DateAndPlaceOfBirth/BirthDate
Type changed to: CBPR_Date on page 197
- on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/GarnishmentRemittance/GarnishmentAdministrator/Identification/PrivateIdentification/DateAndPlaceOfBirth/BirthDate
Type changed to: CBPR_Date on page 197

5.21.2 ProvinceOfBirth

XML Tag: PrvcOfBirth

Presence: [0..1]

Definition: Province where a person was born.

Datatype: "Max35Text" on page 223

5.21.3 CityOfBirth

XML Tag: CityOfBirth

Presence: [1..1]

Definition: City where a person was born.

Datatype: "Max35Text" on page 223

5.21.4 CountryOfBirth

XML Tag: CtryOfBirth

Presence: [1..1]

Definition: Country where a person was born.

Datatype: "CountryCode" on page 201

5.22 DatePeriod2__1

Definition: Range of time defined by a start date and an end date.

⊘ Removed - ⊘ Partial Removed - ◇ Ignored - ◇ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.6.1.1	FromDate	<FrDt>		[1..1]	⚠	55
6.1.6.1.2	ToDate	<ToDt>		[1..1]	⚠	55

Used in element(s)

["FromDate" on page 187](#)

5.22.1 FromDate

XML Tag: FrDt

Presence: [1..1]

Definition: Start date of the range.

Datatype: ["CBPR_Date" on page 197](#)

Usage Guideline details

- on [pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/Tax/Record/Period/FromDate/FromDate](#)
Type changed to: [CBPR_Date on page 197](#)
- on [pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/Tax/Record/TaxAmount/Details/Period/FromDate/FromDate](#)
Type changed to: [CBPR_Date on page 197](#)
- on [pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/TaxRemittance/Record/Period/FromDate/FromDate](#)
Type changed to: [CBPR_Date on page 197](#)
- on [pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/TaxRemittance/Record/TaxAmount/Details/Period/FromDate/FromDate](#)
Type changed to: [CBPR_Date on page 197](#)

5.22.2 ToDate

XML Tag: ToDt

Presence: [1..1]

Definition: End date of the range.

Datatype: ["CBPR_Date" on page 197](#)

Usage Guideline details

- on [pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/Tax/Record/Period/FromDate/ToDate](#)
Type changed to: [CBPR_Date on page 197](#)
- on [pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/Tax/Record/TaxAmount/Details/Period/FromDate/ToDate](#)
Type changed to: [CBPR_Date on page 197](#)
- on [pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/TaxRemittance/Record/Period/FromDate/ToDate](#)
Type changed to: [CBPR_Date on page 197](#)

- on [pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/TaxRemittance/Record/TaxAmount/Details/Period/FromToDate/ToDate](#)
Type changed to: [CBPR_Date](#) on page 197

5.23 DirectDebitTransaction10__1

Definition: Provides further specific details on the direct debit transaction and the related mandate.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.8.2.1	MandateRelatedInformation	<MndtRltdInf>		[0..1]		56
6.1.8.2.2	CreditorSchemeIdentification	<CdtrSchmeld>		[0..1]		57
6.1.8.2.3	PreNotificationIdentification	<PreNtfctnId>		[0..1]		57
6.1.8.2.4	PreNotificationDate	<PreNtfctnDt>		[0..1]		57

Used in element(s)

"DirectDebitTransaction" on page 60

5.23.1 MandateRelatedInformation

XML Tag: MndtRltdInf

Presence: [0..1]

Definition: Provides further details of the direct debit mandate signed between the creditor and the debtor.

The **MndtRltdInf** block contains the following elements (see datatype "[MandateRelatedInformation14__1](#)" on page 102 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.8.3.1	MandateIdentification	<MndtId>		[0..1]		103
6.1.8.3.2	DateOfSignature	<DtOfSgntr>		[0..1]		103
6.1.8.3.3	AmendmentIndicator	<AmdmntInd>		[0..1]		103
6.1.8.3.4	AmendmentInformationDetails	<AmdmntInfDtls>		[0..1]		103
6.1.8.3.5	ElectronicSignature	<ElctrncSgntr>		[0..1]		104
6.1.8.3.6	FirstCollectionDate	<FrstColltnDt>		[0..1]		104
6.1.8.3.7	FinalCollectionDate	<FnIColltnDt>		[0..1]		105
6.1.8.3.8	Frequency	<Frqcy>		[0..1]		105

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.8.3.9	Reason	<Rsn>		[0..1]		105
6.1.8.3.10	TrackingDays	<TrckgDays>		[0..1]		106

5.23.2 CreditorSchemeldentification

XML Tag: CdtrSchmeld

Presence: [0..1]

Definition: Credit party that signs the mandate.

The **CdtrSchmeld** block contains the following elements (see datatype "[PartyIdentification135__1](#)" on [page 119](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.14.1.1	Name	<Nm>		[0..1]		120
6.1.14.1.2	PostalAddress	<PstlAdr>		[0..1]		120
6.1.14.1.3	Identification	<Id>		[0..1]		122
6.1.14.1.4	CountryOfResidence	<CtryOfRes>		[0..1]		123
6.1.14.1.5	ContactDetails	<CtctDtls>		[0..1]		123

5.23.3 PreNotificationIdentification

XML Tag: PreNtfctnId

Presence: [0..1]

Definition: Unique and unambiguous identification of the pre-notification which is sent separately from the direct debit instruction.

Usage: The direct debit pre-notification is used to reconcile separately sent collection information with the direct debit transaction information.

Datatype: "[Max35Text](#)" on [page 223](#)

5.23.4 PreNotificationDate

XML Tag: PreNtfctnDt

Presence: [0..1]

Definition: Date on which the creditor notifies the debtor about the amount and date on which the direct debit instruction will be presented to the debtor's agent.

Datatype: "[CBPR_Date](#)" on [page 197](#)

Usage Guideline details

- on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/PreNotificationDate

Type changed to: CBPR_Date on page 197

5.24 DirectDebitTransactionInformation23__1

Definition: Provides further details specific to the individual direct debit transaction(s) included in the message.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.15.5.17.1	PaymentIdentification	<PmtId>		[1..1]		59
6.1.15.5.17.2	PaymentTypeInformation	<PmtTplnf>		[0..1]		59
6.1.15.5.17.3	InstructedAmount	<InstdAmt>		[1..1]		59
6.1.15.5.17.4	ChargeBearer	<ChrgBr>		[0..1]		60
6.1.15.5.17.5	DirectDebitTransaction	<DrctDbtTx>		[0..1]		60
6.1.15.5.17.6	UltimateCreditor	<UltmtCdtr>		[0..1]		60
6.1.15.5.17.7	DebtorAgent	<DbtrAgt>		[1..1]		61
6.1.15.5.17.8	DebtorAgentAccount	<DbtrAgtAcct>		[0..1]		61
6.1.15.5.17.9	Debtor	<Dbtr>		[1..1]		62
6.1.15.5.17.10	DebtorAccount	<DbtrAcct>		[1..1]		63
6.1.15.5.17.11	UltimateDebtor	<UltmtDbtr>		[0..1]		63
6.1.15.5.17.12	InstructionForCreditorAgent	<InstrForCdtrAgt>		[0..1]		64
6.1.15.5.17.13	Purpose	<Purp>		[0..1]		64
6.1.15.5.17.14	RegulatoryReporting	<RgltryRptg>		[0..10]		65
6.1.15.5.17.15	Tax	<Tax>		[0..1]		65
6.1.15.5.17.16	RelatedRemittanceInformation	<RltdRmtInf>		[0..10]		65
6.1.15.5.17.17	RemittanceInformation	<RmtInf>		[0..1]		66
6.1.15.5.17.18	SupplementaryData	<SplmtryData>		[0..*]		66

Guidelines

1. UltimateCreditorGuideline

UltimateCreditor may only be present if different from Creditor.

2. UltimateDebtorGuideline

UltimateDebtor may only be present if different from Debtor.

Used in element(s)

"DirectDebitTransactionInformation" on page 134

5.24.1 PaymentIdentification

XML Tag: PmtId

Presence: [1..1]

Definition: Set of elements used to reference a payment instruction.

The **PmtId** block contains the following elements (see datatype "PaymentIdentification6_1" on page 124 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.11.2.1	InstructionIdentification	<InstrId>		[0..1]		124
6.1.11.2.2	EndToEndIdentification	<EndToEndId>		[1..1]		125
6.1.11.2.3	UETR	<UETR>		[0..1]		125

5.24.2 PaymentTypeInformation

XML Tag: PmtTpInf

Presence: [0..1]

Definition: Set of elements used to further specify the type of transaction.

The **PmtTpInf** block contains the following elements (see datatype "PaymentTypeInformation29" on page 135 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.16.2.1	InstructionPriority	<InstrPrty>		[0..1]		135
6.1.16.2.2	ServiceLevel	<SvcLvl>		[0..*]	R[0..3]	135
6.1.16.2.3	LocalInstrument	<LclInstrm>		[0..1]		136
6.1.16.2.4	SequenceType	<SeqTp>		[0..1]		136
6.1.16.2.5	CategoryPurpose	<CtgyPurp>		[0..1]		137

5.24.3 InstructedAmount

XML Tag: InstdAmt

Presence: [1..1]

Definition: Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.

Usage: This amount has to be transported unchanged through the transaction chain.

Datatype: ["ActiveOrHistoricCurrencyAndAmount" on page 192](#)

5.24.4 ChargeBearer

XML Tag: ChrgBr

Presence: [0..1]

Definition: Specifies which party/parties will bear the charges associated with the processing of the payment transaction.

Datatype: ["ChargeBearerType1Code" on page 199](#)

5.24.5 DirectDebitTransaction

XML Tag: DrctDbtTx

Presence: [0..1]

Definition: Provides information specific to the direct debit mandate.

The **DrctDbtTx** block contains the following elements (see datatype ["DirectDebitTransaction10__1" on page 56](#) for details)

❌ Removed - ⊗ Partial Removed - ◇ Ignored - ⊗ Partial Ignored - ⚠️ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.8.2.1	MandateRelatedInformation	<MndtRltdInf>		[0..1]		56
6.1.8.2.2	CreditorSchemeIdentification	<CdtrSchmeld>		[0..1]		57
6.1.8.2.3	PreNotificationIdentification	<PreNtfctnId>		[0..1]		57
6.1.8.2.4	PreNotificationDate	<PreNtfctnDt>		[0..1]	⚠️	57

5.24.6 UltimateCreditor

XML Tag: UltmtCdtr

Presence: [0..1]

Definition: Ultimate party to which an amount of money is due.

The **UltmtCdtr** block contains the following elements (see datatype ["PartyIdentification135__1" on page 119](#) for details)

❌ Removed - ⊗ Partial Removed - ◇ Ignored - ⊗ Partial Ignored - ⚠️ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.14.1.1	Name	<Nm>		[0..1]		120
6.1.14.1.2	PostalAddress	<PstlAdr>		[0..1]	⚠️	120

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.14.1.3	Identification	<Id>		[0..1]		122
6.1.14.1.4	CountryOfResidence	<CtryOfRes>		[0..1]		123
6.1.14.1.5	ContactDetails	<CtctDtls>		[0..1]		123

Usage Guideline details

- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/UltimateCreditor**
 - **CBPR_Ultimate_Creditor_TextualRule:**

Usage based on business need and bank service. If an ultimate creditor is involved in the payment, being different from the creditor, it must be provided. Required on Transaction Level, unless bilaterally determined.

- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/UltimateCreditor**
 - **CBPR_Party_Name_Postal_Address_FormalRule:**

If Postal Address is present then Name is mandatory.

For each [Full Message/Document/CustomerDirectDebitInitiationV08/PaymentInformation/DirectDebitTransactionInformation/UltimateCreditor], if at least one occurrence of the following element(s) [UltimateCreditor/PostalAddress] is (are) present, then at least one occurrence of the following element(s) [UltimateCreditor/Name] must be present

5.24.7 DebtorAgent

XML Tag: DbtrAgt

Presence: [1..1]

Definition: Financial institution servicing an account for the debtor.

The **DbtrAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6](#)" on page 27 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.10.4.1	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		27
6.1.10.4.2	BranchIdentification	<BrnchId>		[0..1]		28

5.24.8 DebtorAgentAccount

XML Tag: DbtrAgtAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain.

The **DbtrAgtAcct** block contains the following elements (see datatype "CashAccount38" on page 38 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.1.4.1	Identification	<Id>		[1..1]		38
6.1.1.4.2	Type	<Tp>		[0..1]		39
6.1.1.4.3	Currency	<Ccy>		[0..1]		39
6.1.1.4.4	Name	<Nm>		[0..1]		40
6.1.1.4.5	Proxy	<Prxy>		[0..1]		40

5.24.9 Debtor

XML Tag: Dbtr

Presence: [1..1]

Definition: Party that owes an amount of money to the (ultimate) creditor.

The **Dbtr** block contains the following elements (see datatype "PartyIdentification135__1" on page 119 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.14.1.1	Name	<Nm>		[0..1]	M	120
6.1.14.1.2	PostalAddress	<PstlAdr>		[0..1]	⚠	120
6.1.14.1.3	Identification	<Id>		[0..1]		122
6.1.14.1.4	CountryOfResidence	<CtryOfRes>		[0..1]		123
6.1.14.1.5	ContactDetails	<CtctDtls>		[0..1]	🚫	123

Usage Guideline details

- on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/Debtor
 - **CBPR_Party_Name_Postal_Address_FormalRule:**

If Postal Address is present then Name is mandatory.

For each [Full Message/Document/CustomerDirectDebitInitiationV08/PaymentInformation/DirectDebitTransactionInformation/Debtor], if
 at least one occurrence of the following element(s) [Debtor/PostalAddress]
 is (are) present
 , then
 at least one occurrence of the following element(s) [Debtor/Name] must be
 present

5.24.10 DebtorAccount

XML Tag: DbtrAcct

Presence: [1..1]

Definition: Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction.

The **DbtrAcct** block contains the following elements (see datatype "[CashAccount38](#)" on page 38 for details)

⊘ Removed - ⊘ Partial Removed - ◇ Ignored - ◇ Partial Ignored - ⚠ Details below -
 M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.1.4.1	Identification	<Id>		[1..1]		38
6.1.1.4.2	Type	<Tp>		[0..1]		39
6.1.1.4.3	Currency	<Ccy>		[0..1]		39
6.1.1.4.4	Name	<Nm>		[0..1]		40
6.1.1.4.5	Proxy	<Prxy>		[0..1]		40

5.24.11 UltimateDebtor

XML Tag: UltmtDbtr

Presence: [0..1]

Definition: Ultimate party that owes an amount of money to the (ultimate) creditor.

The **UltmtDbtr** block contains the following elements (see datatype "[PartyIdentification135_1](#)" on page 119 for details)

⊘ Removed - ⊘ Partial Removed - ◇ Ignored - ◇ Partial Ignored - ⚠ Details below -
 M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.14.1.1	Name	<Nm>		[0..1]		120
6.1.14.1.2	PostalAddress	<PstlAdr>		[0..1]	⚠	120
6.1.14.1.3	Identification	<Id>		[0..1]		122
6.1.14.1.4	CountryOfResidence	<CtryOfRes>		[0..1]		123
6.1.14.1.5	ContactDetails	<CtctDtls>		[0..1]	⊘	123

Usage Guideline details

- on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/UltimateDebtor
 - CBPR_Ultimate_Debtor_TextualRule:

Usage based on business need and bank service. If an ultimate debtor is involved in the payment, being different from the debtor, it must be provided.
- on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/UltimateDebtor
 - CBPR_Party_Name_Postal_Address_FormalRule:

If Postal Address is present then Name is mandatory.

For each [Full Message/Document/CustomerDirectDebitInitiationV08/PaymentInformation/DirectDebitTransactionInformation/UltimateDebtor], if
 at least one occurrence of the following element(s) [UltimateDebtor/Postal-Address] is (are) present
 , then
 at least one occurrence of the following element(s) [UltimateDebtor/Name]
 must be present

5.24.12 InstructionForCreditorAgent

XML Tag: InstrForCdtrAgt

Presence: [0..1]

Definition: Further information, related to the processing of the payment instruction, that may need to be acted upon by the creditor agent, depending on agreement between creditor and the creditor agent.

Datatype: "Max140Text" on page 222

5.24.13 Purpose

XML Tag: Purp

Presence: [0..1]

Definition: Underlying reason for the payment transaction.

Usage: Purpose is used by the end-customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain.

The **Purp** block contains the following elements (see datatype "Purpose2Choice" on page 153 for details)

❌ Removed -
 ❌ Partial Removed -
 ◆ Ignored -
 ◆ Partial Ignored -
 ⚠️ Details below -
 M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.12.2.1	Code	<Cd>	{Or	[1..1]		153
6.1.12.2.2	Proprietary	<Prtry>	Or}	[1..1]		154

5.24.14 RegulatoryReporting

XML Tag: RgltryRptg

Presence: [0..10]

Definition: Information needed due to regulatory and statutory requirements.

The **RgltryRptg** block contains the following elements (see datatype "RegulatoryReporting3__1" on page 157 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.19.1.1	DebitCreditReportingIndicator	<DbtCdtRptgInd>		[0..1]		158
6.1.19.1.2	Authority	<Authrty>		[0..1]		158
6.1.19.1.3	Details	<Dtls>		[0..*]		158

5.24.15 Tax

XML Tag: Tax

Presence: [0..1]

Definition: Provides details on the tax.

The **Tax** block contains the following elements (see datatype "TaxInformation8__1" on page 181 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.24.2.1	Creditor	<Cdtr>		[0..1]		181
6.1.24.2.2	Debtor	<Dbtr>		[0..1]		182
6.1.24.2.3	AdministrationZone	<AdmstnZone>		[0..1]		182
6.1.24.2.4	ReferenceNumber	<RefNb>		[0..1]		182
6.1.24.2.5	Method	<Mtd>		[0..1]		182
6.1.24.2.6	TotalTaxableBaseAmount	<TtlTaxblBaseAmt>		[0..1]		183
6.1.24.2.7	TotalTaxAmount	<TtlTaxAmt>		[0..1]		183
6.1.24.2.8	Date	<Dt>		[0..1]		183
6.1.24.2.9	SequenceNumber	<SeqNb>		[0..1]		183
6.1.24.2.10	Record	<Rcrd>		[0..*]		183

5.24.16 RelatedRemittanceInformation

XML Tag: RltdRmtInf

Presence: [0..10]

Definition: Provides information related to the handling of the remittance information by any of the agents in the transaction processing chain.

The **RltdRmtInf** block contains the following elements (see datatype "[RemittanceLocation7](#)" on [page 164](#) for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.4.1	RemittanceIdentification	<RmtId>		[0..1]		165
6.1.20.4.2	RemittanceLocationDetails	<RmtLctnDtls>		[0..*]		165

5.24.17 RemittanceInformation

XML Tag: RmtInf

Presence: [0..1]

Definition: Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system.

The **RmtInf** block contains the following elements (see datatype "[RemittanceInformation16__1](#)" on [page 163](#) for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.5.1	Unstructured	<Ustrd>		[0..*]	R[0..1]	163
6.1.20.5.2	Structured	<Strd>		[0..*]	⚠	164

5.24.18 SupplementaryData

XML Tag: SplmtryData

Presence: [0..*]

Definition: Additional information that cannot be captured in the structured elements and/or any other specific block.

The **SplmtryData** block contains the following elements (see datatype "[SupplementaryData1](#)" on [page 173](#) for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.12.1.1	PlaceAndName	<PlcAndNm>		[0..1]		174
6.1.12.1.2	Envelope	<Envlp>		[1..1]		174

Usage Guideline details

- This element([pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/SupplementaryData](#)) is removed.

5.25 DiscountAmountAndType1

Definition: Specifies the amount with a specific type.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.1.1.4.3.2.1 , 6.1.12.9.2.1	Type	<Tp>		[0..1]		67
6.1.20.1.1.4.3.2.2 , 6.1.12.9.2.2	Amount	<Amt>		[1..1]		67

Used in element(s)

"DiscountAppliedAmount" on page 159, "DiscountAppliedAmount" on page 162

5.25.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the type of the amount.

The **Tp** block contains the following elements (see datatype "[DiscountAmountType1Choice](#)" on page 67 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.1.1.4.3.2.1.1 , 6.1.12.9.2.1.1	Code	<Cd>	{Or	[1..1]		68
6.1.20.1.1.4.3.2.1.2 , 6.1.12.9.2.1.2	Proprietary	<Prtry>	Or}	[1..1]		68

5.25.2 Amount

XML Tag: Amt

Presence: [1..1]

Definition: Amount of money, which has been typed.

Datatype: "[ActiveOrHistoricCurrencyAndAmount](#)" on page 192

5.26 DiscountAmountType1Choice

Definition: Specifies the amount type.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.1.1.4.3.2.1.1 , 6.1.12.9.2.1.1	Code	<Cd>	{Or	[1..1]		68
6.1.20.1.1.4.3.2.1.2 , 6.1.12.9.2.1.2	Proprietary	<Prtry>	Or}	[1..1]		68

Used in element(s)

"Type" on page 67

5.26.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Specifies the amount type, in a coded form.

Datatype: "ExternalDiscountAmountType1Code" on page 209

5.26.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Specifies the amount type, in a free-text form.

Datatype: "Max35Text" on page 223

5.27 DocumentAdjustment1

Definition: Set of elements used to provide information on the amount and reason of the document adjustment.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.1.1.4.3.5.1 , 6.1.12.9.5.1	Amount	<Amt>		[1..1]		69
6.1.20.1.1.4.3.5.2 , 6.1.12.9.5.2	CreditDebitIndicator	<CdtDbtInd>		[0..1]		69
6.1.20.1.1.4.3.5.3 , 6.1.12.9.5.3	Reason	<Rsn>		[0..1]		69
6.1.20.1.1.4.3.5.4 , 6.1.12.9.5.4	AdditionalInformation	<AddtlInf>		[0..1]		69

Used in element(s)

["AdjustmentAmountAndReason" on page 160](#), ["AdjustmentAmountAndReason" on page 162](#)

5.27.1 Amount

XML Tag: Amt

Presence: [1..1]

Definition: Amount of money of the document adjustment.

Datatype: ["ActiveOrHistoricCurrencyAndAmount" on page 192](#)

5.27.2 CreditDebitIndicator

XML Tag: CdtDbtInd

Presence: [0..1]

Definition: Specifies whether the adjustment must be subtracted or added to the total amount.

Datatype: ["CreditDebitCode" on page 201](#)

5.27.3 Reason

XML Tag: Rsn

Presence: [0..1]

Definition: Specifies the reason for the adjustment.

Datatype: ["Max4Text" on page 224](#)

5.27.4 AdditionalInformation

XML Tag: AddtlInf

Presence: [0..1]

Definition: Provides further details on the document adjustment.

Datatype: ["Max140Text" on page 222](#)

5.28 DocumentLineIdentification1__1

Definition: Identifies the documents referred to in the remittance information.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.1.1.4.1.1	Type	<Tp>		[0..1]		70
6.1.20.1.1.4.1.2	Number	<Nb>		[0..1]		70
6.1.20.1.1.4.1.3	RelatedDate	<RltdDt>		[0..1]		70

Used in element(s)

"Identification" on page 71

5.28.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the type of referred document line identification.

The **Tp** block contains the following elements (see datatype "[DocumentLineType1](#)" on page 72 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.1.1.4.1.1.1	CodeOrProprietary	<CdOrPrtry>		[1..1]		72
6.1.20.1.1.4.1.1.2	Issuer	<Issr>		[0..1]		72

5.28.2 Number

XML Tag: Nb

Presence: [0..1]

Definition: Identification of the type specified for the referred document line.

Datatype: "[Max35Text](#)" on page 223

5.28.3 RelatedDate

XML Tag: RltdDt

Presence: [0..1]

Definition: Date associated with the referred document line.

Datatype: "[CBPR_Date](#)" on page 197

Usage Guideline details

- on [pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/ReferredDocumentInformation/LineDetails/Identification/RelatedDate](#)

Type changed to: [CBPR_Date](#) on page 197

5.29 DocumentLineInformation1__1

Definition: Provides document line information.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.1.1.4.1	Identification	<Id>		[1..*]		71
6.1.20.1.1.4.2	Description	<Desc>		[0..1]		71
6.1.20.1.1.4.3	Amount	<Amt>		[0..1]		71

Used in element(s)

"LineDetails" on page 155

5.29.1 Identification

XML Tag: Id

Presence: [1..*]

Definition: Provides identification of the document line.

The **Id** block contains the following elements (see datatype "[DocumentLineIdentification1_1](#)" on page 69 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.1.1.4.1.1	Type	<Tp>		[0..1]		70
6.1.20.1.1.4.1.2	Number	<Nb>		[0..1]		70
6.1.20.1.1.4.1.3	RelatedDate	<RltdDt>		[0..1]		70

5.29.2 Description

XML Tag: Desc

Presence: [0..1]

Definition: Description associated with the document line.

Datatype: "[Max2048Text](#)" on page 223

5.29.3 Amount

XML Tag: Amt

Presence: [0..1]

Definition: Provides details on the amounts of the document line.

The **Amt** block contains the following elements (see datatype "[RemittanceAmount3](#)" on page 161 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.1.1.4.3.1	DuePayableAmount	<DuePyblAmt>		[0..1]		161
6.1.20.1.1.4.3.2	DiscountAppliedAmount	<DscntApldAmt>		[0..*]		162
6.1.20.1.1.4.3.3	CreditNoteAmount	<CdtNoteAmt>		[0..1]		162
6.1.20.1.1.4.3.4	TaxAmount	<TaxAmt>		[0..*]		162
6.1.20.1.1.4.3.5	AdjustmentAmountAndReason	<AdjstmntAmtAndRsn>		[0..*]		162
6.1.20.1.1.4.3.6	RemittedAmount	<RmtdAmt>		[0..1]		163

5.30 DocumentLineType1

Definition: Specifies the type of the document line identification.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.1.1.4.1.1.1	CodeOrProprietary	<CdOrPrtry>		[1..1]		72
6.1.20.1.1.4.1.1.2	Issuer	<Issr>		[0..1]		72

Used in element(s)

"Type" on page 70

5.30.1 CodeOrProprietary

XML Tag: CdOrPrtry

Presence: [1..1]

Definition: Provides the type details of the referred document line identification.

The **CdOrPrtry** block contains the following elements (see datatype "[DocumentLineType1Choice](#)" on page 73 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.1.1.4.1.1.1.1	Code	<Cd>	{Or	[1..1]		73
6.1.20.1.1.4.1.1.1.2	Proprietary	<Prtry>	Or}	[1..1]		73

5.30.2 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Identification of the issuer of the reference document line identificationtype.

Datatype: "Max35Text" on page 223

5.31 DocumentLineType1Choice

Definition: Specifies the type of the document line identification.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.1.1.4.1.1.1.1	Code	<Cd>	{Or	[1..1]		73
6.1.20.1.1.4.1.1.1.2	Proprietary	<Prtry>	Or}	[1..1]		73

Used in element(s)

"CodeOrProprietary" on page 72

5.31.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Line identification type in a coded form.

Datatype: "ExternalDocumentLineType1Code" on page 209

5.31.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Proprietary identification of the type of the remittance document.

Datatype: "Max35Text" on page 223

5.32 FinancialIdentificationSchemeName1Choice

Definition: Sets of elements to identify a name of the organisation identification scheme.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.10.5.2.1	Code	<Cd>	{Or	[1..1]		74
6.1.10.5.2.2	Proprietary	<Prtry>	Or}	[1..1]	🚫	74

🚫 , ⬜ >> Note as not all **FinancialIdentificationSchemeName1Choice** blocks have this element removed and/or ignored. Please refer to the page number next to the element for further details on which elements have been removed and/or ignored.

Used in element(s)

"SchemeName" on page 91

5.32.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalFinancialInstitutionIdentification1Code" on page 210

5.32.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 223

Usage Guideline details

- This element(pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/Direct-DebitTransaction/MandateRelatedInformation/AmendmentInformationDetails/OriginalCreditorAgent/FinancialInstitutionIdentification/Other/SchemeName/Proprietary) is removed.
- This element(pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/Direct-DebitTransaction/MandateRelatedInformation/AmendmentInformationDetails/OriginalDebtorAgent/FinancialInstitutionIdentification/Other/SchemeName/Proprietary) is removed.

5.33 FinancialInstitutionIdentification18

Definition: Specifies the details to identify a financial institution.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.10.2.1	BICFI	<BICFI>		[0..1]	M	75
6.1.10.2.2	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]	⚠	75
6.1.10.2.3	LEI	<LEI>		[0..1]		76
6.1.10.2.4	Name	<Nm>		[0..1]	🚫	76
6.1.10.2.5	PostalAddress	<PstlAdr>		[0..1]	🚫 ⚠	76
6.1.10.2.6	Other	<Othr>		[0..1]	🚫	78

🚫 , ⬜ >> Note as not all **FinancialInstitutionIdentification18** blocks have this element removed and/or ignored. Please refer to the page number next to the element for further details on which elements have been removed and/or ignored.

Used in element(s)

"FinancialInstitutionIdentification" on page 27

5.33.1 BICFI

XML Tag: BICFI

Presence: [0..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: "BICFIDec2014Identifier" on page 196

Usage Guideline details

- on pain.008.001.08/GroupHeader/ForwardingAgent/FinancialInstitutionIdentification/BICFI

This element is now mandatory, the minimum occurrence has been changed to : 1

5.33.2 ClearingSystemMemberIdentification

XML Tag: ClrSysMmbld

Presence: [0..1]

Definition: Information used to identify a member within a clearing system.

The **ClrSysMmbld** block contains the following elements (see datatype "ClearingSystemMemberIdentification2" on page 43 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.10.1.1	ClearingSystemIdentification	<ClrSysId>		[0..1]		43
6.1.10.1.2	MemberIdentification	<Mmbld>		[1..1]		44

Usage Guideline details

- on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification
 - CBPR_Clearing_System_Member_Identification_TextualRule:

To be provided as second preference, unless BICFI, or Name and Address are provided as FI identification.
- on pain.008.001.08/PaymentInformation/CreditorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification
 - CBPR_Clearing_System_Member_Identification_TextualRule:

To be provided as second preference, unless BICFI, or Name and Address are provided as FI identification.

5.33.3 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identifier of the financial institution.

Datatype: "LEIIdentifier" on page 221

5.33.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "Max140Text" on page 222

Usage Guideline details

- This element(pain.008.001.08/GroupHeader/ForwardingAgent/FinancialInstitutionIdentification/Name) is removed.

5.33.5 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24" on page 142 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.18.1.1	AddressType	<AdrTp>		[0..1]		142
6.1.18.1.2	Department	<Dept>		[0..1]		144
6.1.18.1.3	SubDepartment	<SubDept>		[0..1]		144
6.1.18.1.4	StreetName	<StrtNm>		[0..1]		144
6.1.18.1.5	BuildingNumber	<BldgNb>		[0..1]		144
6.1.18.1.6	BuildingName	<BldgNm>		[0..1]		145
6.1.18.1.7	Floor	<Flr>		[0..1]		145
6.1.18.1.8	PostBox	<PstBx>		[0..1]		145

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.18.1.9	Room	<Room>		[0..1]		145
6.1.18.1.10	PostCode	<PstCd>		[0..1]		145
6.1.18.1.11	TownName	<TwnNm>		[0..1]	M	145
6.1.18.1.12	TownLocationName	<TwnLctnNm>		[0..1]		147
6.1.18.1.13	DistrictName	<DstrctNm>		[0..1]		147
6.1.18.1.14	CountrySubDivision	<CtrySubDvsn>		[0..1]		147
6.1.18.1.15	Country	<Ctry>		[0..1]	M	147
6.1.18.1.16	AddressLine	<AdrLine>		[0..7]	R[0..2] R[0..2] R[0..2] R[0..2] R[0..2] R[0..2] R[0..2]	145

⚠, ⚠ >> Note as not all **PstlAdr** blocks have this element removed and/or ignored. Please refer to the page number next to the element for further details on which elements have been removed and/or ignored.

Usage Guideline details

- This element(**pain.008.001.08/GroupHeader/ForwardingAgent/FinancialInstitutionIdentification/PostalAddress**) is removed.
- on **pain.008.001.08/PaymentInformation/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress**
 - **CBPR_Duplication_Postal_Address_TextualRule:**
Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.
- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/MandateRelatedInformation/AmendmentInformationDetails/OriginalCreditorAgent/FinancialInstitutionIdentification/PostalAddress**
 - **CBPR_Duplication_Postal_Address_TextualRule:**
Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.
- on **pain.008.001.08/PaymentInformation/CreditorAgent/FinancialInstitutionIdentification/PostalAddress**
 - **CBPR_Duplication_Postal_Address_TextualRule:**
Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.
- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress**
 - **CBPR_Duplication_Postal_Address_TextualRule:**
Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.

- on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/MandateRelatedInformation/AmendmentInformationDetails/OriginalDebtorAgent/FinancialInstitutionIdentification/PostalAddress

– **CBPR_Duplication_Postal_Address_TextualRule:**

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.

5.33.6 Other

XML Tag: Othr

Presence: [0..1]

Definition: Unique identification of an agent, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "GenericFinancialIdentification1" on page 91 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.10.5.1	Identification	<Id>		[1..1]		91
6.1.10.5.2	SchemeName	<SchmeNm>		[0..1]		91
6.1.10.5.3	Issuer	<Issr>		[0..1]		92

Usage Guideline details

- This element(pain.008.001.08/PaymentInformation/CreditorAgent/FinancialInstitutionIdentification/Other) is removed.
- This element(pain.008.001.08/GroupHeader/ForwardingAgent/FinancialInstitutionIdentification/Other) is removed.
- This element(pain.008.001.08/PaymentInformation/ChargesAccountAgent/FinancialInstitutionIdentification/Other) is removed.
- This element(pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/Other) is removed.

5.34 FinancialInstitutionIdentification18__1

Definition: Specifies the details to identify a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.10.2.1	BICFI	<BICFI>		[0..1]	M	79
6.1.10.2.2	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		79
6.1.10.2.3	LEI	<LEI>		[0..1]		80
6.1.10.2.4	Name	<Nm>		[0..1]	!O	80
6.1.10.2.5	PostalAddress	<PstlAdr>		[0..1]	!O	80
6.1.10.2.6	Other	<Othr>		[0..1]	!O	81

!O , **!D** >> Note as not all **FinancialInstitutionIdentification18__1** blocks have this element removed and/or ignored. Please refer to the page number next to the element for further details on which elements have been removed and/or ignored.

Used in element(s)

"FinancialInstitutionIdentification" on page 30

5.34.1 BICFI

XML Tag: BICFI

Presence: [0..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: "BICFIDec2014Identifier" on page 196

Usage Guideline details

- on **pain.008.001.08/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **pain.008.001.08/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **pain.008.001.08/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **pain.008.001.08/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI**
This element is now mandatory, the minimum occurrence has been changed to : 1

5.34.2 ClearingSystemMemberIdentification

XML Tag: ClrSysMmbld

Presence: [0..1]

Definition: Information used to identify a member within a clearing system.

The **ClrSysMmbld** block contains the following elements (see datatype "ClearingSystemMemberIdentification2__1" on page 44 for details)

🔴 Removed - 🟠 Partial Removed - 🟡 Ignored - 🟡 Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.10.1.1	ClearingSystemIdentification	<ClrSysId>		[0..1]	M	45
6.1.10.1.2	MemberIdentification	<Mmbld>		[1..1]	⚠	45

5.34.3 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identifier of the financial institution.

Datatype: "LEIIdentifier" on page 221

5.34.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "Max140Text" on page 222

Usage Guideline details

- This element(pain.008.001.08/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name) is removed.
- This element(pain.008.001.08/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name) is removed.
- This element(pain.008.001.08/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name) is removed.
- This element(pain.008.001.08/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name) is removed.

5.34.5 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24" on page 142 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.18.1.1	AddressType	<AdrTp>		[0..1]		142
6.1.18.1.2	Department	<Dept>		[0..1]		144
6.1.18.1.3	SubDepartment	<SubDept>		[0..1]		144
6.1.18.1.4	StreetName	<StrtNm>		[0..1]		144
6.1.18.1.5	BuildingNumber	<BldgNb>		[0..1]		144
6.1.18.1.6	BuildingName	<BldgNm>		[0..1]		145
6.1.18.1.7	Floor	<Flr>		[0..1]		145
6.1.18.1.8	PostBox	<PstBx>		[0..1]		145
6.1.18.1.9	Room	<Room>		[0..1]		145
6.1.18.1.10	PostCode	<PstCd>		[0..1]		145
6.1.18.1.11	TownName	<TwnNm>		[0..1]		145
6.1.18.1.12	TownLocationName	<TwnLctnNm>		[0..1]		147
6.1.18.1.13	DistrictName	<DstrctNm>		[0..1]		147
6.1.18.1.14	CountrySubDivision	<CtrySubDvsn>		[0..1]		147
6.1.18.1.15	Country	<Ctry>		[0..1]		147
6.1.18.1.16	AddressLine	<AdrLine>		[0..7]		149

Usage Guideline details

- This element(pain.008.001.08/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress) is removed.
- This element(pain.008.001.08/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress) is removed.
- This element(pain.008.001.08/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress) is removed.
- This element(pain.008.001.08/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress) is removed.

5.34.6 Other

XML Tag: Othr

Presence: [0..1]

Definition: Unique identification of an agent, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericFinancialIdentification1](#)" on [page 91](#) for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.10.5.1	Identification	<Id>		[1..1]		91
6.1.10.5.2	SchemeName	<SchmeNm>		[0..1]		91
6.1.10.5.3	Issuer	<Issr>		[0..1]		92

Usage Guideline details

- This element(pain.008.001.08/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other) is removed.
- This element(pain.008.001.08/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other) is removed.
- This element(pain.008.001.08/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other) is removed.
- This element(pain.008.001.08/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other) is removed.

5.35 Frequency36Choice

Definition: Choice of format for a frequency, for example, the frequency of payment.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.12.7.1	Type	<Tp>	{Or	[1..1]		82
6.1.12.7.2	Period	<Prd>	Or	[1..1]		83
6.1.12.7.3	PointInTime	<PtInTm>	Or}	[1..1]		83

Used in element(s)

"Frequency" on [page 105](#), "OriginalFrequency" on [page 25](#)

5.35.1 Type

XML Tag: Tp

Presence: [1..1]

Definition: Specifies a frequency in terms of a specified period type.

Datatype: "Frequency6Code" on page 218

5.35.2 Period

XML Tag: Prd

Presence: [1..1]

Definition: Specifies a frequency in terms of a count per period within a specified period type.

The **Prd** block contains the following elements (see datatype "FrequencyPeriod1" on page 84 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.12.7.2.1	Type	<Tp>		[1..1]		84
6.1.12.7.2.2	CountPerPeriod	<CntPerPrd>		[1..1]		84

5.35.3 PointInTime

XML Tag: PtInTm

Presence: [1..1]

Definition: Specifies a frequency in terms of an exact point in time or moment within a specified period type.

The **PtInTm** block contains the following elements (see datatype "FrequencyAndMoment1" on page 83 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.12.7.3.1	Type	<Tp>		[1..1]		84
6.1.12.7.3.2	PointInTime	<PtInTm>		[1..1]		84

5.36 FrequencyAndMoment1

Definition: Defines a frequency in terms a specific moment within a specified period type.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.12.7.3.1	Type	<Tp>		[1..1]		84
6.1.12.7.3.2	PointInTime	<PtInTm>		[1..1]		84

Used in element(s)

["PointInTime" on page 83](#)

5.36.1 Type

XML Tag: Tp

Presence: [1..1]

Definition: Period for which the number of instructions are to be created and processed.

Datatype: ["Frequency6Code" on page 218](#)

5.36.2 PointInTime

XML Tag: PtInTm

Presence: [1..1]

Definition: Further information on the exact point in time the event should take place.

Datatype: ["Exact2NumericText" on page 205](#)

5.37 FrequencyPeriod1

Definition: Defines a frequency in terms on counts per period for a specific period type.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.12.7.2.1	Type	<Tp>		[1..1]		84
6.1.12.7.2.2	CountPerPeriod	<CntPerPrd>		[1..1]		84

Used in element(s)

["Period" on page 83](#)

5.37.1 Type

XML Tag: Tp

Presence: [1..1]

Definition: Period for which the number of instructions are to be created and processed.

Datatype: ["Frequency6Code" on page 218](#)

5.37.2 CountPerPeriod

XML Tag: CntPerPrd

Presence: [1..1]

Definition: Number of instructions to be created and processed during the specified period.

Datatype: ["DecimalNumber" on page 202](#)

5.38 Garnishment3__1

Definition: Provides remittance information about a payment for garnishment-related purposes.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
 M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.2.1	Type	<Tp>		[1..1]		85
6.1.20.2.2	Garnishee	<Grnshee>		[0..1]	⚠	85
6.1.20.2.3	GarnishmentAdministrator	<GrnshmtAdmstr>		[0..1]	⚠	86
6.1.20.2.4	ReferenceNumber	<RefNb>		[0..1]		87
6.1.20.2.5	Date	<Dt>		[0..1]	⚠	87
6.1.20.2.6	RemittedAmount	<RmtdAmt>		[0..1]		87
6.1.20.2.7	FamilyMedicalInsuranceIndicator	<FmlyMdclInsrncInd>		[0..1]		88
6.1.20.2.8	EmployeeTerminationIndicator	<MplyeeTermntnInd>		[0..1]		88

Used in element(s)

"GarnishmentRemittance" on page 172

5.38.1 Type

XML Tag: Tp

Presence: [1..1]

Definition: Specifies the type of garnishment.

The **Tp** block contains the following elements (see datatype "GarnishmentType1" on page 88 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
 M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.2.1.1	CodeOrProprietary	<CdOrPrtry>		[1..1]		88
6.1.20.2.1.2	Issuer	<Issr>		[0..1]		89

5.38.2 Garnishee

XML Tag: Grnshee

Presence: [0..1]

Definition: Ultimate party that owes an amount of money to the (ultimate) creditor, in this case, to the garnisher.

The **Grnshee** block contains the following elements (see datatype "PartyIdentification135__1" on page 119 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.14.1.1	Name	<Nm>		[0..1]		120
6.1.14.1.2	PostalAddress	<PstlAdr>		[0..1]		120
6.1.14.1.3	Identification	<Id>		[0..1]		122
6.1.14.1.4	CountryOfResidence	<CtryOfRes>		[0..1]		123
6.1.14.1.5	ContactDetails	<CtctDtls>		[0..1]		123

Usage Guideline details

- on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/GarnishmentRemittance/Garnishee
 - CBPR_Party_Name_Postal_Address_FormalRule:

If Postal Address is present then Name is mandatory.

For each [Full Message/Document/CustomerDirectDebitInitiationV08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/GarnishmentRemittance/Garnishee], if
 at least one occurrence of the following element(s) [Garnishee/PostalAddress] is (are) present
 , then
 at least one occurrence of the following element(s) [Garnishee/Name] must be present

5.38.3 GarnishmentAdministrator

XML Tag: GrnshmtAdmstr

Presence: [0..1]

Definition: Party on the credit side of the transaction who administers the garnishment on behalf of the ultimate beneficiary.

The **GrnshmtAdmstr** block contains the following elements (see datatype "PartyIdentification135_1" on page 119 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.14.1.1	Name	<Nm>		[0..1]		120
6.1.14.1.2	PostalAddress	<PstlAdr>		[0..1]		120
6.1.14.1.3	Identification	<Id>		[0..1]		122

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.14.1.4	CountryOfResidence	<CtryOfRes>		[0..1]		123
6.1.14.1.5	ContactDetails	<CtctDtls>		[0..1]		123

Usage Guideline details

- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/GarnishmentRemittance/GarnishmentAdministrator**

- **CBPR_Party_Name_Postal_Address_FormalRule:**

If Postal Address is present then Name is mandatory.

For each [Full Message/Document/CustomerDirectDebitInitiationV08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/GarnishmentRemittance/GarnishmentAdministrator], if
 at least one occurrence of the following element(s) [GarnishmentAdministrator/PostalAddress] is (are) present
 , then
 at least one occurrence of the following element(s) [GarnishmentAdministrator/Name] must be present

5.38.4 ReferenceNumber

XML Tag: RefNb

Presence: [0..1]

Definition: Reference information that is specific to the agency receiving the garnishment.

Datatype: "Max140Text" on page 222

5.38.5 Date

XML Tag: Dt

Presence: [0..1]

Definition: Date of payment which garnishment was taken from.

Datatype: "CBPR_Date" on page 197

Usage Guideline details

- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/GarnishmentRemittance/Date**

Type changed to: CBPR_Date on page 197

5.38.6 RemittedAmount

XML Tag: RmtdAmt

Presence: [0..1]

Definition: Amount of money remitted for the referred document.

Datatype: ["ActiveOrHistoricCurrencyAndAmount" on page 192](#)

5.38.7 FamilyMedicalInsuranceIndicator

XML Tag: FmlyMdclInsrncInd

Presence: [0..1]

Definition: Indicates if the person to whom the garnishment applies (that is, the ultimate debtor) has family medical insurance coverage available.

Datatype: ["TrueFalseIndicator" on page 235](#)

5.38.8 EmployeeTerminationIndicator

XML Tag: MplyeeTermntnInd

Presence: [0..1]

Definition: Indicates if the employment of the person to whom the garnishment applies (that is, the ultimate debtor) has been terminated.

Datatype: ["TrueFalseIndicator" on page 235](#)

5.39 GarnishmentType1

Definition: Specifies the type of garnishment.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.2.1.1	CodeOrProprietary	<CdOrPrtry>		[1..1]		88
6.1.20.2.1.2	Issuer	<Issr>		[0..1]		89

Used in element(s)

["Type" on page 85](#)

5.39.1 CodeOrProprietary

XML Tag: CdOrPrtry

Presence: [1..1]

Definition: Provides the type details of the garnishment.

The **CdOrPrtry** block contains the following elements (see datatype ["GarnishmentType1Choice" on page 89](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.2.1.1.1	Code	<Cd>	{Or	[1..1]		89
6.1.20.2.1.1.2	Proprietary	<Prtry>	Or}	[1..1]		89

5.39.2 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Identification of the issuer of the garnishment type.

Datatype: "Max35Text" on page 223

5.40 GarnishmentType1Choice

Definition: Specifies the type of garnishment.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.2.1.1.1	Code	<Cd>	{Or	[1..1]		89
6.1.20.2.1.1.2	Proprietary	<Prtry>	Or}	[1..1]		89

Used in element(s)

"CodeOrProprietary" on page 88

5.40.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Garnishment type in a coded form.

Would suggest this to be an External Code List to contain:

GNCS Garnishment from a third party payer for Child Support

GNDP Garnishment from a Direct Payer for Child Support

GTPP Garnishment from a third party payer to taxing agency.

Datatype: "ExternalGarnishmentType1Code" on page 211

5.40.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Proprietary identification of the type of garnishment.

Datatype: "Max35Text" on page 223

5.41 GenericAccountIdentification1

Definition: Information related to a generic account identification.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.1.2.1	Identification	<Id>		[1..1]		90
6.1.1.2.2	SchemeName	<SchmeNm>		[0..1]		90
6.1.1.2.3	Issuer	<Issr>		[0..1]		90

Used in element(s)

"Other" on page 19

5.41.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: "Max34Text" on page 223

5.41.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "AccountSchemeName1Choice" on page 20 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.1.2.2.1	Code	<Cd>	{Or	[1..1]		20
6.1.1.2.2.2	Proprietary	<Prtry>	Or}	[1..1]		20

5.41.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 223

5.42 GenericFinancialIdentification1

Definition: Information related to an identification of a financial institution.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.10.5.1	Identification	<Id>		[1..1]		91
6.1.10.5.2	SchemeName	<SchmeNm>		[0..1]	M	91
6.1.10.5.3	Issuer	<Issr>		[0..1]		92

Used in element(s)

"Other" on page 81, "Other" on page 78

5.42.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: "Max35Text" on page 223

5.42.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "FinancialIdentificationScheme-Name1Choice" on page 73 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.10.5.2.1	Code	<Cd>	{Or	[1..1]		74
6.1.10.5.2.2	Proprietary	<Prtry>	Or}	[1..1]	🚫	74

🚫 , ⬜ >> Note as not all **SchmeNm** blocks have this element removed and/or ignored. Please refer to the page number next to the element for further details on which elements have been removed and/or ignored.

Usage Guideline details

- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/MandateRelatedInformation/AmendmentInformationDetails/OriginalCreditorAgent/FinancialInstitutionIdentification/Other/SchemeName**

This element is now mandatory, the minimum occurrence has been changed to : 1

- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/MandateRelatedInformation/AmendmentInformationDetails/OriginalDebtorAgent/FinancialInstitutionIdentification/Other/SchemeName**

This element is now mandatory, the minimum occurrence has been changed to : 1

5.42.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 223

5.43 GenericIdentification30

Definition: Information related to an identification, for example, party identification or account identification.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.11.1.1	Identification	<Id>		[1..1]		92
6.1.11.1.2	Issuer	<Issr>		[1..1]		92
6.1.11.1.3	SchemeName	<SchmeNm>		[0..1]		93

Used in element(s)

"Proprietary" on page 21

5.43.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Proprietary information, often a code, issued by the data source scheme issuer.

Datatype: "Exact4AlphaNumericText" on page 205

5.43.2 Issuer

XML Tag: Issr

Presence: [1..1]

Definition: Entity that assigns the identification.

Datatype: ["Max35Text" on page 223](#)

5.43.3 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Short textual description of the scheme.

Datatype: ["Max35Text" on page 223](#)

5.44 GenericOrganisationIdentification1

Definition: Information related to an identification of an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.13.1.3.1	Identification	<Id>		[1..1]		93
6.1.13.1.3.2	SchemeName	<SchmeNm>		[0..1]		93
6.1.13.1.3.3	Issuer	<Issr>		[0..1]		95

Used in element(s)

["Other" on page 109](#)

5.44.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: ["Max35Text" on page 223](#)

5.44.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype ["OrganisationIdentificationSchemeName1Choice" on page 110](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.13.1.3.2.1	Code	<Cd>	{Or	[1..1]		111
6.1.13.1.3.2.2	Proprietary	<Prtry>	Or}	[1..1]	!⊗	111

!⊗ , ⊗ >> Note as not all **SchmeNm** blocks have this element removed and/or ignored. Please refer to the page number next to the element for further details on which elements have been removed and/or ignored.

Usage Guideline details

- on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/Debtor/Identification/OrganisationIdentification/Other/SchemeName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pain.008.001.08/GroupHeader/InitiatingParty/Identification/OrganisationIdentification/Other/SchemeName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pain.008.001.08/PaymentInformation/Creditor/Identification/OrganisationIdentification/Other/SchemeName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/MandateRelatedInformation/AmendmentInformationDetails/OriginalCreditorSchemeIdentification/Identification/OrganisationIdentification/Other/SchemeName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/MandateRelatedInformation/AmendmentInformationDetails/OriginalDebtor/Identification/OrganisationIdentification/Other/SchemeName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/CreditorSchemeIdentification/Identification/OrganisationIdentification/Other/SchemeName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/UltimateCreditor/Identification/OrganisationIdentification/Other/SchemeName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/UltimateDebtor/Identification/OrganisationIdentification/Other/SchemeName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/Invoicer/Identification/OrganisationIdentification/Other/SchemeName**
This element is now mandatory, the minimum occurrence has been changed to : 1

- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/Invoicee/Identification/OrganisationIdentification/Other/SchemeName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/GarnishmentRemittance/Garnishee/Identification/OrganisationIdentification/Other/SchemeName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/GarnishmentRemittance/GarnishmentAdministrator/Identification/OrganisationIdentification/Other/SchemeName**
This element is now mandatory, the minimum occurrence has been changed to : 1

5.44.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 223

5.45 GenericPersonIdentification1

Definition: Information related to an identification of a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.17.1.2.1	Identification	<Id>		[1..1]		95
6.1.17.1.2.2	SchemeName	<SchmeNm>		[0..1]		95
6.1.17.1.2.3	Issuer	<Issr>		[0..1]		97

Used in element(s)

"Other" on page 139, "Other" on page 138

5.45.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: "Max35Text" on page 223

5.45.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "PersonIdentificationScheme-Name1Choice" on page 140 for details)

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.17.1.2.2.1	Code	<Cd>	{Or	[1..1]		140
6.1.17.1.2.2.2	Proprietary	<Prtry>	Or}	[1..1]	🚫	141

🚫 , ⚡ >> Note as not all **SchmeNm** blocks have this element removed and/or ignored. Please refer to the page number next to the element for further details on which elements have been removed and/or ignored.

Usage Guideline details

- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/Debtor/Identification/PrivateIdentification/Other/SchemeName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **pain.008.001.08/GroupHeader/InitiatingParty/Identification/PrivateIdentification/Other/SchemeName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **pain.008.001.08/PaymentInformation/Creditor/Identification/PrivateIdentification/Other/SchemeName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/MandateRelatedInformation/AmendmentInformationDetails/OriginalCreditorSchemeIdentification/Identification/PrivateIdentification/Other/SchemeName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/MandateRelatedInformation/AmendmentInformationDetails/OriginalDebtor/Identification/PrivateIdentification/Other/SchemeName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/CreditorSchemeIdentification/Identification/PrivateIdentification/Other/SchemeName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/UltimateCreditor/Identification/PrivateIdentification/Other/SchemeName**
This element is now mandatory, the minimum occurrence has been changed to : 1

- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/UltimateDebtor/Identification/PrivateIdentification/Other/SchemeName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/Invoicer/Identification/PrivateIdentification/Other/SchemeName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/Invoicee/Identification/PrivateIdentification/Other/SchemeName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/GarnishmentRemittance/Garnishee/Identification/PrivateIdentification/Other/SchemeName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/GarnishmentRemittance/GarnishmentAdministrator/Identification/PrivateIdentification/Other/SchemeName**
This element is now mandatory, the minimum occurrence has been changed to : 1

5.45.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 223

5.46 GroupHeader83__1

Definition: Set of characteristics shared by all individual transactions included in the message.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.12.6.1	MessageIdentification	<MsgId>		[1..1]		98
6.1.12.6.2	CreationDateTime	<CreDtTm>		[1..1]		98
6.1.12.6.3	Authorisation	<Authstn>		[0..2]		98
6.1.12.6.4	NumberOfTransactions	<NbOfTx>		[1..1]		99
6.1.12.6.5	ControlSum	<CtrlSum>		[0..1]		99
6.1.12.6.6	InitiatingParty	<InitgPty>		[1..1]		99
6.1.12.6.7	ForwardingAgent	<FwdgAgt>		[0..1]		100

Used in element(s)

["GroupHeader" on page 16](#)

5.46.1 MessageIdentification

XML Tag: MsgId

Presence: [1..1]

Definition: Point to point reference, assigned by the instructing party and sent to the next party in the chain, to unambiguously identify the message.

Usage: The instructing party has to make sure that MessageIdentification is unique per instructed party for a pre-agreed period.

Datatype: ["Max35Text" on page 223](#)

Usage Guideline details

- on [pain.008.001.08/GroupHeader/MessageIdentification](#)

- **CBPR_Message_Identification_TextualRule:**

Forwarding Agent should respect the Message ID provided by the Initiating Party of the pain.008 and pain.002.

5.46.2 CreationDateTime

XML Tag: CreDtTm

Presence: [1..1]

Definition: Date and time at which the message was created.

Datatype: ["CBPR_DateTime" on page 197](#)

Usage Guideline details

- on [pain.008.001.08/GroupHeader/CreationDateTime](#)

Type changed to: [CBPR_DateTime on page 197](#)

5.46.3 Authorisation

XML Tag: Authstn

Presence: [0..2]

Definition: User identification or any user key that allows to check if the initiating party is allowed to initiate transactions from the account specified in the initiation.

Usage: The content is not of a technical nature, but reflects the organisational structure at the initiating side. The authorisation element can typically be used in relay scenarios, payment initiations, payment returns or payment reversals that are initiated on behalf of a different party than the initiating party.

The **Authstn** block contains the following elements (see datatype "[Authorisation1Choice](#)" on page 26 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.12.10.1	Code	<Cd>	{Or	[1..1]		26
6.1.12.10.2	Proprietary	<Prtry>	Or}	[1..1]		26

5.46.4 NumberOfTransactions

XML Tag: NbOfTxS

Presence: [1..1]

Definition: Number of individual transactions contained in the message.

Datatype: "[Max15NumericText](#)" on page 222

5.46.5 ControlSum

XML Tag: CtrlSum

Presence: [0..1]

Definition: Total of all individual amounts included in the message, irrespective of currencies.

Datatype: "[DecimalNumber](#)" on page 202

Usage Guideline details

- This element([pain.008.001.08/GroupHeader/ControlSum](#)) is removed.

5.46.6 InitiatingParty

XML Tag: InitgPty

Presence: [1..1]

Definition: Party that initiates the payment.

Usage: This can either be the creditor or a party that initiates the direct debit on behalf of the creditor.

The **InitgPty** block contains the following elements (see datatype "[PartyIdentification135__1](#)" on page 119 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.14.1.1	Name	<Nm>		[0..1]		120
6.1.14.1.2	PostalAddress	<PstlAdr>		[0..1]		120

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.14.1.3	Identification	<Id>		[0..1]		122
6.1.14.1.4	CountryOfResidence	<CtryOfRes>		[0..1]		123
6.1.14.1.5	ContactDetails	<CtctDtls>		[0..1]		123

Usage Guideline details

- on pain.008.001.08/GroupHeader/InitiatingParty

- CBPR_Party_Name_Postal_Address_FormalRule:

If Postal Address is present then Name is mandatory.

For each [Full Message/Document/CustomerDirectDebitInitiationV08/GroupHeader/InitiatingParty], if
 at least one occurrence of the following element(s) [InitiatingParty/Postal-Address] is (are) present
 , then
 at least one occurrence of the following element(s) [InitiatingParty/Name] must be present

5.46.7 ForwardingAgent

XML Tag: FwdgAgt

Presence: [0..1]

Definition: Financial institution that receives the instruction from the initiating party and forwards it to the next agent in the payment chain for execution.

The **FwdgAgt** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification6" on page 27 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.10.4.1	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		27
6.1.10.4.2	BranchIdentification	<BrnchId>		[0..1]		28

Usage Guideline details

- on pain.008.001.08/GroupHeader/ForwardingAgent

This element is now mandatory, the minimum occurrence has been changed to : 1

5.47 ImplementationSpecification1

Definition: Identifies the implementation specification to which the ISO 20022 message conforms.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - 🚫 Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Registry	<Regy>		[1..1]		101
	Identification	<Id>		[1..1]		101

Used in element(s)

"MarketPractice" on page 12

5.47.1 Registry

XML Tag: Regy

Presence: [1..1]

Definition: Name of the implementation specification registry in which the implementation specification of the ISO 20022 message is maintained.

For example, "MyStandards".

Datatype: "Max350Text" on page 223

5.47.2 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identifier which unambiguously identifies, within the implementation specification registry, the implementation specification to which the ISO 20022 message is compliant. This can be done via a URN. It can also contain a version number or date.

For instance, "2018-01-01 - Version 2" or "urn:uuid:6e8bc430-9c3a-11d9-9669-0800200c9a66".

Datatype: "Max2048Text" on page 223

5.48 LocalInstrument2Choice

Definition: Set of elements that further identifies the type of local instruments being requested by the initiating party.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - 🚫 Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.16.2.3.1	Code	<Cd>	{Or	[1..1]		102
6.1.16.2.3.2	Proprietary	<Prtry>	Or}	[1..1]		102

Used in element(s)

"LocalInstrument" on page 136

5.48.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Specifies the local instrument, as published in an external local instrument code list.

Datatype: "ExternalLocalInstrument1Code" on page 211

5.48.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Specifies the local instrument, as a proprietary code.

Datatype: "Max35Text" on page 223

5.49 MandateRelatedInformation14__1

Definition: Provides further details related to a direct debit mandate signed between the creditor and the debtor.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.8.3.1	MandateIdentification	<MndtId>		[0..1]		103
6.1.8.3.2	DateOfSignature	<DtOfSgntr>		[0..1]		103
6.1.8.3.3	AmendmentIndicator	<AmdmntInd>		[0..1]		103
6.1.8.3.4	AmendmentInformationDetails	<AmdmntInfDtls>		[0..1]		103
6.1.8.3.5	ElectronicSignature	<ElctrncSgntr>		[0..1]		104
6.1.8.3.6	FirstCollectionDate	<FrstColltnDt>		[0..1]		104
6.1.8.3.7	FinalCollectionDate	<FnlColltnDt>		[0..1]		105
6.1.8.3.8	Frequency	<Frqcy>		[0..1]		105
6.1.8.3.9	Reason	<Rsn>		[0..1]		105
6.1.8.3.10	TrackingDays	<TrckgDays>		[0..1]		106

Rules

R15 AmendmentIndicatorTrueRule ✓

If AmendmentIndicator is true, then AmendmentInformationDetails must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00012
- *Error Text:* Invalid message content for true amendment indicator and details.

R16 AmendmentIndicatorFalseRule ✓

If AmendmentIndicator is false, then AmendmentInformationDetails is not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00013
- *Error Text:* Invalid message content for false amendment indicator and details.

Used in element(s)

"MandateRelatedInformation" on page 56

5.49.1 MandateIdentification

XML Tag: MndtId

Presence: [0..1]

Definition: Unique identification, as assigned by the creditor, to unambiguously identify the mandate.

Datatype: "Max35Text" on page 223

5.49.2 DateOfSignature

XML Tag: DtOfSgntr

Presence: [0..1]

Definition: Date on which the direct debit mandate has been signed by the debtor.

Datatype: "CBPR_Date" on page 197

Usage Guideline details

- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/MandateRelatedInformation/DateOfSignature**

Type changed to: CBPR_Date on page 197

5.49.3 AmendmentIndicator

XML Tag: AmdmntInd

Presence: [0..1]

Definition: Indicator notifying whether the underlying mandate is amended or not.

Datatype: "TrueFalseIndicator" on page 235

5.49.4 AmendmentInformationDetails

XML Tag: AmdmntInfDtls

Presence: [0..1]

Definition: List of mandate elements that have been modified.

The **AmdmntInfDtls** block contains the following elements (see datatype "AmendmentInformationDetails13__1" on page 21 for details)

⊖ Removed - ⊖ Partial Removed - ♦ Ignored - ♦ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.8.1.1	OriginalMandateIdentification	<OrgnlMndtId>		[0..1]		22
6.1.8.1.2	OriginalCreditorSchemeIdentification	<OrgnlCdtrSchmId>		[0..1]		22
6.1.8.1.3	OriginalCreditorAgent	<OrgnlCdtrAgt>		[0..1]		22
6.1.8.1.4	OriginalCreditorAgentAccount	<OrgnlCdtrAgtAcct>		[0..1]		23
6.1.8.1.5	OriginalDebtor	<OrgnlDbtr>		[0..1]		23
6.1.8.1.6	OriginalDebtorAccount	<OrgnlDbtrAcct>		[0..1]		23
6.1.8.1.7	OriginalDebtorAgent	<OrgnlDbtrAgt>		[0..1]		24
6.1.8.1.8	OriginalDebtorAgentAccount	<OrgnlDbtrAgtAcct>		[0..1]		24
6.1.8.1.9	OriginalFinalCollectionDate	<OrgnlFnlColltnDt>		[0..1]	⚠	25
6.1.8.1.10	OriginalFrequency	<OrgnlFrqcy>		[0..1]		25
6.1.8.1.11	OriginalReason	<OrgnlRsn>		[0..1]		25
6.1.8.1.12	OriginalTrackingDays	<OrgnlTrckgDays>		[0..1]		26

5.49.5 ElectronicSignature

XML Tag: ElctrncSgntr

Presence: [0..1]

Definition: Additional security provisions, such as a digital signature, as provided by the debtor.

Datatype: "Max1025Text" on page 221

5.49.6 FirstCollectionDate

XML Tag: FrstColltnDt

Presence: [0..1]

Definition: Date of the first collection of a direct debit as per the mandate.

Datatype: "CBPR_Date" on page 197

Usage Guideline details

- on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/MandateRelatedInformation/FirstCollectionDate

Type changed to: [CBPR_Date on page 197](#)

5.49.7 FinalCollectionDate

XML Tag: FnlColltnDt

Presence: [0..1]

Definition: Date of the final collection of a direct debit as per the mandate.

Datatype: ["CBPR_Date" on page 197](#)

Usage Guideline details

- on [pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/MandateRelatedInformation/FinalCollectionDate](#)

Type changed to: [CBPR_Date on page 197](#)

5.49.8 Frequency

XML Tag: Frqcy

Presence: [0..1]

Definition: Regularity with which direct debit instructions are to be created and processed.

The **Frqcy** block contains the following elements (see datatype ["Frequency36Choice" on page 82](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.12.7.1	Type	<Tp>	{Or	[1..1]		82
6.1.12.7.2	Period	<Prd>	Or	[1..1]		83
6.1.12.7.3	PointInTime	<PtInTm>	Or}	[1..1]		83

5.49.9 Reason

XML Tag: Rsn

Presence: [0..1]

Definition: Reason for the direct debit mandate to allow the user to distinguish between different mandates for the same creditor.

The **Rsn** block contains the following elements (see datatype ["MandateSetupReason1Choice" on page 106](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.8.1.11.1 , 6.1.8.3.9.1	Code	<Cd>	{Or	[1..1]		106
6.1.8.1.11.2 , 6.1.8.3.9.2	Proprietary	<Prtry>	Or}	[1..1]		106

5.49.10 TrackingDays

XML Tag: TrckgDays

Presence: [0..1]

Definition: Specifies the number of days the direct debit instruction must be tracked.

Datatype: "Exact2NumericText" on page 205

5.50 MandateSetupReason1Choice

Definition: Specifies the reason for the setup of the mandate.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.8.1.11.1 , 6.1.8.3.9.1	Code	<Cd>	{Or	[1..1]		106
6.1.8.1.11.2 , 6.1.8.3.9.2	Proprietary	<Prtry>	Or}	[1..1]		106

Used in element(s)

"OriginalReason" on page 25, "Reason" on page 105

5.50.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Reason for the mandate setup, as published in an external reason code list.

Datatype: "ExternalMandateSetupReason1Code" on page 212

5.50.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Reason for the mandate setup, in a proprietary form.

Datatype: "Max70Text" on page 224

5.51 NameAndAddress16

Definition: Information that locates and identifies a party.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.3.3.1	Name	<Nm>		[1..1]		107
6.1.20.3.3.2	Address	<Adr>		[1..1]		107

Used in element(s)

"PostalAddress" on page 166

5.51.1 Name

XML Tag: Nm

Presence: [1..1]

Definition: Name by which a party is known and is usually used to identify that party.

Datatype: "Max140Text" on page 222

5.51.2 Address

XML Tag: Adr

Presence: [1..1]

Definition: Postal address of a party.

The **Adr** block contains the following elements (see datatype "PostalAddress24" on page 142 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.18.1.1	AddressType	<AdrTp>		[0..1]		142
6.1.18.1.2	Department	<Dept>		[0..1]		144
6.1.18.1.3	SubDepartment	<SubDept>		[0..1]		144
6.1.18.1.4	StreetName	<StrtNm>		[0..1]		144
6.1.18.1.5	BuildingNumber	<BldgNb>		[0..1]		144
6.1.18.1.6	BuildingName	<BldgNm>		[0..1]		145
6.1.18.1.7	Floor	<Flr>		[0..1]		145
6.1.18.1.8	PostBox	<PstBx>		[0..1]		145
6.1.18.1.9	Room	<Room>		[0..1]		145
6.1.18.1.10	PostCode	<PstCd>		[0..1]		145

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.18.1.11	TownName	<TwnNm>		[0..1]		145
6.1.18.1.12	TownLocationName	<TwnLctnNm>		[0..1]		147
6.1.18.1.13	DistrictName	<DstrctNm>		[0..1]		147
6.1.18.1.14	CountrySubDivision	<CtrySubDvsn>		[0..1]		147
6.1.18.1.15	Country	<Ctry>		[0..1]		147
6.1.18.1.16	AddressLine	<AdrLine>		[0..7]	R[0..3]	149

5.52 OrganisationIdentification29

Definition: Unique and unambiguous way to identify an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.13.1.1	AnyBIC	<AnyBIC>		[0..1]		108
6.1.13.1.2	LEI	<LEI>		[0..1]		109
6.1.13.1.3	Other	<Othr>		[0..*]	 R[0..2] R[0..2] R[0..2] R[0..2]	109

 ,
  >> Note as not all **OrganisationIdentification29** blocks have this element removed and/or ignored. Please refer to the page number next to the element for further details on which elements have been removed and/or ignored.

Used in element(s)

"OrganisationIdentification" on page 114, "OrganisationIdentification" on page 113

5.52.1 AnyBIC

XML Tag: AnyBIC

Presence: [0..1]

Definition: Business identification code of the organisation.

Datatype: "AnyBICDec2014Identifier" on page 194

Usage Guideline details

- on pain.008.001.08/.header/Related/From/OrganisationIdentification/Identification/OrganisationIdentification/AnyBIC
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pain.008.001.08/.header/From/OrganisationIdentification/Identification/OrganisationIdentification/AnyBIC

This element is now mandatory, the minimum occurrence has been changed to : 1

- on `pain.008.001.08/.header/Related/To/OrganisationIdentification/Identification/OrganisationIdentification/AnyBIC`

This element is now mandatory, the minimum occurrence has been changed to : 1

- on `pain.008.001.08/.header/To/OrganisationIdentification/Identification/OrganisationIdentification/AnyBIC`

This element is now mandatory, the minimum occurrence has been changed to : 1

5.52.2 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identification as an alternate identification for a party.

Datatype: "[LEIIdentifier](#)" on page 221

5.52.3 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of an organisation, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericOrganisationIdentification1](#)" on page 93 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.13.1.3.1	Identification	<Id>		[1..1]		93
6.1.13.1.3.2	SchemeName	<SchmeNm>		[0..1]		93
6.1.13.1.3.3	Issuer	<Issr>		[0..1]		95

Usage Guideline details

- This element(`pain.008.001.08/.header/To/OrganisationIdentification/Identification/OrganisationIdentification/Other`) is removed.
- This element(`pain.008.001.08/.header/From/OrganisationIdentification/Identification/OrganisationIdentification/Other`) is removed.
- This element(`pain.008.001.08/.header/Related/To/OrganisationIdentification/Identification/OrganisationIdentification/Other`) is removed.
- This element(`pain.008.001.08/.header/Related/From/OrganisationIdentification/Identification/OrganisationIdentification/Other`) is removed.

- on **pain.008.001.08/GroupHeader/InitiatingParty/Identification/OrganisationIdentification/Other**
This element has change repeatability, the maximum occurrence has been changed to : 2
- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/GarnishmentRemittance/GarnishmentAdministrator/Identification/OrganisationIdentification/Other**
This element has change repeatability, the maximum occurrence has been changed to : 2
- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/Debtor/Identification/OrganisationIdentification/Other**
This element has change repeatability, the maximum occurrence has been changed to : 2
- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/UltimateCreditor/Identification/OrganisationIdentification/Other**
This element has change repeatability, the maximum occurrence has been changed to : 2
- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/GarnishmentRemittance/Garnishee/Identification/OrganisationIdentification/Other**
This element has change repeatability, the maximum occurrence has been changed to : 2
- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/UltimateDebtor/Identification/OrganisationIdentification/Other**
This element has change repeatability, the maximum occurrence has been changed to : 2
- on **pain.008.001.08/PaymentInformation/Creditor/Identification/OrganisationIdentification/Other**
This element has change repeatability, the maximum occurrence has been changed to : 2
- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/Invoicee/Identification/OrganisationIdentification/Other**
This element has change repeatability, the maximum occurrence has been changed to : 2
- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/Invoicer/Identification/OrganisationIdentification/Other**
This element has change repeatability, the maximum occurrence has been changed to : 2
- on **pain.008.001.08/PaymentInformation/UltimateCreditor/Identification/OrganisationIdentification/Other**
This element has change repeatability, the maximum occurrence has been changed to : 2

5.53 OrganisationIdentificationSchemeName1Choice

Definition: Sets of elements to identify a name of the organisation identification scheme.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.13.1.3.2.1	Code	<Cd>	{Or	[1..1]		111

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.13.1.3.2.2	Proprietary	<Prtry>	Or}	[1..1]		111

 ,  >> Note as not all **OrganisationIdentificationSchemeName1Choice** blocks have this element removed and/or ignored. Please refer to the page number next to the element for further details on which elements have been removed and/or ignored.

Used in element(s)

"SchemeName" on page 93

5.53.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalOrganisationIdentification1Code" on page 213

5.53.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 223

Usage Guideline details

- This element(pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/Debtor/Identification/OrganisationIdentification/Other/SchemeName/Proprietary) is removed.
- This element(pain.008.001.08/GroupHeader/InitiatingParty/Identification/OrganisationIdentification/Other/SchemeName/Proprietary) is removed.
- This element(pain.008.001.08/PaymentInformation/Creditor/Identification/OrganisationIdentification/Other/SchemeName/Proprietary) is removed.
- This element(pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/Direct-DebitTransaction/MandateRelatedInformation/AmendmentInformationDetails/OriginalCreditorSchemeIdentification/Identification/OrganisationIdentification/Other/SchemeName/Proprietary) is removed.
- This element(pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/Direct-DebitTransaction/MandateRelatedInformation/AmendmentInformationDetails/OriginalDebtor/Identification/OrganisationIdentification/Other/SchemeName/Proprietary) is removed.
- This element(pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/Direct-DebitTransaction/CreditorSchemeIdentification/Identification/OrganisationIdentification/Other/SchemeName/Proprietary) is removed.

- This element(**pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/UltimateCreditor/Identification/OrganisationIdentification/Other/SchemeName/Proprietary**) is removed.
- This element(**pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/UltimateDebtor/Identification/OrganisationIdentification/Other/SchemeName/Proprietary**) is removed.
- This element(**pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/Invoicer/Identification/OrganisationIdentification/Other/SchemeName/Proprietary**) is removed.
- This element(**pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/Invoicee/Identification/OrganisationIdentification/Other/SchemeName/Proprietary**) is removed.
- This element(**pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/GarnishmentRemittance/Garnishee/Identification/OrganisationIdentification/Other/SchemeName/Proprietary**) is removed.
- This element(**pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/GarnishmentRemittance/GarnishmentAdministrator/Identification/OrganisationIdentification/Other/SchemeName/Proprietary**) is removed.

5.54 OtherContact1

Definition: Communication device number or electronic address used for communication.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.17.2.11.1	ChannelType	<ChanTp>		[1..1]		112
6.1.17.2.11.2	Identification	<Id>		[0..1]		112

Used in element(s)

"Other" on page 48

5.54.1 ChannelType

XML Tag: ChanTp

Presence: [1..1]

Definition: Method used to contact the financial institution's contact for the specific tax region.

Datatype: "Max4Text" on page 224

5.54.2 Identification

XML Tag: Id

Presence: [0..1]

Definition: Communication value such as phone number or email address.

Datatype: "Max128Text" on page 221

5.55 Party38Choice

Definition: Nature or use of the account.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.14.2.1	OrganisationIdentification	<OrgId>	{Or	[1..1]		113
6.1.14.2.2	PrivateIdentification	<PrvtId>	Or}	[1..1]	🚫	113

🚫 , ⬜ >> Note as not all **Party38Choice** blocks have this element removed and/or ignored. Please refer to the page number next to the element for further details on which elements have been removed and/or ignored.

Used in element(s)

"Identification" on page 118

5.55.1 OrganisationIdentification

XML Tag: OrgId

Presence: [1..1]

Definition: Unique and unambiguous way to identify an organisation.

The **OrgId** block contains the following elements (see datatype "[OrganisationIdentification29](#)" on page 108 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.13.1.1	AnyBIC	<AnyBIC>		[0..1]	M	108
6.1.13.1.2	LEI	<LEI>		[0..1]		109
6.1.13.1.3	Other	<Othr>		[0..*]	🚫 R[0..2]	109

🚫 , ⬜ >> Note as not all **OrgId** blocks have this element removed and/or ignored. Please refer to the page number next to the element for further details on which elements have been removed and/or ignored.

5.55.2 PrivateIdentification

XML Tag: PrvtId

Presence: [1..1]

Definition: Unique and unambiguous identification of a person, for example a passport.

The **PrvtId** block contains the following elements (see datatype "[PersonIdentification13](#)" on page 137 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.17.1.1	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		137
6.1.17.1.2	Other	<Othr>		[0..*]	R[0..2]	138

Usage Guideline details

- This element(pain.008.001.08/.header/Related/From/OrganisationIdentification/Identification/Privateldentification) is removed.
- This element(pain.008.001.08/.header/To/OrganisationIdentification/Identification/Privateldentification) is removed.
- This element(pain.008.001.08/.header/From/OrganisationIdentification/Identification/Privateldentification) is removed.
- This element(pain.008.001.08/.header/Related/To/OrganisationIdentification/Identification/Privateldentification) is removed.

5.56 Party38Choice__1

Definition: Nature or use of the account.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.14.2.1	OrganisationIdentification	<OrgId>	{Or	[1..1]		114
6.1.14.2.2	Privateldentification	<PrvtId>	Or}	[1..1]		115

Used in element(s)

"[Identification](#)" on page 122

5.56.1 OrganisationIdentification

XML Tag: OrgId

Presence: [1..1]

Definition: Unique and unambiguous way to identify an organisation.

The **OrgId** block contains the following elements (see datatype "[OrganisationIdentification29](#)" on page 108 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.13.1.1	AnyBIC	<AnyBIC>		[0..1]		108
6.1.13.1.2	LEI	<LEI>		[0..1]		109
6.1.13.1.3	Other	<Othr>		[0..*]	R[0..2] R[0..2] R[0..2] R[0..2]	109

5.56.2 PrivateIdentification

XML Tag: PrvtId

Presence: [1..1]

Definition: Unique and unambiguous identification of a person, for example a passport.

The **PrvtId** block contains the following elements (see datatype "[PersonIdentification13__1](#)" on page 138 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.17.1.1	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		139
6.1.17.1.2	Other	<Othr>		[0..*]	R[0..2] R[0..2] R[0..2] R[0..2]	139

5.57 Party44Choice__1

Definition: Identification of a person, an organisation or a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		115
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		116

Used in element(s)

"From" on page 10, "From" on page 34, "To" on page 11, "To" on page 34

5.57.1 OrganisationIdentification

XML Tag: OrgId

Presence: [1..1]

Definition: Identification of a person or an organisation.

The **OrgId** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 116 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.14.1.1	Name	<Nm>		[0..1]		117
6.1.14.1.2	PostalAddress	<PstlAdr>		[0..1]		117
6.1.14.1.3	Identification	<Id>		[0..1]		118
6.1.14.1.4	CountryOfResidence	<CtryOfRes>		[0..1]		118
6.1.14.1.5	ContactDetails	<CtctDtls>		[0..1]		118

Usage Guideline details

- This element(pain.008.001.08/.header/Related/From/OrganisationIdentification) is removed.
- This element(pain.008.001.08/.header/To/OrganisationIdentification) is removed.
- This element(pain.008.001.08/.header/From/OrganisationIdentification) is removed.
- This element(pain.008.001.08/.header/Related/To/OrganisationIdentification) is removed.

5.57.2 FinancialInstitutionIdentification

XML Tag: FIId

Presence: [1..1]

Definition: Identification of a financial institution.

The **FIId** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6_1](#)" on page 29 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.10.4.1	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		30
6.1.10.4.2	BranchIdentification	<BrnchId>		[0..1]		30

 ,  >> Note as not all **FIId** blocks have this element removed and/or ignored. Please refer to the page number next to the element for further details on which elements have been removed and/or ignored.

5.58 PartyIdentification135

Definition: Specifies the identification of a person or an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.14.1.1	Name	<Nm>		[0..1]		117
6.1.14.1.2	PostalAddress	<PstlAdr>		[0..1]		117
6.1.14.1.3	Identification	<Id>		[0..1]		118
6.1.14.1.4	CountryOfResidence	<CtryOfRes>		[0..1]		118
6.1.14.1.5	ContactDetails	<CtctDtls>		[0..1]		118

Used in element(s)

"CreditorSchemeIdentification" on page 133, "OrganisationIdentification" on page 115, "Ultimate-Creditor" on page 132

5.58.1 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: "Max140Text" on page 222

5.58.2 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24" on page 142 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.18.1.1	AddressType	<AdrTp>		[0..1]		142
6.1.18.1.2	Department	<Dept>		[0..1]		144
6.1.18.1.3	SubDepartment	<SubDept>		[0..1]		144
6.1.18.1.4	StreetName	<StrtNm>		[0..1]		144
6.1.18.1.5	BuildingNumber	<BldgNb>		[0..1]		144
6.1.18.1.6	BuildingName	<BldgNm>		[0..1]		145
6.1.18.1.7	Floor	<Flr>		[0..1]		145
6.1.18.1.8	PostBox	<PstBx>		[0..1]		145
6.1.18.1.9	Room	<Room>		[0..1]		145

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.18.1.10	PostCode	<PstCd>		[0..1]		145
6.1.18.1.11	TownName	<TwnNm>		[0..1]	M	145
6.1.18.1.12	TownLocationName	<TwnLctnNm>		[0..1]		147
6.1.18.1.13	DistrictName	<DstrctNm>		[0..1]		147
6.1.18.1.14	CountrySubDivision	<CtrySubDvsn>		[0..1]		147
6.1.18.1.15	Country	<Ctry>		[0..1]	M	147
6.1.18.1.16	AddressLine	<AdrLine>		[0..7]	!	149

!, **!** >> Note as not all **PstlAdr** blocks have this element removed and/or ignored. Please refer to the page number next to the element for further details on which elements have been removed and/or ignored.

5.58.3 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a party.

The **Id** block contains the following elements (see datatype "Party38Choice" on page 113 for details)

! Removed - **!** Partial Removed - **!** Ignored - **!** Partial Ignored - **!** Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.14.2.1	OrganisationIdentification	<OrgId>	{Or	[1..1]		113
6.1.14.2.2	PrivateIdentification	<PrvtId>	Or}	[1..1]	!	113

!, **!** >> Note as not all **Id** blocks have this element removed and/or ignored. Please refer to the page number next to the element for further details on which elements have been removed and/or ignored.

5.58.4 CountryOfResidence

XML Tag: CtryOfRes

Presence: [0..1]

Definition: Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.

Datatype: "CountryCode" on page 201

5.58.5 ContactDetails

XML Tag: CtctDtls

Presence: [0..1]

Definition: Set of elements used to indicate how to contact the party.

The **CtctDtls** block contains the following elements (see datatype "Contact4" on page 46 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.17.2.1	NamePrefix	<NmPrfx>		[0..1]		47
6.1.17.2.2	Name	<Nm>		[0..1]		47
6.1.17.2.3	PhoneNumber	<PhneNb>		[0..1]		47
6.1.17.2.4	MobileNumber	<MobNb>		[0..1]		47
6.1.17.2.5	FaxNumber	<FaxNb>		[0..1]		47
6.1.17.2.6	EmailAddress	<EmailAdr>		[0..1]		47
6.1.17.2.7	EmailPurpose	<EmailPurp>		[0..1]		47
6.1.17.2.8	JobTitle	<JobTitl>		[0..1]		48
6.1.17.2.9	Responsibility	<Rspnsblty>		[0..1]		48
6.1.17.2.10	Department	<Dept>		[0..1]		48
6.1.17.2.11	Other	<Othr>		[0..*]		48
6.1.17.2.12	PreferredMethod	<PrefrdMtd>		[0..1]		48

Usage Guideline details

- This element(pain.008.001.08/PaymentInformation/UltimateCreditor/ContactDetails) is removed.

5.59 PartyIdentification135__1

Definition: Specifies the identification of a person or an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.14.1.1	Name	<Nm>		[0..1]		120
6.1.14.1.2	PostalAddress	<PstlAdr>		[0..1]		120
6.1.14.1.3	Identification	<Id>		[0..1]		122
6.1.14.1.4	CountryOfResidence	<CtryOfRes>		[0..1]		123
6.1.14.1.5	ContactDetails	<CtctDtls>		[0..1]		123

Used in element(s)

"Creditor" on page 130, "CreditorSchemeIdentification" on page 57, "Debtor" on page 62, "Garnishee" on page 85, "GarnishmentAdministrator" on page 86, "InitiatingParty" on page 99, "Invoicee" on page 171, "Invoicer" on page 170, "OriginalCreditorSchemeIdentification" on page 22, "OriginalDebtor" on page 23, "UltimateCreditor" on page 60, "UltimateDebtor" on page 63

5.59.1 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: "Max140Text" on page 222

Usage Guideline details

- on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/Debtor/Name

This element is now mandatory, the minimum occurrence has been changed to : 1

5.59.2 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24" on page 142 for details)

❌ Removed - ⊗ Partial Removed - ◇ Ignored - ⊠ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.18.1.1	AddressType	<AdrTp>		[0..1]	❌	142
6.1.18.1.2	Department	<Dept>		[0..1]		144
6.1.18.1.3	SubDepartment	<SubDept>		[0..1]		144
6.1.18.1.4	StreetName	<StrtNm>		[0..1]		144
6.1.18.1.5	BuildingNumber	<BldgNb>		[0..1]		144
6.1.18.1.6	BuildingName	<BldgNm>		[0..1]		145
6.1.18.1.7	Floor	<Flr>		[0..1]		145
6.1.18.1.8	PostBox	<PstBx>		[0..1]		145
6.1.18.1.9	Room	<Room>		[0..1]		145
6.1.18.1.10	PostCode	<PstCd>		[0..1]		145
6.1.18.1.11	TownName	<TwnNm>		[0..1]	M	145

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.18.1.12	TownLocationName	<TwnLctnNm>		[0..1]		147
6.1.18.1.13	DistrictName	<DstrctNm>		[0..1]		147
6.1.18.1.14	CountrySubDivision	<CtrySubDvsn>		[0..1]		147
6.1.18.1.15	Country	<Ctry>		[0..1]	M	147
6.1.18.1.16	AddressLine	<AdrLine>		[0..7]	R[0..2] R[0..2] R[0..2] R[0..2] R[0..2] R[0..2] R[0..2]	147

⚠, ⚠ >> Note as not all **PstlAdr** blocks have this element removed and/or ignored. Please refer to the page number next to the element for further details on which elements have been removed and/or ignored.

Usage Guideline details

- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/CreditorSchemeIdentification/PostalAddress**
 - **CBPR_Duplication_Postal_Address_TextualRule:**
Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.
- on **pain.008.001.08/PaymentInformation/Creditor/PostalAddress**
 - **CBPR_Duplication_Postal_Address_TextualRule:**
Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.
- on **pain.008.001.08/GroupHeader/InitiatingParty/PostalAddress**
 - **CBPR_Duplication_Postal_Address_TextualRule:**
Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.
- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/UltimateCreditor/PostalAddress**
 - **CBPR_Duplication_Postal_Address_TextualRule:**
Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.
- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/UltimateDebtor/PostalAddress**
 - **CBPR_Duplication_Postal_Address_TextualRule:**
Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.
- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/GarnishmentRemittance/GarnishmentAdministrator/PostalAddress**

– **CBPR_Duplication_Postal_Address_TextualRule:**

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.

- **on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/Invoicer/PostalAddress**

– **CBPR_Duplication_Postal_Address_TextualRule:**

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.

- **on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/GarnishmentRemittance/Garnishee/PostalAddress**

– **CBPR_Duplication_Postal_Address_TextualRule:**

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.

- **on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/Invoicee/PostalAddress**

– **CBPR_Duplication_Postal_Address_TextualRule:**

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.

- **on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/Debtor/PostalAddress**

– **CBPR_Duplication_Postal_Address_TextualRule:**

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.

- **on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/MandateRelatedInformation/AmendmentInformationDetails/OriginalDebtor/PostalAddress**

– **CBPR_Duplication_Postal_Address_TextualRule:**

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.

- **on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/MandateRelatedInformation/AmendmentInformationDetails/OriginalCreditorSchemeIdentification/PostalAddress**

– **CBPR_Duplication_Postal_Address_TextualRule:**

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.

5.59.3 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a party.

The **Id** block contains the following elements (see datatype "[Party38Choice__1](#)" on page 114 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.14.2.1	OrganisationIdentification	<OrgId>	{Or	[1..1]		114
6.1.14.2.2	PrivateIdentification	<PrvtId>	Or}	[1..1]		115

5.59.4 CountryOfResidence

XML Tag: CtryOfRes

Presence: [0..1]

Definition: Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.

Datatype: "[CountryCode](#)" on page 201

5.59.5 ContactDetails

XML Tag: CtctDtls

Presence: [0..1]

Definition: Set of elements used to indicate how to contact the party.

The **CtctDtls** block contains the following elements (see datatype "[Contact4](#)" on page 46 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.17.2.1	NamePrefix	<NmPrfx>		[0..1]		47
6.1.17.2.2	Name	<Nm>		[0..1]		47
6.1.17.2.3	PhoneNumber	<PhneNb>		[0..1]		47
6.1.17.2.4	MobileNumber	<MobNb>		[0..1]		47
6.1.17.2.5	FaxNumber	<FaxNb>		[0..1]		47
6.1.17.2.6	EmailAddress	<EmailAdr>		[0..1]		47
6.1.17.2.7	EmailPurpose	<EmailPurp>		[0..1]		47
6.1.17.2.8	JobTitle	<JobTitl>		[0..1]		48
6.1.17.2.9	Responsibility	<Rspnsblty>		[0..1]		48
6.1.17.2.10	Department	<Dept>		[0..1]		48

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.17.2.11	Other	<Othr>		[0..*]		48
6.1.17.2.12	PreferredMethod	<PrefrdMtd>		[0..1]		48

Usage Guideline details

- This element(pain.008.001.08/PaymentInformation/Creditor/ContactDetails) is removed.
- This element(pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/Debtor/ContactDetails) is removed.
- This element(pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/GarnishmentRemittance/GarnishmentAdministrator/ContactDetails) is removed.
- This element(pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/Invoicer/ContactDetails) is removed.
- This element(pain.008.001.08/GroupHeader/InitiatingParty/ContactDetails) is removed.
- This element(pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/GarnishmentRemittance/Garnishee/ContactDetails) is removed.
- This element(pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/UltimateCreditor/ContactDetails) is removed.
- This element(pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/Invoicee/ContactDetails) is removed.
- This element(pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/UltimateDebtor/ContactDetails) is removed.

5.60 PaymentIdentification6__1

Definition: Provides further means of referencing a payment transaction.

❌ Removed -
 ⊘ Partial Removed -
 ◇ Ignored -
 ⊠ Partial Ignored -
 ⚠ Details below -
 M Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.11.2.1	InstructionIdentification	<InstrId>		[0..1]	⚠	124
6.1.11.2.2	EndToEndIdentification	<EndToEndId>		[1..1]	⚠	125
6.1.11.2.3	UETR	<UETR>		[0..1]		125

Used in element(s)

"PaymentIdentification" on page 59

5.60.1 InstructionIdentification

XML Tag: InstrId

Presence: [0..1]

Definition: Unique identification as assigned by an instructing party for an instructed party to unambiguously identify the instruction.

Usage: The instruction identification is a point to point reference that can be used between the instructing party and the instructed party to refer to the individual instruction. It can be included in several messages related to the instruction.

Datatype: "Max35Text" on page 223

Usage Guideline details

- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/PaymentIdentification/InstructionIdentification**

– **CBPR_Instruction_Identification_TextualRule:**

If provided, this Id is returned to the ordering party in account statement reporting.

5.60.2 EndToEndIdentification

XML Tag: EndToEndId

Presence: [1..1]

Definition: Unique identification assigned by the initiating party to unambiguously identify the transaction. This identification is passed on, unchanged, throughout the entire end-to-end chain.

Usage: The end-to-end identification can be used for reconciliation or to link tasks relating to the transaction. It can be included in several messages related to the transaction.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 198

Usage Guideline details

- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/PaymentIdentification/EndToEndIdentification**

Type changed to: CBPR_RestrictedFINXMax35Text on page 198

5.60.3 UETR

XML Tag: UETR

Presence: [0..1]

Definition: Universally unique identifier to provide an end-to-end reference of a payment transaction.

Datatype: "UUIDv4Identifier" on page 235

5.61 PaymentInstruction29__1

Definition: Characteristics that apply to the credit side of the payment transactions included in the direct debit initiation.

🚫 Removed - 🚫 Partial Removed - 🔹 Ignored - 🔹 Partial Ignored - ⚠️ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.15.5.1	PaymentInformationIdentification	<PmtInfl>		[1..1]		128
6.1.15.5.2	PaymentMethod	<PmtMtd>		[1..1]		128
6.1.15.5.3	BatchBooking	<BtchBookg>		[0..1]		128
6.1.15.5.4	NumberOfTransactions	<NbOfTxs>		[0..1]	🚫	128
6.1.15.5.5	ControlSum	<CtrlSum>		[0..1]	🚫	129
6.1.15.5.6	PaymentTypeInformation	<PmtTpInf>		[0..1]	🚫	129
6.1.15.5.7	RequestedCollectionDate	<ReqdColltnDt>		[1..1]	⚠️	129
6.1.15.5.8	Creditor	<Cdtr>		[1..1]	⚠️	130
6.1.15.5.9	CreditorAccount	<CdtrAcct>		[1..1]		131
6.1.15.5.10	CreditorAgent	<CdtrAgt>		[1..1]		131
6.1.15.5.11	CreditorAgentAccount	<CdtrAgtAcct>		[0..1]		131
6.1.15.5.12	UltimateCreditor	<UltmtCdtr>		[0..1]	🚫	132
6.1.15.5.13	ChargeBearer	<ChrgBr>		[0..1]	🚫	132
6.1.15.5.14	ChargesAccount	<ChrgsAcct>		[0..1]		133
6.1.15.5.15	ChargesAccountAgent	<ChrgsAcctAgt>		[0..1]		133
6.1.15.5.16	CreditorSchemeIdentification	<CdtrSchmId>		[0..1]	🚫	133
6.1.15.5.17	DirectDebitTransactionInformation	<DrctDbtTxInf>		[1..*]		134

Rules

R7 ChargeBearerRule ✓

If ChargeBearer is present, then DirectDebitTransactionInformation/ChargeBearer is not allowed.

If DirectDebitTransactionInformation/ChargeBearer is present, then ChargeBearer is not allowed.

DirectDebitTransactionInformation/ChargeBearer and ChargeBearer may both be absent.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00112

- *Error Text:* Invalid message content for charge bearer.

R8 ChargesAccountRule ✓

If ChargesAccountAgent is present, then ChargesAccount must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00099
- *Error Text:* Invalid message content for charges agent account.

R9 PaymentTypeInfoRule ✓

If PaymentTypeInfo is present, then DirectDebitTransactionInformation/PaymentTypeInfo is not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00009
- *Error Text:* Invalid message content for payment type information.

R10 CreditorSchemeIdentificationRule ✓

If CreditorSchemeIdentification is present, then DirectDebitTransactionInformation/CreditorSchemeIdentification is not allowed.

If DirectDebitTransactionInformation/CreditorSchemeIdentification is present, then CreditorSchemeIdentification is not allowed.

DirectDebitTransactionInformation/CreditorSchemeIdentification and CreditorSchemeIdentification may both be absent.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00102
- *Error Text:* Invalid message content for credit scheme identification.

R11 UltimateCreditorRule ✓

If UltimateCreditor is present, then DirectDebitTransactionInformation/UltimateCreditor is not allowed.

If DirectDebitTransactionInformation/UltimateCreditor is present, then UltimateCreditor is not allowed.

DirectDebitTransactionInformation/UltimateCreditor and UltimateCreditor may both be absent.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00096
- *Error Text:* Invalid message content for ultimate creditor.

R12 ChargesAccountAgentRule

If ChargesAccountAgent is present, then it must contain a branch of the CreditorAgent. It must not contain a completely different agent.

Error handling: Undefined

Usage Guideline restrictions for this element

- This rule(pain.008.001.08/PaymentInformation/ChargesAccountAgentRule) is removed.

Guidelines**1. UltimateCreditorGuideline**

UltimateCreditor may only be present if different from Creditor.

Used in element(s)

"PaymentInformation" on page 17

5.61.1 PaymentInformationIdentification

XML Tag: PmtInfId

Presence: [1..1]

Definition: Unique identification, as assigned by a sending party, to unambiguously identify the payment information group within the message.

Datatype: "Max35Text" on page 223

5.61.2 PaymentMethod

XML Tag: PmtMtd

Presence: [1..1]

Definition: Specifies the means of payment that will be used to move the amount of money.

Datatype: "PaymentMethod2Code" on page 226

5.61.3 BatchBooking

XML Tag: BtchBookg

Presence: [0..1]

Definition: Identifies whether a single entry per individual transaction or a batch entry for the sum of the amounts of all transactions within the group of a message is requested.

Usage: Batch booking is used to request and not order a possible batch booking.

Datatype: "BatchBookingIndicator" on page 197

5.61.4 NumberOfTransactions

XML Tag: NbOfTxS

Presence: [0..1]

Definition: Number of individual transactions contained in the payment information group.

Datatype: "Max15NumericText" on page 222

Usage Guideline details

- This element(pain.008.001.08/PaymentInformation/NumberOfTransactions) is removed.

5.61.5 ControlSum

XML Tag: CtrlSum

Presence: [0..1]

Definition: Total of all individual amounts included in the group, irrespective of currencies.

Datatype: "DecimalNumber" on page 202

Usage Guideline details

- This element(pain.008.001.08/PaymentInformation/ControlSum) is removed.

5.61.6 PaymentTypeInformation

XML Tag: PmtTpInf

Presence: [0..1]

Definition: Set of elements used to further specify the type of transaction.

The **PmtTpInf** block contains the following elements (see datatype "PaymentTypeInformation29" on page 135 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.16.2.1	InstructionPriority	<InstrPrty>		[0..1]		135
6.1.16.2.2	ServiceLevel	<SvcLvl>		[0..*]	R[0..3]	135
6.1.16.2.3	LocalInstrument	<LclInstrm>		[0..1]		136
6.1.16.2.4	SequenceType	<SeqTp>		[0..1]		136
6.1.16.2.5	CategoryPurpose	<CtgyPurp>		[0..1]		137

Usage Guideline details

- This element(pain.008.001.08/PaymentInformation/PaymentTypeInformation) is removed.

5.61.7 RequestedCollectionDate

XML Tag: ReqdColltnDt

Presence: [1..1]

Definition: Date and time at which the creditor requests that the amount of money is to be collected from the debtor.

Datatype: "CBPR_Date" on page 197

Usage Guideline details

- on pain.008.001.08/PaymentInformation/RequestedCollectionDate
Type changed to: CBPR_Date on page 197

5.61.8 Creditor

XML Tag: Cdtr

Presence: [1..1]

Definition: Party to which an amount of money is due.

The **Cdtr** block contains the following elements (see datatype "PartyIdentification135__1" on page 119 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.14.1.1	Name	<Nm>		[0..1]		120
6.1.14.1.2	PostalAddress	<PstlAdr>		[0..1]	⚠	120
6.1.14.1.3	Identification	<Id>		[0..1]		122
6.1.14.1.4	CountryOfResidence	<CtryOfRes>		[0..1]		123
6.1.14.1.5	ContactDetails	<CtctDtls>		[0..1]	🚫	123

Usage Guideline details

- on pain.008.001.08/PaymentInformation/Creditor

– CBPR_Party_Name_Postal_Address_FormalRule:

If Postal Address is present then Name is mandatory.

For each [Full Message/Document/CustomerDirectDebitInitiationV08/PaymentInformation/Creditor], if
at least one occurrence of the following element(s) [Creditor/PostalAddress]
is (are) present
, then
at least one occurrence of the following element(s) [Creditor/Name] must be present

5.61.9 CreditorAccount

XML Tag: CdtrAcct

Presence: [1..1]

Definition: Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction.

The **CdtrAcct** block contains the following elements (see datatype "CashAccount38" on page 38 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.1.4.1	Identification	<Id>		[1..1]		38
6.1.1.4.2	Type	<Tp>		[0..1]		39
6.1.1.4.3	Currency	<Ccy>		[0..1]	⚠	39
6.1.1.4.4	Name	<Nm>		[0..1]		40
6.1.1.4.5	Proxy	<Prxy>		[0..1]		40

5.61.10 CreditorAgent

XML Tag: CdtrAgt

Presence: [1..1]

Definition: Financial institution servicing an account for the creditor.

The **CdtrAgt** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification6" on page 27 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.10.4.1	FinancialInstitutionIdentification	<FinInstnId>		[1..1]	⚠	27
6.1.10.4.2	BranchIdentification	<BrnchId>		[0..1]	🚫	28

5.61.11 CreditorAgentAccount

XML Tag: CdtrAgtAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the creditor agent at its servicing agent in the payment chain.

The **CdtrAgtAcct** block contains the following elements (see datatype "CashAccount38" on page 38 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.1.4.1	Identification	<Id>		[1..1]		38
6.1.1.4.2	Type	<Tp>		[0..1]		39
6.1.1.4.3	Currency	<Ccy>		[0..1]		39
6.1.1.4.4	Name	<Nm>		[0..1]		40
6.1.1.4.5	Proxy	<Prxy>		[0..1]		40

5.61.12 UltimateCreditor

XML Tag: UltmtCdtr

Presence: [0..1]

Definition: Ultimate party to which an amount of money is due.

The **UltmtCdtr** block contains the following elements (see datatype "PartyIdentification135" on page 116 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.14.1.1	Name	<Nm>		[0..1]		117
6.1.14.1.2	PostalAddress	<PstlAdr>		[0..1]		117
6.1.14.1.3	Identification	<Id>		[0..1]		118
6.1.14.1.4	CountryOfResidence	<CtryOfRes>		[0..1]		118
6.1.14.1.5	ContactDetails	<CtctDtls>		[0..1]		118

Usage Guideline details

- This element(pain.008.001.08/PaymentInformation/UltimateCreditor) is removed.

5.61.13 ChargeBearer

XML Tag: ChrgBr

Presence: [0..1]

Definition: Specifies which party/parties will bear the charges associated with the processing of the payment transaction.

Datatype: "ChargeBearerType1Code" on page 199

Usage Guideline details

- This element(pain.008.001.08/PaymentInformation/ChargeBearer) is removed.

5.61.14 ChargesAccount

XML Tag: ChrgsAcct

Presence: [0..1]

Definition: Account used to process charges associated with a transaction.

Usage: Charges account should be used when charges have to be booked to an account different from the account identified in debtor's account.

The **ChrgsAcct** block contains the following elements (see datatype "[CashAccount38](#)" on page 38 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.1.4.1	Identification	<Id>		[1..1]		38
6.1.1.4.2	Type	<Tp>		[0..1]		39
6.1.1.4.3	Currency	<Ccy>		[0..1]		39
6.1.1.4.4	Name	<Nm>		[0..1]		40
6.1.1.4.5	Proxy	<Prxy>		[0..1]		40

5.61.15 ChargesAccountAgent

XML Tag: ChrgsAcctAgt

Presence: [0..1]

Definition: Agent that services a charges account.

Usage: Charges account agent should only be used when the charges account agent is different from the creditor agent.

The **ChrgsAcctAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6](#)" on page 27 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.10.4.1	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		27
6.1.10.4.2	BranchIdentification	<BrnchId>		[0..1]	🚫	28

5.61.16 CreditorSchemeldentification

XML Tag: CdtrSchmeld

Presence: [0..1]

Definition: Credit party that signs the mandate.

The **CdtrSchmeld** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 116 for details)

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.14.1.1	Name	<Nm>		[0..1]		117
6.1.14.1.2	PostalAddress	<PstlAdr>		[0..1]		117
6.1.14.1.3	Identification	<Id>		[0..1]		118
6.1.14.1.4	CountryOfResidence	<CtryOfRes>		[0..1]		118
6.1.14.1.5	ContactDetails	<CtctDtls>		[0..1]		118

Usage Guideline details

- This element([pain.008.001.08/PaymentInformation/CreditorSchemeIdentification](#)) is removed.

5.61.17 DirectDebitTransactionInformation

XML Tag: DrctDbtTxInf

Presence: [1..*]

Definition: Provides information on the individual transaction(s) included in the message.

The **DrctDbtTxInf** block contains the following elements (see datatype "[DirectDebitTransactionInformation23_1](#)" on page 58 for details)

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.15.5.17.1	PaymentIdentification	<PmtId>		[1..1]		59
6.1.15.5.17.2	PaymentTypeInformation	<PmtTplnf>		[0..1]		59
6.1.15.5.17.3	InstructedAmount	<InstdAmt>		[1..1]		59
6.1.15.5.17.4	ChargeBearer	<ChrgBr>		[0..1]		60
6.1.15.5.17.5	DirectDebitTransaction	<DrctDbtTx>		[0..1]		60
6.1.15.5.17.6	UltimateCreditor	<UltmtCdtr>		[0..1]	⚠	60
6.1.15.5.17.7	DebtorAgent	<DbtrAgt>		[1..1]		61
6.1.15.5.17.8	DebtorAgentAccount	<DbtrAgtAcct>		[0..1]		61
6.1.15.5.17.9	Debtor	<Dbtr>		[1..1]	⚠	62
6.1.15.5.17.10	DebtorAccount	<DbtrAcct>		[1..1]		63

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.15.5.17.11	UltimateDebtor	<UltmtDbtr>		[0..1]		63
6.1.15.5.17.12	InstructionForCreditorAgent	<InstrForCdtrAgt>		[0..1]		64
6.1.15.5.17.13	Purpose	<Purp>		[0..1]		64
6.1.15.5.17.14	RegulatoryReporting	<RgltryRptg>		[0..10]		65
6.1.15.5.17.15	Tax	<Tax>		[0..1]		65
6.1.15.5.17.16	RelatedRemittanceInformation	<RltdRmtInf>		[0..10]		65
6.1.15.5.17.17	RemittanceInformation	<RmtInf>		[0..1]		66
6.1.15.5.17.18	SupplementaryData	<SplmtryData>		[0..*]		66

5.62 PaymentTypeInformation29

Definition: Provides further details of the type of payment.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.16.2.1	InstructionPriority	<InstrPrty>		[0..1]		135
6.1.16.2.2	ServiceLevel	<SvcLvl>		[0..*]	R[0..3] R[0..3]	135
6.1.16.2.3	LocalInstrument	<LclInstrm>		[0..1]		136
6.1.16.2.4	SequenceType	<SeqTp>		[0..1]		136
6.1.16.2.5	CategoryPurpose	<CtgyPurp>		[0..1]		137

Used in element(s)

"PaymentTypeInformation" on page 129, "PaymentTypeInformation" on page 59

5.62.1 InstructionPriority

XML Tag: InstrPrty

Presence: [0..1]

Definition: Indicator of the urgency or order of importance that the instructing party would like the instructed party to apply to the processing of the instruction.

Datatype: "Priority2Code" on page 229

5.62.2 ServiceLevel

XML Tag: SvcLvl

Presence: [0..*]

Definition: Agreement under which or rules under which the transaction should be processed.

The **SvcLvl** block contains the following elements (see datatype "[ServiceLevel8Choice](#)" on page 166 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.16.2.2.1	Code	<Cd>	{Or	[1..1]		167
6.1.16.2.2.2	Proprietary	<Prtry>	Or}	[1..1]		167

Usage Guideline details

- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/PaymentTypeInformation/ServiceLevel**

This element has change repeatability, the maximum occurrence has been changed to : 3

- on **pain.008.001.08/PaymentInformation/PaymentTypeInformation/ServiceLevel**

This element has change repeatability, the maximum occurrence has been changed to : 3

5.62.3 LocalInstrument

XML Tag: LclInstrm

Presence: [0..1]

Definition: User community specific instrument.

Usage: This element is used to specify a local instrument, local clearing option and/or further qualify the service or service level.

The **LclInstrm** block contains the following elements (see datatype "[LocalInstrument2Choice](#)" on page 101 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.16.2.3.1	Code	<Cd>	{Or	[1..1]		102
6.1.16.2.3.2	Proprietary	<Prtry>	Or}	[1..1]		102

5.62.4 SequenceType

XML Tag: SeqTp

Presence: [0..1]

Definition: Identifies the direct debit sequence, such as first, recurrent, final or one-off.

Datatype: "[SequenceType3Code](#)" on page 231

5.62.5 CategoryPurpose

XML Tag: Ctgypurp

Presence: [0..1]

Definition: Specifies the high level purpose of the instruction based on a set of pre-defined categories.

Usage: This is used by the initiating party to provide information concerning the processing of the payment. It is likely to trigger special processing by any of the agents involved in the payment chain.

The **Ctgypurp** block contains the following elements (see datatype "[CategoryPurpose1Choice](#)" on page 41 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.16.2.5.1	Code	<Cd>	{Or	[1..1]		41
6.1.16.2.5.2	Proprietary	<Prtry>	Or}	[1..1]		42

5.63 PersonIdentification13

Definition: Unique and unambiguous way to identify a person.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.17.1.1	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		137
6.1.17.1.2	Other	<Othr>		[0..*]	R[0..2]	138

Used in element(s)

"[PrivateIdentification](#)" on page 113

5.63.1 DateAndPlaceOfBirth

XML Tag: DtAndPlcOfBirth

Presence: [0..1]

Definition: Date and place of birth of a person.

The **DtAndPlcOfBirth** block contains the following elements (see datatype "[DateAndPlaceOfBirth1](#)" on page 51 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.17.1.1.1	BirthDate	<BirthDt>		[1..1]		52

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.17.1.1.2	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		52
6.1.17.1.1.3	CityOfBirth	<CityOfBirth>		[1..1]		52
6.1.17.1.1.4	CountryOfBirth	<CtrtyOfBirth>		[1..1]		52

5.63.2 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of a person, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericPersonIdentification1](#)" on page 95 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.17.1.2.1	Identification	<Id>		[1..1]		95
6.1.17.1.2.2	SchemeName	<SchmeNm>		[0..1]		95
6.1.17.1.2.3	Issuer	<Issr>		[0..1]		97

Usage Guideline details

- on pain.008.001.08/PaymentInformation/UltimateCreditor/Identification/PrivateIdentification/Other

This element has change repeatability, the maximum occurrence has been changed to : 2

5.64 PersonIdentification13__1

Definition: Unique and unambiguous way to identify a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.17.1.1	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		139
6.1.17.1.2	Other	<Othr>		[0..*]	R[0..2] R[0..2] R[0..2] R[0..2]	139

Used in element(s)

"PrivateIdentification" on page 115

5.64.1 DateAndPlaceOfBirth

XML Tag: DtAndPlcOfBirth

Presence: [0..1]

Definition: Date and place of birth of a person.

The **DtAndPlcOfBirth** block contains the following elements (see datatype "[DateAndPlaceOfBirth1__1](#)" on page 52 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.17.1.1.1	BirthDate	<BirthDt>		[1..1]		53
6.1.17.1.1.2	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		54
6.1.17.1.1.3	CityOfBirth	<CityOfBirth>		[1..1]		54
6.1.17.1.1.4	CountryOfBirth	<CtryOfBirth>		[1..1]		54

5.64.2 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of a person, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericPersonIdentification1](#)" on page 95 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.17.1.2.1	Identification	<Id>		[1..1]		95
6.1.17.1.2.2	SchemeName	<SchmeNm>		[0..1]		95
6.1.17.1.2.3	Issuer	<Issr>		[0..1]		97

Usage Guideline details

- on [pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/Debtor/Identification/PrivateIdentification/Other](#)

This element has change repeatability, the maximum occurrence has been changed to : 2

- on [pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/GarnishmentRemittance/GarnishmentAdministrator/Identification/PrivateIdentification/Other](#)

This element has change repeatability, the maximum occurrence has been changed to : 2

- on pain.008.001.08/PaymentInformation/Creditor/Identification/PrivateIdentification/Other
This element has change repeatability, the maximum occurrence has been changed to : 2
- on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/UltimateDebtor/Identification/PrivateIdentification/Other
This element has change repeatability, the maximum occurrence has been changed to : 2
- on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/Invoicee/Identification/PrivateIdentification/Other
This element has change repeatability, the maximum occurrence has been changed to : 2
- on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/Invoicer/Identification/PrivateIdentification/Other
This element has change repeatability, the maximum occurrence has been changed to : 2
- on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/GarnishmentRemittance/Garnishee/Identification/PrivateIdentification/Other
This element has change repeatability, the maximum occurrence has been changed to : 2
- on pain.008.001.08/GroupHeader/InitiatingParty/Identification/PrivateIdentification/Other
This element has change repeatability, the maximum occurrence has been changed to : 2
- on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/UltimateCreditor/Identification/PrivateIdentification/Other
This element has change repeatability, the maximum occurrence has been changed to : 2

5.65 PersonIdentificationSchemeName1Choice

Definition: Sets of elements to identify a name of the identification scheme.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.17.1.2.2.1	Code	<Cd>	{Or	[1..1]		140
6.1.17.1.2.2.2	Proprietary	<Prtry>	Or}	[1..1]	🚫	141

🚫 , ⬜ >> Note as not all **PersonIdentificationSchemeName1Choice** blocks have this element removed and/or ignored. Please refer to the page number next to the element for further details on which elements have been removed and/or ignored.

Used in element(s)

"SchemeName" on page 95

5.65.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: ["ExternalPersonIdentification1Code" on page 214](#)

5.65.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: ["Max35Text" on page 223](#)

Usage Guideline details

- This element([pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/Debtor/Identification/PrivateIdentification/Other/SchemeName/Proprietary](#)) is removed.
- This element([pain.008.001.08/GroupHeader/InitiatingParty/Identification/PrivateIdentification/Other/SchemeName/Proprietary](#)) is removed.
- This element([pain.008.001.08/PaymentInformation/Creditor/Identification/PrivateIdentification/Other/SchemeName/Proprietary](#)) is removed.
- This element([pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/MandateRelatedInformation/AmendmentInformationDetails/OriginalCreditorSchemeIdentification/Identification/PrivateIdentification/Other/SchemeName/Proprietary](#)) is removed.
- This element([pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/MandateRelatedInformation/AmendmentInformationDetails/OriginalDebtor/Identification/PrivateIdentification/Other/SchemeName/Proprietary](#)) is removed.
- This element([pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/CreditorSchemeIdentification/Identification/PrivateIdentification/Other/SchemeName/Proprietary](#)) is removed.
- This element([pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/UltimateCreditor/Identification/PrivateIdentification/Other/SchemeName/Proprietary](#)) is removed.
- This element([pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/UltimateDebtor/Identification/PrivateIdentification/Other/SchemeName/Proprietary](#)) is removed.
- This element([pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/Invoicer/Identification/PrivateIdentification/Other/SchemeName/Proprietary](#)) is removed.
- This element([pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/Invoicee/Identification/PrivateIdentification/Other/SchemeName/Proprietary](#)) is removed.
- This element([pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/GarnishmentRemittance/Garnishee/Identification/PrivateIdentification/Other/SchemeName/Proprietary](#)) is removed.

- This element(pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/GarnishmentRemittance/GarnishmentAdministrator/Identification/PrivateIdentification/Other/SchemeName/Proprietary) is removed.

5.66 PostalAddress24

Definition: Information that locates and identifies a specific address, as defined by postal services.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.18.1.1	AddressType	<AdrTp>		[0..1]	🚫	142
6.1.18.1.2	Department	<Dept>		[0..1]		144
6.1.18.1.3	SubDepartment	<SubDept>		[0..1]		144
6.1.18.1.4	StreetName	<StrtNm>		[0..1]		144
6.1.18.1.5	BuildingNumber	<BldgNb>		[0..1]		144
6.1.18.1.6	BuildingName	<BldgNm>		[0..1]		145
6.1.18.1.7	Floor	<Flr>		[0..1]		145
6.1.18.1.8	PostBox	<PstBx>		[0..1]		145
6.1.18.1.9	Room	<Room>		[0..1]		145
6.1.18.1.10	PostCode	<PstCd>		[0..1]		145
6.1.18.1.11	TownName	<TwnNm>		[0..1]	M	145
6.1.18.1.12	TownLocationName	<TwnLctnNm>		[0..1]		147
6.1.18.1.13	DistrictName	<DstrctNm>		[0..1]		147
6.1.18.1.14	CountrySubDivision	<CtrySubDvsn>		[0..1]		147
6.1.18.1.15	Country	<Ctry>		[0..1]	M	147
6.1.18.1.16	AddressLine	<AdrLine>		[0..7]	🚫 R[0..2] R[0..2] R[0..2] R[0..2] R[0..2] R[0..2] R[0..2]	149

🚫 , ⬜ >> Note as not all **PostalAddress24** blocks have this element removed and/or ignored. Please refer to the page number next to the element for further details on which elements have been removed and/or ignored.

Used in element(s)

"Address" on page 107, "PostalAddress" on page 80, "PostalAddress" on page 120, "PostalAddress" on page 32, "PostalAddress" on page 76, "PostalAddress" on page 117

5.66.1 AddressType

XML Tag: AdrTp

Presence: [0..1]

Definition: Identifies the nature of the postal address.

The **AdrTp** block contains the following elements (see datatype "AddressType3Choice" on page 20 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.18.1.1.1	Code	<Cd>	{Or	[1..1]		20
6.1.18.1.1.2	Proprietary	<Prtry>	Or}	[1..1]		21

Usage Guideline details

- This element(pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/GarnishmentRemittance/GarnishmentAdministrator/PostalAddress/AddressType) is removed.
- This element(pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/Invoicee/PostalAddress/AddressType) is removed.
- This element(pain.008.001.08/PaymentInformation/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/AddressType) is removed.
- This element(pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/UltimateCreditor/PostalAddress/AddressType) is removed.
- This element(pain.008.001.08/PaymentInformation/CreditorSchemeIdentification/PostalAddress/AddressType) is removed.
- This element(pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/Debtor/PostalAddress/AddressType) is removed.
- This element(pain.008.001.08/GroupHeader/InitiatingParty/PostalAddress/AddressType) is removed.
- This element(pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/MandateRelatedInformation/AmendmentInformationDetails/OriginalCreditorAgent/FinancialInstitutionIdentification/PostalAddress/AddressType) is removed.
- This element(pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/Invoicer/PostalAddress/AddressType) is removed.
- This element(pain.008.001.08/PaymentInformation/UltimateCreditor/PostalAddress/AddressType) is removed.
- This element(pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/GarnishmentRemittance/Garnishee/PostalAddress/AddressType) is removed.
- This element(pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/Debtor-Agent/FinancialInstitutionIdentification/PostalAddress/AddressType) is removed.
- This element(pain.008.001.08/PaymentInformation/Creditor/PostalAddress/AddressType) is removed.

- This element(`pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/UltimateDebtor/PostalAddress/AddressType`) is removed.
- This element(`pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/CreditorSchemeIdentification/PostalAddress/AddressType`) is removed.
- This element(`pain.008.001.08/PaymentInformation/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/AddressType`) is removed.
- This element(`pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/MandateRelatedInformation/AmendmentInformationDetails/OriginalCreditorSchemeIdentification/PostalAddress/AddressType`) is removed.
- This element(`pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/MandateRelatedInformation/AmendmentInformationDetails/OriginalDebtor/PostalAddress/AddressType`) is removed.
- This element(`pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/MandateRelatedInformation/AmendmentInformationDetails/OriginalDebtor-Agent/FinancialInstitutionIdentification/PostalAddress/AddressType`) is removed.

5.66.2 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: "Max70Text" on page 224

5.66.3 SubDepartment

XML Tag: SubDept

Presence: [0..1]

Definition: Identification of a sub-division of a large organisation or building.

Datatype: "Max70Text" on page 224

5.66.4 StreetName

XML Tag: StrtNm

Presence: [0..1]

Definition: Name of a street or thoroughfare.

Datatype: "Max70Text" on page 224

5.66.5 BuildingNumber

XML Tag: BldgNb

Presence: [0..1]

Definition: Number that identifies the position of a building on a street.

Datatype: "Max16Text" on page 222

5.66.6 BuildingName

XML Tag: BldgNm

Presence: [0..1]

Definition: Name of the building or house.

Datatype: "Max35Text" on page 223

5.66.7 Floor

XML Tag: Flr

Presence: [0..1]

Definition: Floor or storey within a building.

Datatype: "Max70Text" on page 224

5.66.8 PostBox

XML Tag: PstBx

Presence: [0..1]

Definition: Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for.

Datatype: "Max16Text" on page 222

5.66.9 Room

XML Tag: Room

Presence: [0..1]

Definition: Building room number.

Datatype: "Max70Text" on page 224

5.66.10 PostCode

XML Tag: PstCd

Presence: [0..1]

Definition: Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.

Datatype: "Max16Text" on page 222

5.66.11 TownName

XML Tag: TwnNm

Presence: [0..1]

Definition: Name of a built-up area, with defined boundaries, and a local government.

Datatype: "Max35Text" on page 223

Usage Guideline details

- **on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/GarnishmentRemittance/Garnishee/PostalAddress/TownName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/GarnishmentRemittance/GarnishmentAdministrator/PostalAddress/TownName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/UltimateDebtor/PostalAddress/TownName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pain.008.001.08/PaymentInformation/UltimateCreditor/PostalAddress/TownName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/Invoicer/PostalAddress/TownName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pain.008.001.08/GroupHeader/InitiatingParty/PostalAddress/TownName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/UltimateCreditor/PostalAddress/TownName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/Invoicee/PostalAddress/TownName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pain.008.001.08/PaymentInformation/Creditor/PostalAddress/TownName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pain.008.001.08/PaymentInformation/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/TownName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pain.008.001.08/PaymentInformation/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/TownName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/TownName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/Debtor/PostalAddress/TownName**
This element is now mandatory, the minimum occurrence has been changed to : 1

- on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/MandateRelatedInformation/AmendmentInformationDetails/OriginalCreditorAgent/FinancialInstitutionIdentification/PostalAddress/TownName
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/CreditorSchemeIdentification/PostalAddress/TownName
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/MandateRelatedInformation/AmendmentInformationDetails/OriginalDebtor/PostalAddress/TownName
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/MandateRelatedInformation/AmendmentInformationDetails/OriginalCreditorSchemeIdentification/PostalAddress/TownName
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/MandateRelatedInformation/AmendmentInformationDetails/OriginalDebtorAgent/FinancialInstitutionIdentification/PostalAddress/TownName
This element is now mandatory, the minimum occurrence has been changed to : 1

5.66.12 TownLocationName

XML Tag: TwnLctnNm

Presence: [0..1]

Definition: Specific location name within the town.

Datatype: "Max35Text" on page 223

5.66.13 DistrictName

XML Tag: DstrctNm

Presence: [0..1]

Definition: Identifies a subdivision within a country sub-division.

Datatype: "Max35Text" on page 223

5.66.14 CountrySubDivision

XML Tag: CtrySubDvsn

Presence: [0..1]

Definition: Identifies a subdivision of a country such as state, region, county.

Datatype: "Max35Text" on page 223

5.66.15 Country

XML Tag: Ctry

Presence: [0..1]

Definition: Nation with its own government.

Datatype: "CountryCode" on page 201

Usage Guideline details

- **on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/Invoicee/PostalAddress/Country**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/UltimateDebtor/PostalAddress/Country**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/UltimateCreditor/PostalAddress/Country**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/GarnishmentRemittance/Garnishee/PostalAddress/Country**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pain.008.001.08/PaymentInformation/UltimateCreditor/PostalAddress/Country**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/Invoicer/PostalAddress/Country**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pain.008.001.08/GroupHeader/InitiatingParty/PostalAddress/Country**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/GarnishmentRemittance/GarnishmentAdministrator/PostalAddress/Country**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pain.008.001.08/PaymentInformation/Creditor/PostalAddress/Country**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pain.008.001.08/PaymentInformation/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/Country**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pain.008.001.08/PaymentInformation/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/Country**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/Country**

This element is now mandatory, the minimum occurrence has been changed to : 1

- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/Debtor/PostalAddress/Country**

This element is now mandatory, the minimum occurrence has been changed to : 1

- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/MandateRelatedInformation/AmendmentInformationDetails/OriginalCreditorAgent/FinancialInstitutionIdentification/PostalAddress/Country**

This element is now mandatory, the minimum occurrence has been changed to : 1

- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/CreditorSchemeIdentification/PostalAddress/Country**

This element is now mandatory, the minimum occurrence has been changed to : 1

- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/MandateRelatedInformation/AmendmentInformationDetails/OriginalDebtor/PostalAddress/Country**

This element is now mandatory, the minimum occurrence has been changed to : 1

- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/MandateRelatedInformation/AmendmentInformationDetails/OriginalCreditorSchemeIdentification/PostalAddress/Country**

This element is now mandatory, the minimum occurrence has been changed to : 1

- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/MandateRelatedInformation/AmendmentInformationDetails/OriginalDebtorAgent/FinancialInstitutionIdentification/PostalAddress/Country**

This element is now mandatory, the minimum occurrence has been changed to : 1

5.66.16 AddressLine

XML Tag: AdrLine

Presence: [0..7]

Definition: Information that locates and identifies a specific address, as defined by postal services, presented in free format text.

Datatype: "Max70Text" on page 224

Usage Guideline details

- This element(**pain.008.001.08/PaymentInformation/UltimateCreditor/PostalAddress/AddressLine**) is removed.
- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/CreditorSchemeIdentification/PostalAddress/AddressLine**

This element has change repeatability, the maximum occurrence has been changed to : 2

- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine**

This element has change repeatability, the maximum occurrence has been changed to : 2

- **on pain.008.001.08/PaymentInformation/ChargesAccountAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine**
This element has change repeatability, the maximum occurrence has been changed to : 2
- **on pain.008.001.08/PaymentInformation/Creditor/PostalAddress/AddressLine**
This element has change repeatability, the maximum occurrence has been changed to : 2
- **on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/Invoicer/PostalAddress/AddressLine**
This element has change repeatability, the maximum occurrence has been changed to : 2
- **on pain.008.001.08/PaymentInformation/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine**
This element has change repeatability, the maximum occurrence has been changed to : 2
- **on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/Invoicee/PostalAddress/AddressLine**
This element has change repeatability, the maximum occurrence has been changed to : 2
- **on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/GarnishmentRemittance/GarnishmentAdministrator/PostalAddress/AddressLine**
This element has change repeatability, the maximum occurrence has been changed to : 2
- **on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/UltimateDebtor/PostalAddress/AddressLine**
This element has change repeatability, the maximum occurrence has been changed to : 2
- **on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/UltimateCreditor/PostalAddress/AddressLine**
This element has change repeatability, the maximum occurrence has been changed to : 2
- **on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/Debtor/PostalAddress/AddressLine**
This element has change repeatability, the maximum occurrence has been changed to : 2
- **on pain.008.001.08/GroupHeader/InitiatingParty/PostalAddress/AddressLine**
This element has change repeatability, the maximum occurrence has been changed to : 2
- **on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/MandateRelatedInformation/AmendmentInformationDetails/OriginalCreditorAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine**
This element has change repeatability, the maximum occurrence has been changed to : 2
- **on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/GarnishmentRemittance/Garnishee/PostalAddress/AddressLine**
This element has change repeatability, the maximum occurrence has been changed to : 2
- **on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RelatedRemittanceInformation/RemittanceLocationDetails/PostalAddress/Address/AddressLine**
This element has change repeatability, the maximum occurrence has been changed to : 3

- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/MandateRelatedInformation/AmendmentInformationDetails/OriginalDebtor/PostalAddress/AddressLine**

This element has change repeatability, the maximum occurrence has been changed to : 2

- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/MandateRelatedInformation/AmendmentInformationDetails/OriginalCreditorSchemeIdentification/PostalAddress/AddressLine**

This element has change repeatability, the maximum occurrence has been changed to : 2

- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/MandateRelatedInformation/AmendmentInformationDetails/OriginalDebtorAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine**

This element has change repeatability, the maximum occurrence has been changed to : 2

5.67 ProxyAccountIdentification1

Definition: Information related to a proxy identification of the account.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.1.3.1	Type	<Tp>		[0..1]		151
6.1.1.3.2	Identification	<Id>		[1..1]		152

Used in element(s)

["Proxy" on page 40](#)

5.67.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Type of the proxy identification.

The **Tp** block contains the following elements (see datatype ["ProxyAccountType1Choice" on page 152](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.1.3.1.1	Code	<Cd>	{Or	[1..1]		153
6.1.1.3.1.2	Proprietary	<Prtry>	Or}	[1..1]		153

Usage Guideline details

- **on pain.008.001.08/PaymentInformation/CreditorAccount/Proxy/Type**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pain.008.001.08/PaymentInformation/CreditorAgentAccount/Proxy/Type**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pain.008.001.08/PaymentInformation/ChargesAccount/Proxy/Type**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/MandateRelatedInformation/AmendmentInformationDetails/OriginalCreditorAgentAccount/Proxy/Type**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/MandateRelatedInformation/AmendmentInformationDetails/OriginalDebtorAccount/Proxy/Type**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DirectDebitTransaction/MandateRelatedInformation/AmendmentInformationDetails/OriginalDebtorAgentAccount/Proxy/Type**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DebtorAgentAccount/Proxy/Type**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/DebtorAccount/Proxy/Type**
This element is now mandatory, the minimum occurrence has been changed to : 1

5.67.2 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification used to indicate the account identification under another specified name.

Datatype: "Max2048Text" on page 223

5.68 ProxyAccountType1Choice

Definition: Specifies the scheme used for the identification of an account alias.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.1.3.1.1	Code	<Cd>	{Or	[1..1]		153
6.1.1.3.1.2	Proprietary	<Prtry>	Or}	[1..1]		153

Used in element(s)

["Type" on page 151](#)

5.68.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: ["ExternalProxyAccountType1Code" on page 215](#)

5.68.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: ["Max35Text" on page 223](#)

5.69 Purpose2Choice

Definition: Specifies the underlying reason for the payment transaction.

Usage: Purpose is used by the end-customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.12.2.1	Code	<Cd>	{Or	[1..1]		153
6.1.12.2.2	Proprietary	<Prtry>	Or}	[1..1]		154

Used in element(s)

["Purpose" on page 64](#)

5.69.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Underlying reason for the payment transaction, as published in an external purpose code list.

Datatype: ["ExternalPurpose1Code" on page 215](#)

5.69.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Purpose, in a proprietary form.

Datatype: ["Max35Text" on page 223](#)

5.70 ReferredDocumentInformation7__1

Definition: Set of elements used to identify the documents referred to in the remittance information.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.1.1.1	Type	<Tp>		[0..1]		154
6.1.20.1.1.2	Number	<Nb>		[0..1]		154
6.1.20.1.1.3	RelatedDate	<RltdDt>		[0..1]		155
6.1.20.1.1.4	LineDetails	<LineDtls>		[0..*]		155

Used in element(s)

["ReferredDocumentInformation" on page 169](#)

5.70.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the type of referred document.

The **Tp** block contains the following elements (see datatype ["ReferredDocumentType4" on page 156](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.1.1.1.1	CodeOrProprietary	<CdOrPrtry>		[1..1]		156
6.1.20.1.1.1.2	Issuer	<Issr>		[0..1]		157

5.70.2 Number

XML Tag: Nb

Presence: [0..1]

Definition: Unique and unambiguous identification of the referred document.

Datatype: "Max35Text" on page 223

5.70.3 RelatedDate

XML Tag: RltdDt

Presence: [0..1]

Definition: Date associated with the referred document.

Datatype: "CBPR_Date" on page 197

Usage Guideline details

- on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/ReferredDocumentInformation/RelatedDate
Type changed to: CBPR_Date on page 197

5.70.4 LineDetails

XML Tag: LineDtIs

Presence: [0..*]

Definition: Set of elements used to provide the content of the referred document line.

The **LineDtIs** block contains the following elements (see datatype "DocumentLineInformation1__1" on page 70 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.1.1.4.1	Identification	<Id>		[1..*]		71
6.1.20.1.1.4.2	Description	<Desc>		[0..1]		71
6.1.20.1.1.4.3	Amount	<Amt>		[0..1]		71

5.71 ReferredDocumentType3Choice

Definition: Specifies the type of the document referred in the remittance information.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.1.1.1.1.1	Code	<Cd>	{Or	[1..1]		156
6.1.20.1.1.1.1.2	Proprietary	<Prtry>	Or}	[1..1]		156

Used in element(s)

["CodeOrProprietary" on page 156](#)

5.71.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Document type in a coded form.

Datatype: ["DocumentType6Code" on page 203](#)

5.71.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Proprietary identification of the type of the remittance document.

Datatype: ["Max35Text" on page 223](#)

5.72 ReferredDocumentType4

Definition: Specifies the type of the document referred in the remittance information.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.1.1.1.1	CodeOrProprietary	<CdOrPrtry>		[1..1]		156
6.1.20.1.1.1.2	Issuer	<Issr>		[0..1]		157

Used in element(s)

["Type" on page 154](#)

5.72.1 CodeOrProprietary

XML Tag: CdOrPrtry

Presence: [1..1]

Definition: Provides the type details of the referred document.

The **CdOrPrtry** block contains the following elements (see datatype ["ReferredDocumentType3Choice" on page 155](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.1.1.1.1.1	Code	<Cd>	{Or	[1..1]		156
6.1.20.1.1.1.1.2	Proprietary	<Prtry>	Or}	[1..1]		156

5.72.2 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Identification of the issuer of the reference document type.

Datatype: "Max35Text" on page 223

5.73 RegulatoryAuthority2

Definition: Entity requiring the regulatory reporting information.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.19.1.2.1	Name	<Nm>		[0..1]		157
6.1.19.1.2.2	Country	<Ctry>		[0..1]		157

Used in element(s)

"Authority" on page 158

5.73.1 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name of the entity requiring the regulatory reporting information.

Datatype: "Max140Text" on page 222

5.73.2 Country

XML Tag: Ctry

Presence: [0..1]

Definition: Country of the entity that requires the regulatory reporting information.

Datatype: "CountryCode" on page 201

5.74 RegulatoryReporting3__1

Definition: Information needed due to regulatory and/or statutory requirements.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.19.1.1	DebitCreditReportingIndicator	<DbtCdtRptgInd>		[0..1]		158

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.19.1.2	Authority	<Authrty>		[0..1]		158
6.1.19.1.3	Details	<Dtls>		[0..*]		158

Used in element(s)

"RegulatoryReporting" on page 65

5.74.1 DebitCreditReportingIndicator

XML Tag: DbtCdtRptgInd

Presence: [0..1]

Definition: Identifies whether the regulatory reporting information applies to the debit side, to the credit side or to both debit and credit sides of the transaction.

Datatype: "RegulatoryReportingType1Code" on page 229

5.74.2 Authority

XML Tag: Authrty

Presence: [0..1]

Definition: Entity requiring the regulatory reporting information.

The **Authrty** block contains the following elements (see datatype "RegulatoryAuthority2" on page 157 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.19.1.2.1	Name	<Nm>		[0..1]		157
6.1.19.1.2.2	Country	<Ctry>		[0..1]		157

5.74.3 Details

XML Tag: Dtls

Presence: [0..*]

Definition: Set of elements used to provide details on the regulatory reporting information.

The **Dtls** block contains the following elements (see datatype "StructuredRegulatoryReporting3__1" on page 167 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.19.1.3.1	Type	<Tp>		[0..1]		167

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.19.1.3.2	Date	<Dt>		[0..1]		167
6.1.19.1.3.3	Country	<Ctry>		[0..1]		168
6.1.19.1.3.4	Code	<Cd>		[0..1]		168
6.1.19.1.3.5	Amount	<Amt>		[0..1]		168
6.1.19.1.3.6	Information	<Inf>		[0..*]		168

5.75 RemittanceAmount2

Definition: Nature of the amount and currency on a document referred to in the remittance section, typically either the original amount due/payable or the amount actually remitted for the referenced document.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.12.9.1	DuePayableAmount	<DuePyblAmt>		[0..1]		159
6.1.12.9.2	DiscountAppliedAmount	<DscntApldAmt>		[0..*]		159
6.1.12.9.3	CreditNoteAmount	<CdtNoteAmt>		[0..1]		160
6.1.12.9.4	TaxAmount	<TaxAmt>		[0..*]		160
6.1.12.9.5	AdjustmentAmountAndReason	<AdjstmntAmtAndRsn>		[0..*]		160
6.1.12.9.6	RemittedAmount	<RmtdAmt>		[0..1]		161

Used in element(s)

"ReferredDocumentAmount" on page 169

5.75.1 DuePayableAmount

XML Tag: DuePyblAmt

Presence: [0..1]

Definition: Amount specified is the exact amount due and payable to the creditor.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 192

5.75.2 DiscountAppliedAmount

XML Tag: DscntApldAmt

Presence: [0..*]

Definition: Amount specified for the referred document is the amount of discount to be applied to the amount due and payable to the creditor.

The **DscntApIdAmt** block contains the following elements (see datatype "[DiscountAmountAndType1](#)" on page 67 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.1.1.4.3.2.1 , 6.1.12.9.2.1	Type	<Tp>		[0..1]		67
6.1.20.1.1.4.3.2.2 , 6.1.12.9.2.2	Amount	<Amt>		[1..1]		67

5.75.3 CreditNoteAmount

XML Tag: CdtNoteAmt

Presence: [0..1]

Definition: Amount specified for the referred document is the amount of a credit note.

Datatype: "[ActiveOrHistoricCurrencyAndAmount](#)" on page 192

5.75.4 TaxAmount

XML Tag: TaxAmt

Presence: [0..*]

Definition: Quantity of cash resulting from the calculation of the tax.

The **TaxAmt** block contains the following elements (see datatype "[TaxAmountAndType1](#)" on page 175 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.1.1.4.3.4.1 , 6.1.12.9.4.1	Type	<Tp>		[0..1]		175
6.1.20.1.1.4.3.4.2 , 6.1.12.9.4.2	Amount	<Amt>		[1..1]		176

5.75.5 AdjustmentAmountAndReason

XML Tag: AdjstmntAmtAndRsn

Presence: [0..*]

Definition: Specifies detailed information on the amount and reason of the document adjustment.

The **AdjstmntAmtAndRsn** block contains the following elements (see datatype "[DocumentAdjustment1](#)" on page 68 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.1.1.4.3.5.1 , 6.1.12.9.5.1	Amount	<Amt>		[1..1]		69
6.1.20.1.1.4.3.5.2 , 6.1.12.9.5.2	CreditDebitIndicator	<CdtDbtInd>		[0..1]		69
6.1.20.1.1.4.3.5.3 , 6.1.12.9.5.3	Reason	<Rsn>		[0..1]		69
6.1.20.1.1.4.3.5.4 , 6.1.12.9.5.4	AdditionalInformation	<AddtlInf>		[0..1]		69

5.75.6 RemittedAmount

XML Tag: RmtdAmt

Presence: [0..1]

Definition: Amount of money remitted for the referred document.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 192

5.76 RemittanceAmount3

Definition: Nature of the amount and currency on a document referred to in the remittance section, typically either the original amount due/payable or the amount actually remitted for the referenced document.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.1.1.4.3.1	DuePayableAmount	<DuePyblAmt>		[0..1]		161
6.1.20.1.1.4.3.2	DiscountAppliedAmount	<DscntApldAmt>		[0..*]		162
6.1.20.1.1.4.3.3	CreditNoteAmount	<CdtNoteAmt>		[0..1]		162
6.1.20.1.1.4.3.4	TaxAmount	<TaxAmt>		[0..*]		162
6.1.20.1.1.4.3.5	AdjustmentAmountAndReason	<AdjstmntAmtAndRsn>		[0..*]		162
6.1.20.1.1.4.3.6	RemittedAmount	<RmtdAmt>		[0..1]		163

Used in element(s)

"Amount" on page 71

5.76.1 DuePayableAmount

XML Tag: DuePyblAmt

Presence: [0..1]

Definition: Amount specified is the exact amount due and payable to the creditor.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 192

5.76.2 DiscountAppliedAmount

XML Tag: DscntApldAmt

Presence: [0..*]

Definition: Amount of discount to be applied to the amount due and payable to the creditor.

The **DscntApldAmt** block contains the following elements (see datatype "[DiscountAmountAndType1](#)" on page 67 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.1.1.4.3.2.1 , 6.1.12.9.2.1	Type	<Tp>		[0..1]		67
6.1.20.1.1.4.3.2.2 , 6.1.12.9.2.2	Amount	<Amt>		[1..1]		67

5.76.3 CreditNoteAmount

XML Tag: CdtNoteAmt

Presence: [0..1]

Definition: Amount of a credit note.

Datatype: "[ActiveOrHistoricCurrencyAndAmount](#)" on page 192

5.76.4 TaxAmount

XML Tag: TaxAmt

Presence: [0..*]

Definition: Amount of the tax.

The **TaxAmt** block contains the following elements (see datatype "[TaxAmountAndType1](#)" on page 175 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.1.1.4.3.4.1 , 6.1.12.9.4.1	Type	<Tp>		[0..1]		175
6.1.20.1.1.4.3.4.2 , 6.1.12.9.4.2	Amount	<Amt>		[1..1]		176

5.76.5 AdjustmentAmountAndReason

XML Tag: AdjstmntAmtAndRsn

Presence: [0..*]

Definition: Specifies detailed information on the amount and reason of the adjustment.

The **AdjstmntAmtAndRsn** block contains the following elements (see datatype "DocumentAdjustment1" on page 68 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.1.1.4.3.5.1 , 6.1.12.9.5.1	Amount	<Amt>		[1..1]		69
6.1.20.1.1.4.3.5.2 , 6.1.12.9.5.2	CreditDebitIndicator	<CdtDbtInd>		[0..1]		69
6.1.20.1.1.4.3.5.3 , 6.1.12.9.5.3	Reason	<Rsn>		[0..1]		69
6.1.20.1.1.4.3.5.4 , 6.1.12.9.5.4	AdditionalInformation	<AddtlInf>		[0..1]		69

5.76.6 RemittedAmount

XML Tag: RmtdAmt

Presence: [0..1]

Definition: Amount of money remitted.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 192

5.77 RemittanceInformation16__1

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.5.1	Unstructured	<Ustrd>		[0..*]	R[0..1]	163
6.1.20.5.2	Structured	<Strd>		[0..*]		164

Used in element(s)

"RemittanceInformation" on page 66

5.77.1 Unstructured

XML Tag: Ustrd

Presence: [0..*]

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in an unstructured form.

Datatype: "Max140Text" on page 222

Usage Guideline details

- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Unstructured**

This element has change repeatability, the maximum occurrence has been changed to : 1

5.77.2 Structured

XML Tag: Strd

Presence: [0..*]

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in a structured form.

The **Strd** block contains the following elements (see datatype "[StructuredRemittanceInformation16__1](#)" on page 168 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.1.1	ReferredDocumentInformation	<RfrdDocInf>		[0..*]		169
6.1.20.1.2	ReferredDocumentAmount	<RfrdDocAmt>		[0..1]		169
6.1.20.1.3	CreditorReferenceInformation	<CdtrRefInf>		[0..1]		170
6.1.20.1.4	Invoicer	<Invcr>		[0..1]		170
6.1.20.1.5	Invoicee	<Invcee>		[0..1]		171
6.1.20.1.6	TaxRemittance	<TaxRmt>		[0..1]		172
6.1.20.1.7	GarnishmentRemittance	<GrnshmtRmt>		[0..1]		172
6.1.20.1.8	AdditionalRemittanceInformation	<AddtlRmtInf>		[0..3]		173

Usage Guideline details

- on **pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured**

– **CBPR_Structured_RemittanceInformation_TextualRule:**

Structured can be repeated, however the total business data for all occurrences (excluding tags) must not exceed 9,000 characters.

5.78 RemittanceLocation7

Definition: Provides information on the remittance advice.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.4.1	RemittanceIdentification	<RmtId>		[0..1]		165
6.1.20.4.2	RemittanceLocationDetails	<RmtLctnDtls>		[0..*]		165

Used in element(s)

"RelatedRemittanceInformation" on page 65

5.78.1 RemittanceIdentification

XML Tag: RmtId

Presence: [0..1]

Definition: Unique identification, as assigned by the initiating party, to unambiguously identify the remittance information sent separately from the payment instruction, such as a remittance advice.

Datatype: "Max35Text" on page 223

5.78.2 RemittanceLocationDetails

XML Tag: RmtLctnDtls

Presence: [0..*]

Definition: Set of elements used to provide information on the location and/or delivery of the remittance information.

The **RmtLctnDtls** block contains the following elements (see datatype "RemittanceLocationData1" on page 165 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.3.1	Method	<Mtd>		[1..1]		166
6.1.20.3.2	ElectronicAddress	<ElctrcnAdr>		[0..1]		166
6.1.20.3.3	PostalAddress	<PstlAdr>		[0..1]		166

5.79 RemittanceLocationData1

Definition: Provides additional details on the remittance advice.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.3.1	Method	<Mtd>		[1..1]		166
6.1.20.3.2	ElectronicAddress	<ElctrcnAdr>		[0..1]		166
6.1.20.3.3	PostalAddress	<PstlAdr>		[0..1]		166

Used in element(s)

["RemittanceLocationDetails" on page 165](#)

5.79.1 Method

XML Tag: Mtd

Presence: [1..1]

Definition: Method used to deliver the remittance advice information.

Datatype: ["RemittanceLocationMethod2Code" on page 230](#)

5.79.2 ElectronicAddress

XML Tag: ElctrncAdr

Presence: [0..1]

Definition: Electronic address to which an agent is to send the remittance information.

Datatype: ["Max2048Text" on page 223](#)

5.79.3 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Postal address to which an agent is to send the remittance information.

The **PstlAdr** block contains the following elements (see datatype ["NameAndAddress16" on page 106](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.3.3.1	Name	<Nm>		[1..1]		107
6.1.20.3.3.2	Address	<Adr>		[1..1]		107

5.80 ServiceLevel8Choice

Definition: Specifies the service level of the transaction.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.16.2.2.1	Code	<Cd>	{Or	[1..1]		167
6.1.16.2.2.2	Proprietary	<Prtry>	Or}	[1..1]		167

Used in element(s)

["ServiceLevel" on page 135](#)

5.80.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Specifies a pre-agreed service or level of service between the parties, as published in an external service level code list.

Datatype: ["ExternalServiceLevel1Code" on page 216](#)

5.80.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Specifies a pre-agreed service or level of service between the parties, as a proprietary code.

Datatype: ["Max35Text" on page 223](#)

5.81 StructuredRegulatoryReporting3__1

Definition: Information needed due to regulatory and statutory requirements.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.19.1.3.1	Type	<Tp>		[0..1]		167
6.1.19.1.3.2	Date	<Dt>		[0..1]		167
6.1.19.1.3.3	Country	<Ctry>		[0..1]		168
6.1.19.1.3.4	Code	<Cd>		[0..1]		168
6.1.19.1.3.5	Amount	<Amt>		[0..1]		168
6.1.19.1.3.6	Information	<Inf>		[0..*]		168

Used in element(s)

["Details" on page 158](#)

5.81.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the type of the information supplied in the regulatory reporting details.

Datatype: ["Max35Text" on page 223](#)

5.81.2 Date

XML Tag: Dt

Presence: [0..1]

Definition: Date related to the specified type of regulatory reporting details.

Datatype: "CBPR_Date" on page 197

Usage Guideline details

- on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RegulatoryReporting/Details/Date

Type changed to: CBPR_Date on page 197

5.81.3 Country

XML Tag: Ctry

Presence: [0..1]

Definition: Country related to the specified type of regulatory reporting details.

Datatype: "CountryCode" on page 201

5.81.4 Code

XML Tag: Cd

Presence: [0..1]

Definition: Specifies the nature, purpose, and reason for the transaction to be reported for regulatory and statutory requirements in a coded form.

Datatype: "Max10Text" on page 221

5.81.5 Amount

XML Tag: Amt

Presence: [0..1]

Definition: Amount of money to be reported for regulatory and statutory requirements.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 192

5.81.6 Information

XML Tag: Inf

Presence: [0..*]

Definition: Additional details that cater for specific domestic regulatory requirements.

Datatype: "Max35Text" on page 223

5.82 StructuredRemittanceInformation16__1

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in a structured form.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.1.1	ReferredDocumentInformation	<RfrdDocInf>		[0..*]		169
6.1.20.1.2	ReferredDocumentAmount	<RfrdDocAmt>		[0..1]		169
6.1.20.1.3	CreditorReferenceInformation	<CdtrRefInf>		[0..1]		170
6.1.20.1.4	Invoicer	<Invcr>		[0..1]		170
6.1.20.1.5	Invoicee	<Invcee>		[0..1]		171
6.1.20.1.6	TaxRemittance	<TaxRmt>		[0..1]		172
6.1.20.1.7	GarnishmentRemittance	<GrnshmtRmt>		[0..1]		172
6.1.20.1.8	AdditionalRemittanceInformation	<AddtlRmtInf>		[0..3]		173

Used in element(s)

"Structured" on page 164

5.82.1 ReferredDocumentInformation

XML Tag: RfrdDocInf

Presence: [0..*]

Definition: Provides the identification and the content of the referred document.

The **RfrdDocInf** block contains the following elements (see datatype "[ReferredDocumentInformation7_1](#)" on page 154 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.1.1.1	Type	<Tp>		[0..1]		154
6.1.20.1.1.2	Number	<Nb>		[0..1]		154
6.1.20.1.1.3	RelatedDate	<RltdDt>		[0..1]		155
6.1.20.1.1.4	LineDetails	<LineDtls>		[0..*]		155

5.82.2 ReferredDocumentAmount

XML Tag: RfrdDocAmt

Presence: [0..1]

Definition: Provides details on the amounts of the referred document.

The **RfrdDocAmt** block contains the following elements (see datatype "[RemittanceAmount2](#)" on page 159 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.12.9.1	DuePayableAmount	<DuePyblAmt>		[0..1]		159
6.1.12.9.2	DiscountAppliedAmount	<DscntApldAmt>		[0..*]		159
6.1.12.9.3	CreditNoteAmount	<CdtNoteAmt>		[0..1]		160
6.1.12.9.4	TaxAmount	<TaxAmt>		[0..*]		160
6.1.12.9.5	AdjustmentAmountAndReason	<AdjstmntAmtAndRsn>		[0..*]		160
6.1.12.9.6	RemittedAmount	<RmtdAmt>		[0..1]		161

5.82.3 CreditorReferenceInformation

XML Tag: CdtrRefInf

Presence: [0..1]

Definition: Reference information provided by the creditor to allow the identification of the underlying documents.

The **CdtrRefInf** block contains the following elements (see datatype "[CreditorReferenceInformation2](#)" on page 49 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.9.1.1	Type	<Tp>		[0..1]		49
6.1.9.1.2	Reference	<Ref>		[0..1]		49

5.82.4 Invoicer

XML Tag: Invcr

Presence: [0..1]

Definition: Identification of the organisation issuing the invoice, when it is different from the creditor or ultimate creditor.

The **Invcr** block contains the following elements (see datatype "[PartyIdentification135__1](#)" on page 119 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.14.1.1	Name	<Nm>		[0..1]		120
6.1.14.1.2	PostalAddress	<PstlAdr>		[0..1]		120
6.1.14.1.3	Identification	<Id>		[0..1]		122
6.1.14.1.4	CountryOfResidence	<CtryOfRes>		[0..1]		123

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.14.1.5	ContactDetails	<CtctDtls>		[0..1]		123

Usage Guideline details

- on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/Invoicer
 - CBPR_Party_Name_Postal_Address_FormaRule:

If Postal Address is present then Name is mandatory.

For each [Full Message/Document/CustomerDirectDebitInitiationV08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/Invoicer], if
 at least one occurrence of the following element(s) [Invoicer/PostalAddress]
 is (are) present
 , then
 at least one occurrence of the following element(s) [Invoicer/Name] must be present

5.82.5 Invoicee

XML Tag: Invcee

Presence: [0..1]

Definition: Identification of the party to whom an invoice is issued, when it is different from the debtor or ultimate debtor.

The **Invcee** block contains the following elements (see datatype "[PartyIdentification135__1](#)" on [page 119](#) for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.14.1.1	Name	<Nm>		[0..1]		120
6.1.14.1.2	PostalAddress	<PstlAdr>		[0..1]		120
6.1.14.1.3	Identification	<Id>		[0..1]		122
6.1.14.1.4	CountryOfResidence	<CtryOfRes>		[0..1]		123
6.1.14.1.5	ContactDetails	<CtctDtls>		[0..1]		123

Usage Guideline details

- on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/Invoicee
 - CBPR_Party_Name_Postal_Address_FormaRule:

If Postal Address is present then Name is mandatory.

For each [Full Message/Document/CustomerDirectDebitInitiationV08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/Invoicee], if
 at least one occurrence of the following element(s) [Invoicee/PostalAddress] is (are) present
 , then
 at least one occurrence of the following element(s) [Invoicee/Name] must be present

5.82.6 TaxRemittance

XML Tag: TaxRmt

Presence: [0..1]

Definition: Provides remittance information about a payment made for tax-related purposes.

The **TaxRmt** block contains the following elements (see datatype "[TaxInformation7__1](#)" on page 177 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.24.1.1	Creditor	<Cdtr>		[0..1]		178
6.1.24.1.2	Debtor	<Dbtr>		[0..1]		178
6.1.24.1.3	UltimateDebtor	<UltmtDbtr>		[0..1]		179
6.1.24.1.4	AdministrationZone	<AdmstnZone>		[0..1]		179
6.1.24.1.5	ReferenceNumber	<RefNb>		[0..1]		179
6.1.24.1.6	Method	<Mtd>		[0..1]		179
6.1.24.1.7	TotalTaxableBaseAmount	<TtlTaxblBaseAmt>		[0..1]		180
6.1.24.1.8	TotalTaxAmount	<TtlTaxAmt>		[0..1]		180
6.1.24.1.9	Date	<Dt>		[0..1]		180
6.1.24.1.10	SequenceNumber	<SeqNb>		[0..1]		180
6.1.24.1.11	Record	<Rcrd>		[0..*]		180

5.82.7 GarnishmentRemittance

XML Tag: GrnshmtRmt

Presence: [0..1]

Definition: Provides remittance information about a payment for garnishment-related purposes.

The **GrnshmtRmt** block contains the following elements (see datatype "[Garnishment3__1](#)" on page 85 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.2.1	Type	<Tp>		[1..1]		85
6.1.20.2.2	Garnishee	<Grnshee>		[0..1]		85
6.1.20.2.3	GarnishmentAdministrator	<GrnshmtAdmstr>		[0..1]		86
6.1.20.2.4	ReferenceNumber	<RefNb>		[0..1]		87
6.1.20.2.5	Date	<Dt>		[0..1]		87
6.1.20.2.6	RemittedAmount	<RmtdAmt>		[0..1]		87
6.1.20.2.7	FamilyMedicalInsuranceIndicator	<FmlyMdclInsrncInd>		[0..1]		88
6.1.20.2.8	EmployeeTerminationIndicator	<MplyeeTermntnInd>		[0..1]		88

5.82.8 AdditionalRemittanceInformation

XML Tag: AddtlRmtInf

Presence: [0..3]

Definition: Additional information, in free text form, to complement the structured remittance information.

Datatype: "Max140Text" on page 222

5.83 SupplementaryData1

Definition: Additional information that can not be captured in the structured fields and/or any other specific block.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.12.1.1	PlaceAndName	<PlcAndNm>		[0..1]		174
6.1.12.1.2	Envelope	<Envlp>		[1..1]		174

Rules

R19 SupplementaryDataRule

This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

Error handling: Undefined

Used in element(s)

"SupplementaryData" on page 18, "SupplementaryData" on page 66

5.83.1 PlaceAndName

XML Tag: PlcAndNm

Presence: [0..1]

Definition: Unambiguous reference to the location where the supplementary data must be inserted in the message instance.

In the case of XML, this is expressed by a valid XPath.

Datatype: "Max350Text" on page 223

5.83.2 Envelope

XML Tag: Envlp

Presence: [1..1]

Definition: Technical element wrapping the supplementary data.

5.84 TaxAmount2__1

Definition: Set of elements used to provide information on the tax amount(s) of tax record.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.24.4.8.1	Rate	<Rate>		[0..1]		174
6.1.24.4.8.2	TaxableBaseAmount	<TaxblBaseAmt>		[0..1]		174
6.1.24.4.8.3	TotalAmount	<TtlAmt>		[0..1]		175
6.1.24.4.8.4	Details	<Dtls>		[0..*]		175

Used in element(s)

"TaxAmount" on page 189

5.84.1 Rate

XML Tag: Rate

Presence: [0..1]

Definition: Rate used to calculate the tax.

Datatype: "PercentageRate" on page 227

5.84.2 TaxableBaseAmount

XML Tag: TaxblBaseAmt

Presence: [0..1]

Definition: Amount of money on which the tax is based.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 192

5.84.3 TotalAmount

XML Tag: TtlAmt

Presence: [0..1]

Definition: Total amount that is the result of the calculation of the tax for the record.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 192

5.84.4 Details

XML Tag: Dtls

Presence: [0..*]

Definition: Set of elements used to provide details on the tax period and amount.

The **Dtls** block contains the following elements (see datatype "TaxRecordDetails2__1" on page 190 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.24.3.1	Period	<Prd>		[0..1]		190
6.1.24.3.2	Amount	<Amt>		[1..1]		190

5.85 TaxAmountAndType1

Definition: Specifies the amount with a specific type.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.1.1.4.3.4.1 , 6.1.12.9.4.1	Type	<Tp>		[0..1]		175
6.1.20.1.1.4.3.4.2 , 6.1.12.9.4.2	Amount	<Amt>		[1..1]		176

Used in element(s)

"TaxAmount" on page 160, "TaxAmount" on page 162

5.85.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the type of the amount.

The **Tp** block contains the following elements (see datatype "[TaxAmountType1Choice](#)" on page 176 for details)

Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.1.1.4.3.4.1.1 , Code 6.1.12.9.4.1.1		<Cd>	{Or	[1..1]		176
6.1.20.1.1.4.3.4.1.2 , Proprietary 6.1.12.9.4.1.2		<Prtry>	Or}	[1..1]		176

5.85.2 Amount

XML Tag: Amt

Presence: [1..1]

Definition: Amount of money, which has been typed.

Datatype: "[ActiveOrHistoricCurrencyAndAmount](#)" on page 192

5.86 TaxAmountType1Choice

Definition: Specifies the amount type.

Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20.1.1.4.3.4.1.1 , Code 6.1.12.9.4.1.1		<Cd>	{Or	[1..1]		176
6.1.20.1.1.4.3.4.1.2 , Proprietary 6.1.12.9.4.1.2		<Prtry>	Or}	[1..1]		176

Used in element(s)

"[Type](#)" on page 175

5.86.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Specifies the amount type, in a coded form.

Datatype: "[ExternalTaxAmountType1Code](#)" on page 217

5.86.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Specifies the amount type, in a free-text form.

Datatype: "Max35Text" on page 223

5.87 TaxAuthorisation1

Definition: Details of the authorised tax paying party.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.24.6.4.1	Title	<Titl>		[0..1]		177
6.1.24.6.4.2	Name	<Nm>		[0..1]		177

Used in element(s)

"Authorisation" on page 186

5.87.1 Title

XML Tag: Titl

Presence: [0..1]

Definition: Title or position of debtor or the debtor's authorised representative.

Datatype: "Max35Text" on page 223

5.87.2 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name of the debtor or the debtor's authorised representative.

Datatype: "Max140Text" on page 222

5.88 TaxInformation7__1

Definition: Details about tax paid, or to be paid, to the government in accordance with the law, including pre-defined parameters such as thresholds and type of account.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.24.1.1	Creditor	<Cdtr>		[0..1]		178
6.1.24.1.2	Debtor	<Dbtr>		[0..1]		178
6.1.24.1.3	UltimateDebtor	<UltmtDbtr>		[0..1]		179
6.1.24.1.4	AdministrationZone	<AdmstnZone>		[0..1]		179
6.1.24.1.5	ReferenceNumber	<RefNb>		[0..1]		179

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.24.1.6	Method	<Mtd>		[0..1]		179
6.1.24.1.7	TotalTaxableBaseAmount	<TtlTaxblBaseAmt>		[0..1]		180
6.1.24.1.8	TotalTaxAmount	<TtlTaxAmt>		[0..1]		180
6.1.24.1.9	Date	<Dt>		[0..1]		180
6.1.24.1.10	SequenceNumber	<SeqNb>		[0..1]		180
6.1.24.1.11	Record	<Rcrd>		[0..*]		180

Used in element(s)

"TaxRemittance" on page 172

5.88.1 Creditor

XML Tag: Cdtr

Presence: [0..1]

Definition: Party on the credit side of the transaction to which the tax applies.

The **Cdtr** block contains the following elements (see datatype "TaxParty1" on page 184 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.24.7.1	TaxIdentification	<TaxId>		[0..1]		184
6.1.24.7.2	RegistrationIdentification	<RegnId>		[0..1]		184
6.1.24.7.3	TaxType	<TaxTp>		[0..1]		185

5.88.2 Debtor

XML Tag: Dbtr

Presence: [0..1]

Definition: Identifies the party on the debit side of the transaction to which the tax applies.

The **Dbtr** block contains the following elements (see datatype "TaxParty2" on page 185 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.24.6.1	TaxIdentification	<TaxId>		[0..1]		185
6.1.24.6.2	RegistrationIdentification	<RegnId>		[0..1]		185
6.1.24.6.3	TaxType	<TaxTp>		[0..1]		185

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.24.6.4	Authorisation	<Authstn>		[0..1]		186

5.88.3 UltimateDebtor

XML Tag: UltmtDbtr

Presence: [0..1]

Definition: Ultimate party that owes an amount of money to the (ultimate) creditor, in this case, to the taxing authority.

The **UltmtDbtr** block contains the following elements (see datatype "[TaxParty2](#)" on page 185 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.24.6.1	TaxIdentification	<TaxId>		[0..1]		185
6.1.24.6.2	RegistrationIdentification	<RegnId>		[0..1]		185
6.1.24.6.3	TaxType	<TaxTp>		[0..1]		185
6.1.24.6.4	Authorisation	<Authstn>		[0..1]		186

5.88.4 AdministrationZone

XML Tag: AdmstnZone

Presence: [0..1]

Definition: Territorial part of a country to which the tax payment is related.

Datatype: "[Max35Text](#)" on page 223

5.88.5 ReferenceNumber

XML Tag: RefNb

Presence: [0..1]

Definition: Tax reference information that is specific to a taxing agency.

Datatype: "[Max140Text](#)" on page 222

5.88.6 Method

XML Tag: Mtd

Presence: [0..1]

Definition: Method used to indicate the underlying business or how the tax is paid.

Datatype: "[Max35Text](#)" on page 223

5.88.7 TotalTaxableBaseAmount

XML Tag: TtlTaxblBaseAmt

Presence: [0..1]

Definition: Total amount of money on which the tax is based.

Datatype: ["ActiveOrHistoricCurrencyAndAmount" on page 192](#)

5.88.8 TotalTaxAmount

XML Tag: TtlTaxAmt

Presence: [0..1]

Definition: Total amount of money as result of the calculation of the tax.

Datatype: ["ActiveOrHistoricCurrencyAndAmount" on page 192](#)

5.88.9 Date

XML Tag: Dt

Presence: [0..1]

Definition: Date by which tax is due.

Datatype: ["CBPR_Date" on page 197](#)

Usage Guideline details

- on [pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/TaxRemittance/Date](#)
Type changed to: [CBPR_Date on page 197](#)

5.88.10 SequenceNumber

XML Tag: SeqNb

Presence: [0..1]

Definition: Sequential number of the tax report.

Datatype: ["Number" on page 226](#)

5.88.11 Record

XML Tag: Rcrd

Presence: [0..*]

Definition: Record of tax details.

The **Rcrd** block contains the following elements (see datatype ["TaxRecord2__1" on page 187](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.24.4.1	Type	<Tp>		[0..1]		188
6.1.24.4.2	Category	<Ctgy>		[0..1]		188
6.1.24.4.3	CategoryDetails	<CtgyDtls>		[0..1]		188
6.1.24.4.4	DebtorStatus	<DbtrSts>		[0..1]		188
6.1.24.4.5	CertificateIdentification	<CertId>		[0..1]		188
6.1.24.4.6	FormsCode	<FrmsCd>		[0..1]		189
6.1.24.4.7	Period	<Prd>		[0..1]		189
6.1.24.4.8	TaxAmount	<TaxAmt>		[0..1]		189
6.1.24.4.9	AdditionalInformation	<AddtlInf>		[0..1]		190

5.89 TaxInformation8__1

Definition: Details about tax paid, or to be paid, to the government in accordance with the law, including pre-defined parameters such as thresholds and type of account.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.24.2.1	Creditor	<Cdtr>		[0..1]		181
6.1.24.2.2	Debtor	<Dbtr>		[0..1]		182
6.1.24.2.3	AdministrationZone	<AdmstnZone>		[0..1]		182
6.1.24.2.4	ReferenceNumber	<RefNb>		[0..1]		182
6.1.24.2.5	Method	<Mtd>		[0..1]		182
6.1.24.2.6	TotalTaxableBaseAmount	<TtlTaxblBaseAmt>		[0..1]		183
6.1.24.2.7	TotalTaxAmount	<TtlTaxAmt>		[0..1]		183
6.1.24.2.8	Date	<Dt>		[0..1]		183
6.1.24.2.9	SequenceNumber	<SeqNb>		[0..1]		183
6.1.24.2.10	Record	<Rcrd>		[0..*]		183

Used in element(s)

"Tax" on page 65

5.89.1 Creditor

XML Tag: Cdtr

Presence: [0..1]

Definition: Party on the credit side of the transaction to which the tax applies.

The **Cdtr** block contains the following elements (see datatype "[TaxParty1](#)" on page 184 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.24.7.1	TaxIdentification	<TaxId>		[0..1]		184
6.1.24.7.2	RegistrationIdentification	<RegnId>		[0..1]		184
6.1.24.7.3	TaxType	<TaxTp>		[0..1]		185

5.89.2 Debtor

XML Tag: Dbtr

Presence: [0..1]

Definition: Party on the debit side of the transaction to which the tax applies.

The **Dbtr** block contains the following elements (see datatype "[TaxParty2](#)" on page 185 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.24.6.1	TaxIdentification	<TaxId>		[0..1]		185
6.1.24.6.2	RegistrationIdentification	<RegnId>		[0..1]		185
6.1.24.6.3	TaxType	<TaxTp>		[0..1]		185
6.1.24.6.4	Authorisation	<Authstn>		[0..1]		186

5.89.3 AdministrationZone

XML Tag: AdmstnZone

Presence: [0..1]

Definition: Territorial part of a country to which the tax payment is related.

Datatype: "[Max35Text](#)" on page 223

5.89.4 ReferenceNumber

XML Tag: RefNb

Presence: [0..1]

Definition: Tax reference information that is specific to a taxing agency.

Datatype: "[Max140Text](#)" on page 222

5.89.5 Method

XML Tag: Mtd

Presence: [0..1]

Definition: Method used to indicate the underlying business or how the tax is paid.

Datatype: ["Max35Text" on page 223](#)

5.89.6 TotalTaxableBaseAmount

XML Tag: TtlTaxblBaseAmt

Presence: [0..1]

Definition: Total amount of money on which the tax is based.

Datatype: ["ActiveOrHistoricCurrencyAndAmount" on page 192](#)

5.89.7 TotalTaxAmount

XML Tag: TtlTaxAmt

Presence: [0..1]

Definition: Total amount of money as result of the calculation of the tax.

Datatype: ["ActiveOrHistoricCurrencyAndAmount" on page 192](#)

5.89.8 Date

XML Tag: Dt

Presence: [0..1]

Definition: Date by which tax is due.

Datatype: ["CBPR_Date" on page 197](#)

Usage Guideline details

- [on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/Tax/Date](#)
Type changed to: [CBPR_Date on page 197](#)

5.89.9 SequenceNumber

XML Tag: SeqNb

Presence: [0..1]

Definition: Sequential number of the tax report.

Datatype: ["Number" on page 226](#)

5.89.10 Record

XML Tag: Rcrd

Presence: [0..*]

Definition: Record of tax details.

The **Rcrd** block contains the following elements (see datatype ["TaxRecord2__1" on page 187](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.24.4.1	Type	<Tp>		[0..1]		188
6.1.24.4.2	Category	<Ctgy>		[0..1]		188
6.1.24.4.3	CategoryDetails	<CtgyDtls>		[0..1]		188
6.1.24.4.4	DebtorStatus	<DbtrSts>		[0..1]		188
6.1.24.4.5	CertificateIdentification	<CertId>		[0..1]		188
6.1.24.4.6	FormsCode	<FrmsCd>		[0..1]		189
6.1.24.4.7	Period	<Prd>		[0..1]		189
6.1.24.4.8	TaxAmount	<TaxAmt>		[0..1]		189
6.1.24.4.9	AdditionalInformation	<AddtlInf>		[0..1]		190

5.90 TaxParty1

Definition: Details about the entity involved in the tax paid or to be paid.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.24.7.1	TaxIdentification	<TaxId>		[0..1]		184
6.1.24.7.2	RegistrationIdentification	<RegnId>		[0..1]		184
6.1.24.7.3	TaxType	<TaxTp>		[0..1]		185

Used in element(s)

"Creditor" on page 181, "Creditor" on page 178

5.90.1 TaxIdentification

XML Tag: TaxId

Presence: [0..1]

Definition: Tax identification number of the creditor.

Datatype: "Max35Text" on page 223

5.90.2 RegistrationIdentification

XML Tag: RegnId

Presence: [0..1]

Definition: Unique identification, as assigned by an organisation, to unambiguously identify a party.

Datatype: ["Max35Text" on page 223](#)

5.90.3 TaxType

XML Tag: TaxTp

Presence: [0..1]

Definition: Type of tax payer.

Datatype: ["Max35Text" on page 223](#)

5.91 TaxParty2

Definition: Details about the entity involved in the tax paid or to be paid.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.24.6.1	TaxIdentification	<TaxId>		[0..1]		185
6.1.24.6.2	RegistrationIdentification	<RegnId>		[0..1]		185
6.1.24.6.3	TaxType	<TaxTp>		[0..1]		185
6.1.24.6.4	Authorisation	<Authstn>		[0..1]		186

Used in element(s)

["Debtor" on page 182](#), ["Debtor" on page 178](#), ["UltimateDebtor" on page 179](#)

5.91.1 TaxIdentification

XML Tag: TaxId

Presence: [0..1]

Definition: Tax identification number of the debtor.

Datatype: ["Max35Text" on page 223](#)

5.91.2 RegistrationIdentification

XML Tag: RegnId

Presence: [0..1]

Definition: Unique identification, as assigned by an organisation, to unambiguously identify a party.

Datatype: ["Max35Text" on page 223](#)

5.91.3 TaxType

XML Tag: TaxTp

Presence: [0..1]

Definition: Type of tax payer.

Datatype: "Max35Text" on page 223

5.91.4 Authorisation

XML Tag: Authstn

Presence: [0..1]

Definition: Details of the authorised tax paying party.

The **Authstn** block contains the following elements (see datatype "TaxAuthorisation1" on page 177 for details)

Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.24.6.4.1	Title	<Titl>		[0..1]		177
6.1.24.6.4.2	Name	<Nm>		[0..1]		177

5.92 TaxPeriod2__1

Definition: Period of time details related to the tax payment.

Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.24.5.1	Year	<Yr>		[0..1]		186
6.1.24.5.2	Type	<Tp>		[0..1]		187
6.1.24.5.3	FromToDate	<FrToDt>		[0..1]		187

Used in element(s)

"Period" on page 189, "Period" on page 190

5.92.1 Year

XML Tag: Yr

Presence: [0..1]

Definition: Year related to the tax payment.

Datatype: "CBPR_Date" on page 197

Usage Guideline details

- on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/Tax/Record/Period/Year

Type changed to: CBPR_Date on page 197

- on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/Tax/Record/Tax-Amount/Details/Period/Year
Type changed to: [CBPR_Date on page 197](#)
- on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/TaxRemittance/Record/Period/Year
Type changed to: [CBPR_Date on page 197](#)
- on pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/RemittanceInformation/Structured/TaxRemittance/Record/TaxAmount/Details/Period/Year
Type changed to: [CBPR_Date on page 197](#)

5.92.2 Type

XML Tag: Tp

Presence: [0..1]

Definition: Identification of the period related to the tax payment.

Datatype: ["TaxRecordPeriod1Code" on page 232](#)

5.92.3 FromToDate

XML Tag: FrToDt

Presence: [0..1]

Definition: Range of time between a start date and an end date for which the tax report is provided.

The **FrToDt** block contains the following elements (see datatype ["DatePeriod2__1" on page 54](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.6.1.1	FromDate	<FrDt>		[1..1]		55
6.1.6.1.2	ToDate	<ToDt>		[1..1]		55

5.93 TaxRecord2__1

Definition: Set of elements used to define the tax record.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.24.4.1	Type	<Tp>		[0..1]		188
6.1.24.4.2	Category	<Ctgy>		[0..1]		188
6.1.24.4.3	CategoryDetails	<CtgyDtls>		[0..1]		188

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.24.4.4	DebtorStatus	<DbtrSts>		[0..1]		188
6.1.24.4.5	CertificateIdentification	<CertId>		[0..1]		188
6.1.24.4.6	FormsCode	<FrmsCd>		[0..1]		189
6.1.24.4.7	Period	<Prd>		[0..1]		189
6.1.24.4.8	TaxAmount	<TaxAmt>		[0..1]		189
6.1.24.4.9	AdditionalInformation	<AddtlInf>		[0..1]		190

Used in element(s)

"Record" on page 183, "Record" on page 180

5.93.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: High level code to identify the type of tax details.

Datatype: "Max35Text" on page 223

5.93.2 Category

XML Tag: Ctgy

Presence: [0..1]

Definition: Specifies the tax code as published by the tax authority.

Datatype: "Max35Text" on page 223

5.93.3 CategoryDetails

XML Tag: CtgyDtls

Presence: [0..1]

Definition: Provides further details of the category tax code.

Datatype: "Max35Text" on page 223

5.93.4 DebtorStatus

XML Tag: DbtrSts

Presence: [0..1]

Definition: Code provided by local authority to identify the status of the party that has drawn up the settlement document.

Datatype: "Max35Text" on page 223

5.93.5 CertificateIdentification

XML Tag: CertId

Presence: [0..1]

Definition: Identification number of the tax report as assigned by the taxing authority.

Datatype: "Max35Text" on page 223

5.93.6 FormsCode

XML Tag: FrmsCd

Presence: [0..1]

Definition: Identifies, in a coded form, on which template the tax report is to be provided.

Datatype: "Max35Text" on page 223

5.93.7 Period

XML Tag: Prd

Presence: [0..1]

Definition: Set of elements used to provide details on the period of time related to the tax payment.

The **Prd** block contains the following elements (see datatype "TaxPeriod2__1" on page 186 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.24.5.1	Year	<Yr>		[0..1]		186
6.1.24.5.2	Type	<Tp>		[0..1]		187
6.1.24.5.3	FromDate	<FrToDt>		[0..1]		187

5.93.8 TaxAmount

XML Tag: TaxAmt

Presence: [0..1]

Definition: Set of elements used to provide information on the amount of the tax record.

The **TaxAmt** block contains the following elements (see datatype "TaxAmount2__1" on page 174 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.24.4.8.1	Rate	<Rate>		[0..1]		174
6.1.24.4.8.2	TaxableBaseAmount	<TaxblBaseAmt>		[0..1]		174
6.1.24.4.8.3	TotalAmount	<TtlAmt>		[0..1]		175

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.24.4.8.4	Details	<Dtls>		[0..*]		175

5.93.9 AdditionalInformation

XML Tag: AddtlInf

Presence: [0..1]

Definition: Further details of the tax record.

Datatype: "Max140Text" on page 222

5.94 TaxRecordDetails2__1

Definition: Provides information on the individual tax amount(s) per period of the tax record.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.24.3.1	Period	<Prd>		[0..1]		190
6.1.24.3.2	Amount	<Amt>		[1..1]		190

Used in element(s)

"Details" on page 175

5.94.1 Period

XML Tag: Prd

Presence: [0..1]

Definition: Set of elements used to provide details on the period of time related to the tax payment.

The **Prd** block contains the following elements (see datatype "TaxPeriod2__1" on page 186 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.24.5.1	Year	<Yr>		[0..1]		186
6.1.24.5.2	Type	<Tp>		[0..1]		187
6.1.24.5.3	FromToDate	<FrToDt>		[0..1]		187

5.94.2 Amount

XML Tag: Amt

Presence: [1..1]

Definition: Underlying tax amount related to the specified period.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 192

6 Message Datatypes

Note The following chapter identifies the datatypes that are used in the message.

6.1 ActiveOrHistoricCurrencyAndAmount

Definition: A number of monetary units specified in an active or a historic currency where the unit of currency is explicit and compliant with ISO 4217.

Type: Amount

This data type must be used with the following XML Attributes:

Attribute	Tag	Datatype
Currency	Ccy	"ActiveOrHistoricCurrencyCode" on page 192

Format

fractionDigits	5
minInclusive	0
totalDigits	18

Rules

R13 CurrencyAmount ✓

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00007
- *Error Text:* Invalid currency code or too many decimal digits.

Used in element(s)

"Amount" on page 168, "Amount" on page 190, "Amount" on page 67, "Amount" on page 69, "Amount" on page 176, "CreditNoteAmount" on page 160, "CreditNoteAmount" on page 162, "Due-PayableAmount" on page 159, "DuePayableAmount" on page 161, "InstructedAmount" on page 59, "RemittedAmount" on page 87, "RemittedAmount" on page 161, "RemittedAmount" on page 163, "TaxableBaseAmount" on page 174, "TotalAmount" on page 175, "TotalTaxAmount" on page 183, "TotalTaxAmount" on page 180, "TotalTaxableBaseAmount" on page 183, "TotalTaxableBaseAmount" on page 180

6.2 ActiveOrHistoricCurrencyCode

Definition: A code allocated to a currency by a Maintenance Agency under an international identification scheme, as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds".

Type: CodeSet

Format

pattern [A-Z]{3,3}

Rules

R14 ActiveOrHistoricCurrency ✓

The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

Error handling:

- Error severity: Fatal
- Error Code: D00006
- Error Text: Invalid currency code.

Used in element(s)

["Currency" on page 39](#)

Used in attribute(s)

["ActiveOrHistoricCurrencyAndAmount" on page 192](#)

Restricts

["ParentCurrencyCode" on page 226](#)

6.3 AddressType2Code

Definition: Specifies the type of address.

Type: CodeSet

Code	Name	Definition
ADDR	Postal	Address is the complete postal address.
BIZZ	Business	Address is the business address.
DLVY	DeliveryTo	Address is the address to which delivery is to take place.
HOME	Residential	Address is the home address.
MLTO	MailTo	Address is the address to which mail is sent.
PBOX	POBox	Address is a postal office (PO) box.

Used in element(s)

["Code" on page 20](#)

Restricts

["AddressTypeCode" on page 194](#)

6.4 AddressTypeCode

Definition: Specifies the type of address.

Type: CodeSet

Code	Name	Definition
ADDR	Postal	Address is the complete postal address.
BIZZ	Business	Address is the business address.
DLVY	DeliveryTo	Address is the address to which delivery is to take place.
HOME	Residential	Address is the home address.
MLTO	MailTo	Address is the address to which mail is sent.
PBOX	POBox	Address is a postal office (PO) box.

Is restricted by

["AddressType2Code" on page 193](#)

6.5 AmountDirectionCode

Definition: Specifies if an operation is an increase or a decrease or the result of a reversal operation.

Type: CodeSet

Code	Name	Definition
CRDT	Credit	Operation is an increase.
DBIT	Debit	Operation is a decrease.
RVCD	ReversalCredit	Debit entry used to reverse a previously booked credit entry.
RVDB	ReversalDebit	Credit entry used to reverse a previously booked debit entry.

Is restricted by

["CreditDebitCode" on page 201](#)

6.6 AnyBICDec2014Identifier

Definition: Code allocated to a financial or non-financial institution by the ISO 9362 Registration Authority, as described in ISO 9362: 2014 - "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Type: IdentifierSet

Format

pattern [A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}([A-Z0-9]{3,3}){0,1}

Rules**R18 AnyBIC ✓**

Only a valid Business identifier code is allowed. Business identifier codes for financial or non-financial institutions are registered and published by the ISO 9362 Registration Authority in the ISO directory of BICs, and consists of eight (8) or eleven (11) contiguous characters.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00008
- *Error Text:* Invalid BIC.

Used in element(s)

"AnyBIC" on page 108

6.7 Authorisation1Code

Definition: Specifies the level of approval depending on a number of factors, including payment type, threshold amount or local country or operations practice.

Type: CodeSet

Code	Name	Definition
AUTH	PreAuthorisedFile	Indicates a file has been pre authorised or approved within the originating customer environment and no further approval is required.
FDET	FileLevelAuthorisationDetails	Indicates that a file requires additional file level approval, with the ability to view both the payment information block and supporting customer credit transaction detail.
FSUM	FileLevelAuthorisationSummary	Indicates that a file requires additional file level approval, with the ability to view only the payment information block level information.
ILEV	InstructionLevelAuthorisation	Indicates that a file requires all customer transactions to be authorised or approved.

Used in element(s)

"Code" on page 26

Restricts

"AuthorisationCode" on page 196

6.8 AuthorisationCode

Definition: Specifies the level of approval depending on a number of factors, including payment type, threshold amount or local country or operations practice.

Type: CodeSet

Code	Name	Definition
AUTH	PreAuthorisedFile	Indicates a file has been pre authorised or approved within the originating customer environment and no further approval is required.
FDET	FileLevelAuthorisationDetails	Indicates that a file requires additional file level approval, with the ability to view both the payment information block and supporting customer credit transaction detail.
FSUM	FileLevelAuthorisationSummary	Indicates that a file requires additional file level approval, with the ability to view only the payment information block level information.
ILEV	InstructionLevelAuthorisation	Indicates that a file requires all customer transactions to be authorised or approved.

Is restricted by

"Authorisation1Code" on page 195

6.9 BICFI Dec2014Identifier

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362: 2014 - "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Type: IdentifierSet

Format

pattern [A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}([A-Z0-9]{3,3}){0,1}

Rules

R5 BICFI ✓

Valid BICs for financial institutions are registered and published by the ISO 9362 Registration Authority in the ISO directory of BICs, and consist of eight (8) or eleven (11) contiguous characters.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00001
- *Error Text:* Invalid FI BIC.

Used in element(s)

["BICFI" on page 79](#), ["BICFI" on page 75](#)

6.10 BatchBookingIndicator

Definition: Identifies whether the sending party requests a single debit or credit entry per individual transaction or a batch entry for the sum of the amounts of all transactions.

Type: Indicator

Meaning When True: Identifies that a batch entry for the sum of the amounts of all transactions in the batch or message is requested.

Meaning When False: Identifies that a single entry for each of the transactions in the batch or message is requested.

Used in element(s)

["BatchBooking" on page 128](#)

6.11 CBPR_Date

Definition: This Type restricts the base ISODate to YYYY (exactly 4 digits for the Year) and does not allow use of UTC offset or Zulu indicator with a date.

This datatype has been created by the Publisher of this Usage Guideline.

Type: Date

Format

pattern [0-9]{4}-[0-9]{2}-[0-9]{2}

Used in element(s)

["BirthDate" on page 53](#), ["Date" on page 167](#), ["Date" on page 183](#), ["Date" on page 180](#), ["Date" on page 87](#), ["DateOfSignature" on page 103](#), ["FinalCollectionDate" on page 105](#), ["FirstCollectionDate" on page 104](#), ["FromDate" on page 55](#), ["OriginalFinalCollectionDate" on page 25](#), ["PreNotificationDate" on page 57](#), ["RelatedDate" on page 155](#), ["RelatedDate" on page 70](#), ["RequestedCollectionDate" on page 129](#), ["ToDate" on page 55](#), ["Year" on page 186](#)

6.12 CBPR_DateTime

Definition: A particular point in the progression of time defined by a mandatory date and a mandatory time component, expressed in local time with UTC offset format (YYYY-MM-DDThh:mm:ss.sss+/-hh:mm).

This representation is defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Note on the time format:

1) beginning / end of calendar day

00:00:00 = the beginning of a calendar day

24:00:00 = the end of a calendar day

2) fractions of second in time format

Decimal fractions of seconds may be included. In this case, the involved parties shall agree on the maximum number of digits that are allowed.

Example: 2020-07-16T19:20:30.45+01:00

This datatype has been created by the Publisher of this Usage Guideline.

Type: DateTime

Format

pattern `.*(\+|-)((0[0-9])|(1[0-4])):[0-5][0-9]`

Used in element(s)

["CreationDate" on page 36](#), ["CreationDateTime" on page 98](#)

6.13 CBPR_RestrictedFINXMax28Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 28 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	28
minLength	1
pattern	<code>[0-9a-zA-Z/\-!\?:(\)\.,'\+]+</code>

Used in element(s)

["MemberIdentification" on page 45](#)

6.14 CBPR_RestrictedFINXMax35Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 35 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	35
minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,\'+]+

Used in element(s)

["BusinessMessageIdentifier" on page 35](#), ["BusinessService" on page 36](#), ["EndToEndIdentification" on page 125](#), ["MessageDefinitionIdentifier" on page 35](#)

6.15 ChargeBearerType1Code

Definition: Specifies which party(ies) will pay charges due for processing of the instruction.

Type: CodeSet

Code	Name	Definition
CRED	BorneByCreditor	All transaction charges are to be borne by the creditor.
DEBT	BorneByDebtor	All transaction charges are to be borne by the debtor.
SHAR	Shared	In a credit transfer context, means that transaction charges on the sender side are to be borne by the debtor, transaction charges on the receiver side are to be borne by the creditor. In a direct debit context, means that transaction charges on the sender side are to be borne by the creditor, transaction charges on the receiver side are to be borne by the debtor.
SLEV	FollowingServiceLevel	Charges are to be applied following the rules agreed in the service level and/or scheme. Usage Guideline restrictions for this code • This code(pain.008.001.08/PaymentInformation/DirectDebitTransactionInformation/ChargeBearer/FollowingServiceLevel) is removed.

Used in element(s)

["ChargeBearer" on page 132](#), ["ChargeBearer" on page 60](#)

Restricts

["ChargeBearerTypeCode" on page 199](#)

6.16 ChargeBearerTypeCode

Definition: Specifies which party(ies) will pay charges due for processing of the instruction.

Type: CodeSet

Code	Name	Definition
CRED	BorneByCreditor	All transaction charges are to be borne by the creditor.
DEBT	BorneByDebtor	All transaction charges are to be borne by the debtor.
SHAR	Shared	In a credit transfer context, means that transaction charges on the sender side are to be borne by the debtor, transaction charges on the receiver side are to be borne by the creditor. In a direct debit context, means that transaction charges on the sender side are to be borne by the creditor, transaction charges on the receiver side are to be borne by the debtor.
SLEV	FollowingServiceLevel	Charges are to be applied following the rules agreed in the service level and/or scheme.

Is restricted by

"ChargeBearerType1Code" on page 199

6.17 CopyDuplicate1Code

Definition: Specifies if this document is a copy, a duplicate, or a duplicate of a copy.

Type: CodeSet

Code	Name	Definition
CODU	CopyDuplicate	Message is being sent as a copy to a party other than the account owner, for information purposes and the message is a duplicate of a message previously sent.
COPY	Copy	Message is being sent as a copy to a party other than the account owner, for information purposes.
DUPL	Duplicate	Message is for information/confirmation purposes. It is a duplicate of a message previously sent.

Used in element(s)

"CopyDuplicate" on page 37

Restricts

"CopyDuplicateCode" on page 200

6.18 CopyDuplicateCode

Definition: Specifies if this document is a copy, a duplicate, or a duplicate of a copy.

Type: CodeSet

Code	Name	Definition
CODU	CopyDuplicate	Message is being sent as a copy to a party other than the account owner, for information purposes and the message is a duplicate of a message previously sent.
COPY	Copy	Message is being sent as a copy to a party other than the account owner, for information purposes.
DUPL	Duplicate	Message is for information/confirmation purposes. It is a duplicate of a message previously sent.

Is restricted by

"CopyDuplicate1Code" on page 200

6.19 CountryCode

Definition: Code to identify a country, a dependency, or another area of particular geopolitical interest, on the basis of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

Type: CodeSet

Format

pattern [A-Z]{2,2}

Rules

R6 Country ✓

The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00004
- *Error Text:* Invalid Country Code.

Used in element(s)

"Country" on page 168, "Country" on page 147, "Country" on page 157, "CountryOfBirth" on page 54, "CountryOfBirth" on page 52, "CountryOfResidence" on page 123, "CountryOfResidence" on page 118

6.20 CreditDebitCode

Definition: Specifies if an operation is an increase or a decrease.

Type: CodeSet

Code	Name	Definition
CRDT	Credit	Operation is an increase.
DBIT	Debit	Operation is a decrease.

Used in element(s)

"CreditDebitIndicator" on page 69

Restricts

"AmountDirectionCode" on page 194

6.21 DecimalNumber

Definition: Number of objects represented as a decimal number, for example 0.75 or 45.6.

Type: Quantity

Format

fractionDigits	17
totalDigits	18

Used in element(s)

"ControlSum" on page 99, "ControlSum" on page 129, "CountPerPeriod" on page 84

6.22 DocumentType3Code

Definition: Specifies a type of financial or commercial document.

Type: CodeSet

Code	Name	Definition
DISP	DispatchAdvice	Document is a dispatch advice.
FXDR	ForeignExchangeDealReference	Document is a pre-agreed or pre-arranged foreign exchange transaction to which the payment transaction refers.
PUOR	PurchaseOrder	Document is a purchase order.
RADM	RemittanceAdviceMessage	Document is a remittance advice sent separately from the current transaction.
RPIN	RelatedPaymentInstruction	Document is a linked payment instruction to which the current payment instruction is related, for example, in a cover scenario.
SCOR	StructuredCommunicationReference	Document is a structured communication reference provided by the creditor to identify the referred transaction.

Used in element(s)

"Code" on page 50

Restricts"DocumentTypeCode" on page 204

6.23 DocumentType6Code

Definition: Specifies a type of financial or commercial document.*Type:* CodeSet

Code	Name	Definition
AROI	AccountReceivableOpenItem	Document is a payment that applies to a specific source document.
BOLD	BillOfLading	Document is a shipping notice.
CINV	CommercialInvoice	Document is an invoice.
CMCN	CommercialContract	Document is an agreement between the parties, stipulating the terms and conditions of the delivery of goods or services.
CNFA	CreditNoteRelatedToFinancialAdjustment	Document is a credit note for the final amount settled for a commercial transaction.
CREN	CreditNote	Document is a credit note.
DEBN	DebitNote	Document is a debit note.
DISP	DispatchAdvice	Document is a dispatch advice.
DNFA	DebitNoteRelatedToFinancialAdjustment	Document is a debit note for the final amount settled for a commercial transaction.
HIRI	HireInvoice	Document is an invoice for the hiring of human resources or renting goods or equipment.
MSIN	MeteredServiceInvoice	Document is an invoice claiming payment for the supply of metered services, for example gas or electricity supplied to a fixed meter.
PUOR	PurchaseOrder	Document is a purchase order.
SBIN	SelfBilledInvoice	Document is an invoice issued by the debtor.
SOAC	StatementOfAccount	Document is a statement of the transactions posted to the debtor's account at the supplier.
TSUT	TradeServicesUtilityTransaction	Document is a transaction identifier as assigned by the Trade Services Utility.
VCHR	Voucher	Document is an electronic payment document.

Used in element(s)"Code" on page 156

Restricts"DocumentTypeCode" on page 204

6.24 DocumentTypeCode

Definition: Specifies a type of financial or commercial document.*Type:* CodeSet

Code	Name	Definition
AROI	AccountReceivableOpenItem	Document is a payment that applies to a specific source document.
BOLD	BillOfLading	Document is a shipping notice.
CINV	CommercialInvoice	Document is an invoice.
CMCN	CommercialContract	Document is an agreement between the parties, stipulating the terms and conditions of the delivery of goods or services.
CNFA	CreditNoteRelatedToFinancialAdjustment	Document is a credit note for the final amount settled for a commercial transaction.
CRCP	CustomerReceipt	When the Sale System requires the POI system to print the Customer receipt.
CREN	CreditNote	Document is a credit note.
DEBN	DebitNote	Document is a debit note.
DISP	DispatchAdvice	Document is a dispatch advice.
DNFA	DebitNoteRelatedToFinancialAdjustment	Document is a debit note for the final amount settled for a commercial transaction.
FXDR	ForeignExchangeDealReference	Document is a pre-agreed or pre-arranged foreign exchange transaction to which the payment transaction refers.
HIRI	HireInvoice	Document is an invoice for the hiring of human resources or renting goods or equipment.
HRCP	CashierReceipt	When the Sale system print the Cashier copy of the Payment receipt.
JNRL	Journal	When the POI or the Sale System wants to store a message on the journal printer or electronic journal of the Sale Terminal (it is sometimes a Sale Logging/Journal Printer).
MSIN	MeteredServiceInvoice	Document is an invoice claiming payment for the supply of metered services, for example gas or electricity supplied to a fixed meter.
PUOR	PurchaseOrder	Document is a purchase order.
RADM	RemittanceAdviceMessage	Document is a remittance advice sent separately from the current transaction.

Code	Name	Definition
RPIN	RelatedPaymentInstruction	Document is a linked payment instruction to which the current payment instruction is related, for example, in a cover scenario.
SBIN	SelfBilledInvoice	Document is an invoice issued by the debtor.
SCOR	StructuredCommunicationReference	Document is a structured communication reference provided by the creditor to identify the referred transaction.
SOAC	StatementOfAccount	Document is a statement of the transactions posted to the debtor's account at the supplier.
SRCP	SaleReceipt	When the Sale System requires the POI system to print the Sale receipt.
TSUT	TradeServicesUtilityTransaction	Document is a transaction identifier as assigned by the Trade Services Utility.
VCHR	Voucher	Document is an electronic payment document.

Is restricted by

"DocumentType3Code" on page 202, "DocumentType6Code" on page 203

6.25 Exact2NumericText

Definition: Specifies a numeric string with an exact length of 2 digits.

Type: Text

Format

pattern [0-9]{2}

Used in element(s)

"OriginalTrackingDays" on page 26, "PointInTime" on page 84, "TrackingDays" on page 106

6.26 Exact4AlphaNumericText

Definition: Specifies an alphanumeric string with a length of 4 characters.

Type: Text

Format

pattern [a-zA-Z0-9]{4}

Used in element(s)

"Identification" on page 92

6.27 ExternalAccountIdentification1Code

Definition: Specifies the external account identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 20

Restricts

"ExternalAccountIdentificationCode" on page 206

6.28 ExternalAccountIdentificationCode

Definition: Specifies the external account identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalAccountIdentification1Code" on page 206

6.29 ExternalCashAccountType1Code

Definition: Specifies the nature, or use, of the cash account in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 41

Restricts

"ExternalCashAccountTypeCode" on page 207

6.30 ExternalCashAccountTypeCode

Definition: Specifies the nature, or use, of the cash account in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalCashAccountType1Code" on page 206

6.31 ExternalCategoryPurpose1Code

Definition: Specifies the category purpose, as published in an external category purpose code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 41

Restricts

"ExternalCategoryPurposeCode" on page 208

6.32 ExternalCategoryPurposeCode

Definition: Specifies the category purpose, as published in an external category purpose code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalCategoryPurpose1Code" on page 207

6.33 ExternalClearingSystemIdentification1Code

Definition: Specifies the clearing system identification code, as published in an external clearing system identification code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	5
minLength	1

Used in element(s)

"Code" on page 42

Restricts

"ExternalClearingSystemIdentificationCode" on page 208

6.34 ExternalClearingSystemIdentificationCode

Definition: Specifies the clearing system identification code, as published in an external clearing system identification code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	5
minLength	1

Is restricted by

"ExternalClearingSystemIdentification1Code" on page 208

6.35 ExternalDiscountAmountType1Code

Definition: Specifies the nature, or use, of the amount in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 68

Restricts

"ExternalDiscountAmountTypeCode" on page 209

6.36 ExternalDiscountAmountTypeCode

Definition: Specifies the nature, or use, of the amount in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalDiscountAmountType1Code" on page 209

6.37 ExternalDocumentLineType1Code

Definition: Specifies the document line type as published in an external document type code list.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 73

Restricts

"ExternalDocumentLineTypeCode" on page 210

6.38 ExternalDocumentLineTypeCode

Definition: Specifies the document line type as published in an external document type code list.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalDocumentLineType1Code" on page 209

6.39 ExternalFinancialInstitutionIdentification1Code

Definition: Specifies the external financial institution identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 74

Restricts

"ExternalFinancialInstitutionIdentificationCode" on page 210

6.40 ExternalFinancialInstitutionIdentificationCode

Definition: Specifies the external financial institution identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalFinancialInstitutionIdentification1Code" on page 210

6.41 ExternalGarnishmentType1Code

Definition: Specifies the garnishment type as published in an external document type code list.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 89

Restricts

"ExternalGarnishmentTypeCode" on page 211

6.42 ExternalGarnishmentTypeCode

Definition: Specifies the garnishment type as published in an external document type code list.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalGarnishmentType1Code" on page 211

6.43 ExternalLocalInstrument1Code

Definition: Specifies the external local instrument code in the format of character string with a maximum length of 35 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	35
minLength	1

Used in element(s)

"Code" on page 102

Restricts

"ExternalLocalInstrumentCode" on page 212

6.44 ExternalLocalInstrumentCode

Definition: Specifies the external local instrument code in the format of character string with a maximum length of 35 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	35
minLength	1

Is restricted by

"ExternalLocalInstrument1Code" on page 211

6.45 ExternalMandateSetupReason1Code

Definition: Specifies the external mandate setup reason code in the format of character string with a maximum length of 4 characters.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 106

Restricts

"ExternalMandateSetupReasonCode" on page 213

6.46 ExternalMandateSetupReasonCode

Definition: Specifies the external mandate setup reason code in the format of character string with a maximum length of 4 characters.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalMandateSetupReason1Code" on page 212

6.47 ExternalOrganisationIdentification1Code

Definition: Specifies the external organisation identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 111

Restricts

"ExternalOrganisationIdentificationCode" on page 213

6.48 ExternalOrganisationIdentificationCode

Definition: Specifies the external organisation identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalOrganisationIdentification1Code" on page 213

6.49 ExternalPersonIdentification1Code

Definition: Specifies the external person identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 140

Restricts

"ExternalPersonIdentificationCode" on page 214

6.50 ExternalPersonIdentificationCode

Definition: Specifies the external person identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalPersonIdentification1Code" on page 214

6.51 ExternalProxyAccountType1Code

Definition: Specifies the external proxy account type code, as published in the proxy account type external code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 153

Restricts

"ExternalProxyAccountTypeCode" on page 215

6.52 ExternalProxyAccountTypeCode

Definition: Specifies the external proxy account type code, as published in the proxy account type external code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalProxyAccountType1Code" on page 215

6.53 ExternalPurpose1Code

Definition: Specifies the external purpose code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 153

Restricts

"ExternalPurposeCode" on page 216

6.54 ExternalPurposeCode

Definition: Specifies the external purpose code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalPurpose1Code" on page 215

6.55 ExternalServiceLevel1Code

Definition: Specifies the external service level code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 167

Restricts

"ExternalServiceLevelCode" on page 217

6.56 ExternalServiceLevelCode

Definition: Specifies the nature, or use, of the amount in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalServiceLevel1Code" on page 216

6.57 ExternalTaxAmountType1Code

Definition: Specifies the nature, or use, of the amount in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 176

Restricts

"ExternalTaxAmountTypeCode" on page 217

6.58 ExternalTaxAmountTypeCode

Definition: Specifies the nature, or use, of the amount in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

["ExternalTaxAmountType1Code" on page 217](#)

6.59 Frequency6Code

Definition: Specifies the regularity of an event.

Type: CodeSet

Code	Name	Definition
ADHO	Adhoc	Event takes place on request or as necessary.
DAIL	Daily	Event takes place every day.
FRTN	Fortnightly	Event takes place every two weeks.
INDA	IntraDay	Event takes place several times a day.
MIAN	SemiAnnual	Event takes place every six months or two times a year.
MNTH	Monthly	Event takes place every month or once a month.
QURT	Quarterly	Event takes place every three months or four times a year.
WEEK	Weekly	Event takes place once a week.
YEAR	Annual	Event takes place every year or once a year.

Used in element(s)

["Type" on page 82](#), ["Type" on page 84](#), ["Type" on page 84](#)

Restricts

["FrequencyCode" on page 218](#)

6.60 FrequencyCode

Definition: Specifies the regularity of an event.

Type: CodeSet

Code	Name	Definition
ADHO	Adhoc	Event takes place on request or as necessary.

Code	Name	Definition
BIMN	Bimonthly	Event takes place every two months or six times a year.
CRED	OnCreditEvent	Event occurs due to a credit event occurring for an issuer.
DAIL	Daily	Event takes place every day.
EXPI	OnExpiry	Event occurs on expiry of a financial contract.
FRTN	Fortnightly	Event takes place every two weeks.
HOUL	Hourly	Event takes place every hours.
INDA	IntraDay	Event takes place several times a day.
MIAN	SemiAnnual	Event takes place every six months or two times a year.
MNTH	Monthly	Event takes place every month or once a month.
MOVE	TriggeredByMovement	Event takes place at the end of the day if there was a movement on the account, otherwise nothing is sent that day.
NEVR	Never	Event does never take place.
ODMD	OnDemand	Event takes place on demand.
OVNG	Overnight	Event takes place overnight.
QURT	Quarterly	Event takes place every three months or four times a year.
RATE	Rate	Event takes place based on a change of a rate.
SHFT	Shift	Event associated with a shift.
TEND	TenDays	Event takes place every ten business days.
TRIL	TriAnnual	Event takes place every four months or three times a year.
TWWK	TwiceAWeek	Two times a week
UPFR	Upfront	Event that takes place at the initiation of a trade or agreement.
WEEK	Weekly	Event takes place once a week.
YEAR	Annual	Event takes place every year or once a year.

Is restricted by

"Frequency6Code" on page 218

6.61 IBAN2007Identifier

Definition: The International Bank Account Number is a code used internationally by financial institutions to uniquely identify the account of a customer at a financial institution as described in the 2007

edition of the ISO 13616 standard "Banking and related financial services - International Bank Account Number (IBAN)" and replaced by the more recent edition of the standard.

Type: IdentifierSet

Format

pattern [A-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}

Rules**R17 IBAN ✓**

A valid IBAN consists of all three of the following components: Country Code, check digits and BBAN.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00003
- *Error Text:* Invalid IBAN format or invalid check digits.

Used in element(s)

["IBAN" on page 19](#)

6.62 ISODate

Definition: A particular point in the progression of time in a calendar year expressed in the YYYY-MM-DD format. This representation is defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Type: Date

Used in element(s)

["BirthDate" on page 52](#)

6.63 ISODatetime

Definition: A particular point in the progression of time defined by a mandatory date and a mandatory time component, expressed in either UTC time format (YYYY-MM-DDThh:mm:ss.sssZ), local time with UTC offset format (YYYY-MM-DDThh:mm:ss.sss+/-hh:mm), or local time format (YYYY-MM-DDThh:mm:ss.sss). These representations are defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Note on the time format:

1) beginning / end of calendar day

00:00:00 = the beginning of a calendar day

24:00:00 = the end of a calendar day

2) fractions of second in time format

Decimal fractions of seconds may be included. In this case, the involved parties shall agree on the maximum number of digits that are allowed.

Type: DateTime

6.64 LEIIdentifier

Definition: Legal Entity Identifier is a code allocated to a party as described in ISO 17442 "Financial Services - Legal Entity Identifier (LEI)".

Type: IdentifierSet

Format

pattern	[A-Z0-9]{18,18}[0-9]{2,2}
---------	---------------------------

Used in element(s)

"LEI" on page 80, "LEI" on page 32, "LEI" on page 76, "LEI" on page 109

6.65 Max1025Text

Definition: Specifies a character string with a maximum length of 1025 characters.

Type: Text

Format

maxLength	1025
minLength	1

Used in element(s)

"ElectronicSignature" on page 104

6.66 Max10Text

Definition: Specifies a character string with a maximum length of 10 characters.

Type: Text

Format

maxLength	10
minLength	1

Used in element(s)

"Code" on page 168

6.67 Max128Text

Definition: Specifies a character string with a maximum length of 128 characters.

Type: Text

Format

maxLength	128
minLength	1

Used in element(s)

"Identification" on page 112, "Proprietary" on page 26

6.68 Max140Text

Definition: Specifies a character string with a maximum length of 140 characters.

Type: Text

Format

maxLength	140
minLength	1

Used in element(s)

"AdditionalInformation" on page 190, "AdditionalInformation" on page 69, "AdditionalRemittanceInformation" on page 173, "InstructionForCreditorAgent" on page 64, "Name" on page 80, "Name" on page 120, "Name" on page 32, "Name" on page 47, "Name" on page 76, "Name" on page 107, "Name" on page 117, "Name" on page 157, "Name" on page 177, "ReferenceNumber" on page 182, "ReferenceNumber" on page 179, "ReferenceNumber" on page 87, "Unstructured" on page 163

6.69 Max15NumericText

Definition: Specifies a numeric string with a maximum length of 15 digits.

Type: Text

Format

pattern	[0-9]{1,15}
---------	-------------

Used in element(s)

"NumberOfTransactions" on page 99, "NumberOfTransactions" on page 128

6.70 Max16Text

Definition: Specifies a character string with a maximum length of 16 characters.

Type: Text

Format

maxLength	16
minLength	1

Used in element(s)

"BuildingNumber" on page 144, "PostBox" on page 145, "PostCode" on page 145

6.71 Max2048Text

Definition: Specifies a character string with a maximum length of 2048 characters.

Type: Text

Format

maxLength	2048
minLength	1

Used in element(s)

"Description" on page 71, "ElectronicAddress" on page 166, "EmailAddress" on page 47, "Identification" on page 101, "Identification" on page 152

6.72 Max34Text

Definition: Specifies a character string with a maximum length of 34 characters.

Type: Text

Format

maxLength	34
minLength	1

Used in element(s)

"Identification" on page 90

6.73 Max350Text

Definition: Specifies a character string with a maximum length of 350 characters.

Type: Text

Format

maxLength	350
minLength	1

Used in element(s)

"PlaceAndName" on page 174, "Registry" on page 101

6.74 Max35Text

Definition: Specifies a character string with a maximum length of 35 characters.

Type: Text

Format

maxLength	35
minLength	1

Used in element(s)

["AdministrationZone" on page 182](#), ["AdministrationZone" on page 179](#), ["BuildingName" on page 145](#), ["Category" on page 188](#), ["CategoryDetails" on page 188](#), ["CertificateIdentification" on page 188](#), ["CityOfBirth" on page 54](#), ["CityOfBirth" on page 52](#), ["CountrySubDivision" on page 147](#), ["DebtorStatus" on page 188](#), ["DistrictName" on page 147](#), ["EmailPurpose" on page 47](#), ["FormsCode" on page 189](#), ["Identification" on page 31](#), ["Identification" on page 91](#), ["Identification" on page 93](#), ["Identification" on page 95](#), ["Information" on page 168](#), ["InstructionIdentification" on page 124](#), ["Issuer" on page 51](#), ["Issuer" on page 72](#), ["Issuer" on page 89](#), ["Issuer" on page 90](#), ["Issuer" on page 92](#), ["Issuer" on page 92](#), ["Issuer" on page 95](#), ["Issuer" on page 97](#), ["Issuer" on page 157](#), ["JobTitle" on page 48](#), ["MandatIdentification" on page 103](#), ["MemberIdentification" on page 44](#), ["MessageIdentification" on page 98](#), ["Method" on page 182](#), ["Method" on page 179](#), ["Number" on page 154](#), ["Number" on page 70](#), ["OriginalMandatIdentification" on page 22](#), ["PaymentInformationIdentification" on page 128](#), ["PreNotificationIdentification" on page 57](#), ["Proprietary" on page 20](#), ["Proprietary" on page 41](#), ["Proprietary" on page 42](#), ["Proprietary" on page 42](#), ["Proprietary" on page 50](#), ["Proprietary" on page 68](#), ["Proprietary" on page 73](#), ["Proprietary" on page 74](#), ["Proprietary" on page 89](#), ["Proprietary" on page 102](#), ["Proprietary" on page 111](#), ["Proprietary" on page 141](#), ["Proprietary" on page 153](#), ["Proprietary" on page 154](#), ["Proprietary" on page 156](#), ["Proprietary" on page 167](#), ["Proprietary" on page 176](#), ["ProvinceOfBirth" on page 54](#), ["ProvinceOfBirth" on page 52](#), ["Reference" on page 49](#), ["RegistrationIdentification" on page 184](#), ["RegistrationIdentification" on page 185](#), ["RemittanceIdentification" on page 165](#), ["Responsibility" on page 48](#), ["SchemeName" on page 93](#), ["TaxIdentification" on page 184](#), ["TaxIdentification" on page 185](#), ["TaxType" on page 185](#), ["TaxType" on page 185](#), ["Title" on page 177](#), ["TownLocationName" on page 147](#), ["TownName" on page 145](#), ["Type" on page 167](#), ["Type" on page 188](#)

6.75 Max4Text

Definition: Specifies a character string with a maximum length of 4 characters.

Type: Text

Format

maxLength	4
minLength	1

Used in element(s)

["ChannelType" on page 112](#), ["Reason" on page 69](#)

6.76 Max70Text

Definition: Specifies a character string with a maximum length of 70characters.

Type: Text

Format

maxLength	70
minLength	1

Used in element(s)

"AddressLine" on page 149, "Department" on page 48, "Department" on page 144, "Floor" on page 145, "Name" on page 40, "Proprietary" on page 106, "Room" on page 145, "StreetName" on page 144, "Sub-Department" on page 144

6.77 NamePrefix2Code

Definition: Specifies the terms used to formally address a person.

Type: CodeSet

Code	Name	Definition
DOCT	Doctor	Title of the person is Doctor or Dr.
MADM	Madam	Title of the person is Madam.
MIKS	GenderNeutral	Title of the person is gender neutral (Mx).
MISS	Miss	Title of the person is Miss.
MIST	Mister	Title of the person is Mister or Mr.

Used in element(s)

"NamePrefix" on page 47

Restricts

"NamePrefixCode" on page 225

6.78 NamePrefixCode

Definition: Specifies the terms used to formally address a person.

Type: CodeSet

Code	Name	Definition
DOCT	Doctor	Title of the person is Doctor or Dr.
MADM	Madam	Title of the person is Madam.
MIKS	GenderNeutral	Title of the person is gender neutral (Mx).
MISS	Miss	Title of the person is Miss.
MIST	Mister	Title of the person is Mister or Mr.

Is restricted by

"NamePrefix2Code" on page 225

6.79 Number

Definition: Number of objects represented as an integer.

Type: Quantity

Format

fractionDigits	0
totalDigits	18

Used in element(s)

"SequenceNumber" on page 183, "SequenceNumber" on page 180

6.80 ParentCurrencyCode

Definition: Code allocated to a currency, by a maintenance agency, under an international identification scheme as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds". Valid currency codes are registered with the ISO 4217 Maintenance Agency, and consist of three contiguous letters.

Type: CodeSet

Format

pattern	[A-Z]{3,3}
---------	------------

Is restricted by

"ActiveOrHistoricCurrencyCode" on page 192

6.81 PaymentMethod2Code

Definition: Specifies the transfer method that will be used to transfer the cash.

Type: CodeSet

Code	Name	Definition
DD	DirectDebit	Collection of an amount of money from the debtor's bank account by the creditor. The amount of money and dates of collections may vary.

Used in element(s)

"PaymentMethod" on page 128

Restricts

"PaymentMethodCode" on page 226

6.82 PaymentMethodCode

Definition: Specifies the transfer method that will be used to transfer the cash.

Type: CodeSet

Code	Name	Definition
CHK	Cheque	Written order to a bank to pay a certain amount of money from one person to another person.
CLAS	Classical	Classical method.
DD	DirectDebit	Collection of an amount of money from the debtor's bank account by the creditor. The amount of money and dates of collections may vary.
DIRE	Direct	Direct method.
TRA	TransferAdvice	Transfer of an amount of money in the books of the account servicer. An advice should be sent back to the account owner.
TRF	CreditTransfer	Transfer of an amount of money in the books of the account servicer.

Is restricted by

["PaymentMethod2Code" on page 226](#)

6.83 PercentageRate

Definition: Rate expressed as a percentage, that is, in hundredths, for example, 0.7 is 7/10 of a percent, and 7.0 is 7%.

Type: Rate

Format

fractionDigits	10
totalDigits	11

Used in element(s)

["Rate" on page 174](#)

6.84 PhoneNumber

Definition: The collection of information which identifies a specific phone or FAX number as defined by telecom services.

It consists of a "+" followed by the country code (from 1 to 3 characters) then a "-" and finally, any combination of numbers, "(", ")", "+", and "-" (up to 30 characters).

Type: Text

Format

pattern	\+[0-9]{1,3}-[0-9()+\-]{1,30}
---------	-------------------------------

Used in element(s)

["FaxNumber" on page 47](#), ["MobileNumber" on page 47](#), ["PhoneNumber" on page 47](#)

6.85 PreferredContactMethod1Code

Definition: Preferred method used to reach the individual contact within an organisation.

Type: CodeSet

Code	Name	Definition
CELL	MobileOrCellPhone	Preferred method used to reach the contact is per mobile or cell phone.
FAXX	Fax	Preferred method used to reach the contact is per fax.
LETT	Letter	Preferred method used to reach the contact is per letter.
MAIL	Email	Preferred method used to reach the contact is per email.
PHON	Phone	Preferred method used to reach the contact is per phone.

Used in element(s)

["PreferredMethod" on page 48](#)

Restricts

["PreferredContactMethodCode" on page 228](#)

6.86 PreferredContactMethodCode

Definition: Preferred method used to reach the individual contact within an organisation.

Type: CodeSet

Code	Name	Definition
CELL	MobileOrCellPhone	Preferred method used to reach the contact is per mobile or cell phone.
FAXX	Fax	Preferred method used to reach the contact is per fax.
LETT	Letter	Preferred method used to reach the contact is per letter.
MAIL	Email	Preferred method used to reach the contact is per email.
ONLI	Online	Preferred method used to reach the contact is online.
PHON	Phone	Preferred method used to reach the contact is per phone.

Is restricted by

["PreferredContactMethod1Code" on page 228](#)

6.87 Priority2Code

Definition: Specifies the priority level of an event.

Type: CodeSet

Code	Name	Definition
HIGH	High	Priority level is high.
NORM	Normal	Priority level is normal.

Used in element(s)

"InstructionPriority" on page 135, "Priority" on page 37

Restricts

"PriorityCode" on page 229

6.88 PriorityCode

Definition: Specifies the priority level of an event.

Type: CodeSet

Code	Name	Definition
HIGH	High	Priority level is high.
LOWW	Low	Priority level is low.
NORM	Normal	Priority level is normal.
URGT	Urgent	Priority level is urgent (highest priority possible).

Is restricted by

"Priority2Code" on page 229

6.89 RegulatoryReportingType1Code

Definition: Identifies whether the regulatory reporting information applies to the debit side, to the credit side or to both debit and credit sides of the transaction.

Type: CodeSet

Code	Name	Definition
BOTH	Both	Regulatory information applies to both credit and debit sides.
CRED	Credit	Regulatory information applies to the credit side.
DEBT	Debit	Regulatory information applies to the debit side.

Used in element(s)

["DebitCreditReportingIndicator" on page 158](#)

Restricts

["RegulatoryReportingTypeCode" on page 230](#)

6.90 RegulatoryReportingTypeCode

Definition: Identifies whether the regulatory reporting information applies to the debit side, to the credit side or to both debit and credit sides of the transaction.

Type: CodeSet

Code	Name	Definition
BOTH	Both	Regulatory information applies to both credit and debit sides.
CRED	Credit	Regulatory information applies to the credit side.
DEBT	Debit	Regulatory information applies to the debit side.

Is restricted by

["RegulatoryReportingType1Code" on page 229](#)

6.91 RemittanceLocationMethod2Code

Definition: Specifies the method used to deliver the remittance advice information.

Type: CodeSet

Code	Name	Definition
EDIC	ElectronicDataInterchange	Remittance advice information must be sent through Electronic Data Interchange (EDI).
EMAL	EMail	Remittance advice information must be sent through e-mail.
FAXI	Fax	Remittance advice information must be faxed.
POST	Post	Remittance advice information must be sent through postal services.
SMSM	SMS	Remittance advice information must be sent through by phone as a short message service (SMS).

Code	Name	Definition
URID	UniformResourceIdentifier	Remittance advice information needs to be sent to a Uniform Resource Identifier (URI). URI is a compact string of characters that uniquely identify an abstract or physical resource. URI's are the super-set of identifiers, such as URLs, email addresses, ftp sites, etc, and as such, provide the syntax for all of the identification schemes.

Used in element(s)

["Method" on page 166](#)

Restricts

["RemittanceLocationMethodCode" on page 231](#)

6.92 RemittanceLocationMethodCode

Definition: Specifies the method used to deliver the remittance advice information.

Type: CodeSet

Code	Name	Definition
EDIC	ElectronicDataInterchange	Remittance advice information must be sent through Electronic Data Interchange (EDI).
EMAL	EMail	Remittance advice information must be sent through e-mail.
FAXI	Fax	Remittance advice information must be faxed.
POST	Post	Remittance advice information must be sent through postal services.
SMSM	SMS	Remittance advice information must be sent through by phone as a short message service (SMS).
URID	UniformResourceIdentifier	Remittance advice information needs to be sent to a Uniform Resource Identifier (URI). URI is a compact string of characters that uniquely identify an abstract or physical resource. URI's are the super-set of identifiers, such as URLs, email addresses, ftp sites, etc, and as such, provide the syntax for all of the identification schemes.

Is restricted by

["RemittanceLocationMethod2Code" on page 230](#)

6.93 SequenceType3Code

Definition: Specifies the type of the current transaction that belongs to a sequence of transactions.

Type: CodeSet

Code	Name	Definition
FNAL	Final	Final collection of a series of direct debit instructions.
FRST	First	First collection of a series of direct debit instructions.
OOFF	OneOff	Direct debit instruction where the debtor's authorisation is used to initiate one single direct debit transaction.
RCUR	Recurring	Direct debit instruction where the debtor's authorisation is used for regular direct debit transactions initiated by the creditor.
RPRE	Represented	Collection used to re-present previously reversed or returned direct debit transactions.

Used in element(s)

"SequenceType" on page 136

Restricts

"SequenceTypeCode" on page 232

6.94 SequenceTypeCode

Definition: Specifies the type of the current transaction that belongs to a sequence of transactions.

Type: CodeSet

Code	Name	Definition
FNAL	Final	Final collection of a series of direct debit instructions.
FRST	First	First collection of a series of direct debit instructions.
OOFF	OneOff	Direct debit instruction where the debtor's authorisation is used to initiate one single direct debit transaction.
RCUR	Recurring	Direct debit instruction where the debtor's authorisation is used for regular direct debit transactions initiated by the creditor.
RPRE	Represented	Collection used to re-present previously reversed or returned direct debit transactions.

Is restricted by

"SequenceType3Code" on page 231

6.95 TaxRecordPeriod1Code

Definition: Specifies the period related to the tax payment.

Type: CodeSet

Code	Name	Definition
HLF1	FirstHalf	Tax is related to the first half of the period.
HLF2	SecondHalf	Tax is related to the second half of the period.
MM01	FirstMonth	Tax is related to the second month of the period.
MM02	SecondMonth	Tax is related to the first month of the period.
MM03	ThirdMonth	Tax is related to the third month of the period.
MM04	FourthMonth	Tax is related to the fourth month of the period.
MM05	FifthMonth	Tax is related to the fifth month of the period.
MM06	SixthMonth	Tax is related to the sixth month of the period.
MM07	SeventhMonth	Tax is related to the seventh month of the period.
MM08	EighthMonth	Tax is related to the eighth month of the period.
MM09	NinthMonth	Tax is related to the ninth month of the period.
MM10	TenthMonth	Tax is related to the tenth month of the period.
MM11	EleventhMonth	Tax is related to the eleventh month of the period.
MM12	TwelfthMonth	Tax is related to the twelfth month of the period.
QTR1	FirstQuarter	Tax is related to the first quarter of the period.
QTR2	SecondQuarter	Tax is related to the second quarter of the period.
QTR3	ThirdQuarter	Tax is related to the third quarter of the period.
QTR4	FourthQuarter	Tax is related to the forth quarter of the period.

Used in element(s)

"Type" on page 187

Restricts

"TaxRecordPeriodCode" on page 234

6.96 TaxRecordPeriodCode

Definition: Specifies the period related to the tax payment.

Type: CodeSet

Code	Name	Definition
HLF1	FirstHalf	Tax is related to the first half of the period.
HLF2	SecondHalf	Tax is related to the second half of the period.
MM01	FirstMonth	Tax is related to the second month of the period.
MM02	SecondMonth	Tax is related to the first month of the period.
MM03	ThirdMonth	Tax is related to the third month of the period.
MM04	FourthMonth	Tax is related to the fourth month of the period.
MM05	FifthMonth	Tax is related to the fifth month of the period.
MM06	SixthMonth	Tax is related to the sixth month of the period.
MM07	SeventhMonth	Tax is related to the seventh month of the period.
MM08	EighthMonth	Tax is related to the eighth month of the period.
MM09	NinthMonth	Tax is related to the ninth month of the period.
MM10	TenthMonth	Tax is related to the tenth month of the period.
MM11	EleventhMonth	Tax is related to the eleventh month of the period.
MM12	TwelfthMonth	Tax is related to the twelfth month of the period.
QTR1	FirstQuarter	Tax is related to the first quarter of the period.
QTR2	SecondQuarter	Tax is related to the second quarter of the period.
QTR3	ThirdQuarter	Tax is related to the third quarter of the period.
QTR4	FourthQuarter	Tax is related to the forth quarter of the period.

Is restricted by

"TaxRecordPeriod1Code" on page 232

6.97 TrueFalseIndicator

Definition: A flag indicating a True or False value.

Type: Indicator

Meaning When True: True

Meaning When False: False

Used in element(s)

"AmendmentIndicator" on page 103, "EmployeeTerminationIndicator" on page 88, "FamilyMedicalInsuranceIndicator" on page 88

6.98 UUIDv4Identifier

Definition: Universally Unique Identifier (UUID) version 4, as described in IETF RFC 4122 "Universally Unique Identifier (UUID) URN Namespace".

Type: IdentifierSet

Format

pattern [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}

Used in element(s)

"UETR" on page 125

6.99 UnicodeChartsCode

Definition: codelist containing the names of the UNICODE code block name as specified on <http://unicode.org/Public/UNIDATA/Blocks.txt>.

Type: CodeSet

Rules

R2 ValidationByTable

Error handling: Undefined

Used in element(s)

"CharacterSet" on page 34

6.100 YesNoIndicator

Definition: Indicates a "Yes" or "No" type of answer for an element.

Type: Indicator

Meaning When True: Yes

Meaning When False: No

Used in element(s)

"PossibleDuplicate" on page 37

Legal Notices

Copyright

S.W.I.F.T. SC © 2026. All rights reserved.

This material is a component of MyStandards, the Swift collaborative Web application used to manage standards definitions and industry usage. It can only be used and distributed in accordance with MyStandards Terms of Use.

Unless otherwise agreed in writing with S.W.I.F.T. SC, you have no right to:

- authorise external end users to use this component for other purposes than their internal use.
- remove, alter, cover, obfuscate or cancel from view any copyright or other proprietary rights notices appearing in this physical medium.
- re-sell or authorise another party e.g. software and service providers, to re-sell this component.

Confidentiality

This publication may contain Swift or third-party confidential information. Only disclose it outside your organisation in accordance with MyStandards Terms of Use and your related license rights.

This component is provided 'AS IS'. Swift does not give and excludes any express or implied warranties with respect to this component such as but not limited to any guarantee as to its quality, supply or availability.

Any and all rights, including title, ownership rights, copyright, trademark, patents, and any other intellectual property rights of whatever nature in this component will remain the exclusive property of Swift or its licensors.

Trademarks and Patents

Swift is the trade name of S.W.I.F.T. SC. The following are registered trademarks of Swift: 3SKey, Innotribe, MyStandards, Sibos, Swift, SwiftNet, the Standards Forum logo, the Swift logo, Swift GPI with logo, the Swift GPI logo, and UETR. Other product, service, or company names in this publication are trade names, trademarks, or registered trademarks of their respective owners.