Titleoftheproject :-

Application specific access policies

Overview :-

-(AtLeast 1 page) what is your idea regarding project

List of teammates–

S.no	name	collage	contact
1	**DHANALASHMI. T**	PPG COLLEGE OF ARTS AND SCIENCE	2322k0296.cas@ppg.edu.in
2	JEEVANANTHAM. K	PPG COLLEGE OF ARTS AND SCIENCE	2322k0305.cas@ppg.edu.in
3	ESWARAN. A	PPG COLLEGE OF ARTS AND SCIENCE	2322k0299.cas@ppg.edu.in
4	KEERTISH. K. R	PPG COLLEGE OF ARTS AND SCIENCE	2322k0311.cas@ppg.edu.in
5	GOWTHAM. M	PPG COLLEGE OF ARTS AND SCIENCE	2322k0302.cas@ppg.edu.in

List of Vulnerability Table

S.no	Vulnerability Name	CWE/CVE - No
1	Absolute Path Traversal	CWE 36
2	Sensitive Cookie in HTTPS Session Without 'Secure' Attribute	CWE 614
3	Use of Unmaintained Third Party Components	CWE 1104

REPORT:-

Vulnerability Name:-Absolute Path Traversal

CWE/CVE : -CWE 36

OWASP/SANS Category:-A01:2025 Broken Access Control

Description:-

The Zero Trust security model is a modern cybersecurity framework based on the principle “Never Trust, Always Verify.” It ensures that every user, device, and application must be authenticated and authorized before accessing system resources. The main objective of this project is to implement and manage a Zero Trust architecture to protect systems from unauthorized access and potential cyber threats. This approach helps in identifying and managing security vulnerabilities within the network and applications. By applying Zero Trust principles, the project enhances the overall security, confidentiality, and integrity of organizational data.

Business Impact::-



Common Weakness Enumeration

A community-developed list of SW & HW weaknesses that can become vulnerabilities

New to CWE? Start here!

Home > CWE List > CWE-36: Absolute Path Traversal (4.19.1)

Home | About | Learn | Access Content | Community | Search

CWE-36: Absolute Path Traversal

Weakness ID: 36
Vulnerability Mapping: ALLOWED
Abstraction: Base

View customized information: Conceptual | Operational | Mapping Friendly | Complete | Custom

Description

The product uses external input to construct a pathname that should be within a restricted directory, but it does not properly neutralize absolute path sequences such as "/abs/path" that can resolve to a location that is outside of that directory.

Extended Description

This allows attackers to traverse the file system to access files or directories that are outside of the restricted directory.

Common Consequences

Impact	Details
Execute Unauthorized Code or Commands	**Scope: Integrity, Confidentiality, Availability** The attacker may be able to create or overwrite critical files that are used to execute code, such as programs or libraries.
	Scope: Integrity The attacker may be able to overwrite or create critical files, such as programs, libraries, or important data. If the targeted file is