1. SCOPE

Scope means where a variable can be accessed in your code

types

1: Global Scope

A variable declared outside any function can be used anywhere

2. Function Scope

Variable declared inside a function are only accessible inside that function

3. Block Scope

Variables declared with let and const are limited to the block

2. Initialization

Assigning a value to a variable when it is declared

3. Declaration

Creating a variable so it can be used later in the program

4. Re-declare

Declaring same variable again with same name in same scope

5. Re-assign

Changing the value of variable after it has already initialized

6. Hoisting

Moving declarations to the top of their scope before code runs

Scanned with OKEN Scanner

PascalCase

```
let ProductName = "Laptop"
let OrderId = "1234"
let CustomerName = "Joeva"
let DeliveryStatus = "Succeed"
let PaymentMode = "UPI"
let TotalAmount = 100000
let DiscountValue = 5000
let ShippingAddress = Chennai
let OrderDate = "24-03-2026"
let IsPaymentCompleted = true
```

Snake Case:

```
const user_name = "Jeevarunth"
const user_age = 28
const phone_number = "7397598890"
const email_address = "jeevananthsakthi@gmail.com
const account_balance = 10000000;
const product_name = "car";
const product_price = 1000000
const discount_price = 200000
const total_amount = 800000
const payment_status = "Succeed"
const order_Id = 1234
const order_date = "24-03-2026"
const delivery_status = "Shipped"
const shipping_address = "chennai"
const vehicle_type = "SUV"
const service_type = "wash"
const estimated_time = "30 minutes"
const service_cost = 2000;
```

Scanned with OKEN Scanner

```
var firstName = "Jeevaranth"
var lastName = "S"
var userAge = "28"
val phoneNumber = "7397598890"
val emailId = "jeevaranthsakthi@gmail.com
val isLoggedIn = true
val accountBalance = 50000000
val cityName = "Chennai"
val courseName = "Fullstack"
val isActiveUser = true
```

Scanned with OKEN Scanner