Status	Finished
Started	Tuesday, 20 October 2026, 8:24 AM
Completed	Tuesday, 20 October 2026, 8:29 AM
Duration	5 mins
Grade	**13.00** out of 15.00 (**86.67**%)

Question **1**

Correct

Mark 1.00 out of 1.00

What is the output of the following code?

```
aTuple = (10, 20, 30, 40, 50, 60, 70, 80)
print(aTuple[2:5], aTuple[:4], aTuple[3:])
```

a. (30, 40, 50)(40, 50, 60, 70, 80)

b. (30, 40, 50) (10, 20, 30, 40)

c. (30, 40, 50) (10, 20, 30, 40) (40, 50, 60, 70, 80) ✓

d. (10, 20, 30, 40) (40, 50, 60, 70, 80)

Question **2**

Correct

Mark 1.00 out of 1.00

A python tuple can be created without using any parentheses. (True/False)

a. True ✓

b. False

Question **3**

Correct

Mark 1.00 out of 1.00

Write the Output of the following Code?

t = (15,83,83,52,60,45,52,85,100)

print(min(t)+max(t)+t.count(52))

a. 100

b. Error

c. 117 ✓

d. 2

Question **4**

Correct

Mark 1.00 out of 1.00

What is the output of the given below program?

t = (58, 47, 36, 25, 14, 3)

x = t[2:-1]

print(x)

a. Error

b. (3,14,25)

c. (36, 25, 14) ✓

d. (58,47,36,25)

Question **5**

Correct

Mark 1.00 out of 1.00

What will be the output of following Python code?

```
set1={0,0,9}

print(set1)
```

a. {0,0,9}

b. {0,9} ✓

c. {9}

d. It will throw an error as there are two 0 while creating the set.

Question **6**

Correct

Mark 1.00 out of 1.00

What is the output of the following set operation

```
sampleSet = {"Yellow", "Orange", "Black"}
sampleSet.update(["Blue", "Green", "Red"])
print(sampleSet)
```

a. {'Yellow', 'Orange', 'Red', 'Black', 'Green', 'Blue'} ✓

b. Name Error

c. {'Yellow', 'Orange', 'Black', ["Blue", "Green", "Red"]}

d. TypeError: update() doesn't allow list as a argument.

Question **7**

Correct

Mark 1.00 out of 1.00

What will be printed when the following code executes?

```
a = ("Python Programming")
```

```
print type(a)
```

```

```

a. <class 'tuple'>

b. <class 'str'> ✓

c. str

d. <class 'int'>

Question **8**

Correct

Mark 1.00 out of 1.00

What is printed when the following code is run?

```
tup = ('30', '3', '2', '8')
print(sorted(tup,reverse = True))
```

a. ['2', '3', '8', '30']

b. ['8', '30', '3', '2'] ✓

c. ['30', '8', '3', '2']

d. ['2', '3', '30', '8']

Question **9**

Correct

Mark 1.00 out of 1.00

What is the output of the following union operation

```
set1 = {10, 20, 30, 40}
set2 = {50, 20, "10", 60}

set3 = set1.union(set2)
print(set3)
```

a. {40, 10, 50, 20, 60, 30}

b. {40, 10, '10', 50, 20, 60, 30} ✓

c. SynatxError: Different types cannot be used with sets

d. {40, '10', 50, 20, 60, 30}

Question **10**

Correct

Mark 1.00 out of 1.00

Find the output of the given Python program?

t = (11, 3)

x = 3 * t

print(x)

a. (11,3)(11,3)(11,3)

b. (11,3,11,11,3,11,11,11,3)

c. [11,11,11,3,3,3]

d. (11, 3, 11, 3, 11, 3) ✓

Question **11**

Correct

Mark 1.00 out of 1.00

What is the output of the given below program?

```
t1 = (1,2,3)
t2 = (4,5,6)
x = t1+t2
print(x)
```

a. (1,2,3,4,5,6) ✓

b. (1,2,3,3,2,1)

c. (1,2,3)(4,5,6)

d. Error

Question **12**

Correct

Mark 1.00 out of 1.00

What will be the output of following Python code?

```
set1={2,5,3}

set2={3,1}

set3={}

set3=set1&set2

print(set3)
```

a. {2,5,1}

b. {2,5,3,1}

c. {}

d. {3} ✓

Question **13**

Incorrect

Mark 0.00 out of 1.00

What will the below Python code do?

```
set1={2,3}

set2={3,2}

set3={2,1}

if(set1==set2):

    print("yes")

else:

    print("no")

if(set1==set3):

    print("yes")

else:

    print("no")
```

a. "==" is not supported for set in Python

b. Yes, No

c. Yes, Yes ✗

d. No, No

Question **14**

Correct

Mark 1.00 out of 1.00

Which of the following Python code will create a set?

(i) set1=set((0,9,0))
(ii) set1=set([0,2,9])
(iii) set1={}

a. iii

b. ii

c. i,ii ✓

d. All of the above

Question **15**

Incorrect

Mark 0.00 out of 1.00

What is the output of the following code

```
aSet = {1, 'rec', ('cse', 'ece'), True}
print(aSet)
```

a. {‘rec’, 1, (‘cse’, ‘ece’)}

b. ✗
{‘rec’, True, (‘cse’, ‘ece’)}

c. Error

d. {‘rec’, 1, (‘cse’, ‘ece’),True}