```
Div_A=data.frame(PRN=c(120, 125, 126), Name=c("Ramesh", "Radha", "Aasha"), SGPA=c(6.7, 7.8, 8))
Div_B=data.frame(PRN=c(127, 128, 129), Name=c("Aaroh", "Rima", "mala"), SGPA=c(7, 7.5, 6))
Result=rbind(Div_A, Div_B)
Div_A_Course=data.frame(LAUC=c(23, 22, 12), Phy=c(12, 17, 20))
Div_A_Result=cbind(Div_A, Div_A_Course)
FA=data.frame(PRN=c(123, 124, 125, 126, 127),
               Name=c("Sudha","Prathmesh", "Anita", "Radha", "Mahesh"),FA1_marks=c(12, 23, 21,
22, 10), FA2_marks=c(15, 20, 20, 15, 16))


SA=data.frame(PRN=c(123, 124, 125,  127,128),
              SA_marks=c(16, 14, 10,  15, 18), Result=c("P","P","F","P", "P" ))
# semi_join(x, y, by = "key")   # Keep only rows in x that have a match in y; return columns
from x only


Final_result_S=semi_join(FA, SA, join_by(PRN))
# inner_join(x, y, by = "key")  # Keep only rows that match in both x and y; return columns
from both
Final_result_i=inner_join(FA, SA)
# left_join(x, y, by = "key")   # Keep all rows from x, match with y when possible; return
columns from both
Final_result_l=left_join(FA, SA)
# right_join(x, y, by = "key")  # Keep all rows from y, match with x when possible; return
columns from both
Final_result_r=right_join(FA, SA)
# anti_join(x, y, by = "key")   # Keep only rows in x that have NO match in y; return columns
from x only
Final_result_a=anti_join(FA, SA)
```