

PT No.

DESCRIPTION

NPD(IN)

ITEM CODE

QTY

PIPES

PIPE SMLS 8" A106-B SOUR STD BE B36.10M

PIPE SMLS 4" A106-B SOUR STD BE B36.10M

FITTINGS

ELB 90° SMLS LR 4" A234-WPB SOUR STD BE B16.9

TEE EQ. SMLS 8" A234-WPB SOUR STD BE B16.9

TEE RED. SMLS 8" X 4" A234-WPB SOUR STD BE B16.9

RED. ECC. SMLS 8" X 4" A234-WPB SOUR STD BE B16.9

FLANGES

FLG WNRF 8" A105N SOUR STD, 150# 125 B16.5

FLG WNRF 4" A105N SOUR STD, 600# 125 B16.5

GASKET

GSK SPR WND W/CS CENTERING RING + I - SS 8" 4.50 MM THICK SS316L+GRPH FILL SOUR 150# B16.20

GSK SPR WND W/CS CENTERING RING + I - SS 4" 4.50 MM THICK SS316L+GRPH FILL SOUR 600# B16.20

FASTSNERS

BOLT, STUD+2 NUTS A193 GR B7M/ A194 GR 2HM, CERAMIC FLP COAT SOUR B18.2.1/18.2.2 - 120 mm Length

BOLT, STUD+2 NUTS A193 GR B7M/ A194 GR 2HM, CERAMIC FLP COAT SOUR B18.2.1/18.2.2 - 160 mm Length

8

4

4

8X8

8X4

8X4

8

4

8

4

0.75

0.875

PPS2AERT08ZZABUAIA

PPS2AERT04ZZABUAIA

PE92AZRT04ZZABUAIQ

PTF2AZRT08ZZABUAIQ

PTS2AZRT0804ABUAIQ

PRH2AZRT0804ABUAIQ

PFY2ADRT08ZZACPADH

PFY2ADRT04ZZAEMADH

PGUUB5RT08AIAAAZZC

PGUUB5RT04AIAADZZC

PH8ASCRTAG00120ZZF

PH8ASCRTAH00160ZZF

2.704

0.947

6

1

2

2

1

2

1

2

8

16

DETAILS OF HEAVY WELDING BOSSSES FOR THREADED CONNECTIONS

CONSTRUCTION DETAILS FOR ISOMETRIC PIPING

INSULATION DETAILS FOR HOT PIPING

INSULATION DETAILS FOR COLD PIPING

INSTALLATION OF JACK SCREWS FOR FLANGED JOINTS

AE-036175

AE-036077

AA-036011

AA-036013

AC-036030

NOTES

1. MATERIAL SHOWN WITH A BROKEN LINE AND SPOOLS LISTED IN THE SAUDI ARAMCO FABRICATOR LIST ARE NOT TO BE FABRICATED BY THE VENDOR.

2. PIPING DETAILS SHALL BE CUT AT ALL POINTS MARKED F.W. (FIELD WELD).

3. EACH FABRICATED SECTION SHALL BE CLEARLY MARKED WITH ITS CODE NUMBER.

4. UNLESS OTHERWISE NOTED, (A) ALL DIMENSIONS ARE TO E OR FACE OF FLANGES. (B) BOLT HOLES ON FLANGES STRADDLE C. (C) WELDING ELBOWS ARE LONG RADIUS.

5. FABRICATION SHALL BE IN ACCORDANCE WITH SAUDI ARAMCO SPECIFICATION 01-SAMSS-10.

6. GASKET ALLOWANCE

7. PIPING MATERIAL IS

PIPE SIZE

SCHEDULE

SPECIFICATION

5. WELDING STRESS RELIEF - YES ☐ NO ☐

100% X-RAY ☐ SPOT X-RAY 01-SAMSS-10 ☐

9. TESTING SHOP HYDROSTATIC TEST - YES ☐ NO ☐

THE SHOP HYDROSTATIC TEST SHALL BE CARRIED OUT ON PIECES HAVING ALL ENDS FLANGED. HYDROSTATIC TEST PRESSURE

10. ALL PIPING MATERIAL IS IN ACCORDANCE WITH SAUDI ARAMCO ENGINEERING SPECIFICATION SAMSE-105 CLASS ☐ ALL EXCEPTIONS ARE NOTED ON THE ISOMETRIC.

11. INSULATION REQUIRED - YES ☐ NO ☐

INSULATION SHOWN ON DRAWING

SPOOLS TO BE FABRICATED BY VENDOR

NO. MARK NO. SIZE WEIGHT LBS.

NO. MARK NO. SIZE WEIGHT LBS.

SPOOLS TO BE FABRICATED BY SAUDI ARAMCO

NO. MARK NO. SIZE

NO. MARK NO. SIZE

REFERENCE DRAWINGS

PIPING PLAN YA-212287

P&ID NO. YA-212177-001

PLOT PLAN KEY PLAN NO. YA-212083

INDEX FOR PIPING ISO (AG) PP-867-LI-0003

INDEX FOR PIPING ISO (UG) PP-867-LI-0004

00A 02-05-25 ISSUED FOR CONSTRUCTION

AC/NS KY/PS BSP HJ

REVISION STATUS

REVISION VALIDATION

THIS REVISION NO. 00A IS COVERED FOR ALL APPROVAL AND CERTIFICATION REQUIREMENTS. PER SAMP-334, UNDER DRAWING COMPLETION CERTIFICATE NO. 10-14815-0003-000

PIPE CUT LENGTH SUMMARY

SPL No.

NPD

PC No.

LENGTH

ALLOWANCE

TOTAL LENGTH

S11_SP

8

<9>

0.434

0.000

0.434

S11_SP

8

<12>

0.918

0.000

0.918

S11_SP

8

<15>

0.434

0.000

0.434

S11_SP

8

<18>

0.918

0.000

0.918

S14_SP

4

<13>

0.194

0.000

0.194

S14_SP

4

<14>

0.280

0.000

0.280

S18_SP

4

<19>

0.194

0.000

0.194

S18_SP

4

<20>

0.280

0.000

0.280

SXX_Spool Sequence Number (S01.02..)

SXX_SP - Fab. Spool

SXX_PP - Fab. P to P Doubling (+6M+6M)

SXX_PP - Erec. Random Pipe (RM,12M)

SXX_EP - Erec. Part Loose Fittings

SXX_EF - Erec. Flange (F-Loose Flange, F7B-Blend, F7F-Spectacle)

SXX_EV - Erec. valve

SXX_EPG - Erec. Pipe Plug

SXX_SB - Small Bore Spool Fab.

SXX_SBE - Small Bore Spool Erec.

SXX_SBD - Small Bore Spool Drain

SXX_SBV - Small Bore Spool Vent

X PART NUMBER

<X> PIECE NUMBER

(FX) SHOP WELD

(FX) FIELD WELD

SXX_01 SPOOL NUMBER

ISO For

NOTES :

1. ALL COORDINATES AND ELEVATIONS ARE IN 'METER' AND ALL DIMENSIONS ARE IN 'MM'.

2. PIPE QUANTITY IS IN METERS AND OTHER QUANTITY IN NUMBERS.

3. FOR STANDARD SUPPORT, REFER DOC. NO. "PP-866-ST-0001".

4. IN CASE OF ANY DISCREPANCY FOR LINE CONDITIONS, LINE DATA GIVEN IN LINE LIST SHALL GOVERN

5. FOR SMALL BORE LINES, DIMENSION & ROUTING SHALL BE FIELD ADJUSTED.

6. THE SPECIFIED THEORETICAL LOCATION OF EQUIPMENT NOZZLES, SUPPORTING STRUCTURE SHALL BE VERIFIED BEFORE INSTALLING THE PIPING & INTOLERABLE DISCREPANCIES SHALL BE DISCUSSED WITH DESIGN SITE ENGINEER.

7. ALL THREADED CONNECTION SHALL BE SEAL WELDED, EXCEPT DRAIN AND VENT PLUG.

8. REFER LINE LIST.

9. ALL PRESSURE WELDS, OTHER THAN BUTT WELDS, INCLUDING BRANCH CONNECTIONS SUCH AS BRANCH-OLETS AND BOSS) SHALL BE 100% PTMT EXAMINED. ALL ATTACHMENT WELDS ON PRESSURIZED COMPONENTS THAT ARE NOT HYDROTESTED AFTER MAKING THE ATTACHMENT WELD SHALL BE 100% PTMT EXAMINED.

BUTT WELD

FIELD WELD

INSULATED PIPE

TRACED PIPE

PIPE SUPPORT

PLATFORM PENETRATION

SOCKET WELD

SCREWED JOINT

DESIGN CERTIFICATION (DESIGN AGENCY)

REVIEW FOR KEY DRAWINGS (SAUDI ARAMCO)

OTHER

ENGL. DATE

CERTIFIED BY DATE

CONST. AGENCY/DATE

OPERATIONS DATE

BY DATE

REV. NO.

DATE

REVISION DESCRIPTION

JOB ORDER/REV NO. 10-14815-0003

THIS REVISION IS NOT TO BE USED FOR CONSTRUCTION UNLESS CERTIFIED AND DATED

SAUDI ARABIAN OIL COMPANY

ISOM 8" -MDEA-17357-1CH2P06

DRAWING TYPE ISO

MDEA SERVICE

JFGP GAS PROCESSING TRAIN-4

JAFURAH

SAUDI ARABIA

PLANT NO.

INDEX

DRAWING NUMBER

SHT. NO.

REV. NO.

867

L

YB-215304

03of05

00A

SITE REV. NO. 00A

RESTRICTED

SMART

CADD-03

THIS DRAWING AND THE INFORMATION CONTAINED HEREIN ARE THE SOLE PROPERTY OF SAUDI ARAMCO. NO REPRODUCTION IN FULL OR IN PART, SHALL BE OBTAINED FROM THIS DRAWING WITHOUT THE WRITTEN CONSENT OF SAUDI ARAMCO.