



91. FOR SOUR SERVICE PWHT IS MANDATORY FOR 1. DOUBLE SIDED WELDING, 2. INTERNAL WELD REPAIR 3. INTERNAL WELD BUILD UP FOR DISSIMILAR THICKNESS JOINTS TO OVERCOME MISALIGNMENT.

450444 21-02-2026

450444 21-04-2026

PIPE CUT LENGTH SUMMARY						SIX_Spool Sequence Number (001.002)
SPL No.	NPD	PC No.	LENGTH	ALLOWANCE	TOTAL LENGTH	SIX_PP - Fabs. Spool
S06_SP	2	<12>	0.306	0.000	0.306	SIX_PP - Fabs. P to P Doubling (-6M-6M)
S06_SP	2	<11>	0.349	0.000	0.349	SIX_PP - Eric. Random Pipe (SM-12M)
S06_SP	2	<10>	0.263	0.000	0.263	SIX_PP - Eric. Part Loose Fittings
S06_SP	2	<9>	1.280	0.000	1.280	SIX_PP - Eric. Range (EPC-Lower Range, ERS Blind, EFS Spectacles)
						SIX_EV - Eric. valve
						SIX_EPG - Eric. Pipe Plug
						SIX_SBP - Small Bore Spool Fabs.
						SIX_SBS - Small Bore Spool Eric.

NOTES :

1. ALL COORDINATES AND ELEVATIONS ARE IN "METER" AND ALL DIMENSIONS ARE IN "MM".
2. PIPE QUANTITY IS IN METERS AND OTHER QUANTITY IN NUMBERS.
3. FOR STANDARD SUPPORT, REFER DOC. NO. "PP-86S2T-0001".
4. IN CASE OF ANY DISCREPANCY FOR LINE CONDITIONS, LINE DATA GIVEN IN LINE LIST SHALL GOVERN.
5. FOR SMALL BORE LINES, DIMENSION & ROUTING SHALL BE FIELD ADJUSTED.
6. THE SPECIFIED THEORETICAL LOCATION OF EQUIPMENT NOZZLES, SUPPORTING STRUCTURE SHALL BE VERIFIED BEFORE INSTALLING THE PIPING & INTOLERABLE DISCREPANCIES SHALL BE DISCUSSED WITH DESIGN SITE ENGINEER.
7. ~~ALL THREADED CONNECTION SHALL BE SEAL WELDED, EXCEPT DRAIN AND VENT PLUG.~~
8. REFER LINE LIST.
9. ALL PRESSURE WELDS, OTHER THAN BUTT WELDS, INCLUDING BRANCH CONNECTIONS SUCH AS BRANCH-OLETS, AND BOSS) SHALL BE 100% PT/MT EXAMINED. ALL ATTACHMENT WELDS ON DISCREPANCY CONNECTIONS THAT ARE NOT HYDROTESTED AFTER MAKING THE ATTACHMENT WELD SHALL BE 100% PT/MT EXAMINER.