



FASTBUILD

[Contact](#) | [Licen](#)[Home](#)[Features](#)[Status](#)[Documentation](#)[Download](#)

# Environment Variables

## Summary

### Env Var

[FASTBUILD\\_TEMP\\_PATH](#)[FASTBUILD\\_BROKERAGE\\_PATH](#)[FASTBUILD\\_CACHE\\_PATH](#)[FASTBUILD\\_CACHE\\_MODE](#)

### Purpose

Override system temp path for FASTBuild to use.

Set location of the Brokerage Path for distributed compilation.

Set the location of the cache.

Set the cache mode.

## Details

**FASTBUILD\_TEMP\_PATH**

FASTBuild uses the system temp dir. This can be overridden by setting the FASTBUILD\_TEMP\_PATH. This can be useful in certain cases, such as when certain Anti-Virus software is used that prevents executables being spawned from the temp directory.

## **FASTBUILD\_BROKERAGE\_PATH**

FBuildWorkers signal their availability by writing a token to the "Brokerage Path". The location of the brokerage path can be set via the FASTBUILD\_BROKERAGE\_PATH.

## **FASTBUILD\_CACHE\_PATH**

The location of the FASTBuild cache can be set via the FASTBUILD\_CACHE\_PATH environment variable instead of via the .CachePath option in the [Settings](#) function.

## **FASTBUILD\_CACHE\_MODE**

The cache mode can be set via the FASTBUILD\_CACHE\_MODE environment variable, instead of via the command line [-cache](#) options.

© 2012-2017 Franta Fulin