



Comment	Description	Designator	Footprint	LibRef	Quantity
MS621FE		BATT	MS621FE	SBatery	1
0.1uF/25V	Capacitor	C1, C3, C8, C9, C11, C12, C13, C15, C35, C37, C38, C41, C50	0402c	Cap	13
4.7uF/10V	Capacitor	C2	0402c	Cap	1
22pF	Capacitor	C4, C6, C40	0402c	CAP	3
6pF	Capacitor	C5, C7	0402c	CAP	2
0.1uF	Capacitor	C14, C25, C33	0402C	CAP	3
10pF/NC	Capacitor	C16, C17, C18	0402C	CAP	3
36pF	Capacitor	C22	0402c	Cap	1
4.7uF	Capacitor	C23	0402c	Cap	1
10pF	Capacitor	C24	0402C	CAP	1
1uF/25V	Capacitor	C27	0402C	CAP	1
22uF/10V	Capacitor	C28, C34, C44, C46, C47, C48	0805C	CAP	6
1000uF	Polarized Capacitor (Surface Mount)	C29, C31	7343	Cap Pol3	2
10uF/10V	Capacitor	C32	0402C	CAP	1
33pF	Capacitor	C43	0402C	CAP	1
1N4148		D1	DIODE_SOP	D	1
SMAJ12CA		D2	SMA	DIODE_SCHOTTKY_0	1
DIODE_SCHOTTKY_0		D3, D4	LL-34(D1206)	DIODE_SCHOTTKY_0	2
10R/1A		FB2	0603R	INDUCTOR1	1
IPEX	IPEX	J1, J2	RF-UFL	ANT	2
27nH		L2	0402R	INDUCTOR_1	1
LQW15A		L3	0402R	INDUCTOR_1	1
SRP4020TA-1R0M		L4, L6	L2520	INDUCTOR_1	2
SRP4020TA-2R2M		L5	L2520	INDUCTOR_1	1
LED		LED1, LED2, LED4, LED5	0603LED	LED	4
Header 5	Header, 5-Pin	P7	5x1.25mmSMT	Header 5	1
MMBT3904		Q2, Q4, Q6, Q7, Q18, Q20	SOT23-3	2N1069_1, NPN	6
SI2369DS	NMOSFET	Q3, Q8, Q10, Q12	so23-3	NCE4060K	4
S8050		Q9, Q11, Q13	SOT23-3	2N1069_1	3
1MR	Resistor	R1	0402R	Res3	1
10K/1%		R2, R5, R35, R38, R52	0402R	RES1	5
100K	Resistor	R3	0402R	Res2	1
47K		R4, R11	0402R	RES1	2
10K	Resistor	R6, R18, R30, R42	0402R	RES1, Res2	4
470	Resistor	R7	0402R	Res2	1
1K		R9, R65	0402R	RES1	2
47K		R10, R16, R22, R24, R28, R31, R32, R40, R44, R46	0402R	RES1	10
1K/1%		R12, R29	0402R	RES1	2
336K/1%		R13	0402R	RES1	1
21.5K/1%		R14	0402R	RES1	1
RTH103AT		R15	0603R	RES1	1
534K/1%		R19	0402R	RES1	1
100K/1%		R20, R48	0402R	RES1	2
400K/1%		R21	0402R	RES1	1
10R		R23, R27, R39	0402R	RES1	3
0R		R25, R26	0402R	RES1	2
4K7		R33, R34, R36, R37, R50, R51	0402R	RES1	6
13K/1%		R49	0402R	RES1	1
TPD		T1, T2, T3, T8, T9, T10, T11, T13, T14, T18, T19	TPD	TPD	11
TPD		T4, T5, T6, T7, T15, T16, T17, T20	TP	TPD	8
A7670		U1	A7670	A7670	1
stm324128B	ARM Cortex-M3 32-bit MCU, 64 KB Flash, 8 KB Internal RAM, 51 I/Os, 64-pin LQFP, -40 to 85 degC, Tray	U3	LQFP-64	STM32L100R8 T6	1
SIM688E/SIM68		U5	SIM68MB	SIM68MB	1
SAFFBTG56KB 0FA		U8	SAFFBTG56KB 0FA	SAFFBTG56KB 0FA	1
AW5005DNR		U9	AW5005	AW5005DNR	1
bq24210		U10	QFN50P200X30 0X80-10N	bq2410	1
SLI76CF3600P		U11	QFN127P500X6 0X80-50N	SLI76CF3600P	1
REF3025AIDBZ R		U12	SOT23-3	REF3012	1
LIS2MDL		U13	LIS2MDL	LIS2MDL	1
LSM6DS3TR		U14	LSM6DS3TR-C	LSM6DS3TR	1
BMP388		U15	BMP388	BMP388	1
MX25L51245G MI-10G		U16	SOP127P1030X 239-16N	MX25L51245G MI-10G	1
TPS61023		U17, U19	SOT563-6	TPS61023	2
TPS610997YFF R		U18	TPS610997YFF R	TPS610997YFF R	1
MC-146 32.768K6pF	Crystal Oscillator	Y1	32.768K	XTAL	1
8MHz	Crystal Oscillator	Y2	OSCILLATOR-3	XTAL	1