

Flutter is back at Google I/O on May 19-20! [Register now](#)

[Install](#) > Add to PATH



Add Flutter to your PATH

Learn how to add Flutter to your PATH after downloading the Flutter SDK.

Learn how to add Flutter to your `PATH` environment variable after downloading the SDK. Adding Flutter to your `PATH` allows you to use the `flutter` and `dart` command-line tools in terminals and IDEs.

Tip

If you haven't downloaded Flutter yet, follow [Set up and test drive Flutter](#) instead.

Windows

Add Flutter to your path on Windows.

macOS

Add Flutter to your path on macOS.

Linux

Add Flutter to your path on Linux.

ChromeOS

Add Flutter to your path on ChromeOS.

Windows

To run `flutter` and `dart` commands in a terminal on Windows, add the Flutter SDK's `bin` directory to the `Path` environment variable.

1 Determine your Flutter SDK installation location

Copy the absolute path to the directory that you downloaded and extracted the Flutter SDK into.

2 Navigate to the environment variables settings

1. Press `Windows` + `Pause`.

If your keyboard lacks a `Pause` key, try `Windows` + `Fn` + `B`.

The **System > About** dialog opens.

2. Click **Advanced System Settings > Advanced > Environment Variables...**

The **Environment Variables** dialog opens.

3 **Add the Flutter SDK bin to your path**

1. In the **User variables for (username)** section of the **Environment Variables** dialog, look for the **Path** entry.
2. If the **Path** entry exists, double-click it.

The **Edit Environment Variable** dialog should open.

- a. Double-click inside an empty row.
- b. Type the path to the `bin` directory of your Flutter installation.

Por ejemplo, si descargaste Flutter en un `develop\flutter` carpeta dentro de su directorio de usuarios, escribirías lo siguiente:

```
%USERPROFILE%\develop\flutter\bin
```

- c. Haga clic en la entrada de Flutter que agregó para seleccionarla.
 - d. Haga clic **Subir** hasta que la entrada de Flutter se encuentre en la parte superior de la lista.
 - e. Para confirmar sus cambios, haga clic **OK** tres veces.
3. Si la entrada no existe, haga clic **Nuevo...**

El **Editar variable de entorno** El diálogo debería abrirse.

- a. En el **Nombre variable** caja, tipo `Path`.
- b. En el **Valor variable** caja, escriba la ruta a la `bin` directorio de su instalación de Flutter.

Por ejemplo, si descargaste Flutter en un `develop\flutter` carpeta dentro de su directorio de usuarios, escribirías lo siguiente:

```
%USERPROFILE%\develop\flutter\bin
```

- c. Para confirmar sus cambios, haga clic **OK** tres veces.

4 Aplica tus cambios

Para aplicar este cambio y obtener acceso a la `flutter` herramienta, cerrar y volver a abrir todas las indicaciones de comando abiertas, sesiones en sus aplicaciones de terminal e IDE.

5 Valida tu configuración

Para garantizar que haya agregado correctamente el SDK a su `PATH`, Abra el símbolo del sistema o su aplicación de terminal preferida, Luego intenta ejecutar el `flutter` y `dart` herramientas.

```
$ flutter --version
$ dart --version
```

Si no se encuentra ninguno de los comandos, check out [Solución de problemas de instalación de Flutter](#).

macOS

Correr `flutter` y `dart` comandos en una terminal en macOS, Agregue los SDK de Flutter `bin` directorio al `PATH` entorno variable.

📘 Nota

Los siguientes pasos suponen que estás usando el [shell predeterminado](#) en macOS, Zsh.

Si usas otro shell además de Zsh, check out [este tutorial sobre cómo configurar su PATH](#).

1 Determine la ubicación de instalación de su SDK de Flutter

Copia la ruta absoluta al directorio que deseas descargar y extraje el SDK de Flutter.

2 Abra o cree el archivo de variable de entorno Zsh

Si existe, abre el [Archivo de variable de entorno Zsh](#) `~/.zprofile` en tu editor de texto preferido. Si no existe, crea el `~/.zprofile` archivo.

3 Agregue el contenedor Flutter SDK a su ruta

Al final de tu `~/.zprofile` fişier, Utilice el integrado `export` comando para actualizar el `PATH` variable para incluir el `bin` directorio de su instalación de Flutter.

Reemplazar `<path-to-sdk>` con la ruta a su instalación del SDK de Flutter.

```
export PATH="<path-to-sdk>/bin:$PATH"
```

bash

Por ejemplo, si descargaste Flutter en un `develop/flutter` carpeta dentro de su directorio de usuarios, Agregarías lo siguiente al archivo:

```
export PATH="$HOME/develop/flutter/bin:$PATH"
```

bash

4 Guarda tus cambios

Guarde y luego cierre el `~/.zprofile` archivo que editaste.

5 Aplica tus cambios

Para aplicar este cambio y obtener acceso a la `flutter` herramienta, Cierre y vuelva a abrir todas las sesiones Zsh abiertas en sus aplicaciones de terminal e IDE.

6 Valida tu configuración

To ensure you successfully added the SDK to your `PATH`, open a Zsh session in your preferred terminal, then try running the `flutter` and `dart` tools.

```
$ flutter --version  
$ dart --version
```

If either command isn't found, check out [Flutter installation troubleshooting](#).

Linux

To run `flutter` and `dart` commands in a terminal on Linux, add the Flutter SDK's `bin` directory to the `PATH` environment variable.

1 Determine your Flutter SDK installation location

Copy the absolute path to the directory that you downloaded and extracted the

☰ On this page > macOS

2 Determine your default shell

If you don't know what shell you use, check which shell starts when you open a new console window.

```
$ echo $SHELL
```

3 Add the Flutter SDK bin to your path

To add the `bin` directory of your Flutter installation to your `PATH`:

1. Expand the instructions for your default shell.
2. Copy the provided command.
3. Replace `<path-to-sdk>` with the path to your Flutter SDK install.
4. Run the edited command in your preferred terminal with that shell.

-
- ▶ Expand for `bash` instructions
 - ▶ Expand for `zsh` instructions
 - ▶ Expand for `fish` instructions
 - ▶ Expand for `csh` instructions
 - ▶ Expand for `tcsh` instructions
 - ▶ Expand for `ksh` instructions
 - ▶ Expand for `sh` instructions

4 Apply your changes

To apply this change and get access to the `flutter` tool, close and reopen all open shell sessions in your terminal apps and IDEs.

5 Validate your setup

To ensure you successfully added the SDK to your `PATH`, open your preferred terminal with your default shell, then try running the `flutter` and `dart` tools.

```
$ flutter --version  
$ dart --version
```

If either command isn't found, check out [Flutter installation troubleshooting](#).

ChromeOS

To run `flutter` and `dart` commands in a terminal on chromeOS, add the Flutter SDK's `bin` directory to the `PATH` environment variable.

Note

The following steps assume you've already [turned on Linux support](#) and that you're using Bash or the default shell on ChromeOS.

If you're using a different shell besides the default or Bash, follow the [add to path instructions for Linux](#) instead.

1 Determine your Flutter SDK installation location

Copy the absolute path to the directory that you downloaded and extracted the Flutter SDK into.

2 Add the Flutter SDK bin to your path

To add the `bin` directory of your Flutter installation to your `PATH`:

1. Copy the following command.
2. Replace `<path-to-sdk>` with the path to your Flutter SDK install.
3. Run the edited command in your preferred terminal.

```
$ echo 'export PATH="<path-to-sdk>:$PATH"' >> ~/.bash_profile
```

For example, if you downloaded Flutter into a `develop/flutter` folder inside your user directory, you'd run the following:

```
$ echo 'export PATH="$HOME/develop/flutter/bin:$PATH"' >> ~/.bash_profile
```

3 Apply your changes

To apply this change and get access to the `flutter` tool, close and reopen all open Zsh sessions in your terminal apps and IDEs.

4 Validate your setup

To ensure you successfully added the SDK to your `PATH`, open a Zsh session in your preferred terminal, then try running the `flutter` and `dart` tools.

```
$ flutter --version  
$ dart --version
```

If either command isn't found, check out [Flutter installation troubleshooting](#).

Was this page's content helpful?



Except as otherwise noted, this site is licensed under a [Creative Commons Attribution 4.0 International License](#), and code samples are licensed under the [3-Clause BSD License](#).

[Terms](#)[Brand](#)[Privacy](#)[Security](#)

Built with
Jaspr