PECOS

Predictive Engineering and Computational Sciences

Locally Conservative Discontinuous Petrov-Galerkin for Convection-Diffusion

Truman E. Ellis

Institute for Computational and Engineering Sciences
The University of Texas at Austin

July 25, 2013

A Summary of DPG

Overview of Features

- Robust for singularly perturbed problems
- Stable in the preasymptotic regime
- Designed for adaptive mesh refinement

DPG is a minimum residual method:

$$u_h = \underset{w_h \in U_h}{\arg\min} \frac{1}{2} \|Bw_h - l\|^2_{V'}$$

$$\Updownarrow$$

$$b(u_h, R_V^{-1} B\delta u_h) = l(R_V^{-1} B\delta u_h) \quad \forall \delta u_h \in U_h$$

where $v_{\delta u_h} := R_V^{-1} B\delta u_h$ are the optimal test functions.

DPG for Convection-Diffusion

Start with the strong-form PDE.

$$\nabla \cdot (\beta u) - \epsilon \Delta u = g$$

Rewrite as a system of first-order equations.

$$\begin{aligned} \nabla \cdot (\beta u - \boldsymbol{\sigma}) &= g \\ \frac{1}{\epsilon}\boldsymbol{\sigma} - \nabla u &= \mathbf{0} \end{aligned}$$

Multiply by test functions and integrate by parts over each element, K.

$$\begin{aligned} -(\beta u - \boldsymbol{\sigma}, \nabla v)_K + ((\beta u - \boldsymbol{\sigma}) \cdot \mathbf{n}, v)_{\partial K} &= (g, v)_K \\ \frac{1}{\epsilon}(\boldsymbol{\sigma}, \boldsymbol{\tau})_K + (u, \nabla \cdot \boldsymbol{\tau})_K - (u, \tau_n)_{\partial K} &= 0 \end{aligned}$$

Use the ultraweak (DPG) formulation to obtain bilinear form $b(u, v) = l(v)$.

$$\begin{aligned} -(\beta u - \boldsymbol{\sigma}, \nabla v)_K + (\hat{f}, v)_{\partial K} + \frac{1}{\epsilon}(\boldsymbol{\sigma}, \boldsymbol{\tau})_K & \\ + (u, \nabla \cdot \boldsymbol{\tau})_K - (\hat{u}, \tau_n)_{\partial K} &= (g, v)_K \end{aligned}$$

Local Conservation

The local conservation law in convection diffusion is

$$\int_{\partial K} \hat{f} = \int_K g \,,$$

which is equivalent to having $\mathbf{v}_K := \{v, \boldsymbol{\tau}\} = \{1_K, \mathbf{0}\}$ in the test space. In general, this is not satisfied by the optimal test functions. Following Moro et al[2], we can enforce this condition with Lagrange multipliers:

$$L(u_h, \boldsymbol{\lambda}) = \frac{1}{2} \left\| R_V^{-1}(Bu_h - l) \right\|_V^2 - \sum_K \lambda_K \underbrace{\langle Bu_h - l, \mathbf{v}_K \rangle}_{\langle \hat{f}, 1_K \rangle_{\partial K} - \langle g, 1_K \rangle_K} \,,$$

where $\boldsymbol{\lambda} = \{\lambda_1, \cdots, \lambda_N\}$.

Local Conservation

Finding the critical points of $L(u, \boldsymbol{\lambda})$, we get the following equations.

$$\frac{\partial L(u_h, \boldsymbol{\lambda})}{\partial u_h} = b(u_h, R_V^{-1} B\delta u_h) - l(R_V^{-1} B\delta u_h) - \sum_K \lambda_K b(\delta u_h, \mathbf{v}_K) = 0 \quad \forall \delta u_h \in U_h$$

$$\frac{\partial L(u_h, \boldsymbol{\lambda})}{\partial \lambda_K} = -b(u_h, \mathbf{v}_K) + l(\mathbf{v}_K) = 0 \quad \forall K$$

A few consequences:

- We've turned our minimization problem into a saddlepoint problem.
- Only need to find the optimal test function in the orthogonal complement of constants.

Optimal Test Functions

For each $\mathbf{u} = \{u, \boldsymbol{\sigma}, \hat{u}, \hat{f}\} \in \mathbf{U}_h$, find $\mathbf{v_u} = \{v_\mathbf{u}, \boldsymbol{\tau}_\mathbf{u}\} \in \mathbf{V}$ such that

$$(\mathbf{v_u}, \mathbf{w})_\mathbf{V} = b(\mathbf{u}, \mathbf{w}) \quad \forall \mathbf{w} \in \mathbf{V}$$

where $\mathbf{V}$ becomes $\mathbf{V}_{p+\Delta p}$ in order to make this computationally tractable. Chan et al[1] developed the following robust norm for convection-diffusion.

$$\begin{aligned}\|(v,\boldsymbol{\tau})\|^2_{\mathbf{V},\Omega_h} &= \|\nabla\cdot\boldsymbol{\tau}\|^2 + \left\|\min\left\{\frac{1}{\sqrt{\epsilon}}, \frac{1}{\sqrt{|K|}}\right\}\boldsymbol{\tau}\right\|^2 \\ &\quad + \epsilon\|\nabla v\|^2 + \|\boldsymbol{\beta}\cdot\nabla v\|^2 \qquad \underbrace{+\left\|\min\left\{\sqrt{\frac{\epsilon}{|K|}}, 1\right\} v\right\|^2}_{\text{no longer necessary to make this a norm}}\end{aligned}$$

Optimal Test Functions

For each $\mathbf{u} = \{u, \boldsymbol{\sigma}, \hat{u}, \hat{f}\} \in \mathbf{U}_h$, find $\mathbf{v_u} = \{v_\mathbf{u}, \boldsymbol{\tau}_\mathbf{u}\} \in \mathbf{V}$ such that

$$(\mathbf{v_u}, \mathbf{w})_\mathbf{V} = b(\mathbf{u}, \mathbf{w}) \quad \forall \mathbf{w} \in \mathbf{V}$$

where $\mathbf{V}$ becomes $\mathbf{V}_{p+\Delta p}$ in order to make this computationally tractable. Chan et al[1] developed the following robust norm for convection-diffusion.

$$\|(v, \boldsymbol{\tau})\|^2_{\mathbf{V},\Omega_h} = \|\nabla \cdot \boldsymbol{\tau}\|^2 + \left\| \min\left\{ \frac{1}{\sqrt{\epsilon}}, \frac{1}{\sqrt{|K|}} \right\} \boldsymbol{\tau} \right\|^2 + \epsilon \|\nabla v\|^2 + \|\boldsymbol{\beta} \cdot \nabla v\|^2 \underbrace{+ \left(\frac{1}{|K|} \int_K v \right)^2}_{\text{zero mean term}}$$

Erickson-Johnson Problem

On domain $\Omega = [0,1]^2$, with $\beta = (1,0)^T$, $f = 0$ and boundary conditions

$$\hat{f} = u_0, \quad \beta_n \leq 0\,, \qquad \hat{u} = 0, \quad \beta_n > 0$$

Separation of variabes gives an analytic solution

$$u(x,y) = C_0 + \sum_{n=1}^{\infty} C_n \frac{\exp(r_2(x-1)) - \exp(r_1(x-1))}{r_1\exp(-r_2) - r_2\exp(-r_1)} \cos(n\pi y)$$





J. Chan, N. Heuer, T Bui-Thanh, and L. Demkowicz.
Robust DPG method for convection-dominated diffusion problems ii: a natural inflow condition.
Technical Report 21, ICES, 2012.

D. Moro, N.C. Nguyen, and J. Peraire.
A hybridized discontinuous Petrov-Galerkin scheme for scalar conservation laws.
Int.J. Num. Meth. Eng., 2011.
in print.