Discontinuous Petrov-Galerkin (DPG) Method With Optimal Test Functions

Progress Report

Leszek Demkowicz

World Congress on Computational Mechanics

Barcelona, July 20 - July 25, 2014

THE UNIVERSITY OF TEXAS AT AUSTIN

Collaboration:

THE UNIVERSITY OF TEXAS AT AUSTIN

Portland State: J. Gopalakrishnan

ICES: T. Bui-Thanh, O. Ghattas, B. Moser, T. Ellis, J. Zitelli

Argonne: N. Roberts

Boeing: D. Young

Basque U: D. Pardo

C.U. of Hong-Kong: W. Qiu

KAUST: V. Calo

Livermoore: J. Bramwell

Los Alamos: M. Shaskov

Rice: J. Chan

Sandia: P.N. Bochev, K.J. Peterson, D. Ridzal and Ch. M. Siefert

C.U. Chile: I. Muga, N. Heuer

U. Helsinki: A. Niemi

U. Nevada: J. Li

U. Tel-Aviv I. Harari

Three DPG Punchlines

1. DPG Method is a Ritz method. It supports adaptivity with no preasymptotic behavior.
2. You can control the norm in which you want to converge.
3. DPG is easy to code.

Three DPG Punchlines

THE UNIVERSITY OF TEXAS AT AUSTIN

1. DPG Method is a Ritz method. It supports adaptivity with no preasymptotic behavior.
2. You can control the norm in which you want to converge.
3. DPG is easy to code.

Primal DPG Method for Maxwell equations.

Assume

$$J_S^{\text{imp}} = n \times H^{imp}$$

and look for the unknown surface current on the skeleton also in the same form.

$$\begin{cases} E \in H(\text{curl}, \Omega), \; n \times E = n \times E^{\text{imp}} \text{ on } \Gamma_1 \\ \hat{h} \in \text{tr}_{\Gamma_h} H(\text{curl}, \Omega), \; n \times \hat{h} = n \times (-i\omega H^{imp}) \text{ on } \Gamma_2 \\ (\frac{1}{\mu} \boldsymbol{\nabla} \times E, \boldsymbol{\nabla}_h \times F) + ((-\omega^2 \epsilon + i\omega\sigma) E, F) + \langle n \times \hat{h}, F \rangle_{\Gamma_h} = -i\omega (J^{\text{imp}}, F) \\ \qquad \forall F \in H(\text{curl}, \Omega_h) \, . \end{cases}$$

FE discretization for curl-curl problem

Hexahedral meshes

$H(\text{curl})$ element for electric field E:

$$(\mathcal{P}^{p-1} \otimes \mathcal{P}^p \otimes \mathcal{P}^p) \times (\mathcal{P}^p \otimes \mathcal{P}^{p-1} \otimes \mathcal{P}^p) \times (\mathcal{P}^p \otimes \mathcal{P}^p \otimes \mathcal{P}^{p-1})$$

and trace of the same element for flux (surface current) $\hat{h}$.

Same element for the enriched space but with order $p + \Delta p$.

In reported experiments: $p = 2$, $\Delta p = 2$.

A 3D Maxwell example

Take a cube $(0,2)^3$



Fichera corner

Divide it into eight smaller cubes and remove one:



Fichera corner microwave

Attach a waveguide:



$\epsilon = \mu = 1, \sigma = 0$
$\omega = 5$(1.6 wavelengths in the cube)

Cut the waveguide and use the lowest propagating mode for BC along the cut.

Fichera corner microwave, $p = 2$.



Initial mesh and real part of E_1

Fichera corner microwave, $p = 2$.



Mesh and real part of E_1 after two refinements

Fichera corner microwave, $p = 2$.



Mesh and real part of E_1 after four refinements

Fichera corner microwave, $p = 2$.



Mesh and real part of E_1 after six refinements

Fichera corner microwave, $p = 2$.



Mesh and real part of E_1 after eight refinements

From Ph.D. Dissertation of Jesse Chan: Compressible Navier-Stokes Equations: Carter's flat plate problem [1] [2]



$$\mathrm{M}_\infty = 3, \mathrm{Re}_L = 1000, \mathrm{Pr} = 0.72, \gamma = 1.4, \theta_\infty = 390^o[\mathrm{R}]$$

[1] L.D., J.T. Oden, W. Rachowicz, ``A New Finite Element Method for Solving Compressible Navier-Stokes Equations Based on an Operator Splitting Method and hp Adaptivity,'', *Comput. Methods Appl. Mech. Engrg.*, **84**, 275-326, 1990.

[2] J. Chan, L.D., R. Moser, ``A DPG method for steady viscous compressible flow,'' *Computers and Fluids*, to appear.

Compressible Navier-Stokes

Extrapolation to Compressible NS Equations



(c) Initial mesh

(d) 12 refinements

Figure : $\mathrm{Re} = 1000$, initial and final meshes.

Compressible Navier-Stokes

Extrapolation to Compressible NS Equations



Figure : $\mathrm{Re} = 10,000$, $p = 2$, initial mesh.

Compressible Navier-Stokes

Extrapolation to Compressible NS Equations



Figure : $\mathrm{Re} = 10,000$, $p = 2$, refinement number 1.

Compressible Navier-Stokes

Extrapolation to Compressible NS Equations





Figure : $\mathrm{Re} = 10,000$, $p = 2$, refinement number 2.

Compressible Navier-Stokes

Extrapolation to Compressible NS Equations





Figure : $\mathrm{Re} = 10,000$, $p = 2$, refinement number 3.

Compressible Navier-Stokes

Extrapolation to Compressible NS Equations



Figure : $\mathrm{Re} = 10,000$, $p = 2$, refinement number 4.

Compressible Navier-Stokes

Extrapolation to Compressible NS Equations



Figure : $\mathrm{Re} = 10,000$, $p = 2$, refinement number 5.

Compressible Navier-Stokes

Extrapolation to Compressible NS Equations





Figure : $\mathrm{Re} = 10,000$, $p = 2$, refinement number 6.

Compressible Navier-Stokes

Extrapolation to Compressible NS Equations



Figure : $\mathrm{Re} = 10,000$, $p = 2$, refinement number 7.

Compressible Navier-Stokes

Extrapolation to Compressible NS Equations





Figure : $\mathrm{Re} = 10,000$, $p = 2$, refinement number 8.

Compressible Navier-Stokes

Extrapolation to Compressible NS Equations



Figure : $\mathrm{Re} = 10,000$, $p = 2$, refinement number 9.

Compressible Navier-Stokes

Extrapolation to Compressible NS Equations



Figure : $\mathrm{Re} = 10,000$, $p = 2$, refinement number 10.

Compressible Navier-Stokes

Extrapolation to Compressible NS Equations





Figure : $\mathrm{Re} = 10,000$, $p = 2$, refinement number 11.

Compressible Navier-Stokes

Extrapolation to Compressible NS Equations



Figure : $\mathrm{Re} = 10,000$, $p = 2$, refinement number 12.

Compressible Navier-Stokes

Extrapolation to Compressible NS Equations



Figure : $\mathrm{Re} = 10,000$, $p = 2$, refinement number 13.

Compressible Navier-Stokes

Extrapolation to Compressible NS Equations





Figure : $\mathrm{Re} = 10,000$, $p = 2$, refinement number 14.

Compressible Navier-Stokes

Extrapolation to Compressible NS Equations





Figure : $\mathrm{Re} = 10,000$, $p = 2$, refinement number 15.

Compressible Navier-Stokes

THE UNIVERSITY OF TEXAS AT AUSTIN

Extrapolation to Compressible NS Equations



Figure : $\mathrm{Re} = 10,000$, $p = 2$, refinement number 16.

From Ph.D. Dissertation of Jesse Chan: Compressible Navier-Stokes Equations: Holden ramp problem [3] [4]



Figure : $M_\infty = 6, \mathrm{Re}_{\mathrm{plate}} = 33,936, \mathrm{Pr} = 0.72, \gamma = 1.4, \theta_\infty = 390^o[\mathrm{R}]$

[3] L.D., J.T. Oden, W. Rachowicz, ``A New Finite Element Method for Solving Compressible Navier-Stokes Equations Based on an Operator Splitting Method and hp Adaptivity,'', *Comput. Methods Appl. Mech. Engrg.*, **84**, 275-326, 1990.

[4] J. Chan, L.D., R. Moser, ``A DPG method for steady viscous compressible flow,'' *Computers and Fluids*, to appear.

Compressible Navier-Stokes

Extrapolation to Compressible NS Equations





Figure : Mach 6, $\mathrm{Re} \approx 34,000$, $p = 2$, initial mesh.

Compressible Navier-Stokes

Extrapolation to Compressible NS Equations



Figure : Mach 6, $\mathrm{Re} \approx 34,000$, $p = 2$, refinement number 1.



Figure : Mach 6, $\mathrm{Re} \approx 34,000$, $p = 2$, refinement number 2.

Compressible Navier-Stokes

Extrapolation to Compressible NS Equations



Figure : Mach 6, $\mathrm{Re} \approx 34,000$, $p = 2$, refinement number 3.

Compressible Navier-Stokes

Extrapolation to Compressible NS Equations





Figure : Mach 6, $\mathrm{Re} \approx 34,000$, $p = 2$, refinement number 4.

Compressible Navier-Stokes

Extrapolation to Compressible NS Equations



Figure : Mach 6, $\mathrm{Re} \approx 34,000$, $p = 2$, refinement number 5.

Compressible Navier-Stokes

Extrapolation to Compressible NS Equations



Figure : Mach 6, $\mathrm{Re} \approx 34,000$, $p = 2$, refinement number 6.

Compressible Navier-Stokes

Extrapolation to Compressible NS Equations



Figure : Mach 6, $\mathrm{Re} \approx 34,000$, $p = 2$, refinement number 7.

Compressible Navier-Stokes

Extrapolation to Compressible NS Equations



Figure : Mach 6, $\mathrm{Re} \approx 34,000$, $p = 2$, refinement number 8.

Compressible Navier-Stokes

THE UNIVERSITY OF TEXAS AT AUSTIN

Extrapolation to Compressible NS Equations



Figure : Mach 6, $\mathrm{Re} \approx 34,000$, $p = 2$, refinement number 9.

Compressible Navier-Stokes

Extrapolation to Compressible NS Equations



Figure : Mach 6, $\mathrm{Re} \approx 34,000$, $p = 2$, refinement number 10.



Figure : Mach 6, $\mathrm{Re} \approx 34,000$, $p = 2$, refinement number 11.

Compressible Navier-Stokes

Extrapolation to Compressible NS Equations



Figure : Mach 6, $\mathrm{Re} \approx 34,000$, $p = 2$, refinement number 12.

Compressible Navier-Stokes

Extrapolation to Compressible NS Equations



Figure : Mach 6, $\mathrm{Re} \approx 34,000$, $p = 2$, refinement number 13.

Compressible Navier-Stokes

Extrapolation to Compressible NS Equations



Figure : Mach 6, $\mathrm{Re} \approx 34,000$, $p = 2$, refinement number 14.

Compressible Navier-Stokes

Extrapolation to Compressible NS Equations



Figure : Mach 6, $\mathrm{Re} \approx 34,000$, $p = 2$, refinement number 15.

Compressible Navier-Stokes

Extrapolation to Compressible NS Equations



Figure : Mach 6, $\mathrm{Re} \approx 34,000$, $p = 2$, refinement number 16.

Compressible Navier-Stokes

Extrapolation to Compressible NS Equations





Figure : Mach 6, $\mathrm{Re} \approx 34,000$, $p = 2$, refinement number 17.

Compressible Navier-Stokes

Extrapolation to Compressible NS Equations



Figure : Mach 6, $\mathrm{Re} \approx 34,000$, $p = 2$, refinement number 18.

Compressible Navier-Stokes

Extrapolation to Compressible NS Equations



Figure : Mach 6, $\mathrm{Re} \approx 34,000$, $p = 2$, refinement number 19.

Compressible Navier-Stokes

Extrapolation to Compressible NS Equations



Figure : Mach 6, $\mathrm{Re} \approx 34,000$, $p = 2$, refinement number 20.

Compressible Navier-Stokes

Extrapolation to Compressible NS Equations



Figure : Mach 6, $\mathrm{Re} \approx 34,000$, $p = 2$, refinement number 21.

Compressible Navier-Stokes

THE UNIVERSITY OF TEXAS AT AUSTIN

Extrapolation to Compressible NS Equations



Figure : Mach 6, $\mathrm{Re} \approx 34,000$, $p = 2$, refinement number 22.

Compressible Navier-Stokes

Extrapolation to Compressible NS Equations



Figure : Mach 6, $\mathrm{Re} \approx 34,000$, $p = 2$, refinement number 23.

Compressible Navier-Stokes

Extrapolation to Compressible NS Equations



Figure : Mach 6, $\mathrm{Re} \approx 34,000$, $p = 2$, refinement number 24.

From Ph.D. Proposal of Truman Ellis: Space-Time Compressible Navier-Stokes Equations: Sod Shock Tube Problem [5]

[5] G.A. Sod, ``A Survey of Several Finite Difference Methods for Systems of Nonlinear Hyperbolic Conservation Laws'', *J. Comp. Methods Phys.*, **27**, 1-31, 1978.

Transient Compressible Navier-Stokes

Sod Shock Tube with $\mu = 10^{-5}$





Transient Compressible Navier-Stokes

Sod Shock Tube with $\mu = 10^{-5}$





Transient Compressible Navier-Stokes

Sod Shock Tube with $\mu = 10^{-5}$





Transient Compressible Navier-Stokes

Sod Shock Tube with $\mu = 10^{-5}$





Transient Compressible Navier-Stokes

Sod Shock Tube with $\mu = 10^{-5}$





Transient Compressible Navier-Stokes

Sod Shock Tube with $\mu = 10^{-5}$





Transient Compressible Navier-Stokes

Sod Shock Tube with $\mu = 10^{-5}$





Transient Compressible Navier-Stokes

Sod Shock Tube with $\mu = 10^{-5}$





Transient Compressible Navier-Stokes

Sod Shock Tube with $\mu = 10^{-5}$





Transient Compressible Navier-Stokes

Sod Shock Tube with $\mu = 10^{-5}$





Transient Compressible Navier-Stokes

Sod Shock Tube with $\mu = 10^{-5}$





Transient Compressible Navier-Stokes

Sod Shock Tube with $\mu = 10^{-5}$





Transient Compressible Navier-Stokes

Sod Shock Tube with $\mu = 10^{-5}$





Transient Compressible Navier-Stokes

Sod Shock Tube with $\mu = 10^{-5}$





Transient Compressible Navier-Stokes

Sod Shock Tube with $\mu = 10^{-5}$





From Ph.D. Dissertation of Nathan V. Roberts: Incompressible Navier-Stokes: Flow Past a Cylinder[6]



$[\mathrm{Re}_D = 40]$

[6] L.S.G. Kovasznay. ``Hot-wire investigation of the wake behind cylinders at low Reynolds numbers.'' *Proceedings of the Royal Society of London. Series A, Mathematical and Physical Sciences*, **198**(1053):174-190, 1949.

Incompressible Navier-Stokes

Domain: 240×120 cylinder diameters. Begin with a $p = 3$ preliminary mesh that simply captures geometry (detail):





Perform initial anisotropic refinements to get aspect ratios below 2:





Incompressible Navier-Stokes

Initial Mesh ($p = 3$), and horizontal velocity solution:





Mesh detail, and horizontal velocity solution





Relative energy error of solution: 9.76×10^{-2}.

Incompressible Navier-Stokes

Mesh after 1 h-refinement, and horizontal velocity solution:





Mesh detail, and horizontal velocity solution





Relative energy error of solution: 1.81×10^{-2}.

Mesh after 2 h-refinements, and horizontal velocity solution:





Mesh detail, and horizontal velocity solution





Relative energy error of solution: 3.26×10^{-3}.

Incompressible Navier-Stokes

Mesh after 3 h-refinements, and horizontal velocity solution:




Mesh detail, and horizontal velocity solution




Relative energy error of solution: 1.29×10^{-3}.

Incompressible Navier-Stokes

Mesh after 4 h-refinements, and horizontal velocity solution:





Mesh detail, and horizontal velocity solution





Relative energy error of solution: 5.74×10^{-4}.

Camellia: A Software Framework for DPG

THE UNIVERSITY OF TEXAS AT AUSTIN

Chan, Ellis, and Roberts results were computed using Camellia.[7]

Camellia:

- is easy to use (Stokes cavity flow h-adaptive driver takes $\approx$ 130 lines of code)
- supports MPI, h- and p- adaptivity
- built atop Trilinos
- supports 1-3D spatial meshes (1D and 3D just added)
- space-time meshes coming soon
- open source release planned for 2015

[7] Nathan V. Roberts. ``Camellia: A software framework for discontinuous Petrov-Galerkin methods.'' *Computers & Mathematics with Applications*, 2014 (in review).

Three DPG Punchlines

1. DPG Method is a Ritz method. It supports adaptivity with no preasymptotic behavior.
2. You can control the norm in which you want to converge.
3. DPG is easy to code.

The simplest singular perturbation problem: reaction-dominated diffusion [8]

[8] L.D. and I. Harari, ``Primal DPG Method for Reaction dominated Diffusion'', in preparation.

The simplest singular perturbation problem:

Reaction-dominated diffusion

$$
\left\{
\begin{array}{rll}
u & = 0 & \text{on } \Gamma \\
-\epsilon^2 \Delta u + c(x) u & = f & \text{in } \Omega
\end{array}
\right.
$$

where $0 < c_0 \leq c(x) \leq c_1$.

Standard variational formulation:

$$
\left\{
\begin{array}{l}
u \in H^1(\Omega) \\
\\
\epsilon^2 (\nabla u, \nabla v) + (cu, v) = (f, v) \quad v \in H^1(\Omega)
\end{array}
\right.
$$

Standard Galerkin method delivers the best approximation error in the energy norm:

$$
\|u\|^2_{\epsilon^k} := \epsilon^k \|\nabla u\|^2 + \|c^{1/2} u\|^2, \quad k = 2
$$

Convergence in ``balanced'' norm

THE UNIVERSITY OF TEXAS AT AUSTIN

Fact: Under favorable regularity conditions, the solution is *uniformly* bounded in data f in a ``balanced'' norm [9] :

$$\|u\|_\epsilon^2 := \epsilon\|\nabla u\|^2 + \|c^{1/2}u\|^2$$

i.e.

$$\|u\|_\epsilon \lesssim \|f\|_{\text{appropriate}}$$

Question: Can we select the test norm in such a way that the DPG method will be *robust* in the balanced norm ?

$$\|u - u_h\|_\epsilon + \|\hat{t} - \hat{t}_h\|_? \lesssim \inf_{w_h} \|u - w_h\|_\epsilon + \inf_{\hat{r}_h} \|\hat{t} - \hat{r}_h\|_?$$

[9] R. Lin and M. Stynes, ``A balanced finite element method for singularly perturbed reaction-diffusion problems'', *SIAM J. Numer. Anal.*, **50(5):** 2729--2743, 2012.

A bit of history:

Optimal test functions of Barret and Morton [10] [11]

For each $w \in U_h$, determine the corresponding v_w that solves the auxiliary variational problem:

$$\left\{ \begin{array}{l} v_w \in H_0^1(\Omega) \\ \underbrace{\epsilon^2(\nabla \delta u, \nabla v_w) + (c\,\delta u, v_w)}_{\text{the bilinear form we have}} = \underbrace{\epsilon(\nabla \delta u, w) + (c\,\delta u, w)}_{\text{the bilinear form we want}} \quad \forall \delta u \in H_0^1(\Omega) \end{array} \right.$$

With the optimal test functions, the Galerkin orthogonality for the original form changes into Galerkin orthogonality in the desired, ``balanced'' norm:

$$\epsilon^2(\nabla(u-u_h), \nabla v_w) + (c\,(u-u_h), v_w) = 0 \quad \Longrightarrow \quad \epsilon(\nabla(u-u_h), \nabla v_u) + (c\,(u-u_h), w) = 0$$

Consequently, the PG solution delivers the best approximation error in the desired norm.

[10] J.W. Barret and K. W. Morton, ``Approximate Symmetrization and Petrov-Galerkin Methods for Diffusion-Convection Problems'', *Comp. Meth. Appl. Mech and Engng.*, **46**, 97 (1984).

[11] L. D. and J. T. Oden, ``An Adaptive Characteristic Petrov-Galerkin Finite Element Method for Convection-Dominated Linear and Nonlinear Parabolic Problems in One Space Variable'', *Journal of Computational Physics*, **68(1):** 188--273, 1986.

Constructing optimal test norm [12]

THE UNIVERSITY OF TEXAS AT AUSTIN

Theorem

Let v_u *be the Barret-Morton optimal test function corresponding to* u. *Let* $\|v_u\|_V$ *be a test norm such that*

$$\|v_u\|_V \lesssim \|u\|_\epsilon$$

Then

$$\|u - u_h\|_\epsilon \lesssim \|u - u_h\|_E = \inf_{w_h \in U_h} \|u - w_h\|_E \leq \textit{BAE estimate}$$

Proof:

$$\begin{aligned} \|u\|_\epsilon^2 &= \epsilon(\nabla u, \nabla u) + (cu, u) = \epsilon^2(\nabla u, \nabla v_u) + (cu, v_u) \\ &= b((u, \hat{t}), v_u) \leq \frac{b((u,\hat{t}), v_u)}{\|v_u\|_V} \|v_u\|_V \\ &\leq \sup_v \frac{b((u,\hat{t}), v_u)}{\|v\|_V} \|v_u\|_V = \|(u, \hat{t})\|_E \|v_u\|_V \\ &\lesssim \|(u, \hat{t})\|_E \|u\|_\epsilon \end{aligned}$$

[12] L. D., M. Heuer, ``Robust DPG Method for Convection-Dominated Diffusion Problems,'' *SIAM J. Num. Anal*, **51:** 2514--2537, 2013.

Constructing optimal test norm

The point: Construction of the optimal test norm is reduced to the stability (robustness) analysis for the Barret-Morton test functions.

Lemma

Let

$$\|v\|_V^2 := \epsilon^3 \|\nabla v\|^3 + \|c^{1/2} v\|^2$$

Then

$$\|v_u\| \lesssim \|u\|_\epsilon$$

In order to avoid boundary layers in the optimal test functions (that we cannot resolve using simple enriched space) we scale the reaction term with a mesh-dependent factor:

$$\|v\|_{V,mod}^2 := \epsilon^3 \|\nabla v\|^3 + \min\{1, \frac{\epsilon^3}{h^2}\} \|c^{1/2} v\|^2$$

Manufactured solution of Lin and Stynes, $\epsilon = 10^{-1}$



The functions exhibits strong boundary layers invisible in this scale.

Range: (-0.6,0.6)

Manufactured solution of Lin and Stynes, $\epsilon = 10^{-1}$



Zoom on the north boundary layer.

Optimal mesh for $\epsilon = 10^{-1}$



Optimal h-adaptive mesh and numerical solution for $\epsilon = 10^{-1}$

Lin/Stynes example, $\epsilon = 1$



Residual and ``balanced'' error of u for h-adaptive solution, $p = 2$

Lin/Stynes example, $\epsilon = 10^0, 10^{-1}$



Residual and ``balanced'' error of u for h-adaptive solution, $p = 2$

Lin/Stynes example, $\epsilon = 10^0, 10^{-1}, 10^{-2}$.

THE UNIVERSITY OF TEXAS AT AUSTIN



Residual and ``balanced'' error of u for h-adaptive solution, $p = 2$

Lin/Stynes example, $\epsilon = 10^0, 10^{-1}, 10^{-2}, 10^{-3}$.

THE UNIVERSITY OF TEXAS AT AUSTIN



Residual and ``balanced'' error of u for h-adaptive solution, $p = 2$

Lin/Stynes example, $\epsilon = 10^0, 10^{-1}, 10^{-2}, 10^{-3}, 10^{-}$



Residual and ``balanced'' error of u for h-adaptive solution, $p = 2$

Other tricks we can play: zooming on the solution

Question: Can we select the test norm in such a way that the DPG method would deliver high accuracy in a preselected subdomain, e.g. $(0, \frac{1}{2})^2 \subset (0, 1)^2$?
Answer: Yes!



Optimal mesh and the corresponding pointwise error (range $(-0.001 - 0.001)$.

Three DPG Punchlines

1. DPG Method is a Ritz method. It supports adaptivity with no preasymptotic behavior.
2. You can control the norm in which you want to converge.
3. DPG is easy to code.

Other Applications

- Wave propagation problems (sonars, full wave form inversion in geomechanics, cloaking)

Other Applications

- Wave propagation problems (sonars, full wave form inversion in geomechanics, cloaking)
- Elasticity, shells (volumetric, shear, membrane locking)

Other Applications

- Wave propagation problems (sonars, full wave form inversion in geomechanics, cloaking)
- Elasticity, shells (volumetric, shear, membrane locking)
- Metamaterials