

Buffer From A ponyfill for Buffer.from, uses native implementation if available. Installation npm install --save buffer-from 1	Usage const bufferFrom = require('buffer-from') console.log(bufferFrom([1, 2, 3, 4])) //=> <Buffer 01 02 03 04> const arr = new Uint8Array([1, 2, 3, 4]) console.log(bufferFrom(arr.buffer, 1, 2)) //=> <Buffer 02 03> 2	console.log(bufferFrom('test', 'utf8')) //=> <Buffer 74 65 73 74> const buf = bufferFrom('test') console.log(bufferFrom(buf)) //=> <Buffer 74 65 73 74> 3	API bufferFrom(array) • array <Array> Allocates a new Buffer using an array of octets. 4
8 See also • buffer-alloc A ponyfill for Buffer.alloc • buffer-alloc-unsafe A ponyfill for Buffer.allocUnsafe 6	7 bufferFrom(string[, encoding]) Copies the passed buffer data onto a new Buffer instance. • string <String> A string to encode. • encoding <String> The encoding of string. Default: 'utf8' Creates a new Buffer containing the given JavaScript string string. If provided, the encoding parameter identifies the character encoding of string. 10	6 bufferFrom(buffer) created Buffer will share the same allocated memory as the TypedArray. The optional byteOffset and length arguments specify a memory range within the ArrayBuffer that will be shared by the Buffer. • buffer <Buffer> An existing Buffer to copy data from 11	5 bufferFrom(arrayBuffer[, byteOffset[, length]]) • arrayBuffer <ArrayBuffer> The .buffer property of a TypedArray or ArrayBuffer • byteOffset <Integer> Where to start copying from arrayBuffer. Default: 0 • length <Integer> How many bytes to copy from arrayBuffer. Default: arrayBuffer.length - byteOffset When passed a reference to the .buffer property of a TypedArray instance, the newly 12
16	15	14	13