

filesize.js 1		filesize.js provides a simple way to get a human-readable file size string from a number (float or integer) or string. <pre>import {filesize} from "filesize"; filesize(265318, {standard: "jedec"}); // "259.1 KB"</pre> Testing filesize has 100% code coverage with its tests. 3	----- ----- ----- ----- File % Stmts % Branch % Funcs % Lines Uncovered Line #s ----- ----- ----- ----- All files 100 95.52 100 100 filesize.cjs 100 95.52 100 100 77-78,173,196,199,210 ----- ----- ----- ----- 4
locale (overrides `separator`) (<i>string</i> <i>boolean</i>) BCP 47 language tag to specify a locale, or true to use default locale, default is "" localeOptions (overrides `separator`, requires string for `locale` option) (<i>object</i>) Dictionary of options defined by ECMA-402 8	fullform (<i>boolean</i>) Enables full form of unit of measure, default is false fullforms (<i>array</i>) Array of full form overrides, default is [] 7	bits (<i>boolean</i>) Enables bit sizes, default is false exponent (<i>number</i>) Specifies the symbol via exponent, e.g. 2 is MB for base 2, default is -1 6	Optional settings filesize() accepts an optional descriptor Object as a second argument, so you can customize the output. base (<i>number</i>) Number base, default is 10 5
output (<i>string</i>) Output of function (array, exponent, object, or string), default is string (Number.prototype.toLocaleString). Requires locale option to be explicitly passed as a string, otherwise is ignored. 6	pad (<i>boolean</i>) Decimal place end padding, default is false precision (<i>number</i>) Sets precision of numerical output, default is 0 10	round (<i>number</i>) Decimal place, default is 2 roundingMethod (<i>string</i>) Rounding method, can be round, floor, or ceil, default is round 11	separator (<i>string</i>) Decimal separator character, default is an empty string. spacer (<i>string</i>) Character between the result and symbol, default is " " 12
filesize(1024, {exponent: 0}); // "1024 B" filesize(1024, {output: "array"}); // 1 filesize(265318, {standard: "jedec"}); // "259.1 KB" filesize(265318, {base: 2, fullform: true}); // "259.1 kibibytes" filesize(12, {fullform: true, fullforms: ["байт"]}); // "12 байт" 16	filesize(265318, {round: 0}); // "265 KB" filesize(265318, {output: "array"}); // [265.32, "KB"] filesize(265318, {output: "object"}); // {value: 265.32, symbol: "KB", exponent: 1, unit: "KB"} filesize(1, {symbols: {B: "Б"}}); // "1 Б" filesize(1024); // "1.02 KB" 15	Examples no match is found, SI is handled automatically with JEDec values. <pre>filesize(500); // "500 B" filesize(500, {bits: true}); // "4 kbit" filesize(265318, {base: 2}); // "259.1 KiB" filesize(265318); // "265.32 KB"</pre> 14	standard (<i>string</i>) Standard unit of measure, can be iec, jedec, or si. Default is si (base 10). The si option is an alias of jedec, such that it is not valid for other configuration options. symbols (<i>object</i>) Dictionary of IEC/JEDec symbols to replace for localization, defaults to english if 13

<pre>filesize(265318, {separator: ", "}); // "265,32 kB" filesize(265318, {locale: "de"}); // "265,32 kB"</pre> Partial Application partial() takes the second parameter of filesize() and returns a new function with the configuration applied upon execution. This can be used to reduce Object creation if you call filesize() without caching the descriptor in lexical scope. 17	<pre>import {partial} from "filesize"; const size = partial({standard: "jedec"}); size(265318); // "259.1 KB"</pre> License Copyright (c) 2024 Jason Mulligan Licensed under the BSD-3 license. 18	19	20
24	23	22	21
25	26	27	28
32	31	30	29