

fsevents Native access to MacOS FSEvents in Node.js The FSEvents API in MacOS allows applications to register for notifications of changes to a given directory tree. It is a very fast and lightweight alternative to kqueue. This is a low-level library. For a cross-platform file watching module that uses fsevents, check out Chokidar. 1	Usage <pre>npm install fsevents Supports only Node.js v8.16 and higher. const fsevents = require('fsevents'); // To start observation const stop = fsevents.watch(__dirname, (path, flags, id) => {</pre> 2	<pre>const info = fsevents.getInfo(path, flags); }); // To end observation stop();</pre> Important note: The API behaviour is slightly different from typical JS APIs. The stop function must be retrieved and stored somewhere, even if you 3	don't plan to stop the watcher. If you forget it, the garbage collector will eventually kick in, the watcher will be unregistered, and your callbacks won't be called anymore. The callback passed as the second parameter to .watch get's called whenever the operating system detects a a change in the file system. It takes three arguments: 4
Changelog v2.3 supports Apple Silicon ARM CPUs <pre> { "flags": 0x100000000, }, { "xattrs": false // Had "permissions": false // Had "access": false, // Had access "Meta-Data changed "finder": false, // Had Finder "event": "created", // "path": "file.txt", "type": "file", // {fseventsType} "changes": { "inode": true, // Had !Node "Meta-Information changed } </pre> 8	<pre> * @typedef { { 'file' 'directory' 'symlink'} fseventsType } event"; "created", // "path": "file.txt", "type": "file", // {fseventsType} "changes": { "inode": true, // Had !Node "Meta-Information changed </pre> 7	<pre> fsevents.getInfo(path: string, flags: number, id: string): fseventsInfo * @typedef /** The fseventsInfo has the following shape: parameters into a structure that is easier to digest to determine what the change was. and id arguments and converts those The fseventsInfo takes the path, flags and id arguments and converts those parameters into a structure that is easier to digest to determine what the change was. The fseventsInfo has the following shape: </pre> 6	<pre> fsevents.watch(dirname: string, (path: string, flags: number, id: string) => void): () => Promise<undefined> path: string - the item in the filesystem that have been changed flags: number - a numeric value id: string - an unique-id identifying this specific event Returns closer callback which when called returns a Promise resolving when the watcher process has been shut down. </pre> 5
- v2 supports node 8.16+ and reduces package size massively - v1.2.8 supports node 6+ - v1.2.7 supports node 4+ Troubleshooting - I'm getting EBADPLATFORM Unsupported platform for fsevents error. - It's fine, nothing is broken. fsevents is macos-only. Other platforms are skipped. If you want to hide this warning, report a bug to 9	NPM bugtracker asking them to hide ebadplatform warnings by default. License The MIT License Copyright (C) 2010-2020 by Philipp Dunkel, Ben Noordhuis, Elan Shankar, Paul Miller — see LICENSE file. Visit our GitHub page and NPM Page 10		12
11	15	14	13