

markdown-it-table-of-contents A table of contents plugin for Markdown-it. Simple, customizable and with a default slugifier that matches that of markdown-it-anchor (>5.0.0). Usage CommonJS: 1	var MarkdownIt = require("markdown-it"); var md = new MarkdownIt(); md.use(require("markdown-it-anchor").default); // Optional, but makes sense as you really want to link to something, see info about recommended plugins below md.use(require("markdown-it-table-of-contents")); 2	ESM: import MarkdownIt from 'markdown-it'; import MarkdownItTOC from 'markdown-it-table-of-contents'; const md = new MarkdownIt(); md.use(MarkdownItTOC); 3 Then add `` where you want the table of contents to be added in your document.</div> <div>Want to use a table of contents generator client-side in the browser? Try my ``	webcomponent: table-of-contents-element on GitHub. Advantage: can use more sophisticated query selector and better support for HTML customization. Example markdown This markdown: # Heading 4
8 containerClass the class for etc) levels to use [1, 2] Headings includeLevel These options are available: md.use(require("markdown-it-table-of-contents"), options); Description Default Name	7 You may specify options when using the plugin, like so: Options <p>Some even nicer text</p> <h2 id="sub-heading-2">Sub heading 2</h2> <p>Some nice text</p> <h2 id="sub-heading-1">Sub heading 1</h2>	9 Heading Sub heading 1 Sub heading 2 	5 <h1 id="heading">Heading</h1> ... would render this HTML using the default options specified in "usage" above: Some even nicer text ## Sub heading 2 Some nice text ## Sub heading 1
9 slugify A custom slugification function encodeURIComponent, 's+/g, '- markerPattern Regex pattern of the marker to be /^\\[\\[toc Description Default Name	10 omitTag replaced with TOC HTML comment tag to exclude next headline from TOC listType Type of list (ul for ul Description Default Name	11 format unordered, ol for ordered) A function for formatting headings (see below) containerHeaderHtml Optional HTML string undefined Description Default Name	12 containerFooterHtml for container header Optional HTML string undefined transformLink A function for transforming undefined Description Default Name
16 transformLink transform the link as you like. transformLink is an optional function for advanced use cases. parser object. This should only be need for md - markdown-it's internal markdown 2. function format(content, md) { // manipulate the headings as you like here. return manipulatedHeadingString; }	15 format format is an optional function for changing how the headings are displayed in the TOC. By default, TOC headings will be formatted using markdown-it's internal MD formatting rules (i.e. it will be formatted using the same rules / extensions as other markdown in your document). You can override this behavior by specifying a custom format function. The function should accept two arguments: 1. content - The heading text, as a markdown string.	14 getTokensText extracting text from tokens for titles transforming the container for closing tag A function for extracting text from tokens for titles getDescriptionDefault Name	13 transformContainerOpen A function for transforming the container opening tag A function for transforming the container transformContainerClose (see source) Description Default Name

<pre>function transformLink(link) { // transform the link as you like here. return transformedLink; } transformContainerOpen and transformContainerClose can be used to replace the container element with one or several more like so: md.use(markdownItTOC, { transformContainerOpen: () => { 17</pre>	<pre> return '<button>Toggle</ button><h3>Table of Contents</ h3>'; }, transformContainerClose: () => { return ''; } }); getTokensText is a function that can be used to change how text is extracted from tokens to support more ways how headlines are build. See source code for more 18</pre>	information or the equivalent function in markdown-it-anchor. Recommended plugins By default, markdown-it-table-of-contents collects all headings and renders a nested list. It uses the slugify() function to create anchor targets for the links in the list. However, the headlines in your markdown document are not touched by markdown-it- table-of-contents. You'd have a nice table of contents, but the links don't link to anything. 19	That's why you need another plugin to generate ids (anchor link targets) for all of your headlines. There are two recommended plugins to achieve this: markdown-it-anchor This plugin transforms all headlines in a markdown document so that the HTML code includes an id. It <i>slugifies</i> the headline: <pre>## Hello world, I think you should read this article 20</pre>
Ad <pre>### A message from our sponsors # Article md.use(require("markdown-it-attrs")) ; md.use(require("markdown-it-anchor")) ; 24</pre>	<pre>var md = new MarkdownIt({ md.use(markdownItTOC, { "includeLevel": [2,3,4] }) }); Consider the full example below: Furthermore, markdown-it-table-of- contents can handle unusual heading orders. already have an id attribute. markdown-it-anchor ignores headlines that Of course, both plugins can be combined. Full example with unusual headline order 23</pre>	<pre>## Hello world, I think you should read this article {#hello} <h2 id="hello">Hello world, I think you should read this article</ h2> Becomes short anchors: useful, if you have long headlines but want 22</pre>	Becomes <pre><h2 id="hello-world-i-think-you- should-read-this- article">Hello world, I think you should read this article</ h2> Becomes This plugin lets you attach custom attributes to your headlines. This is especially 21</pre>
<pre>## Hello world, I think you should read this article {#hello} Lorem ipsum ## What's next? Read this next... #### See related articles {#related} HTML output: 25</pre>	<pre><h1 id="article">Article</h1> <p> A message from our sponsors</ a> 26</pre>	<pre> Hello world, I think you should read this article What's next? See related articles 27</pre>	<pre> </p> <h3 id="a-message-from-our- sponsors">A message from our sponsors</h3> <p>Ad</p> 28</pre>
Additional infos - This plugin outputs a semantically correct table of contents. Sub-Lists are rendered within the parent tag and not as a separate (empty) . - Headlines can be in an arbitrary order. For example, h3, h2, h4. Please note that the jump from h2 to h4 causes a double- indentation, which is correct. 32	<pre>const md = new MarkdownIt({ html: true }); You can override the HTML comment by using the option omitTag as explained above. Both, the tag and the actual comment in the Markdown file are case-insensitive. want to exclude. Furthermore, you need to allow HTML in MarkdownIT: 31</pre>	Example for omitting headlines from the TOC If you want to exclude single headlines, you can use a special HTML comment to omit the next headline from the TOC: <pre><!-- omit from toc --> # Title For this to work, the HTML comment must come right in the line before the headline you 30</pre>	<pre><h2 id="hello">Hello world, I think you should read this article</ h2> <p>Lorem ipsum</p> <h2 id="what's-next%3F">What's next?</ h2> <p>Read this next...</p> <h4 id="related">See related articles</h4> 29</pre>