

mdurl  CI no status 1		URL utilities for markdown-it parser. API .encode(str [, exclude, keepEncoded]) -> String Percent-encode a string, avoiding double encoding. Don't touch /a-zA-Z0-9/ + excluded chars + /[a-zA-Z0-9]{2}/ (if not 3	disabled). Broken surrورات are replaced with U+FFFD. Params: str - input string. exclude - optional, ;/?:@&=+\$,-_~*'()#. Additional chars to keep intact (except /a-zA-Z0-9/). keepEncoded - optional, true. By default it skips already encoded sequences (/a-zA-Z0-9){2}/. If set to false, % will be encoded. 4
8 - decode.componentChars is the same as in the decodeURIComponent() function - For example, decode('something', decode.defaultChars) has the same behavior as decodeURIComponent('something') on a correctly encoded input.	7 decode.defaultChars, decode.componentChars You can use these constants as second argument to decode function. - decode.defaultChars is the same as in the standard decodeURIComponent() function	9 .decode(str [, exclude]) -> String The equivalent of the encodeURIComponent() function (except encode() doesn't throw). - Decode percent-encoded string. Invalid percent-encoded sequences (e.g. %2G) are left as is. Invalid UTF-8 characters are replaced with U+FFFD. - Params: str - input string.	5 encode.defaultChars, encode.componentChars You can use these constants as second argument to encode function. - encode.defaultChars is the same as in the standard encodeURIComponent() function - encode.componentChars is the same as in the encodeURIComponent() function - For example, encode('something', encodeURIComponent(componentChars, true)) is roughly
9 .parse(url, slashesDenoteHost) -> urlObs Parse url string. Similar to node's url.parse, but without any normalizations and query string parse. url - input url (string) slashesDenoteHost - if url starts with //, expect a hostname after it. Optional, false. Result (hash): - protocol - slashes	10 - auth - port - hostname - hash - search - pathname Difference with node's url: - No leading slash in paths, e.g. in url.parse('http://foo?bar') pathname is ``, not/`	11 - Backslashes are not replaced with slashes, so http:\\example.org\\ is treated like a relative path - Trailing colon is treated like a part of the path, i.e. in http://example.org:foo pathname is :foo - Nothing is URL-encoded in the resulting object, (in joyent/node some chars in auth and paths are encoded) - url.parse() does not have parseQueryString argument	12 6. Removed extraneous result properties: host, path, query, etc., which can be constructed using other parts of the url. .format(urlObject) Format an object previously obtained with .parse() function. Similar to node's url.format. License MIT
11	13	14	13