

minimist v1.2.8			License
<pre> \$ node example/parse.js -x 3 -y 4 -n5 -abc --deep=boop foo bar baz { _: ['foo', 'bar', 'baz'], x: 3, y: 4, n: 5, a: true, b: true, c: true, deep: 'boop' } </pre>	<pre> var argv = require('minimist')(process.argv.slice(2)); console.log(argv); \$ node example/parse.js -a beep -b doop { _: [], a: 'beep', b: 'doop' } </pre> example	parse argument options This module is the guts of optimist's argument parser without all the fanciful decoration.	
security Previous versions had a prototype pollution bug that could cause privilege escalation in some circumstances when handling untrusted user input. Please use version 1.2.6 or later: https://security.snyk.io/vuln/SNYK-JS-MINIMIST-2429795 (version <=1.2.5) https://snyk.io/vuln/SNYK-JS-MINIMIST-559764 (version <=1.2.3)	methods <pre> var parseArgs = require('minimist') </pre> <pre> var argv = parseArgs(args, opts={}) </pre> Return an argument object argv populated with the array arguments from args. argv._ contains all the arguments that didn't have an option associated with them.	Numeric-looking arguments will be returned as numbers unless opts.string or opts.boolean is set for that argument name. Any arguments after '--' will not be parsed and will end up in argv._. options can be: - opts.string - a string or array of strings argument names to always treat as strings - opts.boolean - a boolean, string or array of strings to always treat as booleans. if true will treat all double hyphenated arguments	without equal signs as boolean (e.g. affects --foo, not -f or --foo=bar) - opts.alias - an object mapping string names to strings or arrays of string argument names to use as aliases - opts.default - an object mapping string argument names to default values - opts.stopEarly - when true, populate argv._ with everything after the first non-option - opts['--'] - when true, populate argv._ with everything before the -- and
license MIT	<pre> npm install minimist </pre> With npm do: install	opts.unknown - a function which is invoked with a command line parameter not defined in the opts configuration object. If the function returns false, the unknown option is not added to argv.	Here's an example: argv['--'] with everything after the --. <pre> > require('./')(one two three -- four five --six'.split(' '), { '--': _: ['one', 'two', 'three'], '--': ['four', 'five', '--six'] }) </pre> Note that with opts['--'] set, parsing for arguments still stops after the --.