

	posthtml-match-helper Expand CSS selectors into PostHTML matcher objects	 build passing	
1 8 Basic usage <pre>import matchHelper from "posthtml-match-helper"; tree.match(matchHelper("div.class"), function (node) { // do stuff with matched node... });</pre> The basic template for selectors (and order of features) looks like this: <pre>"tag#id.class[attr=value] [otherattr='start']"</pre>	2 7 Attribute selectors: any number of standard attribute selectors can be used including the following non-standard: ◦ [attr=value]: matches attributes with values that do not contain value. • Multiple node selectors: "div, span" returns [{"tag": "div"}, {"tag": "span"}]. 1 Multiple attribute selectors for the same attribute are not supported (this includes mixing classnames and attribute selectors matching class).	3 6 Introduction This PostHTML plugin can turn simple CSS selectors into matcher objects. Supported features: • Tags: "div" returns {"tag": "div"}. • Ids: "#bar" returns {"attrs": {"id": "bar"}}. • Classes: ".foo" returns {"attrs": {"class": "foo"}}. (?:\s foo(?:\s \$) / }). Any number of classnames supported.	4 5
9 Advanced usage <pre>import matchHelper from "posthtml-match-helper"; tree.match(matchHelper("input.my-control[type!='radio'] [checked], input[value^='foo'] [checked]"), function (node) { // do stuff with matched node... });</pre>	10 Classnames with escaped characters If you need to match nodes with classnames that use escaped characters, like those in Tailwind CSS utilities with arbitrary values, use the following syntax: <pre>// do stuff with node that matched either of the selectors... });</pre>	11 <pre>import matchHelper from "posthtml-match-helper"; tree.match(matchHelper("input.\\ [display:none\\]"), function (node) { // do stuff with node that matched either of the selectors... });</pre>	12 The helper function Arguments matcher (string) - A CSS selector that describes the node you want to match in PostHTML. Returns A matcher object or an array of matcher objects.
16	15	14	13