

WOODY CONTROLLER BODY | ACRYLIC SIDE | rev A | 2 per instrument | 4 mm acrylic

Acrylic side - plan, seen from outside the body; X along the body from the mouth end, Y up from the bottom edge (in the oak bottom's groove)



CUTS AND DEPTH (one file per layer, all in one frame; depths from the face named)

face	depth	what	file (in this folder)
-	through	outline	side.dxf

NOTES

- MATERIAL: acrylic (PMMA) sheet (nominal), 4 thick (stack.side_t, nominal)
- TINT: dark grey (settled, fabrication.side_tint)
- SURFACE: frosted, on the outside face (fabrication.side_surface, side_frosted_face: tbd)
- EDGES: as laser cut (fabrication.acrylic_edge)
- TOL: profile +/-0.1 (fabrication.acrylic_profile_tol)
- HOLES: none. One closed outline, cut through
- FIT: stands in a groove in the oak top and the oak bottom (stack.groove_depth, groove_clear): the sheet's own thickness tolerance must stay inside the groove (fabrication.acrylic_profile_tol covers the profile only)
- QTY PER INSTRUMENT: 2 | BOM SIDE-ACRYLIC: TBD (candidate)

OPEN FIGURES this part depends on: 12 tbd, so blocking, of 21 tbd or nominal (each with what decides it: mechanical/fab/open-figures.csv)

stack.cap_clear, stack.side_inset, stack.groove_depth, ends.mouth_cap_t, ends.tail_cap_t, layout.mouth_extra, layout.tail_clear, layout.underside_clear, boards.sensor_lead_row, boards.umb_adapter_t, boards.board_clear, fabrication.side_frosted_face