

WIFI PASSWORD

- yellowpencil

SLIDE DOWNLOAD

- www.github.com/jeffreybergier/ga-start-building-mobile-apps

START BUILDING MOBILE APPS

AN INTRO TO IOS PROGRAMMING USING XCODE AND SWIFT

2016/05/16

*Jeffrey Bergier
UX Designer & iOS Developer*

JEFFREY BERGIER

UX Designer @ Riverbed
TA @ General Assembly

Teacher @ MobileBridge
Addicted iOS Dev @ Home



@jeffburg



jeffburg.com



WaterMe

Plant Watering
Reminders



Gratuity

The Simple Tip
Calculator

2016/05/16 – START BUILDING MOBILE APPS

AGENDA

- Mobile Intro
- Learn basics of Xcode IDE
- stretch break
- Learn programming basics with Swift
- stretch break
- Make a basic iOS application
- stretch break
- Dive a little deeper into Swift
- Resources

MOBILE INTRO

MOBILE INTRO

- 2 Primary Avenues
 - Web
 - iOS App
- Always default to web
 - Can still have dedicated app icon on home screen
 - Supports offline use
 - No “Disney” filter app review
 - Instant updates
 - No installation necessary
 - Potentially cross-platform

MOBILE INTRO

- › Why Go Native?
 - › Performance
 - › Device specific capabilities
 - › Sensors, Camera, Location, Backgrounding
 - › 3D / OpenGL / Metal
 - › Notifications
- › Note that many of the above items are now do-able on web
 - › Camera, Pictures
 - › Location
 - › Notifications (Desktop Safari only right now)

THAT BEING SAID, I LOVE NATIVE!

- › I like learning 1 language and being able to do everything
 - › As opposed to HTML/CSS/Javascript as 3 languages
- › I like that the developer ecosystem is contained
 - › Apple maintains huge influence over how things “should” work
 - › The web is a wild west of frameworks and approaches
- › I can’t stand CSS. I find Auto Layout much easier

MOBILE INTRO

- › Just remember to think critically about your project and whether the user experience will be better on web vs native
 - › Is performance stretched on Web?
 - › Is this something a user will only use 1 time and be hesitant to install permanently on their device?
 - › Does this use unique features of native?
- › e.g Amazon Shopping (great on web, terrible native)
- › e.g. Instagram (great on native, questionable on web)

SET EXPECTATIONS

- › Learning iOS
in 21 days

Days 1 - 10
Teach yourself variables, constants, arrays, strings, expressions, statements, functions,...



Days 11 - 21
Teach yourself program flow, pointers, references, classes, objects, inheritance, polymorphism,



Days 22 - 697
Do a lot of recreational programming. Have fun hacking but remember to learn from your mistakes.



Days 698 - 3648
Interact with other programmers. Work on programming projects together. Learn from them.



Days 3649 - 7781
Teach yourself advanced theoretical physics and formulate a consistent theory of quantum gravity.




Days 7782 - 14611
Teach yourself biochemistry, molecular biology, genetics,...



Day 14611
Use knowledge of biology to make an age-reversing potion.



Day 14611
Use knowledge of physics to build flux capacitor and go back in time to day 21.



Day 21
Replace younger self.



As far as I know, this is the easiest way to

"Teach Yourself C++ in 21 Days".

MOBILE INTRO

- › We are going to barely touch the surface
- › Basics of Swift
- › Basics of iOS
 - › From here on out referred to as Cocoa or Cocoa Touch
- › Leave you with resources so you can combine tonight's lesson with online resources so you can continue learning.

2016/05/16 – START BUILDING MOBILE APPS


AGENDA

- Mobile Intro
- Learn basics of Xcode IDE
- stretch break
- Learn programming basics with Swift
- stretch break
- Make a basic iOS application
- stretch break
- Dive a little deeper into Swift
- Resources

XCODE

XCODE


- › Apple's primary IDE for the iOS/watchOS/tvOS/macOS platforms
- › Available Free from Mac App Store and <http://developer.apple.com>
- › It does everything:
 - › Code editor with auto complete and warnings for common mistakes
 - › Interface Builder
 - › Compiler
 - › Debugger
 - › Unit Testing
 - › Submitting to App Store




Navigator area

Debug area

Utilities area






```
        } completion:NULL];
    } else {
        [self.gameLogo setAlpha:alpha];
        [self.warriorButton setAlpha:
         alpha];
        [self.archerButton setAlpha:alpha
        ];
    }
}

- (IBAction)chooseArcher:(id)sender {
    [self startGameWithHeroType:
     APAHeroTypeArcher];
}

#pragma mark - Starting the Game
- (void)startGameWithHeroType:
     (APAHeroType)type {
    [self hideUIElements:YES animated:YES]
```

Insert Action



A context menu is open over the "Adventure" project name in the Project Navigator. The menu items are: Adventure (disabled), Adventure iOS (selected and highlighted in blue), Edit Scheme..., New Scheme..., and Manage Schemes... .

To the right of the menu, the "Target" section of the interface shows a list of available targets:

- iOS Device
- iOS Simulator
 - iPhone Retina (3.5-inch)
 - iPhone Retina (4-inch)
 - iPad
 - iPad Retina (selected and highlighted in blue)

CPU 0% // Start the progress indicator animation.
Memory 12.6 MR [self.loadingProgressIndicator startAnimating]; Thread 1: breakpoint 2.1

-(APAViewController *) 0x97698e0
▶ UIViewController
▶ _skView = (SKView *) 0x977b410
▶ _gameLogo = (UIImageView *) 0x9773320
▶ LoadingProgressIndicator = (UIActivityIndicatorView *) 0x9774d20


A screenshot of a game logo. The word "ADVENTURE" is written in gold, stylized letters that appear to be melting or dripping down a dark, jagged rock formation. The rock formation has several dark, craggy edges and some small, white, rocky debris at the bottom.

A _gameLogo Open With Preview

e before we initialize and load it.
hCompletionHandler:^{
s.size;

o see a similar amount of the scene as on iPad.
ne to be double the size of the view, which is
nch. This effectively scales the scene to 50%.
UIUserInterfaceIdiomPhone) {


AdventureScene alloc] initWithSize:viewSize];
deAspectFill;
d1 > 0 -[APAViewController viewWillAppear:]
<CALayer: 0x9773ca0>>
Printing description of self->_gameLogo:
<UIImageView: 0x9773320; frame = (120 -10;
375 220); autoresizingMask = W+H;
userInteractionEnabled = NO; layer =
<CALayer: 0x9773ca0>>
(lldb)
d20 All Output





- = +



0 -[AAPLListDocumentsViewController prepareForSegue:sender:]







New Playground Authoring Features

New playground files in Xcode 6.3 show results in-line within the playground document. The new format also makes it easy to create gorgeous playgrounds with stylized text and embedded images. Playgrounds are perfect for documentation, tutorials, or samples you include with your projects.

Using simple plain text markup you can quickly create new headings, lists, **bold** or *italic* text, and [links](#) from within playground comments. Select the Editor -> Show Documentation as Rich Text menu option to see your playground rendered with styles enabled.

```
import Cocoa  
  
// Let's play with mathematics and an in-line graph  
for count in 0...100 {  
    sin(1000.0 / Double(count))
```



```
}
```

(101 times)

Playgrounds contain their own resource bundle. Just drag images or other assets into the Resources folder of the playground using Show Package Contents in Finder.

```
// Load a full color image directly from within the playground's Resources folder  
var vacationImage = NSImage(named: "Tortolla.jpg")
```

w 5,808 h 1,952



XCODE

- Create New Project
- Add Button and View to Storyboard
- Change the text in the button and the color of the view
- Run in the simulator
- Zip (01)

2016/05/16 – START BUILDING MOBILE APPS

AGENDA

- Mobile Intro
- Learn basics of Xcode IDE
- stretch break
- Learn programming basics with Swift
- stretch break
- Make a basic iOS application
- stretch break
- Dive a little deeper into Swift
- Resources

BREAK

2016/05/16 – START BUILDING MOBILE APPS

AGENDA

- Mobile Intro
- Learn basics of Xcode IDE
- stretch break
- Learn programming basics with Swift
- stretch break
- Make a basic iOS application
- stretch break
- Dive a little deeper into Swift
- Resources

SWIFT BASICS

SWIFT



Swift. A modern programming language
that is safe, fast, and interactive.

Swift is a powerful and intuitive programming language for iOS, OS X, tvOS, and watchOS. Writing Swift code is interactive and fun, the syntax is concise yet expressive, and apps run lightning-fast. Swift is ready for your next project — or addition into your current app — because Swift code works side-by-side with Objective-C.

SWIFT - THE GOOD



Strongly Typed

Playgrounds

Swift. A modern programming language
that is safe, fast, and interactive.

OMG! Yes!

Swift is a powerful and intuitive programming language for iOS, OS X, tvOS, watchOS. Writing Swift code is interactive and fun, the syntax is concise yet expressive, and apps run lightning-fast. Swift is ready for your next project — or addition into your current app — because Swift code works side-by-side with Objective-C.

Compatible

SWIFT - THE BAD



Swift. A modern programming language
that is safe, fast, and interactive.

Swift is a powerful and intuitive programming language for iOS, OS X, t
watchOS. Writing Swift code is interactive and fun, the syntax is concise yet expressive,
and apps run lightning-fast. Swift is ready for your next project — or addition into your
current app — because Swift code works side-by-side with Objective-C.

OMG! Yes!

Massive
Legacy

BASIC SWIFT TYPES

String

Int

Double

Bool

Optional

Array

Dictionary

DECLARING VARIABLES AND CONSTANTS

```
var myName: String = "Jeff"
```

```
let currentYear: Int = 2016
```

DECLARING VARIABLES AND CONSTANTS

```
var myName: String = "Jeff"
```

Variable
Keyword

No Semicolon! 😊

```
let currentYear: Int = 2016
```

Constant
Keyword

Name

Data Type

Data Value

DECLARING VARIABLES AND CONSTANTS

```
var myName = "Jeff"
```

Type Inference



```
let currentYear = 2016
```

BOOL

let isNervous = true

BOOL

let isNervous = true



Objective-C used
YES / NO

STRONGLY TYPED

- › Once a variable is declared, its type cannot change
 - › This is for both explicit and inferred types
- › This makes code easier to reason about
- › But it makes conversion from one type to another a PITA
- › This is where Swift differs most from “easy” languages
 - › Javascript, Python, Ruby, etc

STRONGLY TYPED

```
1 var currentYear = "MMXVI"
```

```
2 currentYear = 2016
```

! Cannot assign value of type 'Int' to type 'String'

BASIC SWIFT TYPES

String

Int

Double

Bool

Optional

Array

Dictionary

XCODE PLAYGROUND

- Create a new iOS playground
- Declare constants of type: String, Int, Double, Bool
- Show how to check type
- Try to change constant
- Zip (02)

FUNCTIONS / METHODS

```
func extendStateRestoration() {  
    // extend state here  
}
```

FUNCTIONS / METHODS

```
func extendStateRestoration() {  
    // extend state here  
}
```

Keyword

Function Name

Function arguments.
None in this case.

Opening and closing
braces for code block

FUNCTIONS / METHODS WITH ARGUMENS

```
func openURL(url: NSURL) {  
    // Log the URL to the console  
    NSLog("The URL is: \(url)")  
}
```

FUNCTIONS / METHODS WITH ARGUMENS

```
func openURL(url: NSURL){  
    // Log the URL to the console  
    NSLog("The URL is: \(url)")  
}
```

Function Name

First Argument “Internal” Name

First Argument Type

FUNCTIONS / METHODS WITH ARGUMENS

```
func openURL(url: NSURL) {  
    // Log the URL to the console  
    NSLog("The URL is: \(url)")  
}
```

Print / Log
command

String
“Interpolation”

FUNCTIONS / METHODS WITH RETURN VALUES

```
func canOpenURL(url: NSURL) -> Bool {  
    // I can totally open this URL  
    return true  
}
```

FUNCTIONS / METHODS WITH RETURN VALUES

Swift ASCII Art Indicating
there is a return value

```
func canOpenURL(url: NSURL) -> Bool {  
    // I can totally open this URL  
    return true  
}
```

Required: Any function that has
a return type must call return
before the end

Return Type

XCODE PLAYGROUND

- Create a no argument function
 - Call it
- Create a 1 argument function
 - Call it
- Create a function that returns a value
 - Call it
- Zip (03)

FUNCTIONS / METHODS WITH MULTIPLE ARGUMENTS

```
func performActionWithString1(string1: String, andString2 string2: String) {  
    NSLog(@"%@", string1)  
    NSLog(@"%@", string2)  
}
```

```
performActionWithString1("My String", andString2: "My Other String")
```

FUNCTIONS / METHODS WITH MULTIPLE ARGUMENTS

Function Name

Arg1 External Name

Arg2 External Name

```
func performActionWithString1(string1: String, andString2 string2: String) {  
    NSLog(@"%@", string1)  
    NSLog(@"%@", string2)  
}
```

Arg1 Internal Name

Arg 2 Internal Name

```
performActionWithString1("My String", andString2: "My Other String")
```

FUNCTIONS / METHODS WITH MULTIPLE ARGUMENTS

Function Name

Arg1 External Name

Arg2 External Name

```
func performActionWithString1(string1: String, andString2 string2: String) {  
    NSLog(@"%@", string1)  
    NSLog(@"%@", string2)  
}
```

Arg1 Internal Name

Arg 2 Internal Name

```
performActionWithString1("My String", andString2: "My Other String")
```

Arg1 Internal Name

Arg 2 Internal Name

METHODS SHOULD SOUND LIKE PROSE

```
-animateWithDuration:  
    delay:  
usingSpringWithDamping:  
initialSpringVelocity:  
    options:  
animations:  
completion:
```

METHODS SHOULD SOUND LIKE PROSE

```
UIView.animateWithDuration(1.0,  
    delay: 0.0,  
    usingSpringWithDamping: 1.0,  
    initialSpringVelocity: 1.0,  
    options: options,  
    animations: {  
        // finished state of the UI  
    }, completion: { success in  
        // code to run when finished  
    })
```

2016/05/16 – START BUILDING MOBILE APPS

AGENDA

- Mobile Intro
- Learn basics of Xcode IDE
- stretch break
- Learn programming basics with Swift
- stretch break
- Make a basic iOS application
- stretch break
- Dive a little deeper into Swift
- Resources

BREAK

2016/05/16 – START BUILDING MOBILE APPS


AGENDA

- Mobile Intro
- Learn basics of Xcode IDE
- stretch break
- Learn programming basics with Swift
- stretch break
- Make a basic iOS application
- stretch break
- Dive a little deeper into Swift
- Resources

IOS APP

View Controller Scene

- View Controller
 - Top Layout Guide
 - Bottom Layout Guide
- View
 - L Bill Amount:
 - F \$100
 - L Tip Amount:
 - L \$10
 - L Total Amount:
 - L \$110
 - B Calculate Tip
- First Responder
- Exit
- Storyboard Entry Point



Text Field

Text Plain
Text
Color Black Default
Font System 14.0
Alignment Center Center Center Center
Placeholder \$100
Background Background Image
Disabled Disabled Background Image
Border Style
Clear Button Never appears
Min Font Size 17
Adjust to Fit
Capitalization None
Correction Default
Spell Checking Default
Keyboard Type Default
Appearance Default
Return Key Default
Auto-enable Return Key
Secure Text Entry

Button - Intercepts touch events and sends an action message to a target object when it's tapped.

Bar Button Item - Represents an item on a UIToolbar or UINavigationItem object.

Fixed Space Bar Button Item - Represents a fixed space item on a UIToolbar object.

button

PROPERTIES AND METHODS - COCOA OBJECTS

- › Properties - Describe an object
 - › eg. A physical car has:
 - › Make
 - › Model
 - › Color
- › Methods - Functions that let an object do stuff
 - › eg. A car can do:
 - › Start engine
 - › Drive forward
- › The difference between these and our playgrounds is these live at the top level of our custom objects in Cocoa.

IBOUTLETS AND IB ACTIONS - COCOA OBJECTS

- › **IBOutlet** - Property that lets our code communicate with the interface
- › **IBAction** - Function that lets the interface communicate with our code

TIP CALCULATE SNEAK PEAK

```
import UIKit

class ViewController: UIViewController {

    @IBOutlet weak var totalAmountLabel: UILabel!
    @IBOutlet weak var tipAmountLabel: UILabel!
    @IBOutlet weak var billAmountTextField: UITextField!

    @IBAction func calculateTip(sender: UIButton) {
        // get the double value of the string in the text field
        let billAmount = Double(self.billAmountTextField.text!)!

        // hard code our tip percentage
        let tipPercentage = 0.2

        // calculate the tip amount and update the UI
        let tipAmount = billAmount * tipPercentage
        self.tipAmountLabel.text = "$\(tipAmount)"

        // calculate the total amount and update the UI
        let total = billAmount + tipAmount
        self.totalAmountLabel.text = "$\(total)"
    }
}
```

XCODE

- Create a tip calculator
- Layout the interface
- Create an IBAction for the button
- Create outlets for the labels
- Do the math
- Zip (04)

2016/05/16 – START BUILDING MOBILE APPS

AGENDA

- Mobile Intro
- Learn basics of Xcode IDE
- stretch break
- Learn programming basics with Swift
- stretch break
- Make a basic iOS application
- stretch break
- Dive a little deeper into Swift
- Resources

BREAK

2016/05/16 – START BUILDING MOBILE APPS

AGENDA

- Mobile Intro
- Learn basics of Xcode IDE
- stretch break
- Learn programming basics with Swift
- stretch break
- Make a basic iOS application
- stretch break
- Dive a little deeper into Swift
- Resources

SWIFT OPTIONALS

BASIC SWIFT TYPES

String

Int

Double

Bool

Optional

Array

Dictionary

BASIC SWIFT TYPES

~~String~~

~~Int~~

~~Double~~

~~Bool~~

Optional ←

What the heck is
this thing?

Array

Dictionary

BASIC SWIFT TYPES

~~String~~

~~Int~~

~~Double~~

~~Bool~~



Optional ←

Array

Dictionary

Swift has its own
Schrödinger Cat Type





OPTIONALS

- Optionals are actually very similar to Booleans
- Booleans are special kind of type called an ENUM(eration)
- Enums contain a set list of possible options
- For example:
 - True / False
 - Logged In / Logged Out
 - Not Downloading / Downloading / Downloaded
 - Not Downloading / Downloading / Downloaded / Error

OPTIONALS

- Optionals are just this same Enum concept but the options are
 - None
 - Some



OPTIONALS

- › Optionals are just this same Enum concept but the options are
 - › None
 - › Some



OPTIONALS

- › Optionals are just this same Enum concept but the options are
 - › None
 - › Some



OPTIONALS

- › Optionals allow Swift developers to explicitly specify what is known and when.
 - › “compile time” knowledge
 - › VS
 - › “runtime” knowledge
- › For example. Downloading an image:
 - › You have a URL. You tell the code to download the URL
 - › But there is no guarantee the server will actually send you an image
 - › It could send you a 404 error which is an HTML file... or nothing...
 - › Either way, its not an image and you don't know this at “compile time”

EXPRESSING OPTIONALITY

String?
Int?
Double?
Bool?
Anything?

? - Indicates
Optional



```
16 let imageURLString: String = "http://fantasyjunction.com/img/  
cars/xlarge/118011.jpg"  
17 let imageURL: NSURL? = NSURL(string: imageURLString)  
18 let imageData: NSData? = NSData(contentsOfURL: imageURL!)  
19 let image: UIImage? = UIImage(data: imageData!)
```



"http://fantasyjunction.co...
http://fantasyjunction.co...
<ffd8ffe0 00104a46 494...
w 800 h 533



OPTIONALS

- › ? = The type we're dealing with is optional
- › ! = I'm super confident that the cat is alive
 - › If I'm wrong, I accept that my app will crash for my users if the cat is dead
- › But, there is a way to deal with optionals in a safe way
 - › So that you can present an error to the user if the cat is dead
 - › This is never an easy conversation :-/

```
17 let imageURLString: String = "http://fantasyjunction.com/img/cars/xlarge/  
118011.jpg"  
18 let imageURL: NSURL? = NSURL(string: imageURLString)  
19  
20 if let imageURL = imageURL {  
21     // now the NSURL cat is alive  
22     let imageData = NSData(contentsOfURL: imageURL)|  
23 } else {  
24     // sorry, the NSURL cat is dead. Time to show an error to the user  
25 }
```

Confirmed String
(non-optional)



```
17 let imageURLString: String = "http://fantasyjunction.com/img/cars/xlarge/  
118011.jpg"  
18 let imageURL: NSURL? = NSURL(string: imageURLString) ← Optional NSURL  
19  
20 if let imageURL = imageURL { ← safely unwrap the optional  
21 // now the NSURL cat is alive  
22 let imageData = NSData(contentsOfURL: imageURL)|  
23 } else {  
24 // sorry, the NSURL cat is dead. Time to show an error to the user  
25 }
```

Now the imageURL constant
can be used safely

XCODE PLAYGROUNDS

- Create an optional string
- Set it to NIL
- Experiment with Printing it
- Safely Unwrap it
- Zip (05)

SWIFT COLLECTION TYPES

BASIC SWIFT TYPES

String

Int

Double

Bool

Optional

Array

Dictionary

ARRAY

- Ordered list of items
- Its #1 job in life is to keep items in order
- Strongly Typed
- Mixed Type arrays are allowed but not recommended
- Get items out by asking the array for the item at an Integer index
- Arrays are 0-indexed
- Runtime crash caused by asking the Array for an item that doesn't exist.

ARRAY

```
let pets: [String] = ["Fido", "Sable", "Jack"]
```

ARRAY

Strongly Typed

Square brackets
indicate array

```
let pets: [String] = ["Fido", "Sable", "Jack"]
```

Comma Separated

ARRAY

Type can be inferred



```
let pets = ["Fido", "Sable", "Jack"]
```

ARRAY

```
14 let myFavoritePet = pets[1]
```

"Sable"

```
15
```

```
! 16 let myLeastFavoritePet = pets[4]
```

! error

```
17 ! Execution was interrupted, reason: EXC_BAD_INSTRUCTION (code=EXC_I386_INV...
```

ARRAY

Pick your item via its number in the list

List is 0 indexed. So 1 is the second item.

Special square brackets syntax is called “Subscripting”

```
14 let myFavoritePet = pets[1]
```

"Sable"

15

```
! 16 let myLeastFavoritePet = pets[4]
```

! error

17

```
! Execution was interrupted, reason: EXC_BAD_INSTRUCTION (code=EXC_I386_INV...
```

If you ask for an entry that does not exist, you get a runtime crash.

DICTIONARY

- › Key / value pairs
- › Unordered
- › The Key is strongly typed and the Value is strongly typed
 - › But they do not need to be the same type.
- › Access the value by asking for the dictionary for it via the key.
- › Its ok to ask the dictionary for an item with a key that does not exist.
 - › It returns nothing. No crash.

DICTIONARY

```
9 let ages: [String : Int] = ["Sam" : 22, "Jim" : 49]      ["Sam": 2...
10
11 let jimsAge = ages["Jim"]                                49
12 let jessiesAge = ages["Jessie"]                          nil
```

DICTIONARY

Strongly Typed

Square bracket with Colon
indicates Dictionary

```
9 let ages: [String : Int] = ["Sam" : 22, "Jim" : 49]
10
11 let jimsAge = ages["Jim"]
12 let jessiesAge = ages["Jessie"]
```

["Sam": 2...

49
nil

Subscripting to get
the value out

When you ask for something
that doesn't exist, you get NIL

XCODE PLAYGROUNDS

- Create an Array
- Get an item out of the array
- Create a dictionary
- Get an item out of the dictionary
- Zip (06)

2016/05/16 – START BUILDING MOBILE APPS

AGENDA

- Mobile Intro
- Learn basics of Xcode IDE
- stretch break
- Learn programming basics with Swift
- stretch break
- Make a basic iOS application
- stretch break
- Dive a little deeper into Swift
- Resources

SWIFT AND COCOA TOUCH RESOURCES

RESOURCES

<https://www.raywenderlich.com/category/swift>

Alternative – For Complete Beginners to Programming

The iOS Apprentice is the best option, but if you don't feel like signing up for the newsletter, don't worry - we have an alternative option for you.

This series is a gentle introduction to Swift for those who are completely new to programming. Enjoy!

- [Learn to Code iOS Apps with Swift Tutorial 1: Welcome to Programming](#)
- [Learn to Code iOS Apps with Swift Tutorial 2: Your First Project](#)
- [Learn to Code iOS Apps with Swift Tutorial 3: Arrays, Objects, and Classes](#)
- [Learn To Code iOS Apps With Swift Tutorial 4: Your First App](#)
- [Learn To Code iOS Apps With Swift Tutorial 5: Making it Beautiful](#)

Alternative – For Experienced Programmers

If you are already an experienced programmer and want a "quick start" to Swift, this is the best option for you.

In this series, you'll learn the basics of the Swift language, and will make a basic tip calculator app using what you have learned.

- [Swift 2 Tutorial: A Quick Start](#)
- [Swift 2 Tutorial Part 2: A Simple iOS App](#)
- [Swift 2 Tutorial Part 3: Tuples, Protocols, Delegates, and Table Views](#)



2016/05/16 – START BUILDING MOBILE APPS

AGENDA

- Mobile Intro
- Learn basics of Xcode IDE
- stretch break
- Learn programming basics with Swift
- stretch break
- Make a basic iOS application
- stretch break
- Dive a little deeper into Swift
- Resources

Q&A

(SLIDES)

<https://github.com/jeffreybergier/ga-start-building-mobile-apps>

*Jeffrey Bergier
UX Designer & iOS Developer*