



IMDG - UN card

UN 1057

UN number 1057		Shipping name LIGHTERS / LIGHTER REFILLS LIGHTERE / REFILLER TIL LIGHTERE				
Class 2.1	Packing group —	Hazard labels 2.1	Marine pollutant Maybe	EmS F-D, S-U	<i>ADR transport category: 2 ADR tunnel: (D)</i>	
Hazard labels 		Marking UN 1057 LIGHTERS / LIGHTER REFILLS				
Packaging Can be packed in approved packaging according to packing instruction P002. Note: Rigid outer packagings meeting the packing group II performance level shall be used. The packagings shall be designed and constructed and arranged to prevent movement, inadvertent ignition of the devices or inadvertent release of flammable gas or liquid (PP84).						
Mixed packaging The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.						
Remarks Lighters and lighter refills shall comply with the provisions of the country in which they were filled. They shall be provided with protection against inadvertent discharge. The liquid portion of the gas shall not exceed 85% of the capacity of the receptacle at 15°C. The receptacles, including the closures, shall be capable of withstanding an internal pressure of twice the pressure of the liquefied petroleum gas at 55°C. The valve mechanisms and ignition devices shall be securely sealed, taped or otherwise fastened or designed to prevent operation or leakage of the contents during transport. Lighters shall not contain more than 10 g of liquefied petroleum gas. Lighter refills shall not contain more than 65 g of liquefied petroleum gas (SP 201).						
Properties and observations Lighters or lighter refills containing butane or other flammable gas.						
Tank type: Not allowed		Transport in bulk		Orange panel		
Tank provisions: —		Not allowed		1057		
Stowage and segregation						
Stowage Stay clear of living quarters (SW2).						
Segregation Check the segregation table for sea transport. There are no special requirements for segregation.						
Placarding of the transport unit Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.						
Foodstuff The substance is not required to be kept separate from food and feed.						
Limited quantities (LQ) <i>Combination packaging</i> Inner: Not allowed Outer: <i>Trays</i> Inner: Not allowed Outer:			Excepted quantities (EQ) <i>Combination packaging</i> Inner: Not allowed Outer:			