



IMDG - UN card

UN 1080

UN number 1080		Shipping name SULPHUR HEXAFLUORIDE SVOVLHEXAFLUORID				
Class 2.2	Packing group —	Hazard labels 2.2	Marine pollutant Maybe	EmS F-C, S-V	<i>ADR transport category: 3 ADR tunnel: (C/E)</i>	
Hazard labels 		Marking UN 1080 SULPHUR HEXAFLUORIDE				
Packaging		Can be packed in approved packaging according to packing instruction P200.				
Mixed packaging		The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.				
Remarks		See special provision 392 in the IMDG Code.				
Properties and observations		Liquefied, non-flammable, odourless gas. Much heavier than air (5.1).				
Tank type:		Transport in bulk		Orange panel		
Not allowed		Not allowed				
Tank provisions:		—				
Stowage and segregation						
Stowage		There are no special requirements for stowage.				
Segregation		Check the segregation table for sea transport. There are no special requirements for segregation.				
Placarding of the transport unit		Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.				
Foodstuff		The substance is not required to be kept separate from food and feed.				
Limited quantities (LQ)		Parcel label:		Excepted quantities (EQ)		
<i>Combination packaging</i> Inner: 120 mL Outer: 30 kg				<i>Combination packaging</i> Inner: 30 mL Outer: 1000 mL		
<i>Trays</i> Inner: 120 mL Outer: 20 kg				Must be packed in an intermediate packaging with cushioning material. Max 1000 parcels per vehicle/container.		
						