



IMDG - UN card

UN 1157

UN number 1157		Shipping name DIISOBUTYL KETONE DIISOBUTYLKETON				
Class 3	Packing group III	Hazard labels 3	Marine pollutant Maybe	EmS F-E, S-D	<i>ADR transport category: 3</i> <i>ADR tunnel: (D/E)</i>	
Hazard labels 		Marking UN 1157 DIISOBUTYL KETONE				
Packaging Can be packed in approved packaging according to packing instruction P001. Can also be packaged in large packagings (LP01).						
Mixed packaging The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.						
Remarks There are no special provisions for this substance.						
Properties and observations Colourless liquid. Flashpoint: 49 °C c.c. Explosive limits: 0.8% to 7.1%. Immiscible with water.						
Tank type: T2		Transport in bulk		Orange panel		
Tank provisions: TP1		Not allowed		1157		
Stowage and segregation						
Stowage There are no special requirements for stowage.						
Segregation Check the segregation table for sea transport. There are no special requirements for segregation.						
Placarding of the transport unit Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.						
Foodstuff The substance is not required to be kept separate from food and feed.						
Limited quantities (LQ) <i>Combination packaging</i> Inner: 5 L Outer: 30 kg <i>Trays</i> Inner: 5 L Outer: 20 kg		Parcel label: 				
		Excepted quantities (EQ) <i>Combination packaging</i> Inner: 30 mL Outer: 1000 mL Must be packed in an intermediate packaging with cushioning material. Max 1000 parcels per vehicle/container.				
		Parcel label: 				