



IMDG - UN card

UN 1194

UN number 1194		Shipping name ETHYL NITRITE SOLUTION ETHYLNITRITOPLØSNING				
Class 3	Packing group I	Hazard labels 3+6.1	Marine pollutant Maybe	EmS F-E, S-D	ADR transport category: 1 ADR tunnel: (C/E)	
Hazard labels  		Marking UN 1194 ETHYL NITRITE SOLUTION				
Packaging	Can be packed in approved packaging according to packing instruction P001.					
Mixed packaging	The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.					
Remarks	The transport of the following substances is prohibited: AMMONIUM HYPOCHLORITE; AMMONIUM NITRATE liable to self-heating sufficient to initiate decomposition; AMMONIUM NITRITES and mixtures of an inorganic nitrite with an ammonium salt; CHLORIC ACID, AQUEOUS SOLUTION with more than 10% chloric acid; ETHYL NITRITE pure; HYDROCYANIC ACID, AQUEOUS SOLUTION (HYDROGEN CYANIDE, AQUEOUS SOLUTION) with more than 20% hydrogen cyanide; HYDROGEN CHLORIDE, REFRIGERATED LIQUID; HYDROGEN CYANIDE SOLUTION, IN ALCOHOL with more than 45% hydrogen cyanide; MERCURY OXYCYANIDE pure; METHYL NITRITE; PERCHLORIC ACID with more than 72% acid, by mass; SILVER PICRATE, dry or wetted with less than 30% water by mass; ZINC AMMONIUM NITRITE. See also special provisions 349, 350, 351, 352 and 353 (SP 900).					
Properties and observations	Alcoholic solution of ethyl nitrite. Extremely volatile, with an aromatic, ethereal odour. Explosive limits of the pure product: 3% to 50%. Boiling point of pure product: 17 °C. Miscible or partially miscible with water. Decomposes under exposure to air, light, water or heat to evolve toxic nitrous fumes. Toxic if swallowed, by skin contact or by inhalation. Inhalation of ethyl nitrite vapours, even in small quantities, rapidly affects the heart and can be dangerous. Transport of ETHYL NITRITE pure is prohibited.					
Tank type:	Not allowed	Transport in bulk		Orange panel		
Tank provisions:	–	Not allowed		1194		
Stowage and segregation						
Stowage	Stay clear of living quarters (SW2).					
Segregation	Check the segregation table for sea transport. There are no special requirements for segregation.					
Placarding of the transport unit	Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.					
Foodstuff	The substance must be kept separate from food and feedstuffs.					
Limited quantities (LQ)			Excepted quantities (EQ)			
Combination packaging			Combination packaging			
Inner: Not allowed			Inner: Not allowed			
Outer:			Outer:			
Trays						
Inner: Not allowed						
Outer:						