



IMDG - UN card

UN 1251

UN number 1251		Shipping name METHYL VINYL KETONE, STABILIZED METHYLVINYLKETON, STABILISERET				
Class 6.1	Packing group I	Hazard labels 6.1+3+8	Marine pollutant Maybe	EmS F-E, S-C	<i>ADR transport category: 1</i> <i>ADR tunnel: (C/D)</i>	
Hazard labels   		Marking UN 1251 METHYL VINYL KETONE, STABILIZED				
Packaging	Can be packed in approved packaging according to packing instruction P601.					
Mixed packaging	The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.					
Remarks	This substance is toxic by inhalation (SP 354). When substances are stabilized by temperature control, the provisions of 7.3.7 apply. When chemical stabilization is employed, the person offering the packaging, IBC or tank for transport shall ensure that the level of stabilization is sufficient to prevent the substance in the packaging, IBC or tank from dangerous polymerization at a bulk mean temperature of 50°C, or, in the case of a portable tank, 45°C. Where chemical stabilization becomes ineffective at lower temperatures within the anticipated duration of transport, temperature control is required. In making this determination factors to be taken into consideration include, but are not limited to, the capacity and geometry of the packaging, IBC or tank and the effect of any insulation present, the temperature of the substance when offered for transport, the duration of the journey and the ambient temperature conditions typically encountered in the journey (considering also the season of year), the effectiveness and other properties of the stabilizer employed, applicable operational controls imposed by regulation (e.g. requirements to protect from sources of heat, including other cargo transported at a temperature above ambient) and any other relevant factors." (SP 386).					
Properties and observations	Colourless liquid with a pungent odour. Miscible with water. Explosive limits: 2.1% to 15.6%. Flashpoint: -7 °C c.c. Highly toxic if swallowed, by skin contact or by inhalation. Causes burns to skin, eyes and mucous membranes.					
Tank type:	T22	Transport in bulk		Orange panel		
Tank provisions:	TP2 TP13	Not allowed		1251		
Stowage and segregation						
Stowage	Must be protected from sources of heat (SW1). Stay clear of living quarters (SW2).					
Segregation	Segregation as for class 3 (SG5). Stow "away from" class 4.1 (SG8). "Away from": May not be loaded into the same transport unit without the permission of the authorities.					
Placarding of the transport unit	Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.					
Foodstuff	The substance must be kept separate from food and feedstuffs.					
Limited quantities (LQ)			Excepted quantities (EQ)			
<i>Combination packaging</i> Inner: Not allowed Outer:			<i>Combination packaging</i> Inner: Not allowed Outer:			
<i>Trays</i> Inner: Not allowed Outer:						