



IMDG - UN card

UN 1259

UN number 1259		Shipping name NICKEL CARBONYL NICKELCARBONYL				
Class 6.1	Packing group I	Hazard labels 6.1+3	Marine pollutant Yes	EmS F-E, S-D	<i>ADR transport category: 1</i> <i>ADR tunnel: (C/D)</i>	
Hazard labels   		Marking UN 1259 NICKEL CARBONYL				
Packaging		Can be packed in approved packaging according to packing instruction P601.				
Mixed packaging		The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.				
Remarks		There are no special provisions for this substance.				
Properties and observations		Colourless or yellow, volatile, flammable liquid. Flashpoint: below -20 °C c.c. Oxidizes in air and explodes at a temperature of 60 °C. Lower explosive limit: 2.0%. Immiscible with water. Highly toxic if swallowed, by skin contact or by inhalation.				
Tank type:	Not allowed	Transport in bulk		Orange panel		
Tank provisions:	—	Not allowed		1259		
Stowage and segregation						
Stowage		Stay clear of living quarters (SW2).				
Segregation		Check the segregation table for sea transport. Stow “separated longitudinally by an intervening complete compartment or hold from” class 1 (SG63).				
Placarding of the transport unit		Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.				
Foodstuff		The substance must be kept separate from food and feedstuffs.				
Limited quantities (LQ)			Excepted quantities (EQ)			
<i>Combination packaging</i> Inner: Not allowed Outer:			<i>Combination packaging</i> Inner: Not allowed Outer:			
<i>Trays</i> Inner: Not allowed Outer:						