



IMDG - UN card

UN 1303

UN number 1303	Shipping name VINYLIDENE CHLORIDE, STABILIZED VINYLIDENCHLORID, STABILISERET					
Class 3	Packing group I	Hazard labels 3	Marine pollutant Yes	EmS F-E, S-D	ADR transport category: 1 ADR tunnel: (D/E)	
Hazard labels  		Marking UN 1303 VINYLIDENE CHLORIDE, STABILIZED				
Packaging	Can be packed in approved packaging according to packing instruction P001.					
Mixed packaging	The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.					
Remarks	When substances are stabilized by temperature control, the provisions of 7.3.7 apply. When chemical stabilization is employed, the person offering the packaging, IBC or tank for transport shall ensure that the level of stabilization is sufficient to prevent the substance in the packaging, IBC or tank from dangerous polymerization at a bulk mean temperature of 50°C, or, in the case of a portable tank, 45°C. Where chemical stabilization becomes ineffective at lower temperatures within the anticipated duration of transport, temperature control is required. In making this determination factors to be taken into consideration include, but are not limited to, the capacity and geometry of the packaging, IBC or tank and the effect of any insulation present, the temperature of the substance when offered for transport, the duration of the journey and the ambient temperature conditions typically encountered in the journey (considering also the season of year), the effectiveness and other properties of the stabilizer employed, applicable operational controls imposed by regulation (e.g. requirements to protect from sources of heat, including other cargo transported at a temperature above ambient) and any other relevant factors." (SP 386).					
Properties and observations	Colourless to straw-coloured, volatile liquid with a sweet odour. Flashpoint: -28 °C c.c. Explosive limits: 6.5% to 15.5%. Boiling point: 32 °C. Immiscible with water.					
Tank type:	T12	Transport in bulk		Orange panel		
Tank provisions:	TP2 TP7	Not allowed		1303		
Stowage and segregation						
Stowage	Must be protected from sources of heat (SW1). Stay clear of living quarters (SW2).					
Segregation	Check the segregation table for sea transport. The substance belongs to group: liquid halogenated hydrocarbons (SGG10).					
Placarding of the transport unit	Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.					
Foodstuff	The substance is not required to be kept separate from food and feed.					
Limited quantities (LQ)			Excepted quantities (EQ)			
Combination packaging			Combination packaging			
Inner: Not allowed			Inner: 30 mg el. mL			
Outer:			Outer: 300 mg el. mL			
Trays			Must be packed in an intermediate packaging with cushioning material. Max 1000 parcels per vehicle/container.			
Inner: Not allowed						
Outer:						
			Parcel label: 			