



IMDG - UN card

UN 1362

UN number 1362		Shipping name 🇬🇧 CARBON, ACTIVATED 🇩🇪 KUL, AKTIVT				
Class 4.2	Packing group III	Hazard labels 4.2	Marine pollutant Maybe	EmS F-A, S-J	<i>ADR transport category: 4 ADR tunnel: (E)</i>	
Hazard labels 		Marking UN 1362 CARBON, ACTIVATED				
Packaging	Can be packed in approved packaging according to packing instruction P002. Note: 5H1, 5L1 and 5M1 bags are allowed if they are overpacked in plastic bags and are wrapped in shrink or stretch wrap on pallets (PP11). Packagings shall be hermetically sealed (PP31).					
Mixed packaging	The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.					
Remarks	If the chemical or physical properties of a substance covered by this description are such that, when tested, it does not meet the established defining criteria for the class or division listed in column 3, or any other class or division, it is not subject to the provisions of the IMDG Code except in the case of a marine pollutant where 2.10.3 applies (SP 223). The provisions of the IMDG Code do not apply to: non-activated carbon blacks of mineral origin; a consignment of carbon if it passes the tests for self-heating substances as reflected in the Manual of Tests and Criteria (see 33.4.3.3), and is accompanied by a certificate from a laboratory accredited by the competent authority, stating that the product to be loaded has been correctly sampled by trained staff from that laboratory and that the sample was correctly tested and has passed the test; and carbons made by a steam activation process (SP 925).					
Properties and observations	Black powder or granules. Liable to heat slowly and ignite spontaneously in air. The material as offered for shipment should have been sufficiently heat-treated and should be cooled down to ambient temperature before packing.					
Tank type:	T1	Transport in bulk		Orange panel		
Tank provisions:	TP33	Not allowed		1362		
Stowage and segregation						
Stowage	Must be protected from sources of heat (SW1). Keep as cool as reasonably practicable (H2).					
Segregation	Check the segregation table for sea transport. There are no special requirements for segregation.					
Placarding of the transport unit	Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.					
Foodstuff	The substance is not required to be kept separate from food and feed.					
Limited quantities (LQ)			Excepted quantities (EQ)			
<i>Combination packaging</i>			<i>Combination packaging</i>			
Inner: Not allowed			Inner: 30 mg el. mL			
Outer:			Outer: 1000 mg el. mL			
<i>Trays</i>			Must be packed in an intermediate packaging with cushioning material. Max 1000 parcels per vehicle/container.			
Inner: Not allowed						
Outer:						
			Parcel label: 			