




IMDG - UN card

UN 1395

UN number 1395	Shipping name ALUMINIUM FERROSILICON POWDER ALUMINIUMFERROSILICIUMPULVER				
Class 4.3	Packing group II	Hazard labels 4.3+6.1	Marine pollutant Maybe	EmS F-G, S-N	<i>ADR transport category: 2 ADR tunnel: (D/E)</i>
Hazard labels  		Marking UN 1395 ALUMINIUM FERROSILICON POWDER			
Packaging	Can be packed in approved packaging according to packing instruction P410. Note: Packagings shall be hermetically sealed (PP31). Bags are not allowed (PP40).				
Mixed packaging	The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.				
Remarks	Requires a certificate from the maker or shipper, stating that the shipment was stored under cover, but in the open air, in the size in which it was packaged, for not less than 3 days prior to shipment (SP 932).				
Properties and observations	In contact with water, caustic alkalis or acids, evolves hydrogen, a flammable gas. Impurities may, under similar circumstances, produce phosphine and arsine, which are highly toxic gases.				
Tank type:	T3	Transport in bulk		Orange panel	
Tank provisions:	TP33	BK2		1395	
Stowage and segregation					
Stowage	Stay clear of living quarters (SW2). If under deck, stow in a mechanically ventilated space (SW5). Keep as dry as reasonably practicable (H1).				
Segregation	Check the segregation table for sea transport. In addition: from goods of classes 2.1 and 3 when stowed on deck of a containership a minimum distance of two container spaces athwartship shall be maintained, when stowed on ro-ro ships a distance of 6 m athwartship shall be maintained (SG26). Stow "away from" SGG10 – liquid halogenated hydrocarbons (SG32). Stow "separated from" SGG1 – acids (SG35). Stow "separated from" SGG18 – alkalis (SG36). "Away/seperated from": May not be loaded into the same transport unit.				
Placarding of the transport unit	Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.				
Foodstuff	The substance must be kept separate from food and feedstuffs.				
Limited quantities (LQ) <i>Combination packaging</i> Inner: 500 g Outer: 30 kg <i>Trays</i> Inner: 500 g Outer: 20 kg		Excepted quantities (EQ) <i>Combination packaging</i> Inner: 30 mg el. mL Outer: 500 mg el. mL Must be packed in an intermediate packaging with cushioning material. Max 1000 parcels per vehicle/container.			
Parcel label: 		Parcel label: 			