



IMDG - UN card

UN 1398

UN number 1398		Shipping name ALUMINIUM SILICON POWDER, UNCOATED ALUMINIUMSILICIUMPULVER, IKKE OVERTRUKKET				
Class 4.3	Packing group III	Hazard labels 4.3	Marine pollutant Maybe	EmS F-G, S-N	<i>ADR transport category: 3 ADR tunnel: (E)</i>	
Hazard labels 		Marking UN 1398 ALUMINIUM SILICON POWDER, UNCOATED				
Packaging		Can be packed in approved packaging according to packing instruction P410. Note: Packagings shall be hermetically sealed (PP31).				
Mixed packaging		The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.				
Remarks		When coated, this substance is not subject to the provisions of the IMDG Code (SP 37). If the chemical or physical properties of a substance covered by this description are such that, when tested, it does not meet the established defining criteria for the class or division listed in column 3, or any other class or division, it is not subject to the provisions of the IMDG Code except in the case of a marine pollutant where 2.10.3 applies (SP 223). Requires a certificate from the maker or shipper, stating that the shipment was stored under cover, but in the open air, in the size in which it was packaged, for not less than 3 days prior to shipment (SP 932).				
Properties and observations		In contact with water, caustic alkalis or acids, generates heat and evolves hydrogen, a flammable gas. May also evolve silanes, which are toxic and may ignite spontaneously.				
Tank type: T1		Transport in bulk BK2			Orange panel 1398	
Tank provisions: TP33						
Stowage and segregation						
Stowage		Stay clear of living quarters (SW2). If under deck, stow in a mechanically ventilated space (SW5). Keep as dry as reasonably practicable (H1).				
Segregation		Check the segregation table for sea transport. The substance belongs to group: powdered metals (SGG15). In addition: from goods of classes 2.1 and 3 when stowed on deck of a containership a minimum distance of two container spaces athwartship shall be maintained, when stowed on ro-ro ships a distance of 6 m athwartship shall be maintained (SG26). Stow "away from" SGG10 – liquid halogenated hydrocarbons (SG32). Stow "separated from" SGG1 – acids (SG35). Stow "separated from" SGG18 – alkalis (SG36). "Away/separated from": May not be loaded into the same transport unit.				
Placarding of the transport unit		Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.				
Foodstuff		The substance is not required to be kept separate from food and feed.				
Limited quantities (LQ) <i>Combination packaging</i> Inner: 1 kg Outer: 30 kg <i>Trays</i> Inner: 1 kg Outer: 20 kg		Parcel label: 		Excepted quantities (EQ) <i>Combination packaging</i> Inner: 30 mg Outer: 1000 mg Must be packed in an intermediate packaging with cushioning material. Max 1000 parcels per vehicle/container. 		