



IMDG - UN card

UN 1408

UN number 1408		Shipping name FERROSILICON FERROSILICIUM				
Class 4.3	Packing group III	Hazard labels 4.3+6.1	Marine pollutant Maybe	EmS F-G, S-N	ADR transport category: 3 ADR tunnel: (E)	
Hazard labels  		Marking UN 1408 FERROSILICON				
Packaging		Can be packed in suitable packaging according to packing instruction P003. Note: Any sift-proof, tearproof receptacle may be used (PP20). The packaging shall be vented (PP10).				
Mixed packaging		The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.				
Remarks		This substance, when it contains less than 30% or not less than 90% silicon, is not subject to the provisions of the IMDG Code (SP 39). If the chemical or physical properties of a substance covered by this description are such that, when tested, it does not meet the established defining criteria for the class or division listed in column 3, or any other class or division, it is not subject to the provisions of the IMDG Code except in the case of a marine pollutant where 2.10.3 applies (SP 223). Requires a certificate from the maker or shipper, stating that the shipment was stored under cover, but in the open air, in the size in which it was packaged, for not less than 3 days prior to shipment (SP 932).				
Properties and observations		In contact with moisture, water, alkalis or acids, may evolve hydrogen, a flammable gas, which may form explosive mixtures with air, and also arsine and phosphine, which are highly toxic gases. These gases are evolved in proportions which, under mechanically ventilated conditions, make the poison hazard by far predominant over the explosion hazard. The rate of gas evolution is greatest from freshly broken surfaces, so is liable to increase whenever the cargo is disturbed, such as during loading. Toxic if swallowed, by skin contact or by vapour inhalation.				
Tank type:	T1	Transport in bulk		Orange panel		
Tank provisions:	TP33	BK2		1408		
Stowage and segregation						
Stowage		Stay clear of living quarters (SW2). If under deck, stow in a mechanically ventilated space (SW5). Keep as dry as reasonably practicable (H1).				
Segregation		Check the segregation table for sea transport. In addition: from goods of classes 2.1 and 3 when stowed on deck of a containership a minimum distance of two container spaces athwartship shall be maintained, when stowed on ro-ro ships a distance of 6 m athwartship shall be maintained (SG26). Stow "separated from" SGG1 – acids (SG35). Stow "separated from" SGG18 – alkalis (SG36). "Seperated from": May not be loaded into the same transport unit.				
Placarding of the transport unit		Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.				
Foodstuff		The substance must be kept separate from food and feedstuffs.				
Limited quantities (LQ) <i>Combination packaging</i> Inner: 1 kg Outer: 30 kg <i>Trays</i> Inner: 1 kg Outer: 20 kg		Parcel label: 		Excepted quantities (EQ) <i>Combination packaging</i> Inner: 30 mg Outer: 1000 mg Must be packed in an intermediate packaging with cushioning material. Max 1000 parcels per vehicle/container. 		