



IMDG - UN card

UN 1418

UN number 1418		Shipping name MAGNESIUM POWDER / MAGNESIUM ALLOYS POWDER MAGNESIUMPULVER / MAGNESIUMLEGERINGSPULVER				
Class 4.3	Packing group III	Hazard labels 4.3+4.2	Marine pollutant Maybe	EmS F-G, S-O	ADR transport category: 3 ADR tunnel: (E)	
Hazard labels 		Marking UN 1418 MAGNESIUM POWDER / MAGNESIUM ALLOYS POWDER				
Packaging Can be packed in approved packaging according to packing instruction P410. Note: Packagings shall be hermetically sealed (PP31).						
Mixed packaging The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.						
Remarks If the chemical or physical properties of a substance covered by this description are such that, when tested, it does not meet the established defining criteria for the class or division listed in column 3, or any other class or division, it is not subject to the provisions of the IMDG Code except in the case of a marine pollutant where 2.10.3 applies (SP 223).						
Properties and observations In contact with moisture, water or acids, evolves hydrogen, a flammable gas. Magnesium dust is easily ignited, causing explosion. May explode when in contact with oxidizing substances. For fire-fighting purposes, dry lithium chloride powder, dry sodium chloride or graphite powder should be carried on board when this substance is transported. Reacts with liquid halogenated hydrocarbons.						
Tank type: T1		Transport in bulk			Orange panel	
Tank provisions: TP33		Not allowed			1418	
Stowage and segregation						
Stowage		Keep as dry as reasonably practicable (H1).				
Segregation		Check the segregation table for sea transport. The substance belongs to group: powdered metals (SGG15). In addition: from goods of classes 2.1 and 3 when stowed on deck of a containership a minimum distance of two container spaces athwartship shall be maintained, when stowed on ro-ro ships a distance of 6 m athwartship shall be maintained (SG26). Stow "away from" SGG10 – liquid halogenated hydrocarbons (SG32). Stow "separated from" SGG1 – acids (SG35). "Away/seperated from": May not be loaded into the same transport unit.				
Placarding of the transport unit		Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.				
Foodstuff		The substance is not required to be kept separate from food and feed.				
Limited quantities (LQ)				Excepted quantities (EQ)		
Combination packaging				Combination packaging		
Inner: Not allowed				Inner: 30 mg el. mL		
Outer:				Outer: 1000 mg el. mL		
Trays				Must be packed in an intermediate packaging with cushioning material. Max 1000 parcels per vehicle/container.		
Inner: Not allowed						
Outer:						