



IMDG - UN card

UN 1559

UN number 1559		Shipping name ARSENIC PENTOXIDE ARSEN PENTAOXID				
Class 6.1	Packing group II	Hazard labels 6.1	Marine pollutant Maybe	EmS F-A, S-A	<i>ADR transport category: 2 ADR tunnel: (D/E)</i>	
Hazard labels 		Marking UN 1559 ARSENIC PENTOXIDE				
Packaging Can be packed in approved packaging according to packing instruction P002.						
Mixed packaging The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.						
Remarks There are no special provisions for this substance.						
Properties and observations White, deliquescent powder. Soluble in water. Toxic if swallowed, by skin contact or by dust inhalation.						
Tank type: T3		Transport in bulk		Orange panel		
Tank provisions: TP33		Not allowed		1559		
Stowage and segregation						
Stowage There are no special requirements for stowage.						
Segregation Check the segregation table for sea transport. There are no special requirements for segregation.						
Placarding of the transport unit Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.						
Foodstuff The substance must be kept separate from food and feedstuffs.						
Limited quantities (LQ) <i>Combination packaging</i> Inner: 500 g Outer: 30 kg <i>Trays</i> Inner: 500 g Outer: 20 kg		Parcel label: 				
		Excepted quantities (EQ) <i>Combination packaging</i> Inner: 1 mg el. mL Outer: 500 mg el. mL Must be packed in an intermediate packaging with cushioning material. Max 1000 parcels per vehicle/container.				
		Parcel label: 				