




IMDG - UN card

UN 1644

UN number 1644		Shipping name MERCURY SALICYLATE KVIKSØLV SALICYLAT				
Class 6.1	Packing group II	Hazard labels 6.1	Marine pollutant Yes	EmS F-A, S-A	<i>ADR transport category: 2</i> <i>ADR tunnel: (D/E)</i>	
Hazard labels  		Marking UN 1644 MERCURY SALICYLATE				
Packaging		Can be packed in approved packaging according to packing instruction P002.				
Mixed packaging		The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.				
Remarks		There are no special provisions for this substance.				
Properties and observations		White powder. Insoluble in water. Toxic if swallowed, by skin contact or by dust inhalation.				
Tank type: T3		Transport in bulk		Orange panel		
Tank provisions: TP33		Not allowed		1644		
Stowage and segregation						
Stowage		There are no special requirements for stowage.				
Segregation		Check the segregation table for sea transport. The substance belongs to group: heavy metals and their salts (including their organometallic compounds) (SGG7). The substance belongs to group: mercury and mercury compounds (SGG11).				
Placarding of the transport unit		Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.				
Foodstuff		The substance must be kept separate from food and feedstuffs.				
Limited quantities (LQ) <i>Combination packaging</i> Inner: 500 g Outer: 30 kg <i>Trays</i> Inner: 500 g Outer: 20 kg		Parcel label: 		Excepted quantities (EQ) <i>Combination packaging</i> Inner: 1 mg el. mL Outer: 500 mg el. mL Must be packed in an intermediate packaging with cushioning material. Max 1000 parcels per vehicle/container. 		