



IMDG - UN card

UN 1829

UN number 1829		Shipping name SULPHUR TRIOXIDE, STABILIZED SVOVLTRIOXID, STABILISERET				
Class 8	Packing group I	Hazard labels 8	Marine pollutant Maybe	EmS F-A, S-B	ADR transport category: 1 ADR tunnel: (E)	
Hazard labels 		Marking UN 1829 SULPHUR TRIOXIDE, STABILIZED				
Packaging		Can be packed in approved packaging according to packing instruction P001.				
Mixed packaging		The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.				
Remarks		When substances are stabilized by temperature control, the provisions of 7.3.7 apply. When chemical stabilization is employed, the person offering the packaging, IBC or tank for transport shall ensure that the level of stabilization is sufficient to prevent the substance in the packaging, IBC or tank from dangerous polymerization at a bulk mean temperature of 50°C, or, in the case of a portable tank, 45°C. Where chemical stabilization becomes ineffective at lower temperatures within the anticipated duration of transport, temperature control is required. In making this determination factors to be taken into consideration include, but are not limited to, the capacity and geometry of the packaging, IBC or tank and the effect of any insulation present, the temperature of the substance when offered for transport, the duration of the journey and the ambient temperature conditions typically encountered in the journey (considering also the season of year), the effectiveness and other properties of the stabilizer employed, applicable operational controls imposed by regulation (e.g. requirements to protect from sources of heat, including other cargo transported at a temperature above ambient) and any other relevant factors." (SP 386).				
Properties and observations		Very deliquescent solid. Melting point may be as low as 17 °C. Reacts violently with water, generating heat. May cause fire in contact with organic materials such as wood, cotton or straw. In the presence of moisture, highly corrosive to most metals. Causes severe burns to skin, eyes and mucous membranes.				
Tank type: T20		Transport in bulk		Orange panel		
Tank provisions: TP4 TP13 TP25 TP26		Not allowed		1829		
Stowage and segregation						
Stowage		Must be protected from sources of heat (SW1). Stay clear of living quarters (SW2).				
Segregation		Check the segregation table for sea transport. The substance belongs to group: acids (SGG1). Stow "separated from" SGG18 – alkalis (SG36). Stow "separated from" SGG6 – cyanides (SG49). "Seperated from": May not be loaded into the same transport unit.				
Placarding of the transport unit		Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.				
Foodstuff		The substance must be kept separate from food and feedstuffs.				
Limited quantities (LQ)			Excepted quantities (EQ)			
Combination packaging Inner: Not allowed Outer:			Combination packaging Inner: Not allowed Outer:			
Trays Inner: Not allowed Outer:						