



IMDG - UN card

UN 1863

UN number 1863		Shipping name FUEL, AVIATION, TURBINE ENGINE FLYBRÆNDSTOF				
Class 3	Packing group III	Hazard labels 3	Marine pollutant Maybe	EmS F-E, S-E	<i>ADR transport category: 3 ADR tunnel: (D/E)</i>	
Hazard labels 		Marking UN 1863 FUEL, AVIATION, TURBINE ENGINE				
Packaging		Can be packed in approved packaging according to packing instruction P001. Can also be packaged in large packagings (LP01).				
Mixed packaging		The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.				
Remarks		If the chemical or physical properties of a substance covered by this description are such that, when tested, it does not meet the established defining criteria for the class or division listed in column 3, or any other class or division, it is not subject to the provisions of the IMDG Code except in the case of a marine pollutant where 2.10.3 applies (SP 223).				
Properties and observations		Immiscible with water.				
Tank type: T2		Transport in bulk		Orange panel		
Tank provisions: TP1		Not allowed		1863		
Stowage and segregation						
Stowage		There are no special requirements for stowage.				
Segregation		Check the segregation table for sea transport. There are no special requirements for segregation.				
Placarding of the transport unit		Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.				
Foodstuff		The substance is not required to be kept separate from food and feed.				
Limited quantities (LQ)		Parcel label:		Excepted quantities (EQ)		
Combination packaging				Combination packaging		
Inner: 5 L				Inner: 30 mL		
Outer: 30 kg				Outer: 1000 mL		
Trays				Must be packed in an intermediate packaging with cushioning material. Max 1000 parcels per vehicle/container.		
Inner: 5 L						
Outer: 20 kg						