



IMDG - UN card

UN 1869

UN number 1869		Shipping name MAGNESIUM / MAGNESIUM ALLOYS MAGNESIUM / MAGNESIUMLEGERINGER				
Class 4.1	Packing group III	Hazard labels 4.1	Marine pollutant Maybe	EmS F-G, S-G	<i>ADR transport category: 3 ADR tunnel: (E)</i>	
Hazard labels 		Marking UN 1869 MAGNESIUM / MAGNESIUM ALLOYS				
Packaging Can be packed in approved packaging according to packing instruction P002. Note: The packaging shall be vented (PP10). Can also be packaged in large packagings (LP02).						
Mixed packaging The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.						
Remarks These substances, when they contain not more than 50% magnesium, are not subject to the provisions of the IMDG Code (SP 59). Bars, ingots or sticks are not subject to the provisions of the IMDG Code (SP 920).						
Properties and observations Silvery white metal. Burns with an intense white light and heat. In contact with water, especially seawater, may evolve hydrogen, a flammable gas. Reacts readily with acids and caustic alkali, evolving hydrogen. Reacts readily with iron oxide, producing a thermite effect. Forms explosive mixtures with oxidizing substances.						
Tank type: T1		Transport in bulk		Orange panel		
Tank provisions: TP33		Not allowed		1869		
Stowage and segregation						
Stowage		Keep as dry as reasonably practicable (H1).				
Segregation		Check the segregation table for sea transport. Stow "separated from" class 5.1 (SG17). Stow "separated from" goods of classes 2.1 and 3 (SG25). In addition: from goods of classes 2.1 and 3 when stowed on deck of a containership a minimum distance of two container spaces athwartship shall be maintained, when stowed on ro-ro ships a distance of 6 m athwartship shall be maintained (SG26). Stow "away from" SGG10 – liquid halogenated hydrocarbons (SG32). Stow "separated from" SGG1 – acids (SG35). "Away/seperated from": May not be loaded into the same transport unit.				
Placarding of the transport unit		Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.				
Foodstuff		The substance is not required to be kept separate from food and feed.				
Limited quantities (LQ) <i>Combination packaging</i> Inner: 5 kg Outer: 30 kg <i>Trays</i> Inner: 5 kg Outer: 20 kg		Parcel label: 		Excepted quantities (EQ) <i>Combination packaging</i> Inner: 30 mg Outer: 1000 mg Must be packed in an intermediate packaging with cushioning material. Max 1000 parcels per vehicle/container. 		