



IMDG - UN card

UN 1977

UN number 1977		Shipping name NITROGEN, REFRIGERATED LIQUID NITROGEN, KØLET, FLYDENDE				
Class 2.2	Packing group —	Hazard labels 2.2	Marine pollutant Maybe	EmS F-C, S-V	ADR transport category: 3 ADR tunnel: (C/E)	
Hazard labels 		Marking UN 1977 NITROGEN, REFRIGERATED LIQUID				
Packaging		Can be packed in suitable packaging according to packing instruction P203.				
Mixed packaging		The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.				
Remarks		This gas contained in open cryogenic receptacles with a maximum capacity of 1 L constructed with glass double walls having the space between the inner and outer wall evacuated (vacuum insulated) is not subject to the provisions of the IMDG Code provided each receptacle is transported in an outer packaging with suitable cushioning or absorbent materials to protect it from impact damage (SP 345). Open cryogenic receptacles conforming to the requirements of packing instruction P203 and containing no dangerous goods except for UN 1977, nitrogen, refrigerated liquid, which is fully absorbed in a porous material, are not subject to any other provisions of the IMDG Code (SP 346).				
Properties and observations		Liquefied, non-flammable, odourless gas. Lighter than air (0.97). Arrangements for the containment of the liquid nitrogen and fittings in use should be appropriate to the potential danger to the structure of the freight container or ship from the effect of misuse or accidental spillage.				
Tank type:	T75	Transport in bulk		Orange panel		
Tank provisions:	TP5	Not allowed		1977		
Stowage and segregation						
Stowage		There are no special requirements for stowage.				
Segregation		Check the segregation table for sea transport. There are no special requirements for segregation.				
Placarding of the transport unit		Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.				
Foodstuff		The substance is not required to be kept separate from food and feed.				
Limited quantities (LQ)		Parcel label:		Excepted quantities (EQ)		
Combination packaging				Combination packaging		
Inner: 120 mL				Inner: 30 mL		
Outer: 30 kg				Outer: 1000 mL		
Trays				Must be packed in an intermediate packaging with cushioning material. Max 1000 parcels per vehicle/container.		
Inner: 120 mL						
Outer: 20 kg						