



IMDG - UN card

UN 2214

UN number 2214		Shipping name PHthalic ANHYDRIDE PHthalSYREANHYDRID				
Class 8	Packing group III	Hazard labels 8	Marine pollutant Maybe	EmS F-A, S-B	<i>ADR transport category: 3 ADR tunnel: (E)</i>	
Hazard labels 		Marking UN 2214 PHTHALIC ANHYDRIDE				
Packaging Can be packed in approved packaging according to packing instruction P002. Can also be packaged in large packagings (LP02).						
Mixed packaging The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.						
Remarks Phthalic anhydride in the solid state and tetrahydrophthalic anhydride, with not more than 0.05% maleic anhydride, are not subject to the provisions of the IMDG Code. Phthalic anhydride molten at a temperature above its flashpoint, with not more than 0.05% maleic anhydride, shall be classified under UN 3256 (SP 169). A consignment of this substance that is accompanied by a shipper's certificate stating that it does not contain more than 0.05% maleic anhydride is not subject to the provisions of the IMDG Code (SP 939).						
Properties and observations White powder or flakes and lumps containing a high proportion of dust. Melting point: 131 °C. The vapour of the molten substance has a flashpoint of 152 °C c.c. and forms a flammable atmosphere with explosive limits of 1.7% to 10.4%. Causes burns to skin, eyes and mucous membranes. May be carried in the molten state. The molten substance can cause severe skin burns.						
Tank type: T1		Transport in bulk		Orange panel		
Tank provisions: TP33		Not allowed		2214		
Stowage and segregation						
Stowage		There are no special requirements for stowage.				
Segregation		Check the segregation table for sea transport. The substance belongs to group: acids (SGG1). Stow "separated from" SGG18 – alkalis (SG36). Stow "separated from" SGG6 – cyanides (SG49). "Seperated from": May not be loaded into the same transport unit.				
Placarding of the transport unit		Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.				
Foodstuff		The substance must be kept separate from food and feedstuffs.				
Limited quantities (LQ) <i>Combination packaging</i> Inner: 5 kg Outer: 30 kg <i>Trays</i> Inner: 5 kg Outer: 20 kg		Parcel label: 		Excepted quantities (EQ) <i>Combination packaging</i> Inner: 30 mg Outer: 1000 mg Must be packed in an intermediate packaging with cushioning material. Max 1000 parcels per vehicle/container. Parcel label: 		