



IMDG - UN card

UN 2283

UN number 2283		Shipping name 🇬🇧 ISOBUTYL METHACRYLATE, STABILIZED 🇩🇪 ISOBUTYLMETHACRYLAT, STABILISERET				
Class 3	Packing group III	Hazard labels 3	Marine pollutant Maybe	EmS F-E, S-D	<i>ADR transport category: 3 ADR tunnel: (D/E)</i>	
Hazard labels 		Marking UN 2283 ISOBUTYL METHACRYLATE, STABILIZED				
Packaging Can be packed in approved packaging according to packing instruction P001. Can also be packaged in large packagings (LP01).						
Mixed packaging The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.						
Remarks When substances are stabilized by temperature control, the provisions of 7.3.7 apply. When chemical stabilization is employed, the person offering the packaging, IBC or tank for transport shall ensure that the level of stabilization is sufficient to prevent the substance in the packaging, IBC or tank from dangerous polymerization at a bulk mean temperature of 50°C, or, in the case of a portable tank, 45°C. Where chemical stabilization becomes ineffective at lower temperatures within the anticipated duration of transport, temperature control is required. In making this determination factors to be taken into consideration include, but are not limited to, the capacity and geometry of the packaging, IBC or tank and the effect of any insulation present, the temperature of the substance when offered for transport, the duration of the journey and the ambient temperature conditions typically encountered in the journey (considering also the season of year), the effectiveness and other properties of the stabilizer employed, applicable operational controls imposed by regulation (e.g. requirements to protect from sources of heat, including other cargo transported at a temperature above ambient) and any other relevant factors." (SP 386).						
Properties and observations Colourless liquid. Flashpoint: 49 °C c.c. Immiscible with water. Irritating to skin, eyes and mucous membranes.						
Tank type: T2		Transport in bulk		Orange panel		
Tank provisions: TP1		Not allowed		2283		
Stowage and segregation						
Stowage Must be protected from sources of heat (SW1).						
Segregation Check the segregation table for sea transport. There are no special requirements for segregation.						
Placarding of the transport unit Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.						
Foodstuff The substance is not required to be kept separate from food and feed.						
Limited quantities (LQ) <i>Combination packaging</i> Inner: 5 L Outer: 30 kg <i>Trays</i> Inner: 5 L Outer: 20 kg		Excepted quantities (EQ) <i>Combination packaging</i> Inner: 30 mL Outer: 1000 mL Must be packed in an intermediate packaging with cushioning material. Max 1000 parcels per vehicle/container.				
Parcel label: 		Parcel label: 				