



IMDG - UN card

UN 2304

UN number 2304		Shipping name NAPHTHALENE, MOLTEN NAPHTHALEN, SMELTET				
Class 4.1	Packing group III	Hazard labels 4.1	Marine pollutant Yes	EmS F-A, S-H	<i>ADR transport category: 3</i> <i>ADR tunnel: (E)</i>	
Hazard labels  		Marking UN 2304 NAPHTHALENE, MOLTEN				
Packaging Cannot be packed in packaging. Mixed packaging The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another. Remarks There are no special provisions for this substance. Properties and observations Molten liquid with a persistent odour. Melting point: 80 °C. Evolves flammable vapours. As the melting point of naphthalene approximates very closely its flashpoint, care should be taken to avoid all possible causes of ignition. Contact between water and molten naphthalene above 110 °C must be avoided, as the addition of water will cause violent foaming or even an explosion.						
Tank type: T1	Transport in bulk Not allowed		Orange panel 2304			
Stowage and segregation						
Stowage There are no special requirements for stowage. Segregation Check the segregation table for sea transport. There are no special requirements for segregation. Placarding of the transport unit Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea. Foodstuff The substance is not required to be kept separate from food and feed.						
Limited quantities (LQ) <i>Combination packaging</i> Inner: Not allowed Outer: <i>Trays</i> Inner: Not allowed Outer:			Excepted quantities (EQ) <i>Combination packaging</i> Inner: Not allowed Outer:			