



IMDG - UN card

UN 2351

UN number 2351		Shipping name 🇬🇧 BUTYL NITRITES 🇩🇰 BUTYLNITRITER				
Class 3	Packing group II	Hazard labels 3	Marine pollutant Maybe	EmS F-E, S-D	<i>ADR transport category: 2</i> <i>ADR tunnel: (D/E)</i>	
Hazard labels 		Marking UN 2351 BUTYL NITRITES				
Packaging Can be packed in approved packaging according to packing instruction P001.						
Mixed packaging The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.						
Remarks There are no special provisions for this substance.						
Properties and observations Yellowish, volatile, oily liquids. Partially miscible with water. Decompose on exposure to air, light, water or heat, evolving toxic nitrous fumes. Harmful by inhalation.						
Tank type: T4		Transport in bulk		Orange panel		
Tank provisions: TP1		Not allowed		2351		
Stowage and segregation						
Stowage Stay clear of living quarters (SW2).						
Segregation Check the segregation table for sea transport. There are no special requirements for segregation.						
Placarding of the transport unit Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.						
Foodstuff The substance is not required to be kept separate from food and feed.						
Limited quantities (LQ) <i>Combination packaging</i> Inner: 1 L Outer: 30 kg <i>Trays</i> Inner: 1 L Outer: 20 kg		Parcel label: 		Excepted quantities (EQ) <i>Combination packaging</i> Inner: 30 mL Outer: 500 mL Must be packed in an intermediate packaging with cushioning material. Max 1000 parcels per vehicle/container.		
				Parcel label: 		