



IMDG - UN card

UN 2471

UN number 2471		Shipping name OSMIUM TETROXIDE OSMIUMTETRAOXID				
Class 6.1	Packing group I	Hazard labels 6.1	Marine pollutant Yes	EmS F-A, S-A	<i>ADR transport category: 1 ADR tunnel: (C/E)</i>	
Hazard labels  		Marking UN 2471 OSMIUM TETROXIDE				
Packaging		Can be packed in approved packaging according to packing instruction P002. Note: Paper or fibre inner packagings are not permitted (PP30). Packagings shall be hermetically sealed (PP31).				
Mixed packaging		The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.				
Remarks		There are no special provisions for this substance.				
Properties and observations		Pale yellow, crystalline, volatile solid with an irritating odour. Highly toxic if swallowed, by skin contact or by inhalation.				
Tank type: T6		Transport in bulk		Orange panel		
Tank provisions: TP33		Not allowed		2471		
Stowage and segregation						
Stowage		Stay clear of living quarters (SW2).				
Segregation		Check the segregation table for sea transport. There are no special requirements for segregation.				
Placarding of the transport unit		Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.				
Foodstuff		The substance must be kept separate from food and feedstuffs.				
Limited quantities (LQ)			Excepted quantities (EQ)		Parcel label:	
<i>Combination packaging</i> Inner: Not allowed Outer:			<i>Combination packaging</i> Inner: 1 mg el. mL Outer: 300 mg el. mL			
<i>Trays</i> Inner: Not allowed Outer:			Must be packed in an intermediate packaging with cushioning material. Max 1000 parcels per vehicle/container.			