



IMDG - UN card

UN 2485

UN number 2485		Shipping name n-BUTYL ISOCYANATE n-BUTYLISOCYANAT				
Class 6.1	Packing group I	Hazard labels 6.1+3	Marine pollutant Maybe	EmS F-E, S-D	<i>ADR transport category: 1 ADR tunnel: (C/D)</i>	
Hazard labels  		Marking UN 2485 n-BUTYL ISOCYANATE				
Packaging		Can be packed in approved packaging according to packing instruction P602.				
Mixed packaging		The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.				
Remarks		This substance is toxic by inhalation (SP 354).				
Properties and observations		Colourless liquid with a pungent odour. Immiscible with water but reacts violently with it, evolving gases. Flashpoint: 19 °C c.c. Highly toxic if swallowed, by skin contact or by inhalation. Irritating to skin, eyes and mucous membranes.				
Tank type: T20		Transport in bulk Not allowed		Orange panel 2485		
Tank provisions: TP2 TP13						
Stowage and segregation						
Stowage		Stay clear of living quarters (SW2).				
Segregation		Check the segregation table for sea transport. There are no special requirements for segregation.				
Placarding of the transport unit		Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.				
Foodstuff		The substance must be kept separate from food and feedstuffs.				
Limited quantities (LQ) <i>Combination packaging</i> Inner: Not allowed Outer: <i>Trays</i> Inner: Not allowed Outer:			Excepted quantities (EQ) <i>Combination packaging</i> Inner: Not allowed Outer:			