



IMDG - UN card

UN 2606

UN number 2606		Shipping name METHYL ORTHOSILICATE METHYLORTHOSILICAT				
Class 6.1	Packing group I	Hazard labels 6.1+3	Marine pollutant Maybe	EmS F-E, S-D	<i>ADR transport category: 1</i> <i>ADR tunnel: (C/D)</i>	
Hazard labels  		Marking UN 2606 METHYL ORTHOSILICATE				
Packaging Can be packed in approved packaging according to packing instruction P602.						
Mixed packaging The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.						
Remarks This substance is toxic by inhalation (SP 354).						
Properties and observations Colourless, flammable liquid with an ethereal odour. Immiscible with water. Flashpoint: -18 °C to 19 °C c.c. Highly toxic if swallowed, by skin contact or by inhalation. May cause blindness.						
Tank type: T20		Transport in bulk		Orange panel		
Tank provisions: TP2 TP13		Not allowed		2606		
Stowage and segregation						
Stowage Stay clear of living quarters (SW2).						
Segregation Check the segregation table for sea transport. There are no special requirements for segregation.						
Placarding of the transport unit Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.						
Foodstuff The substance must be kept separate from food and feedstuffs.						
Limited quantities (LQ) <i>Combination packaging</i> Inner: Not allowed Outer: <i>Trays</i> Inner: Not allowed Outer:			Excepted quantities (EQ) <i>Combination packaging</i> Inner: Not allowed Outer:			