



IMDG - UN card

UN 2724

UN number 2724		Shipping name MANGANESE NITRATE MANGANNITRAT				
Class 5.1	Packing group III	Hazard labels 5.1	Marine pollutant Maybe	EmS F-A, S-Q	<i>ADR transport category: 3 ADR tunnel: (E)</i>	
Hazard labels 		Marking UN 2724 MANGANESE NITRATE				
Packaging Can be packed in approved packaging according to packing instruction P002. Can also be packaged in large packagings (LP02).						
Mixed packaging The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.						
Remarks There are no special provisions for this substance.						
Properties and observations Pale pink deliquescent crystals. Soluble in water. Melting point between 26 °C and 35 °C. Mixtures with combustible material are readily ignited and may burn fiercely. Solutions in water are slightly corrosive. Harmful if swallowed.						
Tank type: T1		Transport in bulk		Orange panel		
Tank provisions: TP33		Not allowed		2724		
Stowage and segregation						
Stowage There are no special requirements for stowage.						
Segregation Check the segregation table for sea transport. There are no special requirements for segregation.						
Placarding of the transport unit Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.						
Foodstuff The substance is not required to be kept separate from food and feed.						
Limited quantities (LQ) <i>Combination packaging</i> Inner: 5 kg Outer: 30 kg <i>Trays</i> Inner: 5 kg Outer: 20 kg		Parcel label: 				
		Excepted quantities (EQ) <i>Combination packaging</i> Inner: 30 mg Outer: 1000 mg Must be packed in an intermediate packaging with cushioning material. Max 1000 parcels per vehicle/container.				
		Parcel label: 				