



IMDG - UN card

UN 2881

UN number 2881		Shipping name METAL CATALYST, DRY METALKATALYSATOR, TØR				
Class 4.2	Packing group III	Hazard labels 4.2	Marine pollutant Maybe	EmS F-G, S-M	<i>ADR transport category: 3</i> <i>ADR tunnel: (E)</i>	
Hazard labels 		Marking UN 2881 METAL CATALYST, DRY (Note: The proper shipping name must be supplemented with the substance's technical description in brackets)				
Packaging	Can be packed in approved packaging according to packing instruction P002. Note: Packagings shall be hermetically sealed (PP31). Can also be packaged in large packagings (LP02).					
Mixed packaging	The substance may be packaged with other substances in the same outer packaging if: - it is permitted to load the substances together, and - the substances do not react dangerously with one another.					
Remarks	If the chemical or physical properties of a substance covered by this description are such that, when tested, it does not meet the established defining criteria for the class or division listed in column 3, or any other class or division, it is not subject to the provisions of the IMDG Code except in the case of a marine pollutant where 2.10.3 applies (SP 223).					
Properties and observations	Liable to ignite spontaneously in air.					
Tank type:	T1	Transport in bulk		Orange panel		
Tank provisions:	TP33	Not allowed		2881		
Stowage and segregation						
Stowage	Keep as dry as reasonably practicable (H1).					
Segregation	Check the segregation table for sea transport. The substance belongs to group: heavy metals and their salts (including their organometallic compounds) (SGG7). The substance belongs to group: powdered metals (SGG15). Stow "separated from" goods of classes 2.1 and 3 (SG25). In addition: from goods of classes 2.1 and 3 when stowed on deck of a containership a minimum distance of two container spaces athwartship shall be maintained, when stowed on ro-ro ships a distance of 6 m athwartship shall be maintained (SG26). "Seperated from": May not be loaded into the same transport unit.					
Placarding of the transport unit	Containers, semi-trailers and tank containers must be marked with enlarged hazard labels (placards) on all four sides. Railway wagons must at least be marked with placards on both sides. All other transport units, e.g. trucks etc., must at least be placarded on both sides and at the back. The placards must have a size of at least 250 x 250 mm, and be of such quality that the labeling is still visible after 3 months at sea.					
Foodstuff	The substance is not required to be kept separate from food and feed.					
Limited quantities (LQ) <i>Combination packaging</i> Inner: Not allowed Outer: <i>Trays</i> Inner: Not allowed Outer:			Excepted quantities (EQ) <i>Combination packaging</i> Inner: 30 mg el. mL Outer: 1000 mg el. mL Must be packed in an intermediate packaging with cushioning material. Max 1000 parcels per vehicle/container.			
			Parcel label: 			